




## **UROLOGY**

|   | LOWER URINARY TRACT   |
|---|-----------------------|
| 2 | UPPER URINARY TRACT   |
| 3 | PEDIATRIC UROLOGY     |
| 4 | AUXILIARY INSTRUMENTS |
| 5 | LAPAROSCOPY           |





**LOWER URINARY TRACT** 



## **LOWER URINARY TRACT**

| BASIC SETS/OVER  | RVIEW OF PANOVIEW TELESCOPES                   |
|------------------|--|
| URETHROTOMY      |  |
| OPTICAL URETHRO  | OTOMES   |
| URETHROTOME F    | OR BLIND SLITTING                              |
| CYSTOSCOPY       |  |
| CYSTO-URETHROS   | SCOPE 8650                                     |
| "MIDI-SIZE" CYST | TO-URETHROSCOPE                                |
| ATRAUMATIC CON   | MPACT CYSTO-URETHROSCOPE                       |
| FLEXIBLE FIBER C | CYSTOSCOPE                                     |
| "VISION EF" FLEX | IBLE SENSOR CYSTOSCOPES                        |
| "MAMBA" FLEXIBI  | LE SENSOR CYSTOSCOPES                          |
| "SYSTEM BLUE" F  | FOR PHOTODYNAMIC DIAGNOSTICS (PDD)             |
| TRANSURETHRAL    | . RESECTION (TUR)                              |
| "SHARK" RESECTO  | OSCOPES (MONOPOLAR/BIPOLAR)                    |
| "E-LINE" RESECTO | OSCOPE, LONG SHEATH                            |
| "MIDI-SIZE" RESE | :CTOSCOPE                                      |
| "SYSTEM BLUE" F  | FOR PHOTODYNAMIC DIAGNOSTICS (PDD)             |
| "SHARK" ELECTRO  | ODES (MONOPOLAR/BIPOLAR) – "E-LINE" ELECTRODES |
| ACCESSORIES FO   | OR RESECTOSCOPE SHEATHS                        |



## **LOWER URINARY TRACT**

| ANATOMIC ENDOSCOPIC ENUCLEATION OF THE PROSTATE (AEEP) |
|--|
| LASER ENUCLEATION (HoLEP/ThuLEP/GreenLEP)              |
| BIPOLAR ENUCLEATION (BipoLEP)                          |
| MORCELLATION   |
| "SHARK" MORCESCOPE                                     |
| "PIRANHA" MORCELLATION SYSTEM                          |
| LASER ENERGY SOURCES                                   |
| "MEGA PULSE 70+" HOLMIUM:YAG LASER (Ho:YAG)            |
| "PULVIS 60+" THULIUM FIBER LASER (TFL)                 |
| HF ENERGY SOURCES                                      |
| HF GENERATOR 2260                                      |
| HF CONNECTION CABLE                                    |
| SUCTION IRRIGATION PUMP                                |
| FLUID CONTROL 2225                                     |



## BASIC EQUIPMENT FOR CYSTOSCOPY

CYSTO-URETHROSCOPES 8650

| Product                                    | Product no. | Quantity | Catalog/Section     |
|--|-------------|----------|---------------------|
| Endoscopes and instruments                 |             |          |                     |
| Sheath for cystoscope 19.5 Fr              | 8650.0341   | 1        |                     |
| Adapter for cystoscope                     | 8650.264    | 1        |                     |
| Working insert for cystoscope 0/30/70      | 8650.204    | 1        |                     |
| Universal sealing valve 1–6 Fr             | 4712348     | 1        |                     |
| Viewing obturator for cystoscope 19.5 Fr   | 8650.724    | 1        |                     |
| Opt. biopsy forceps, "Marburg" model       | 8650.614    | 1        | Urology/Cystoscopes |
| Opt. grasping forceps, straight            | 8650.684    | 1        |                     |
| Telescope 0° Ø 4 mm WL 298 mm              | 8650.414    | 1        |                     |
| Telescope 70° Ø 4 mm WL 302 mm             | 8650.415    | 1        |                     |
| Urethrotome 15–45 Fr WL 236 mm             | 8517.00     | 1        |                     |
| Bladder syringe 150 ml Ø 54 mm             | 822.31      | 1        |                     |
| Flexible adapter for bladder syringe       | 822.13      | 1        |                     |
| Perforated basket for standard telescope 2 | 38016       | 1        |                     |
| Container (W x H x D) 400 x 60 x 200 mm    | 33022       | 1        | Hygiene             |



## BASIC EQUIPMENT FOR TUR

TELESCOPE 4 MM, 12°/30° 24/26 Fr, ACTIVE, CONTINUOUS IRRIGATION

| Product                                     | Product no.    | Quantity | Catalog/Section                 |
|---|----------------|----------|---------------------------------|
| Endoscopes and instruments                  |                |          |                                 |
| Outer sheath for resectoscope 26 Fr         | 8675426        | 1        |                                 |
| Inner sheath for resectoscope 24 Fr         | 8675324        | 1        |                                 |
| Dilatations obturator f. resectoscope 24 Fr | 8673224        | 1        |                                 |
| Obturator for resectoscope 24 Fr            | 8673024        | 1        |                                 |
| Viewing obturator for resectoscope 24 Fr    | 8673124        | 1        |                                 |
| Working element, active, bipo 0/12/30°      | 8680.205       | 1        |                                 |
| Telescope 12° Ø 4 mm WL 297 mm              | 8654.431       | 1        |                                 |
| Telescope blue 12° Ø 4 mm WL 298 mm         | 8654.531       | 1        | Urology/Resectoscopes           |
| Telescope 30° Ø 4 mm WL 300 mm              | 8654.422       | 1        |                                 |
| Telescope blue 30° Ø 4 mm WL 299 mm         | 8654.522       | 1        |                                 |
| Cutting electrode mono 24 Fr 12/30°         | 46782435       | 1        |                                 |
| Coag. electrode mono 22–24 Fr 12/30°        | 46782201       | 1        |                                 |
| Protective sterilization sleeve             | 33030          | 1        |                                 |
| HF monopolar connection cable               | see URO103/104 | 1        | 1                               |
| Urethrotome 15–45 Fr WL 236 mm              | 8517.00        | 1        | Urology/Urethrotomes            |
| Knife for urethrotome                       | 8517.90        | 1        |                                 |
| Irrigation pump for HYS/URO/LAP bndl        | 22250011       | 1        | Urology/Resectoscopes           |
| Bladder syringe 150 ml Ø 54 mm              | 822.31         | 1        | - Urology/Auxiliary instruments |
| Flexible adapter for bladder syringe        | 822.13         | 1        |                                 |



## BASIC EQUIPMENT FOR TUR

TELESCOPE 4 MM, 0°

24 Fr, PASSIVE, INTERMITTENT IRRIGATION WITH CENTRAL STOPCOCK

| Product                                     | Product no.    | Quantity | Catalog/Section               |
|---|----------------|----------|-------------------------------|
| Endoscopes and instruments                  |                |          |                               |
| Sheath for resectoscope 24 Fr               | 8676424        | 1        |                               |
| Connection part for resectoscope 24 Fr      | 8676342        | 1        |                               |
| Dilatations obturator f. resectoscope 24 Fr | 8673224        | 1        |                               |
| Viewing obturator for resectoscope 24 Fr    | 8673124        | 1        | Urology/Resectoscopes         |
| Obturator for resectoscope 24 Fr            | 8673024        | 1        |                               |
| Working element, passive, mono 0°           | 8681224        | 1        |                               |
| Telescope 0° Ø 4 mm WL 298 mm               | 8650.414       | 1        |                               |
| Telescope blue 0° Ø 4 mm WL 298 mm          | 8650.514       | 1        |                               |
| Cutting electrode mono 24 Fr 0°             | 46792435       | 1        |                               |
| Protective sterilization sleeve             | 33030          | 1        |                               |
| HF monopolar connection cable               | see URO103/104 | 1        |                               |
| Urethrotome 15–45 Fr WL 236 mm              | 8517.00        | 1        | - Urology/Urethrotomes        |
| Knife for urethrotome                       | 8517.90        | 1        |                               |
| Bladder syringe 150 ml Ø 54 mm              | 822.31         | 1        | Urology/Auxiliary instruments |
| Flexible adapter for bladder syringe        | 822.13         | 1        |                               |



#### BASIC EQUIPMENT FOR TUR

RESECTOSCOPE, MONOPOLAR TELESCOPE 4 MM, 0°

24 Fr, PASSIVE, INTERMITTENT IRRIGATION WITH ROTATABLE IRRIGATION ADAPTER

| Product  | Product no.                | Quantity | Catalog/Section               |  |
|--|----------------------------|----------|-------------------------------|--|
| Endoscopes and instruments   | Endoscopes and instruments |          |                               |  |
| Sheath for resectoscope 24 Fr  | 8676324                    | 1        |                               |  |
| Irrigation adapter for resectoscope 24/26 Fr with 4 mm Luer connection               | 8676354                    | 1        | Urology/Resectoscopes         |  |
| Irrigation adapter for resectoscope 24/26 Fr with 3 mm Luer connection with stopcock | 8676361                    | 1        |                               |  |
| Two-way stopcock, maintenance-free   | 88351                      | 1        |                               |  |
| Dilatations obturator f. resectoscope 24 Fr  | 8673224                    | 1        |                               |  |
| Viewing obturator for resectoscope 24 Fr   | 8673124                    | 1        |                               |  |
| Obturator for resectoscope 24 Fr   | 8673024                    | 1        |                               |  |
| Working element, passive, mono 0°  | 8681224                    | 1        |                               |  |
| Telescope 0° Ø 4 mm WL 298 mm  | 8650.414                   | 1        |                               |  |
| Telescope blue 0° Ø 4 mm WL 298 mm   | 8650.514                   | 1        |                               |  |
| Cutting electrode mono 24 Fr 0°  | 46792435                   | 1        |                               |  |
| Protective sterilization sleeve  | 33030                      | 1        |                               |  |
| HF monopolar connection cable  | see URO103/104             | 1        |                               |  |
| Urethrotome 15–45 Fr WL 236 mm   | 8517.00                    | 1        | Urology/Urethrotomes          |  |
| Knife for urethrotome  | 8517.90                    | 1        |                               |  |
| Bladder syringe 150 ml Ø 54 mm   | 822.31                     | 1        | Harley Westling               |  |
| Flexible adapter for bladder syringe   | 822.13                     | 1        | Urology/Auxiliary instruments |  |



## BASIC EQUIPMENT FOR TUR

RESECTOSCOPE, BIPOLAR
TELESCOPE 4 MM, 12°/30°
22/24 Fr, ACTIVE, CONTINUOUS IRRIGATION

| Product                                  | Product no. | Quantity | Catalog/Section                 |
|--|-------------|----------|---------------------------------|
| Endoscopes and instruments               |             |          |                                 |
| Outer sheath for resectoscope 24 Fr      | 8675424     | 1        |                                 |
| Inner sheath for resectoscope 22 Fr      | 8675322     | 1        |                                 |
| Viewing obturator for resectoscope 22 Fr | 8673122     | 1        |                                 |
| Obturator for resectoscope 22 Fr         | 8673022     | 1        |                                 |
| Working element, active, bipo 0/12/30°   | 8680.205    | 1        |                                 |
| Telescope 12° Ø 4 mm WL 297 mm           | 8654.431    | 1        |                                 |
| Telescope blue 12° Ø 4 mm WL 298 mm      | 8654.531    | 1        | Urology/Resectoscopes           |
| Telescope 30° Ø 4 mm WL 300 mm           | 8654.422    | 1        |                                 |
| Telescope blue 30° Ø 4 mm WL 299 mm      | 8654.522    | 1        |                                 |
| Cutting electrode bipo 22 Fr 12/30°      | 4622.1333   | 1        |                                 |
| Coag. electrode bipo 22 Fr 12/30°        | 4623.0243   | 1        |                                 |
| BiVAP-Elektrode bipo 22 Fr 12/30°        | 46300223    | 1        |                                 |
| HF bipolar connection cable              | see URO105  | 1        |                                 |
| Urethrotome 15–45 Fr WL 236 mm           | 8517.00     | 1        | Urology/Urethrotomes            |
| Knife for urethrotome                    | 8517.90     | 1        |                                 |
| Irrigation pump for HYS/URO/LAP bndl     | 22250011    | 1        | Urology/Resectoscopes           |
| Bladder syringe 150 ml Ø 54 mm           | 822.31      | 1        | - Urology/Auxiliary instruments |
| Flexible adapter for bladder syringe     | 822.13      | 1        |                                 |



## BASIC EQUIPMENT FOR TUR

RESECTOSCOPE, BIPOLAR
TELESCOPE 4 MM, 12°/30°
24/26 Fr, ACTIVE, CONTINUOUS IRRIGATION

| Product                                     | Product no. | Quantity | Catalog/Section               |
|---|-------------|----------|-------------------------------|
| Endoscopes and instruments                  |             |          |                               |
| Outer sheath for resectoscope 26 Fr         | 8675426     | 1        |                               |
| Inner sheath for resectoscope 24 Fr         | 8675324     | 1        |                               |
| Dilatations obturator f. resectoscope 24 Fr | 8673224     | 1        |                               |
| Obturator for resectoscope 24 Fr            | 8673024     | 1        |                               |
| Viewing obturator for resectoscope 24 Fr    | 8673124     | 1        |                               |
| Working element, active, bipo 0/12/30°      | 8680.205    | 1        |                               |
| Telescope 12° Ø 4 mm WL 297 mm              | 8654.431    | 1        | Live Logy/December 2          |
| Telescope blue 12° Ø 4 mm WL 298 mm         | 8654.531    | 1        | Urology/Resectoscopes         |
| Telescope 30° Ø 4 mm WL 300 mm              | 8654.422    | 1        |                               |
| Telescope blue 30° Ø 4 mm WL 299 mm         | 8654.522    | 1        |                               |
| Coag. electrode bipo 22 Fr 12/30°           | 4623.0243   | 1        |                               |
| BiVAP-Elektrode bipo 22 Fr 12/30°           | 46300223    | 1        |                               |
| BiVAP-Elektrode bipo 24–26 Fr 12/30°        | 46300243    | 1        |                               |
| HF bipolar connection cable                 | see URO105  | 1        |                               |
| Urethrotome 15–45 Fr WL 236 mm              | 8517.00     | 1        | - Urology/Urethrotomes        |
| Knife for urethrotome                       | 8517.90     | 1        |                               |
| Irrigation pump for HYS/URO/LAP bndl        | 22250011    | 1        | Urology/Resectoscopes         |
| Bladder syringe 150 ml Ø 54 mm              | 822.31      | 1        | Urology/Auxiliary instruments |
| Flexible adapter for bladder syringe        | 822.13      | 1        |                               |



## BASIC EQUIPMENT FOR TUR

RESECTOSCOPE, BIPOLAR TELESCOPE 4 MM, 12°

24 Fr, ACTIVE, INTERMITTENT IRRIGATION WITH CENTRAL STOPCOCK

| Product                                     | Product no. | Quantity | Catalog/Section               |
|---|-------------|----------|-------------------------------|
| Endoscopes and instruments                  |             |          |                               |
| Outer sheath for resectoscope 26 Fr         | 8675426     | 1        | Urology/Resectoscopes         |
| Inner sheath for resectoscope 24 Fr         | 8675324     | 1        |                               |
| Dilatations obturator f. resectoscope 24 Fr | 8673224     | 1        |                               |
| Obturator for resectoscope 24 Fr            | 8673024     | 1        |                               |
| Viewing obturator for resectoscope 24 Fr    | 8673124     | 1        |                               |
| Working element, active, bipo 0/12/30°      | 8680.205    | 1        |                               |
| Telescope 12° Ø 4 mm WL 297 mm              | 8654.431    | 1        |                               |
| Telescope blue 12° Ø 4 mm WL 298 mm         | 8654.531    | 1        |                               |
| Coag. electrode bipo 22 Fr 12/30°           | 4623.0243   | 1        |                               |
| BiVAP-Elektrode bipo 22 Fr 12/30°           | 46300223    | 1        |                               |
| BiVAP-Elektrode bipo 24–26 Fr 12/30°        | 46300243    | 1        |                               |
| HF bipolar connection cable                 | see URO105  | 1        |                               |
| Urethrotome 15–45 Fr WL 236 mm              | 8517.00     | 1        | Urology/Urethrotomes          |
| Knife for urethrotome                       | 8517.90     | 1        |                               |
| Irrigation pump for HYS/URO/LAP bndl        | 22250011    | 1        | Urology/Resectoscopes         |
| Bladder syringe 150 ml Ø 54 mm              | 822.31      | 1        | Urology/Auxiliary instruments |
| Flexible adapter for bladder syringe        | 822.13      | 1        |                               |



## **Shark**HoLEP, ThuLEP BASIC LASER ENUCLEATION SET I

STANDARD LASER RESECTOSCOPE 24/26 Fr

| Product   | Product no. | Quantity | Catalog/Section           |
|---|-------------|----------|---------------------------|
| "PIRANHA" morcellator   |             |          | '                         |
| Suction pump  | 2208001     | 1        |                           |
| 1-pedal footswitch  | 2030108     | 1        |                           |
| Bottle holder   | 64031.381   | 1        |                           |
| Sound absorber (Pack= 3 PCS)  | 35100.115   | 1        |                           |
| RECTO PUMP connection tube  | 8170.6554   | 1        |                           |
| Overflow protection/bacteria filter (Pack = 10 PCS)                                       | 2228.901    | 1        |                           |
| Secretion container, 2 I, without cover   | 8170.6551   | 1        |                           |
| Cover for secretion trap 8170.6551, reusable  | 8170.6552   | 1        |                           |
| Optional: 3 L suction jar for RCS   | 077.0130    |          |                           |
| Power cable, cable length 3 m   | 2440.03     | 1        | Urology/Laser enucleation |
| Tube for suction  | 41702208    | 1        |                           |
| Collecting container  | 2208120     | 1        |                           |
| Motor Control Unit 2303   | 2303.001    | 1        |                           |
| Also: Power cable, cable length 3 m   | 2440.03     | 1        |                           |
| Motor handpiece max. 6,000 rpm  | 8564122     | 1        |                           |
| Irrigation adapter for motor handpiece 8564.021   | 163951      |          |                           |
| Rotary morcellator Ø 4.8 mm WL 335 mm   | 49700113    | 1        |                           |
| Rotary morcellator Ø 4.8 mm WL 385 mm for morcellator telescopes from other manufacturers | 49700103    | 1        |                           |
| Laser resectoscope 24/26 Fr   |             |          |                           |
| Telescope 30° Ø 4 mm WL 300 mm  | 8654.422    | 1        |                           |
| Telescope 12° Ø 4 mm WL 297 mm  | 8654.431    | 1        |                           |
| Also: <b>Fiber light cable bndl</b> , Ø 2.5 mm, 2.3 m long                                | 806625231   | 1        |                           |
| for reprocessing: Perforated basket for standard telescope 2                              | 38016       | 1        | Urology/Laser enucleation |
| Laser working element, passive 12/30°   | 8654382     | 1        |                           |
| Alternative: Laser working insert 12/30°  | 8654383     | 1        |                           |
| Guide tube laser therapy 1,000 µm 24 Fr   | 8654991     | 1        |                           |
| Guide tube laser therapy 600 µm 24 Fr   | 8654993     | 1        |                           |
| Guide tube laser therapy 600 µm 24 Fr   | 8654995     | 1        |                           |
| Guide tube laser therapy 600 µm 24 Fr   | 8654997     | 1        |                           |
| Curette 22–24 Fr for prostate chips   | 8654998     | 1        |                           |



Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with

your contact partner or directly with Richard Wolf GmbH.

## Holep, Thulep Basic Laser enucleation set i

STANDARD LASER RESECTOSCOPE 24/26 Fr

Perforated basket for Morcescope with small part basket

**Product** Product no. Quantity Catalog/Section Laser resectoscope 24/26 Fr Outer sheath for resectoscope 26 Fr 8675426 Inner sheath for resectoscope 24 Fr 8675324 1 Obturator for resectoscope 24 Fr 8673024 1 Urology/Laser enucleation 8673124 Viewing obturator for resectoscope 24 Fr 1 Dilatations obturator f. resectoscope 24 Fr 8673224 1 **MORCESCOPE** Morcescope 0° 24 Fr WL 199 mm 8970407 1 1 Autom. sealing element ID 5.7 mm 8920.311 103.00 1 Pressure ball Tube with LUER-LOCK connector 886.00 1 Urology/Laser enucleation 6.01 Cleaning brush Ø 11 mm TL 360 mm 1 Also: Fiber light cable bndl  $\varnothing 3.5$  mm, 2.3 m long 806635231

38012

1



# HOLEP, THULEP BASIC LASER ENUCLEATION SET II

LASER ENUCLEATION SHEATH FOR **BLUNT** ENUCLEATION 24/26 Fr

| Product   | Product no. | Quantity | Catalog/Section           |
|---|-------------|----------|---------------------------|
| "PIRANHA" morcellator   |             |          |                           |
| Suction pump  | 2208001     | 1        |                           |
| 1-pedal footswitch  | 2030108     | 1        |                           |
| Bottle holder   | 64031.381   | 1        |                           |
| Sound absorber (Pack= 3 PCS)  | 35100.115   | 1        |                           |
| RECTO PUMP connection tube  | 8170.6554   | 1        |                           |
| Overflow protection/bacteria filter (Pack = 10 PCS)                                       | 2228.901    | 1        |                           |
| Secretion container, 2 I, without cover   | 8170.6551   | 1        |                           |
| Cover for secretion trap 8170.6551, reusable  | 8170.6552   | 1        |                           |
| Optional: 3 L suction jar for RCS   | 077.0130    |          |                           |
| Power cable, cable length 3 m   | 2440.03     | 1        | Urology/Laser enucleation |
| Tube for suction  | 41702208    | 1        |                           |
| Collecting container  | 2208120     | 1        |                           |
| Motor Control Unit 2303   | 2303.001    | 1        |                           |
| Also: <b>Power cable</b> , cable length 3 m   | 2440.03     | 1        |                           |
| Motor handpiece max. 6,000 rpm  | 8564122     | 1        |                           |
| Irrigation adapter for motor handpiece 8564.021   | 163951      |          |                           |
| Rotary morcellator Ø 4.8 mm WL 335 mm   | 49700113    | 1        |                           |
| Rotary morcellator Ø 4.8 mm WL 385 mm for morcellator telescopes from other manufacturers | 49700103    | 1        |                           |
| Laser resectoscope 24/26 Fr   |             |          |                           |
| Telescope 30° Ø 4 mm WL 300 mm  | 8654.422    | 1        |                           |
| Telescope 12° Ø 4 mm WL 297 mm  | 8654.431    | 1        |                           |
| Also: <b>Fiber light cable bndl</b> , Ø 2.5 mm, 2.3 m long                                | 806625231   | 1        |                           |
| for reprocessing: Perforated basket for standard telescope 2                              | 38016       | 1        |                           |
| Laser working element, passive 12/30°   | 8654382     | 1        |                           |
| Alternative: Laser working insert 12/30°  | 8654383     | 1        | Urology/Laser enucleation |
| Guide tube laser therapy 1,000 µm 24 Fr   | 8654991     | 1        |                           |
| Guide tube laser therapy 600 μm 24 Fr   | 8654993     | 1        |                           |
| Guide tube laser therapy 600 μm 24 Fr   | 8654995     | 1        |                           |
| Guide tube laser therapy 600 μm 24 Fr   | 8654997     | 1        |                           |
| Curette 22–24 Fr for prostate chips   | 8654998     | 1        |                           |



# HOLEP, THULEP BASIC LASER ENUCLEATION SET II

#### LASER ENUCLEATION SHEATH FOR **BLUNT** ENUCLEATION

| Product   | Product no. | Quantity | Catalog/Section           |  |
|---|-------------|----------|---------------------------|--|
| Laser enucleation sheath for blunt enucleation 24/26 Fr |             |          |                           |  |
| Outer sheath for resectoscope 26 Fr                     | 8675426     | 1        |                           |  |
| Inner sheath for laser therapy 24 Fr                    | 8675524     | 1        |                           |  |
| Obturator for resectoscope 24 Fr                        | 8673324     | 1        |                           |  |
| Alternative:  | '           |          |                           |  |
| Outer sheath for resectoscope 26 Fr                     | 8675426     | 1        | Urology/Laser enucleation |  |
| Inner sheath for resectoscope 24 Fr                     | 8675324     | 1        |                           |  |
| Obturator for resectoscope 24 Fr                        | 8673024     | 1        |                           |  |
| Dilatations obturator f. resectoscope 24 Fr             | 8673224     | 1        |                           |  |
| MORCESCOPE  |             |          |                           |  |
| Morcescope 0° 24 Fr WL 199 mm                           | 8970407     | 1        |                           |  |
| Autom. sealing element ID 5.7 mm                        | 8920.311    | 1        |                           |  |
| Pressure ball   | 103.00      | 1        |                           |  |
| Tube with LUER-LOCK connector                           | 886.00      | 1        |                           |  |
| Cleaning brush Ø 11 mm TL 360 mm                        | 6.01        | 1        | Urology/Laser enucleation |  |

806635231

38012

Also:

Fiber light cable bndl

Ø 3.5 mm, 2.3 m long

with small part basket

Perforated basket for Morcescope



# HOLEP, THULEP BASIC LASER ENUCLEATION SET III

#### STANDARD LASER RESECTOSCOPE 24/26 Fr AND BIPOLAR RESECTION

| Product   | Product no. | Quantity | Catalog/Section           |
|---|-------------|----------|---------------------------|
| "PIRANHA" morcellator   |             |          |                           |
| Suction pump  | 2208001     | 1        |                           |
| 1-pedal footswitch  | 2030108     | 1        |                           |
| Bottle holder   | 64031.381   | 1        |                           |
| Sound absorber (Pack= 3 PCS)  | 35100.115   | 1        |                           |
| RECTO PUMP connection tube  | 8170.6554   | 1        |                           |
| Overflow protection/bacteria filter (Pack = 10 PCS)                                       | 2228.901    | 1        |                           |
| Secretion container, 2 I, without cover   | 8170.6551   | 1        |                           |
| Cover for secretion trap 8170.6551, reusable  | 8170.6552   | 1        |                           |
| Optional: 3 L suction jar for RCS   | 077.0130    |          |                           |
| Power cable, cable length 3 m   | 2440.03     | 1        | Urology/Laser enucleation |
| Tube for suction  | 41702208    | 1        |                           |
| Collecting container  | 2208120     | 1        |                           |
| Motor Control Unit 2303   | 2303.001    | 1        |                           |
| Also: <b>Power cable</b> , cable length 3 m   | 2440.03     | 1        |                           |
| Motor handpiece max. 6,000 rpm  | 8564122     | 1        |                           |
| Irrigation adapter for motor handpiece 8564.021   | 163951      |          |                           |
| Rotary morcellator Ø 4.8 mm WL 335 mm   | 49700113    | 1        |                           |
| Rotary morcellator Ø 4.8 mm WL 385 mm for morcellator telescopes from other manufacturers | 49700103    | 1        |                           |
| Laser resectoscope 24/26 Fr   |             |          |                           |
| Telescope 30° Ø 4 mm WL 300 mm  | 8654.422    | 1        |                           |
| Telescope 12° Ø 4 mm WL 297 mm  | 8654.431    | 1        |                           |
| Also: <b>Fiber light cable bndl</b> , Ø 2.5 mm, 2.3 m long                                | 806625231   | 1        |                           |
| for reprocessing: Perforated basket for standard telescope 2                              | 38016       | 1        |                           |
| Laser working element, passive 12/30°   | 8654382     | 1        |                           |
| Alternative: Laser working insert 12/30°  | 8654383     | 1        | Urology/Laser enucleation |
| Guide tube laser therapy 1,000 µm 24 Fr   | 8654991     | 1        |                           |
| Guide tube laser therapy 600 µm 24 Fr   | 8654993     | 1        |                           |
| Guide tube laser therapy 600 µm 24 Fr   | 8654995     | 1        |                           |
| Guide tube laser therapy 600 µm 24 Fr   | 8654997     | 1        |                           |
| Curette 22–24 Fr for prostate chips   | 8654998     | 1        |                           |



| IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# HOLEP, THULEP BASIC LASER ENUCLEATION SET III

#### STANDARD LASER RESECTOSCOPE 24/26 Fr AND BIPOLAR RESECTION


| Product  | Product no. | Quantity | Catalog/Section             |
|--|-------------|----------|-----------------------------|
| aser resectoscope 24/26 Fr                                 |             |          |                             |
| Outer sheath for resectoscope 26 Fr                        | 8675426     | 1        |                             |
| Inner sheath for resectoscope 24 Fr                        | 8675324     | 1        |                             |
| Obturator for resectoscope 24 Fr                           | 8673024     | 1        | Urology/Laser enucleation   |
| Viewing obturator for resectoscope 24 Fr                   | 8673124     | 1        |                             |
| Dilatations obturator f. resectoscope 24 Fr                | 8673224     | 1        |                             |
| Bipolar resectoscope 24/26 Fr                              |             |          |                             |
| Working element, active, bipo 0/12/30                      | 8680.205    | 1        |                             |
| Optional: working element, passive, bipo 0/12/30°          | 8680.225    | 1        |                             |
| Cutting electrode bipo 24 Fr 12/30°                        | 4622.1313   | 1        | - Urology/Laser enucleation |
| Coag. electrode bipo 24–26 Fr 12/30°                       | 4623.0223   | 1        |                             |
| HF bipolar connection cable L 3 m                          | 8108.232    | 1        |                             |
| HF bipolar connection cable L 5 m                          | 8108.252    | 1        |                             |
| HF bipolar connection cable L 3 m                          | 8108.231    | 1        |                             |
| HF bipolar connection cable L 3 m                          | 8108.251    | 1        |                             |
| Morcescope   |             |          |                             |
| Morcescope 0° 24 Fr WL 199 mm                              | 8970407     | 1        |                             |
| Autom. sealing element ID 5.7 mm                           | 8920.311    | 1        |                             |
| Pressure ball  | 103.00      | 1        |                             |
| Tube with LUER-LOCK connector                              | 886.00      | 1        |                             |
| Cleaning brush Ø 11 mm TL 360 mm                           | 6.01        | 1        | Urology/Laser enucleation   |
| Also:  |             |          |                             |
| Fiber light cable bndl<br>Ø 3.5 mm, 2.3 m long             | 806635231   | 1        |                             |
| Perforated basket for Morcescope<br>with small part basket | 38012       | 1        |                             |

RICHARD

spirit of excellence

#### **TELESCOPES**

#### **OVERVIEW**



|                                     | Direction of view | Color coding | Ø          | WL     | TL     | Product no. |          |     |  |        |        |            |
|-------------------------------------|-------------------|--------------|------------|--------|--------|-------------|----------|-----|--|--------|--------|------------|
| Telescope 0° Ø 4 mm WL 298 mm       |                   |              |            | 4.0 mm | 298 mm | 365 mm      | 8650.414 |     |  |        |        |            |
| Telescope blue 0° Ø 4 mm WL 298 mm  | 0°                | Blue         | 4.0 111111 | 298 mm | 365 mm | 8650.514**  |          |     |  |        |        |            |
| Telescope 12° Ø 4 mm WL 297 mm      | 12°               | Orange       | 4.0 mm     | 297 mm | 363 mm | 8654.431    |          |     |  |        |        |            |
| Telescope blue 12° Ø 4 mm WL 298 mm | 12                | Orange       | 4.0 mm     | 298 mm | 363 mm | 8654.531**  |          |     |  |        |        |            |
| Telescope 30° Ø 4 mm WL 300 mm      | 30°               |              | 4.0 mm     | 300 mm | 364 mm | 8654.422    |          |     |  |        |        |            |
| Telescope blue 30° Ø 4 mm WL 299 mm |                   | 30°          | 30°        | 30°    | 30°    | 30°         | Dod      | Red |  | 299 mm | 364 mm | 8654.522** |
| Telescope 30° Ø 3.3 mm WL 299 mm    |                   |              |            |        |        |             |          |     |  |        |        |            |
| Telescope 25° Ø 4 mm WL 342 mm      | 25°               |              | 4.0 mm     | 342 mm | 404 mm | 8668.433*   |          |     |  |        |        |            |
| Telescope 70° Ø 4 mm WL 302 mm      | 70°               |              | 4.0 mm     | 302 mm | 364 mm | 8650.415    |          |     |  |        |        |            |
| Telescope blue 70° Ø 4 mm WL 303 mm | 70                | Tellow       | 4.0 111111 | 303 mm | 364 mm | 8650.515**  |          |     |  |        |        |            |

<sup>\*</sup> Only available in 25°.

The PANOVIEW telescopes are marked "blue" to distinguish them and they can also be used with your existing PDD system, of course.

| Recommended accessories  |  | Product no. |
|--|--|-------------|
| Perforated basket for standard telescope 2   | Internal dimensions (W x H x D): 454 x 52 x 40 mm<br>External dimensions (W x H x D): 481 x 54 x 59 mm | 38016       |
| Fiber light cable bndl<br>consisting of:<br>Fiber light cable (80662523), projector-side adapter (8095.07),<br>and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long   | 806625231   |

<sup>\*\*</sup> We have adapted our PANOVIEW telescopes to our new, high-performance blue PDD system.

#### **OPTICAL URETHROTOME 8667**



FOR TELESCOPE 4 MM, 0°



| for optically controlled slitting of urethral strictures.  | Product no. |
|--|-------------|
| Sheath for urethrotome 20.5 Fr SL 195 mm, with instrument port for lateral catheter insertion (4 Fr)       | 8667.011    |
| Obturator for urethrotome 20.5 Fr WL 231 mm, oval, cannulated, distal end rounded                          | 8667.111    |
| Outer sheath for urethrotome 20.5 Fr SL 187 mm, oval, laterally open, for placing a 16 Fr balloon catheter | 8667.161    |
| Adapter for cystoscope with 1 instrument port, max. capacity 10 Fr, TL 79 mm                               | 8652.264    |
| Working element, urethrotome, passive 0/12° Receptacle for stricture scalpels                              | 8667.911    |

| Telescope                     | Direction of view | Ø    | WL     | TL     | Product no. |  |
|-------------------------------|-------------------|------|--------|--------|-------------|--|
| Telescope 0° Ø 4 mm WL 298 mm | 0°                | 4 mm | 298 mm | 365 mm | 8650.414 H  |  |

| Recommended accessories   |  | Product no. |
|---|--|-------------|
| Perforated basket for standard telescope 2  | Internal dimensions (W x H x D): 454 x 52 x 40 mm<br>External dimensions (W x H x D): 481 x 54 x 59 mm | 38016       |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long   | 806625231   |
| Stricture scalpels  |  | see URO21   |

## STRICTURE SCALPELS

#### FOR OPTICAL URETHROTOME 8667

| Stricture scalpels with ceramic cutter   |  | Cutting edge                  | Product no.             |
|--|--|-------------------------------|-------------------------|
| Solid sheath   | Scalpel 20.5 Fr ceramic, semi-circular                         | Semi-circular                 | 8667.961                |
| Sheath with central bore hole (for 4 Fr ureteral catheter)                             | Scalpel 20.5 Fr ceramic, semi-circular                         | Semi-circular                 | 8667.966                |
| Sheath with central bore hole (for 4 Fr ureteral catheter)                             | Scalpel 20.5 Fr ceramic, shark fin                             | Shark fin for narrow stenoses | 8667.971                |
| Solid sheath   | Scalpel 20.5 Fr ceramic, lancet-shaped                         | Lancet-shaped                 | 8667.981                |
|  |  |                               |                         |
| Stricture scalpels (steel)   |  | Cutting edge                  | Product no.             |
| Stricture scalpels (steel)  Sheath with central bore hole (for 4 Fr ureteral catheter) | Scalpel 20.5 Fr, semi-circular                                 | Cutting edge Semi-circular    | Product no.<br>8667.965 |
| Sheath with central bore hole  | Scalpel 20.5 Fr, semi-circular  Scalpel 20.5 Fr, semi-circular |                               |                         |
| Sheath with central bore hole (for 4 Fr ureteral catheter)                             |  | Semi-circular                 | 8667.965                |

| Recommended accessories  |                              | Product no. |
|--|------------------------------|-------------|
| Protective sterilization sleeve Receptacle for max. 5 electrodes, reusable | AUTOGLAVE<br>134° C / 273° F | 33030       |



## OPTICAL MINI URETHROTOME



FOR TELESCOPE 3.3 MM, 0°



| for optically controlled slitting of urethral strictures.   | Product no. |
|---|-------------|
| Sheath for urethrotome 16.5 Fr with supply and drain stopcock, lateral instrument port (4 Fr), distal end slanted, and automatic lock | 8670.011    |
| Obturator for urethrotome 16.5 Fr Oval, cannulated, distal end rounded  | 8670.111    |
| Outer sheath for urethrotome 16.5 Fr Oval, laterally open, for placing a 16 Fr balloon catheter                                       | 8670.061    |
| Outer sheath for urethrotome 16.5 Fr Oval, laterally open, for placing a 12 Fr balloon catheter                                       | 8670.161    |
| Working element, urethrotome, passive 0° Receptacle for stricture scalpels  | 8670.911    |
| Also:   |             |

| Telescope                       | Direction of view | Ø      | WL     | TL     | Product no. |        |
|---------------------------------|-------------------|--------|--------|--------|-------------|--------|
| Telescope 0° Ø 3.3 mm WL 297 mm | 0°                | 3.3 mm | 297 mm | 362 mm | 8660.424 H  | D<br>D |

| Recommended accessories  |  | Product no. |
|--|--|-------------|
| Perforated basket for standard telescope 2   | Internal dimensions (W x H x D): 454 x 52 x 40 mm<br>External dimensions (W x H x D): 481 x 54 x 59 mm | 38016       |
| Fiber light cable bndl<br>consisting of:<br>Fiber light cable (80662523), projector-side adapter (8095.07),<br>and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long   | 806625231   |
| Stricture scalpels   |  | see URO23   |



## STRICTURE SCALPELS


#### FOR OPTICAL MINI URETHROTOME 8670

| Stricture scalpels with ceramic cutter                     |  | Cutting edge  | Product no. |
|--|--|---------------|-------------|
| Solid sheath   | Scalpel 16.5 Fr ceramic, semi-circular | Semi-circular | 8670.961    |
| Sheath with central bore hole (for 4 Fr ureteral catheter) | Scalpel 16.5 Fr ceramic, semi-circular | Semi-circular | 8670.966    |
| Sheath with central bore hole (for 4 Fr ureteral catheter) | Scalpel 16.5 Fr ceramic, lancet-shaped | Lancet-shaped | 8670.981    |

| Recommended accessories  |                              | Product no. |
|--|------------------------------|-------------|
| Protective sterilization sleeve Receptacle for max. 5 electrodes, reusable | AUTOGLAVE<br>134° C / 273° F | 33030       |



## URETHROTOME FOR BLIND SLITTING






#### CYSTO-URETHROSCOPE 8650



SHEATH SYSTEMS FOR TELESCOPE 4 MM, 0°, 12°, 30°, 70°, AND ADAPTERS



Sheath for cystoscope bndl

Fr Color coding

Sheath for cystoscope 16 Fr comprising:
Sheath for cystoscope 16 Fr (8650.0145), obturator for cystoscope

16 Fr Yellow

1 x 5\*

8650.0141

Sheath for cystoscope 16 Fr comprising: Sheath for cystoscope 16 Fr (8650.0145), obturator for cystoscope Fr 16 Fr (8650.0147), and tube with LUER-LOCK connector (886.00) Sheath for cystoscope 17.5 Fr comprising: 1 x 5 or 17.5 Sheath for cystoscope 17.5 Fr (8650.0245), obturator for cystoscope 8650.0241 Green 2 x 4 17.5 Fr (8650.0247), and tube with LUER-LOCK connector (886.00) Sheath for cystoscope 19.5 Fr comprising: 1 x 7 or 19.5 8650.0341 Sheath for cystoscope 19.5 Fr (8650.0345), obturator for cystoscope Red Fr 2 x 5 19.5 Fr (8650.0347), and tube with LUER-LOCK connector (886.00) 231 mm Sheath for cystoscope 21 Fr comprising: 21 1 x 10 or Sheath for cystoscope 21 Fr (8650.0445), obturator for cystoscope 8650.0441 Blue Fr 2 x 6 21 Fr (8650.0447), and tube with LUER-LOCK connector (886.00) Sheath for cystoscope 23 Fr comprising: 23 1 x 12 or Sheath for cystoscope 23 Fr (8650.0545), obturator for cystoscope White 8650.0541 Fr 2 x 7 23 Fr (8650.0547), and tube with LUER-LOCK connector (886.00) Sheath for cystoscope 25 Fr comprising: 25 Sheath for cystoscope 25 Fr (8650.0645), obturator for cystoscope Black 1 x 5 8650.0641 25 Fr (8650.0647), and tube with LUER-LOCK connector (886.00)

<sup>\*</sup> Urethroscopic only (cystoscopic only suitable for diagnostics via adapter 8650.254)



| H    | ł |   |
|------|---|---|
| High |   | w |

| PANOVIEW   | Direction of view | ø      | WL     | TL     | Product no. |  |
|--|-------------------|--------|--------|--------|-------------|--|
| Telescope 0° Ø 4 mm WL 298 mm  | 0°                |        | 298 mm | 365 mm | 8650.414    |  |
| Telescope 12° Ø 4 mm WL 297 mm   | 12°               | 4      | 297 mm | 363 mm | 8654.431    |  |
| Telescope 30° Ø 4 mm WL 300 mm   | 30°               | 4 mm   | 300 mm | 364 mm | 8654.422    |  |
| Telescope 70° Ø 4 mm WL 302 mm   | 70°               |        | 302 mm | 364 mm | 8650.415    |  |
| Telescope blue 0° Ø 4 mm WL 298 mm   | 0°                |        | 298 mm | 365 mm | 8650.514    |  |
| Telescope blue 12° Ø 4 mm WL 298 mm  | 12°               | 4 mm - | 298 mm | 363 mm | 8654.531    |  |
| Telescope blue 30° Ø 4 mm WL 299 mm  | 30°               |        | 299 mm | 364 mm | 8654.522    |  |
| Telescope blue 70° Ø 4 mm WL 303 mm  | 70°               |        | 303 mm | 362 mm | 8650.515    |  |
| for individual adapters/sheaths and obturators, see URO26 / for accessories, see URO29—URO30 |                   |        |        |        |             |  |



## CYSTO-URETHROSCOPE 8650



SHEATH SYSTEMS FOR TELESCOPE 4 MM, 0°, 12°, 30°, 70°, AND ADAPTERS

| Individual sheaths and obturators |         |              |                 | Ad          | apters for cystosco                   | ppe                                   |                                       |
|-----------------------------------|---------|--------------|-----------------|-------------|---------------------------------------|---------------------------------------|---------------------------------------|
|                                   |         |              |                 |             | 4.                                    |                                       |                                       |
|                                   |         |              |                 |             | Only for diagnostics                  | 1 instrument port                     | 2 instrument ports                    |
| Individual sheath and obturator   | Fr      | SL/WL        | Color<br>coding | Product no. | Adapter for<br>cystoscope<br>TL 60 mm | Adapter for<br>cystoscope<br>TL 60 mm | Adapter for<br>cystoscope<br>TL 60 mm |
| Sheath for cystoscope 16 Fr       |         | SL<br>231 mm |                 | 8650.0145   |                                       |                                       |                                       |
| Obturator for cystoscope 16 Fr    | 16 Fr   | WL<br>249 mm | Yellow          | 8650.0147   |                                       |                                       |                                       |
| Sheath for cystoscope 17.5 Fr     | 17.5.5  | SL<br>231 mm | 0               | 8650.0245   |                                       |                                       |                                       |
| Obturator for cystoscope 17.5 Fr  | 17.5 Fr | WL<br>249 mm | Green           | 8650.0247   |                                       |                                       |                                       |
| Sheath for cystoscope 19.5 Fr     | 10.5.5  | SL<br>231 mm |                 | 8650.0345   |                                       |                                       |                                       |
| Obturator for cystoscope 19.5 Fr  | 19.5 Fr | WL<br>251 mm | Red             | 8650.0347   |                                       | 0/50 0/4                              | 0/50.004                              |
| Sheath for cystoscope 21 Fr       | 03.5    | SL<br>231 mm | DI.             | 8650.0445   | 8650.254                              | 8650.264                              | 8650.284                              |
| Obturator for cystoscope 21 Fr    | - 21 Fr | WL<br>249 mm | Blue            | 8650.0447   |                                       |                                       |                                       |
| Sheath for cystoscope 23 Fr       | 02.5    | SL<br>231 mm | \A/L:4-         | 8650.0545   |                                       |                                       |                                       |
| Obturator for cystoscope 23 Fr    | 23 Fr   | WL<br>249 mm | White           | 8650.0547   |                                       |                                       |                                       |
| Sheath for cystoscope 25 Fr       | 05.5    | SL<br>231 mm | Die             | 8650.0645   |                                       |                                       |                                       |
| Obturator for cystoscope 25 Fr    | 25 Fr   | WL<br>249 mm | Black           | 8650.0647   |                                       |                                       |                                       |

| Recommended accessories   |  | Product no. |
|---|--|-------------|
| Perforated basket for standard telescope 2  | Internal dimensions (W x H x D): 454 x 52 x 40 mm<br>External dimensions (W x H x D): 481 x 54 x 59 mm | 38016       |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long   | 806625231   |



#### CYSTO-URETHROSCOPE 8650



SHEATH SYSTEMS FOR TELESCOPE 4 MM, 30°, 70°, AND INSERTS WITH ALBARRÁN LEVER



|        | @L/<br><b>/ 27</b> |  |
|--------|--------------------|--|
| a alba |                    |  |

| Sheath for cystoscope bndl  | Fr         | Color<br>coding | SL         | Capacity<br>in Fr  | Product no. |
|---|------------|-----------------|------------|--------------------|-------------|
| Sheath for cystoscope 17.5 Fr comprising: Sheath for cystoscope 17.5 Fr (8650.0245), obturator for cystoscope 17.5 Fr (8650.0247), and tube with LUER-LOCK connector (886.00)       | 17.5<br>Fr | Green           |            | 1 x 5 or<br>2 x 4  | 8650.0241   |
| Sheath for cystoscope 19.5 Fr comprising:<br>Sheath for cystoscope 19.5 Fr (8650.0345), obturator for cystoscope<br>19.5 Fr (8650.0347), and tube with LUER-LOCK connector (886.00) | 19.5<br>Fr | Red             | 231 mm     | 1 x 7 or<br>2 x 5  | 8650.0341   |
| Sheath for cystoscope 21 Fr comprising: Sheath for cystoscope 21 Fr (8650.0445), obturator for cystoscope 21 Fr (8650.0447), and tube with LUER-LOCK connector (886.00)             | 21<br>Fr   | Blue            | 231 111111 | 1 x 10 or<br>2 x 6 | 8650.0441   |
| Sheath for cystoscope 23 Fr comprising: Sheath for cystoscope 23 Fr (8650.0545), obturator for cystoscope 23 Fr (8650.0547), and tube with LUER-LOCK connector (886.00)             | 23<br>Fr   | White           |            | 1 x 12 or<br>2 x 7 | 8650.0541   |

Ø

4 mm

4 mm

WL

300 mm

302 mm

299 mm

303 mm

TL

364 mm

364 mm

364 mm

362 mm

**Direction of view** 

30°

70°

30°

70°

Telescope 30° Ø 4 mm WL 300 mm

Telescope 70° Ø 4 mm WL 302 mm

Telescope blue 30° Ø 4 mm WL 299 mm

Telescope blue 70° Ø 4 mm WL 303 mm

**PANOVIEW** 



8650.515

HD

| adapters/sheaths |  |
|------------------|--|

| Recommended accessories  |  | Product no. |
|--|--|-------------|
| Perforated basket for standard telescope 2   | Internal dimensions (W x H x D): 454 x 52 x 40 mm<br>External dimensions (W x H x D): 481 x 54 x 59 mm | 38016       |
| Fiber light cable bndl<br>consisting of:<br>Fiber light cable (80662523), projector-side adapter (8095.07),<br>and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long   | 806625231   |

**URO27** 



| IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

## CYSTO-URETHROSCOPE 8650




SHEATH SYSTEMS FOR TELESCOPE 4 MM, 30°, 70°, AND INSERTS WITH ALBARRÁN LEVER

| Individual sheaths and obturators |         |              |                 |             |                                     |                                       |
|-----------------------------------|---------|--------------|-----------------|-------------|-------------------------------------|---------------------------------------|
|                                   |         |              |                 |             |                                     |                                       |
|                                   |         |              |                 |             | 1 instrument port                   | 2 instrument ports                    |
| Individual sheath and obturator   | Fr      | SL/WL        | Color<br>coding | Product no. | Working insert for cystoscope 30/70 | Working insert for cystoscope 0/30/70 |
| Sheath for cystoscope 17.5 Fr     | 17.5 Fr | SL<br>231 mm | Groon           | 8650.0245   |                                     |                                       |
| Obturator for cystoscope 17.5 Fr  | 17.5 FI | WL<br>249 mm | Green           | 8650.0247   |                                     |                                       |
| Sheath for cystoscope 19.5 Fr     | 19.5 Fr | SL<br>231 mm | Red             | 8650.0345   |                                     |                                       |
| Obturator for cystoscope 19.5 Fr  | 17.511  | WL<br>251 mm | Keu             | 8650.0347   | 9450 214                            |                                       |
| Sheath for cystoscope 21 Fr       | 21 Fr   | SL<br>231 mm | Blue            | 8650.0445   | 8650.214                            | 8650.204                              |
| Obturator for cystoscope 21 Fr    | ZIF     | WL<br>249 mm | Blue            | 8650.0447   |                                     |                                       |
| Sheath for cystoscope 23 Fr       | 00.5-   | SL<br>231 mm | \A/IL !±-       | 8650.0545   |                                     |                                       |
| Obturator for cystoscope 23 Fr    | 23 Fr   | WL<br>249 mm | White           | 8650.0547   |                                     |                                       |



#### OPTICAL FORCEPS AND SCISSORS

FOR CYSTO-URETHROSCOPE 8650 WITH TELESCOPE 4 MM, 0°




| for cysto-urethroscop | e <b>865</b> 0 with telescop           | e 4 mm, 0°  | Suitable for sheaths from | Product no. |
|-----------------------|--|---|---------------------------|-------------|
| <b>%</b>              | Opt. coag. biopsy<br>forceps<br>Tauber | for combined biopsy and hemostasis.  Particularly suitable for bladder mapping and quadrant biopsies. Immediate hemostasis without changing instruments or performing a time-consuming reorientation. | 21 Fr                     | 8650.624    |



IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

#### **VIEWING OBTURATORS**

#### FOR INSERTING THE SHEATH WHILE VIEWING FOR 4 MM TELESCOPES FrOM 0° TO 30°




| Recommended accessories | Product no.    |
|-------------------------|----------------|
| HF connection cable     | see UR0103/104 |



#### **MIDI-SIZE**

#### CYSTO-URETHROSCOPE



## 

#### spirit of excellence

IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

## **MIDI-SIZE**


#### FLEXIBLE AUXILIARY INSTRUMENTS

|  |                                       | WL     | TL     | Fr | Product no. |
|--|---------------------------------------|--------|--------|----|-------------|
|  | Flex. biopsy forceps 5 Fr WL 315 mm   | 315 mm | 465 mm | 5  | 829.05      |
|  | Flex. biopsy forceps 7 Fr WL 375 mm   | 375 mm | 490 mm | 7  | 829.07      |
|  | Flex. grasping forceps 5 Fr WL 315 mm | 315 mm | 465 mm | 5  | 828.05      |
|  | Flex. grasping forceps 7 Fr WL 365 mm | 365 mm | 515 mm | 7  | 828.07      |
|  | Flex. scissors 7 Fr WL 375 mm         | 375 mm | 490    | 7  | 830.07      |



## ATRAUMATIC COMPACT CYSTO-URETHROSCOPE

14/17 Fr, 25° AND ADAPTERS



|  | Direction  |        |        |       | Working o                 | channel |             |
|--|------------|--------|--------|-------|---------------------------|---------|-------------|
|  | of view WL |        |        |       | for auxiliary instruments | Shape   | Product no. |
| Cystoscope 25° 14 Fr WL 218 mm with straight eyepiece, atraumatically shaped tip | 25°        | 218 mm | 358 mm | 14 Fr | Up to<br>5 Fr             | Oval    | 8642.403    |
| Cystoscope 25° 17 Fr WL 224 mm with straight eyepiece, atraumatically shaped tip | 25°        | 224 mm | 364 mm | 17 Fr | Up to<br>7 Fr             | Oval    | 8645.403    |
| Also:  |            |        |        |       |                           |         |             |

| 71100.                  |                                       |        |        |    |             |
|-------------------------|---------------------------------------|--------|--------|----|-------------|
|                         |                                       | WL     | TL     | Fr | Product no. |
|                         | Flex. biopsy forceps 7 Fr WL 375 mm   | 375 mm | 490 mm | 7  | 829.07      |
|                         | Flex. biopsy forceps 5 Fr WL 315 mm   | 315 mm | 465 mm | 5  | 829.05      |
|                         | Flex. grasping forceps 7 Fr WL 365 mm | 365 mm | 515 mm | 7  | 828.07      |
|                         | Flex. grasping forceps 5 Fr WL 315 mm | 315 mm | 465 mm | 5  | 828.05      |
|                         | Flex. scissors 7 Fr WL 375 mm         | 375 mm | 490 mm | 7  | 830.07      |
| =                       | Coag. electrode mono 6 Fr WL 400 mm   | 400 mm | -      | 6  | 823.06      |
| Electrode shape: button | Coag. electrode mono 5 Fr WL 400 mm   | 400 mm | -      | 5  | 823.05      |

| Recommended accessories   |  | Product no. |
|---|--|-------------|
| Perforated basket for cysto-urethroscope  | Internal dimensions (W x H x D): 435 x 54 x 73 mm<br>External dimensions (W x H x D): 451 x 64 x 80 mm | 38013       |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long   | 806625231   |



IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

#### FORCEPS AND SCISSORS

## SMALL MODULAR SYSTEM **HySafe**

FOR ATRAUMATIC COMPACT CYSTO-URETHROSCOPES 14/17 Fr, 25°

| Grasping forceps jaw insert with                         | ı sheath    |    |        | Handle with overload protection | Complete instrument  • Jaw section |
|--|-------------|----|--------|---------------------------------|------------------------------------|
|  | n           | _  |        |                                 | • Handle                           |
|  | Product no. | Fr | WL     | 8083.001                        | Product no.                        |
| Grasping forceps bndl Distal angled with pike-mouth jaws | 8642.6508   | 5  | 340 mm | •                               | 8642.6502                          |
|  | 8645.6508   | 7  | 325 mm | •                               | 8645.6502                          |
| Grasping forceps bndl - Spoon                            | 8642.6008   | 5  | 340 mm | •                               | 8642.6002                          |
|  | 8645.6008   | 7  | 340 mm | •                               | 8645.6002                          |
| Biopsy forceps bndl                                      | 8642.6318   | 5  | 340 mm | •                               | 8642.6312                          |
| Scissors bndl  | 8642.6818   | 5  | 340 mm | •                               | 8642.6812                          |
| Grasping forceps bndl                                    | 8968.6808   | 6  | 425 mm | •                               | 8968.6802                          |


FLEXIBLE FIBER CYSTOSCOPES



spirit of excellence

## FLEXIBLE FIBER CYSTOSCOPES 5 MM/15 Fr

CHANNEL 2.5 MM/7.5 Fr



|  | Outer Ø | Working<br>channel | WL     | Control lever in distal<br>direction – articulation<br>downward | Control lever in distal<br>direction – articulation<br>upward | Product no. |
|--|---------|--------------------|--------|---|---|-------------|
| Fiber cystoscope 15 Fr<br>WL 400 mm  |         |                    |        | •   |   | 7305.001    |
| Slanted distal tip Articulation +210°/-150° Direction of view 0°, angle of view 110°   | 15 Fr   | 7.5 Fr             | 400 mm |   | •   | 7305.006    |
| Fiber cystoscope bndl  consisting of: Fiber cystoscope 15 Fr WL 400 mm (7305.001)  Adapter with 2 irrigation valves and 1 instrument port (7305.782)Leakage tester for flex. endoscopes (163.903)  Pressure equalization valve (163.904)  Cleaning brush Ø 3 mm, TL 1,200 mm (Pack = 10 PCS) (7990002)   |         |                    | •      |   | 730500111   |             |
| Fiber cystoscope bndl  consisting of: Fiber cystoscope 15 Fr WL 400 mm (7305.006)  Adapter with 2 irrigation valves and 1 instrument port (7305.782)  Leakage tester for flex. endoscopes (163.903)  Pressure equalization valve (163.904)  Cleaning brush Ø 3 mm, TL 1,200 mm (Pack = 10 PCS) (7990002) |         |                    |        | •   | 730500611   |             |

| Recommended accessories   |                                 | Product no. |
|---|---------------------------------|-------------|
| Fiber light cable bndl consisting of: Fiber light cable Ø 2.5 mm, TL 2.3 m (80662523), projector-side adapter (8095.07), and endoscope- | Ø 2.5 mm, 2.3 m long            | 806625231   |
| Perforated basket for flexible endoscopes   | (W x H x D): 448 x 106 x 288 mm | 33016       |
| Also: fixing ring Ø 50.39 mm  |                                 | 643301261   |



IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

## FLEXIBLE FIBER CYSTOSCOPES 5 MM/15 Fr

#### TECHNICAL DATA/AUXILIARY INSTRUMENTS

| Fiber cystoscope 15 Fr WL 400 mm    | 7305.001/7305.006          |
|-------------------------------------|----------------------------|
| Distal tip                          | Slanted distal tip         |
| Sheath diameter                     | 15 Fr                      |
| Number of working channels          | 1                          |
| Working/irrigation channel diameter | 7.5 Fr                     |
| Articulation                        | 210° upward, 150° downward |
| Working length                      | 400 mm                     |
| Angle of view                       | 110°                       |
| Direction of view                   | 0°                         |

| Auxiliary instruments |  | Outer Ø          | WL     | TL     | Product no. |
|-----------------------|--|------------------|--------|--------|-------------|
|                       | Flex. biopsy forceps 5 Fr WL 550 mm         1.6 mm         5 Fr         550 mm         7 |                  |        |        | 829.051     |
|                       | Flex. grasping forceps 5 Fr WL 550 mm  | 1.6 mm<br>5 Fr   | 550 mm | 680 mm | 8735.685    |
|                       | Flex. grasping forceps 6.6 Fr WL 550 mm  | 2.0 mm<br>6.6 Fr | 550 mm | 690 mm | 8736.685    |
|                       | Adapter with 2 Luer connections, male, quick-release mec                                 | 7305.781         |        |        |             |
|                       | Adapter with 2 irrigation valves and 1 instrument port, quice                            | 7305.782         |        |        |             |
| 1                     | Also:<br>Luer sealing cap  | 15023205         |        |        |             |
|                       | RIWO rubber cap, capacity 0.8 mm   | 88.01            |        |        |             |
|                       | Universal sealing valve 1–6 Fr<br>for inserting auxiliary instruments of 1–6 Fr          | 4712348          |        |        |             |

"VISION EF" FLEXIBLE SENSOR CYSTOSCOPES



spirit of excellence

# vision EF FLEXIBLE 1-CHANNEL SENSOR CYSTOSCOPES



|   | Outer Ø                     | Working<br>channel | WL        | Control lever in distal<br>direction – articulation<br>downward | Control lever in distal<br>direction – articulation<br>upward | Product no. |
|---|-----------------------------|--------------------|-----------|---|---|-------------|
| Sensor cystoscope 16.2 Fr<br>WL 400 mm<br>Slanted distal tip  | 16.2 Fr                     | 7.5 Fr             | 400 mm    | •   |   | 73151001    |
| Articulation +210°/-210°<br>Direction of view 0°,<br>angle of view 110°   | 10.211                      | 7.011              | 400 IIIII |   | •   | 73151006    |
| Sensor cystoscope bndl consisting of: Sensor cystoscope 16.2 Fr, WL 400 mi leakage tester for flex. endoscopes (16 pressure equalization valve (163.904) cleaning brush Ø 5 mm, TL 1,200 mm | 33.903),<br>), Luer sealing | cap (150232        | ,         | •   |   | 731510012   |
| Fiber cystoscope bndl consisting of: Sensor cystoscope 16.2 Fr, WL 400 mi leakage tester for flex. endoscopes (16 pressure equalization valve (163.904) cleaning brush Ø 5 mm, TL 1,200 mm  | 33.903),<br>), Luer sealing | cap (150232        |           |   | •   | 731510062   |

| Recommended accessories  |                                 | Product no. |
|--|---------------------------------|-------------|
| <b>Fiber light cable bndl</b> consisting of:<br>Fiber light cable Ø 2.5 mm,TL 2.3 m (80662523),<br>projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long            | 806625231   |
| Perforated basket for flexible endoscopes  | (W x H x D): 448 x 106 x 288 mm | 33016       |
| Also: fixing ring Ø 50.39 mm   |                                 | 643301261   |
| Flexible auxiliary instruments   |                                 | see URO39   |



# vision EF FLEXIBLE SENSOR CYSTOSCOPES

# TECHNICAL DATA

| Sensor cystoscope 16.2 Fr WL 400 mm  | 73151001/73151006   |
|--|---|
| Distal tip   | Cylindrical, atraumatic, slanted plastic tip 11.5 Fr  |
| Sheath diameter  | 16.2 Fr   |
| Number of working channels   | 1   |
| Working/irrigation channel diameter  | 7.5 Fr  |
| Articulation   | 210° upward, 210° downward  |
| Working length   | 400 mm  |
| Angle of view  | 110°  |
| Illumination   | Two distally integrated LEDs  |
| Handle   | Ergonomic handle design with axial cable outlet   |
| Positioning of the working and irrigation channel in relation to the picture | At 3 o'clock  |
| Endopicture  | Octagonal, detail enhancement, automatic white balance, and brightness control, no focusing necessary |
| Cable length   | 2.5 m   |



# **vision EF**FLEXIBLE SENSOR CYSTOSCOPES

# **AUXILIARY INSTRUMENTS**

|   |   | Outer Ø        | WL     | ΤL     | Product no. |
|---|---|----------------|--------|--------|-------------|
|   | Flex. biopsy forceps 5 Fr WL 550 mm   | 1.6 mm<br>5 Fr | 550 mm | 700 mm | 829.051     |
|   | Flex. grasping forceps 5 Fr WL 550 mm   | 1.6 mm<br>5 Fr | 550 mm | 680 mm | 8735.685    |
|   | Adapter with 2 irrigation valves and 1 instrument port, quick-                  | 7305.782       |        |        |             |
|   | Also: Luer sealing cap  | 15023205       |        |        |             |
| • | RIWO rubber cap, capacity 0.8 mm  | 88.01          |        |        |             |
|   | Universal sealing valve 1–6 Fr<br>for inserting auxiliary instruments of 1–6 Fr | 4712348        |        |        |             |
|   | Adapter for machine leakage tests   |                |        |        | 163.905     |


"VISION EF" FLEXIBLE SENSOR CYSTOSCOPES



IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# **Mana**FLEXIBLE SENSOR CYSTOSCOPES

# FOR ENDOCAM Logic 4K CONTROLLER



|  | Outer Ø                     | channel       | WL         | direction – articulation downward | upward | Product no. |
|--|-----------------------------|---------------|------------|-----------------------------------|--------|-------------|
| Sensor cystoscope<br>16.2 Fr WL 400 mm<br>Slanted distal tip   | 16.2 Fr                     | 7.5 Fr        | 400 mm     | •                                 |        | 7315001     |
| Articulation +210°/-210°  Direction of view 0°,  angle of view 110°  | 10.211                      | 7.511         | 400 111111 |                                   | •      | 7315006     |
| Sensor cystoscope bndl consisting of: Sensor cystoscope 16.2 Fr, WL 400 m leakage tester for flex. endoscopes (16.2 pressure equalization valve (163.904 cleaning brush Ø 5 mm, TL 1,200 mm              | 63.903),<br>), Luer sealing | j cap (15023) | ,          | •                                 |        | 73150012    |
| Sensor cystoscope bndl<br>consisting of:<br>Sensor cystoscope 16.2 Fr, WL 400 m<br>leakage tester for flex. endoscopes (16<br>pressure equalization valve (163.904<br>cleaning brush Ø 5 mm, TL 1,200 mm | 63.903),<br>), Luer sealing | y cap (15023) | ,          |                                   | •      | 73150062    |

| Recommended accessories  |                                 | Product no. |
|--|---------------------------------|-------------|
| Fiber light cable bndl consisting of: Fiber light cable Ø 2.5 mm, TL 2.3 m (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long            | 806625231   |
| Perforated basket for flexible endoscopes  | (W x H x D): 448 x 106 x 288 mm | 33016       |
| Also: fixing ring Ø 50.39 mm   |                                 | 643301261   |
| Flexible auxiliary instruments   |                                 | see URO42   |



"MAMBA" FLEXIBLE SENSOR CYSTOSCOPES

# Mamaa FLEXIBLE SENSOR CYSTOSCOPE

# TECHNICAL DATA

| Sensor cystoscope 16.2 Fr WL 400 mm  | 7315001/7315006   |
|--|---|
| Distal tip   | 11.5 Fr, atraumatic tip made of plastic, two distally integrated LEDs   |
| Sheath diameter  | 16.2 Fr   |
| Number of working channels   | 1   |
| Working/irrigation channel diameter  | 7.5 Fr  |
| Articulation   | 210° upward, 210° downward  |
| Working length   | 400 mm  |
| Angle of view  | 110°  |
| Handle   | Ergonomic handle design with axial cable outlet   |
| Positioning of the working and irrigation channel in relation to the picture | At 3 o'clock  |
| Endopicture  | Octagonal, 3 levels of detail magnification, and 6x digital zoom; automatic white balance, light control, and focus |
| Compatible camera control unit   | ENDOCAM Logic 4K ENDOCAM Logic HD   |

| Required video equipment   |  | Product no. |
|--|--|-------------|
| S) billion in the second of th | ENDOCAM Logic 4K camera control unit bndl consisting of: ENDOCAM Logic 4K camera control unit (5525301) Handheld remote control (5525401) 1x USB flash memory 32 GB (72321829) 1x HDMI/HDMI cable, lockable, 3.0 m (103847) 1x power cable (2440.03) | 55253011    |

# FLEXIBLE SENSOR CYSTOSCOPE

# ACCESSORIES AND AUXILIARY INSTRUMENTS

|      |   | Outer Ø        | WL     | TL     | Product no. |
|------|---|----------------|--------|--------|-------------|
|      | Flex. biopsy forceps 5 Fr WL 550 mm   | 1.6 mm<br>5 Fr | 550 mm | 700 mm | 829.051     |
|      | Flex. grasping forceps 5 Fr WL 550 mm   | 1.6 mm<br>5 Fr | 550 mm | 700 mm | 828.051     |
| -45- | Adapter with 2 irrigation valves and 1 instrument port, quick                 | 7305.782       |        |        |             |
|      | Also: Luer sealing cap  | 15023205       |        |        |             |
|      | RIWO rubber cap, capacity 0.8 mm  | 88.01          |        |        |             |
|      | for inserting auxiliary instruments of 1–6 Fr  Universal sealing valve 1–6 Fr | 4712348        |        |        |             |
|      | Adapter for machine leakage tests   |                |        |        | 163.905     |

# System blue SYSTEM COMPONENTS

IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

FOR PHOTODYNAMIC DIAGNOSTICS (PDD)



|   |                  |               |        | Product no. |
|---|------------------|---------------|--------|-------------|
| ENDOLIGHT LED blue bndl consisting of: ENDOLIGHT LED blue (5165001), patch cable, RJ45 SFTP, 0.5 m (72325378), and power cable 3 m long (2440.03)   | toggle footswitc | h (2030.105), |        | 51650011    |
| ENDOCAM Logic 4K camera control unit bndl consisting of: ENDOCAM Logic 4K camera control unit (5525301), handheld remote control USB flash memory 32 GB (72321829), HDMI/HDMI cable, lockable, 3.0 m (103 | 55253011         |               |        |             |
| ENDOCAM Logic HD Pendual camera head blue<br>Cable length 3 m   | 5525833          |               |        |             |
| Also:   |                  |               |        |             |
| PANOVIEW  | Ø                | WL            | TL     | Product no. |
| Tologopa blue 0° Ø 4 mm WI 209 mm   |                  | 200 mm        | 265 mm | 9450 514    |

| PANOVIEW   | Ø      | WL     | TL     | Product no. |
|--|--------|--------|--------|-------------|
| Telescope blue 0° Ø 4 mm WL 298 mm   |        | 298 mm | 365 mm | 8650.514    |
| Telescope blue 12° Ø 4 mm WL 298 mm  | 4.0    | 298 mm | 363 mm | 8654.531    |
| Telescope blue 30° Ø 4 mm WL 299 mm  | 4.0 mm | 299 mm | 364 mm | 8654.522    |
| Telescope blue 70° Ø 4 mm WL 303 mm  |        | 303 mm | 362 mm | 8650.515    |
| Special fiber light cable 3.5 mm, 2.3 m set consisting of: Fiber light cable blue Ø 3.5 mm (80673523), endoscope-side adapter (809509) | 3.5 mm |        | 2.3 m  | 806735231   |




# System blue

# SYSTEM COMPONENTS FOR PHOTODYNAMIC DIAGNOSTICS (PDD) CYSTOSCOPY

| Cystoscopy  | Product no.                                  |           |  |  |
|---|--|-----------|--|--|
| Recommendation: PDD cysto-urethroscope with adapter |  |           |  |  |
|   | PANOVIEW telescope blue 70° Ø 4 mm WL 303 mm | 8650.515  |  |  |
|   | Adapter for cystoscope                       | 8650.284  |  |  |
|   | Sheath for cystoscope 19.5 Fr                | 8650.0341 |  |  |
|   | Obturator for cystoscope 19.5 Fr             | 8650.0347 |  |  |



### FOR RESECTOSCOPES TELESCOPE 4 MM, 0°, 12°, 30°



|                                     | Direction of view | Color coding | Ø          | WL     | TL     | Product no. |          |          |            |
|-------------------------------------|-------------------|--------------|------------|--------|--------|-------------|----------|----------|------------|
| Telescope 0° Ø 4 mm WL 298 mm       | . O°              | Blue         | 4.0 mm     | 298 mm | 365 mm | 8650.414    |          |          |            |
| Telescope blue 0° Ø 4 mm WL 298 mm  | U                 | blue         | 4.0 mm     | 298 mm | 365 mm | 8650.514**  |          |          |            |
| Telescope 12° Ø 4 mm WL 297 mm      | - 12°             | Orange       | 4.0 mm     | 297 mm | 363 mm | 8654.431    |          |          |            |
| Telescope blue 12° Ø 4 mm WL 298 mm | 12                | Orange       | 4.0 111111 | 298 mm | 363 mm | 8654.531**  |          |          |            |
| Telescope 30° Ø 4 mm WL 300 mm      |                   | Red          | Red        | 4.0 mm | 300 mm | 364 mm      | 8654.422 |          |            |
| Telescope blue 30° Ø 4 mm WL 299 mm | 30°               |              |            | Red    | Pod    | 4.0 111111  | 299 mm   | 364 mm   | 8654.522** |
| Telescope 30° Ø 3.3 mm WL 299 mm    |                   |              |            |        | 3.3 mm | 299 mm      | 360 mm   | 8656.422 |            |
| Telescope 25° Ø 4 mm WL 342 mm      | 25°               |              | 4.0 mm     | 342 mm | 404 mm | 8668.433*   |          |          |            |
| Telescope 70° Ø 4 mm WL 302 mm      | 70°               | Yellow       |            | 4.0 mm | 302 mm | 364 mm      | 8650.415 |          |            |
| Telescope blue 70° Ø 4 mm WL 303 mm | 70                | -Tellow-     | 4.0 111111 | 303 mm | 364 mm | 8650.515**  |          |          |            |


<sup>\*</sup> Only available in 25°.

The PANOVIEW telescopes are marked "blue" to distinguish them and they can also be used with your existing PDD system, of course.

| Recommended accessories  |  | Product no. |
|--|--|-------------|
| Perforated basket for standard telescope 2   | Internal dimensions (W x H x D): 454 x 52 x 40 mm<br>External dimensions (W x H x D): 481 x 54 x 59 mm | 38016       |
| Fiber light cable bndl<br>consisting of:<br>Fiber light cable (80662523), projector-side adapter (8095.07),<br>and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long   | 806625231   |

"SHARK" RESECTOSCOPES (MONOPOLAR/BIPOLAR)

 $<sup>\</sup>ensuremath{^{**}}$  We have adapted our PANOVIEW telescopes to our new, high-performance blue PDD system.



Sheath size

22/24 Fr

24 Fr

24/26 Fr

26 Fr

Direction of vi

0° 12° 30°

CI = continuous irrigation II = intermittent irrigation

CI

CI



#### Sheaths for continuous irrigation



#### Sheaths for intermittent irrigation




\* Not suitable for 22/24 Fr Double sheath system

#### Monopolar working elements

|      | Ac                       | tive                                  | Pas         | sive          |
|------|--------------------------|---------------------------------------|-------------|---------------|
|      | Handle closed            | Handle closed with comfort thumb rest | Handle open | Handle closed |
| riew | 000                      |                                       |             |               |
|      | 8681205*                 | -                                     | 8681224*    | -             |
|      | 8674205                  | 8674234                               | 8674224     | 8674225       |
|      | Spare rubber cap, red (  | Pack = 5 pcs)                         | <br>        | 8874          |
|      | Thumb ring with relative | ly large inner diameter               | <br>        | 15008.159     |

IX23 || Subject to modifications. Please note that some products may not be available in all countries. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.





#### **Obturators**

| Obturator | Viewing obturator | Dilatations obturator |
|-----------|-------------------|-----------------------|
|           |                   |                       |
|           | 53.               | €                     |
| 8673022   | 8673122           | -                     |
| 8673024   | 8673124           | 8673224               |
| 8673026   | 8673126           | 8673226               |

# Telescopes, Ø 4 mm

| Standard                           | PDD       |
|------------------------------------|-----------|
|                                    |           |
| 8650.414                           | 8650.514  |
| 8654.431                           | 8654.531  |
| 8654.422                           | 8654.522  |
| Fiber light cable 2.5 mm 3.0 m set | 806625301 |

Sheath size

22/24 Fr

24 Fr

24/26 Fr

26 Fr

CI

CI

**Shark** 



# Sheaths for continuous irrigation

# CI Double sheath system Outer sheath Inner sheath 8675424 8675322 8675426 8675324

#### Sheaths for intermittent irrigation



#### **Bipolar working elements**


| Ac                                     | Active                 |  | Pas         | ssive         |
|--|------------------------|--|-------------|---------------|
| Handle closed                          | Handle open            |  | Handle open | Handle closed |
| 70                                     |                        |  |             |               |
| 8680.205                               | 8680.204               |  | 8680.224    | 8680.225      |
| Spare rubber cap, black (Pack = 5 pcs) |                        |  |             |               |
| Thumb ring with relative               | y large inner diameter |  |             | 15008.159     |

Direction of view 0° 12° 30°

CI = continuous irrigation

= intermittent irrigation





#### **Obturators**

| Obturator | Viewing obturator | Dilatations obturator |
|-----------|-------------------|-----------------------|
|           |                   |                       |
|           | 53.               | €                     |
| 8673022   | 8673122           | -                     |
| 8673024   | 8673124           | 8673224               |
| 8673026   | 8673126           | 8673226               |

# Telescopes, Ø 4 mm

| Standard                           | PDD       |
|------------------------------------|-----------|
|                                    |           |
| 8650.414                           | 8650.514  |
| 8654.431                           | 8654.531  |
| 8654.422                           | 8654.522  |
| Fiber light cable 2.5 mm 3.0 m set | 806625301 |

# **Shark**MONOPOLAR RESECTOSCOPE




spirit of excellence

X23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with

contact partner or directly with Richard Wolf GmbH

FOR TELESCOPE 4 MM, 0°, 12°, 30° WITH CONTINUOUS IRRIGATION DOUBLE SHEATH SYSTEM FOR RESECTION IN SALINE SOLUTION







# FOR TELESCOPE 4 MM, 0°, 12°, 30° WITH INTERMITTENT IRRIGATION AND ROTATABLE IRRIGATION ADAPTER FOR RESECTION IN SALINE SOLUTION




'SHARK" RESECTOSCOPES (MONOPOLAR/BIPOLAR)



# MONOPOLAR RESECTOSCOPE


FOR TELESCOPE 4 MM, 0°, 12°, 30° WITH INTERMITTENT IRRIGATION WITH CENTRAL STOPCOCK FOR RESECTION IN SALINE SOLUTION



| Telescopes                 |   | see URO45      |
|----------------------------|---|----------------|
| Working elements           |   | see URO56      |
| Electrodes                 | V | see URO65-68   |
| Monopolar connection cable |   | see URO103/104 |



#### FOR TELESCOPE 4 MM, 0°, 12°, 30° WITH CONTINUOUS IRRIGATION DOUBLE SHEATH SYSTEM FOR RESECTION IN SALINE SOLUTION



| Telescopes               | see URO45        |
|--------------------------|------------------|
| Working elements         | see URO57        |
| Electrodes               | <br>see URO69-71 |
| Bipolar connection cable | see URO105       |

"SHARK" RESECTOSCOPES (MONOPOLAR/BIPOLAR)






| Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with


contact partner or directly with Richard Wolf GmbH

FOR TELESCOPE 4 MM, 0°, 12°, 30° WITH INTERMITTENT IRRIGATION AND ROTATABLE IRRIGATION ADAPTER FOR RESECTION IN SALINE SOLUTION



FOR TELESCOPE 4 MM, 0°, 12°, 30°





| Telescopes               |          | see URO45    |
|--------------------------|----------|--------------|
| Working elements         |          | see URO57    |
| Electrodes               | <u> </u> | see URO69-71 |
| Bipolar connection cable |          | see URO105   |

"SHARK" RESECTOSCOPES (MONOPOLAR/BIPOLAR)





FOR RESECTOSCOPES, MONOPOLAR TELESCOPE 4 MM, 0°, 12°, 30°

| Direction of view 0°   | Handle variants  | Cutting | Product no. |
|--|------------------|---------|-------------|
| Active working element<br>mono 0°<br>Cut is made against spring pressure | Handle<br>closed | Active  | 8681205*    |
| Passive working element mono 0°  Cut is made with spring pressure        | Handle<br>open   | Passive | 8681224*    |

<sup>\*</sup> Not suitable for 22/24 Fr Double sheath system

| Direction of view 12°/30°  | Handle variants                                | Cutting | Product no. |
|--|--|---------|-------------|
| Active working element<br>mono 12/30°<br>Cut is made against spring pressure | Handle<br>closed                               |         | 8674205     |
| Active working element<br>mono 12/30°<br>Cut is made against spring pressure | Handle<br>closed<br>with comfort<br>thumb rest | Active  | 8674234     |
| Passive working element<br>mono 12/30°<br>Cut is made with spring pressure   | Handle<br>open                                 |         | 8674224     |
| Passive working element<br>mono 12/30°<br>Cut is made with spring pressure   | Handle<br>closed                               | Passive | 8674225     |

| Recommended accessories           |   | Product no. |
|-----------------------------------|---|-------------|
| Rubber cap, red<br>(Pack = 5 PCS) | for sealing off the electrode clamping mechanism on the working element | 8874        |
| Thumb ring                        | with relatively large inner diameter                                    | 15008.159   |



FOR RESECTOSCOPES, BIPOLAR TELESCOPE 4 MM, 0°, 12°, 30°

| Direction of view 0°/12°/30°  | Handle variants  | Cutting | Product no. |
|---|------------------|---------|-------------|
| Active working element bipo 0/12/30°  Cut is made against spring pressure | Handle<br>open   | Aakira  | 8680.204    |
| Active working element bipo 0/12/30°  Cut is made against spring pressure | Handle<br>closed | Active  | 8680.205    |
| Passive working element bipo 0/12/30°  Cut is made with spring pressure   | Handle<br>open   | Passive | 8680.224    |
| Passive working element bipo 0/12/30°  Cut is made with spring pressure   | Handle<br>closed | russive | 8680.225    |

| ı | Recommended accessories             |   | Product no. |
|---|-------------------------------------|---|-------------|
|   | Rubber cap, black<br>(Pack = 5 PCS) | for sealing off the electrode clamping mechanism on the working element | 8880        |
|   | Thumb ring                          | with relatively large inner diameter                                    | 15008.159   |

"SHARK" RESECTOSCOPES (MONOPOLAR/BIPOLAR)




X23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with

our contact partner or directly with Richard Wolf GmbH.

# MONOPOLAR WORKING ELEMENTS

FOR RESECTOSCOPE, LONG SHEATH MONOPOLAR TELESCOPE 4 MM,  $25^{\circ}$ 




|                                | Direction of view | Ø      | WL     | TL     | Product no. |
|--------------------------------|-------------------|--------|--------|--------|-------------|
| Telescope 25° Ø 4 mm WL 342 mm | 0°                | 4.0 mm | 342 mm | 404 mm | 8668.433 H  |
| Recommended accessories        |                   |        |        |        | Product no. |

| Recommended accessories   |   | Product no.    |
|---|---|----------------|
| Perforated basket for standard telescope 2  | Internal dimensions (W x H x D): 454 x 52 x 40 mm External dimensions (W x H x D): 481 x 54 x 59 mm | 38016          |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long  | 806625231      |
| Monopolar connection cable  |   | see URO103/104 |



### **MIDI** size

#### **RESECTOSCOPE**



| Recommended accessories  |  | Product no.    |
|--|--|----------------|
| Perforated basket for standard telescope 2   | Internal dimensions (W x H x D): 454 x 52 x 40 mm<br>External dimensions (W x H x D): 481 x 54 x 59 mm | 38016          |
| Fiber light cable bndl<br>consisting of:<br>Fiber light cable (80662523), projector-side adapter<br>(8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long   | 806625231      |
| Container (W x H x D) 300 x 60 x 200 mm  |  | 33020          |
| Monopolar connection cable   |  | see URO103/104 |



| IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# **MIDI** size

# **AUXILIARY INSTRUMENTS**

| Stricture scalpels with ceramic cutter |                                | Cutting surface                      | Product no. |
|--|--------------------------------|--------------------------------------|-------------|
|  | Scalpel 14.5 Fr, lancet-shaped | Lancet-shaped,<br>cuts on both sides | 8677981     |
|  | Scalpel 14.5 Fr, sickle-shaped | Sickle-shaped                        | 8677931     |

| Electrodes |   | Electrode shape | Product no. |
|------------|---|-----------------|-------------|
| 8          | Coag. electrode mono 14.5 Fr 0° Stem color yellow   | Button          | 8416011     |
| Ó          | Cutting electrode mono 14.5 Fr 0° Stem color yellow | Round loop      | 8416031     |
|            | Hook electrode mono 14.5 Fr 0° Stem color yellow    | Hook            | 8416091     |

Product no.

# System blue

# SYSTEM COMPONENTS

FOR PHOTODYNAMIC DIAGNOSTICS (PDD)



| ENDOLIGHT LED blue bndl consisting of: ENDOLIGHT LED blue (5165001), patch cable, RJ45 SFTP, 0.5 m (723253 and power cable 3 m long (2440.03)   | 51650011 |              |                  |                         |
|---|----------|--------------|------------------|-------------------------|
| ENDOCAM Logic 4K camera control unit bndl consisting of: ENDOCAM Logic 4K camera control unit (5525301), handheld remote co USB flash memory 32 GB (72321829), HDMI/HDMI cable, lockable, 3.0 m | 55253011 |              |                  |                         |
| ENDOCAM Logic HD Pendual camera head blue<br>Cable length 3 m   |          |              |                  | 5525833                 |
| Also:   |          |              |                  |                         |
|   |          |              |                  |                         |
| PANOVIEW  | Ø        | WL           | TL               | Product no.             |
| PANOVIEW  Telescope blue 0° Ø 4 mm WL 298 mm  | Ø        | WL<br>298 mm | <b>TL</b> 365 mm | Product no.<br>8650.514 |
|   |          |              |                  |                         |
| Telescope blue 0° Ø 4 mm WL 298 mm  | Ø 4.0 mm | 298 mm       | 365 mm           | 8650.514                |
| Telescope blue 0° Ø 4 mm WL 298 mm  Telescope blue 12° Ø 4 mm WL 298 mm   |          | 298 mm       | 365 mm<br>363 mm | 8650.514<br>8654.531    |

"SYSTEM BLUE" FOR PHOTODYNAMIC DIAGNOSTICS (PDD)

1.14



# System blue

# SYSTEM COMPONENTS FOR PHOTODYNAMIC DIAGNOSTICS (PDD)

TUR-B (MONOPOLAR RESECTION OF BLADDER TUMORS)

|  | B)   | Product no.   |
|--|--|---|
| <b>Recommendation: TUR-B/monopolar SHARK co</b><br>2/24 Fr, 30°, for monopolar resection of bladder tu |  |   |
|  | Working element, active, mono 12/30° Active, closed  | 8674205   |
| Suark  | Optional: working element, passive, mono 12/30° Passive, closed  | 8674225   |
|  | Outer sheath for resectoscope 24 Fr  | 8675424   |
| *V   | Inner sheath for resectoscope 22 Fr  | 8675322   |
|  | Obturator for resectoscope 22 Fr   | 8673022   |
|  | Viewing obturator for resectoscope 22 Fr   | 8673122   |
|  | Special fiber light cable 3.5 mm, 2.3 m SET  | 806735231   |
|  | Telescope blue 30° Ø 4 mm WL 299 mm  | 8654.522  |
|  | Optional: telescope blue 12° Ø 4 mm WL 298 mm  | 8654.531  |
|  | Cutting electrode mono 22 Fr 12/30° In individual sterile packaging (Pack = 10 PCS)  | 46782225  |
|  | Coag. electrode mono 22–24 Fr 12/30° In individual sterile packaging (Pack = 5 PCS)  | 46782201  |
| ecommendation: TUR-B/monopolar SHARK con<br>/26 Fr, 30°, for monopolar resection of bladder tu         |  |   |
|  | Working element, active, mono 12/30° Active, closed  | 8674205   |
| Shark  | Optional: working element, passive, mono 12/30° Passive, closed  | 8674225   |
|  | Outer sheath for resectoscope 26 Fr  |   |
|  |  | 8675426   |
| ***  | Inner sheath for resectoscope 24 Fr  | 8675426   |
| ****   | Obturator for resectoscope 24 Fr   |   |
| ***  |  | 8675324   |
|  | Obturator for resectoscope 24 Fr   | 8675324<br>8673024                                    |
|  | Obturator for resectoscope 24 Fr  Viewing obturator for resectoscope 24 Fr   | 8675324<br>8673024<br>8673124                         |
|  | Obturator for resectoscope 24 Fr  Viewing obturator for resectoscope 24 Fr  Dilatations obturator f. resectoscope 24 Fr  | 8675324<br>8673024<br>8673124<br>8673224              |
|  | Obturator for resectoscope 24 Fr  Viewing obturator for resectoscope 24 Fr  Dilatations obturator f. resectoscope 24 Fr  Special fiber light cable 3.5 mm, 2.3 m SET | 8675324<br>8673024<br>8673124<br>8673224<br>806735231 |

"SYSTEM BLUE" FOR PHOTODYNAMIC DIAGNOSTICS (PDD)



spirit of excellence

# System blue

# SYSTEM COMPONENTS FOR PHOTODYNAMIC DIAGNOSTICS (PDD)

TUR-B (BIPOLAR RESECTION OF BLADDER TUMORS)

| TON D (DII OLIIN NEGLOTION OF DETABLE   | K Tomorroy   |             |
|---|--|-------------|
| Transurethral resection of the bladder (TUR-B)  |  | Product no. |
| Recommendation: TUR-B/bipolar SHARK continuous i 22/24 Fr, 30°, for bipolar resection of bladder tumors | rrigation resectoscope   |             |
| GCA-16  | Working element, active, bipo 0/12/30°<br>Active, closed                           | 8680.205    |
| Sualik  | Optional: working element, passive, bipo 0/12/30°<br>Passive, closed               | 8680.225    |
| 0.40  | Outer sheath for resectoscope 24 Fr  | 8675424     |
|   | Inner sheath for resectoscope 22 Fr  | 8675322     |
|   | Obturator for resectoscope 22 Fr   | 8673022     |
|   | Viewing obturator for resectoscope 22 Fr   | 8673122     |
|   | Special fiber light cable 3.5 mm, 2.3 m SET  | 806735231   |
|   | Telescope blue 30° Ø 4 mm WL 299 mm  | 8654.522    |
|   | Optional: telescope blue 12° Ø 4 mm WL 298 mm                                      | 8654.531    |
|   | Cutting electrode bipo 22 Fr 12/30° In individual sterile packaging (Pack = 3 PCS) | 4622.2533   |
|   | Cutting electrode bipo 22 Fr 12/30° In individual sterile packaging (Pack = 3 PCS) | 4622.1333   |
|   | Coag. electrode bipo 22 Fr 12/30° In individual sterile packaging (Pack = 3 PCS)   | 4623.0243   |
| Recommendation: TUR-B/bipolar SHARK continuous i 24/26 Fr, 30°, for bipolar resection of bladder tumors | rrigation resectoscope   |             |
| C Shark   | Working element, active, bipo 0/12/30°<br>Active, closed                           | 8680.205    |
|   | Ontional: working alament nassive him 0/12/20°                                     |             |



| <b>Working element, active, bipo 0/12/30°</b><br>Active, closed  | 8680.205  |  |  |  |  |
|--|-----------|--|--|--|--|
| Optional: working element, passive, bipo 0/12/30°<br>Passive, closed   | 8680.225  |  |  |  |  |
| Outer sheath for resectoscope 26 Fr  | 8675426   |  |  |  |  |
| Inner sheath for resectoscope 24 Fr  | 8675324   |  |  |  |  |
| Obturator for resectoscope 24 Fr   | 8673024   |  |  |  |  |
| Viewing obturator for resectoscope 24 Fr   | 8673124   |  |  |  |  |
| Special fiber light cable 3.5 mm, 2.3 m SET  | 806735231 |  |  |  |  |
| Telescope blue 30° Ø 4 mm WL 299 mm  | 8654.522  |  |  |  |  |
| Optional: telescope blue 12° Ø 4 mm WL 298 mm  | 8654.531  |  |  |  |  |
| Optional: telescope blue 12° Ø 4 mm WL 298 mm  | 8654.531  |  |  |  |  |
| Cutting electrode bipo 24–26 Fr 12/30° In individual sterile packaging (Pack = 3 PCS)  | 4622.2513 |  |  |  |  |
| Cutting electrode bipo 24 Fr 12/30° In individual sterile packaging (Pack = 3 PCS)   | 4622.1313 |  |  |  |  |
| Cutting electrode bipo 24–26 Fr 12/30° (oval, specifically for en bloc resection) In individual sterile packaging (Pack = 3 PCS) | 4622.1323 |  |  |  |  |
| Cutting electrode bipo 24–26 Fr 12/30° In individual sterile packaging (Pack = 3 PCS)  | 4623.0223 |  |  |  |  |



FOR MULTIPLE USE 12°/30°

### 12°/30°, for multiple use, monopolar

|    | Designation                             | Dunalisat         |          | for sheath   | sizes [in Fr]   |              | Color coding |           | Model    |
|----|---|-------------------|----------|--------------|-----------------|--------------|--------------|-----------|----------|
|    | Designation                             | Bracket           | CI 22/24 | <u>II</u> 24 | <b>Cl</b> 24/26 | <b>II</b> 26 | Branch       | Stem      | Model    |
|    | Cutting electrode mono<br>22 Fr 12/30°  |                   | •        | -            | _               | -            | Green        | Dark gray | 86782235 |
|    | Cutting electrode mono<br>24 Fr 12/30°  | Loop<br>Ø 0.35 mm | _        | •            | •               | -            | Yellow       | Dark gray | 86782435 |
|    | Cutting electrode mono<br>26 Fr 12/30°  |                   | _        | -            | -               | •            | Black        | Dark gray | 86782635 |
| )  | Cutting electrode mono<br>24 Fr 12/30°  | Loop<br>Ø 0.8 mm  | -        | •            | •               | -            | Yellow       | Dark gray | 86782480 |
|    | Coag. electrode mono<br>22–24 Fr 12/30° | Roller            | •        | •            | •               | -            | Green        | Dark gray | 86782201 |
|    | Coag. electrode mono<br>26 Fr 12/30°    |                   | -        | -            | -               | •            | Black        | Dark gray | 86782601 |
| 6  | Coag. electrode mono<br>22–24 Fr 12/30° | Ball              | •        | •            | •               | -            | Green        | Dark gray | 86782202 |
|    | Coag. electrode mono<br>22–24 Fr 12/30° |                   | •        | •            | •               | -            | Green        | Dark gray | 86782203 |
| \$ | Coag. electrode<br>mono 26 Fr 12/30°    | Button            | -        | -            | _               | •            | Black        | Dark gray | 86782603 |
|    | Knife electrode mono<br>22–24 Fr 12/30° | - Knife           | •        | •            | •               | -            | Green        | Dark gray | 86782204 |
|    | Knife electrode mono<br>26 Fr 12/30°    | Kille             | -        | -            | -               | •            | Black        | Dark gray | 86782604 |
|    | Hook electrode mono<br>22–24 Fr 12/30°  | Hook              | •        | •            | •               | -            | Green        | Dark gray | 86782205 |
| 9  | Hook electrode mono<br>26 Fr 12/30°     | HOUK              | _        | _            | _               | •            | Black        | Dark gray | 86782605 |

• Suitable for corresponding sheath size - Not suitable

CI = continuous irrigation

= intermittent irrigation

|  | Product no. |
|--|-------------|
|  | 33030       |
| The second secon |             |

MONOPOLAR ELECTRODES

spirit of excellence

FOR MULTIPLE USE 12°/30°

### 12°/30°, for multiple use, monopolar

|   | Designation                            | Bracket          | for sheath sizes [in Fr] |              |          |              | Color coding |           | Model    |
|---|--|------------------|--------------------------|--------------|----------|--------------|--------------|-----------|----------|
|   | Designation                            | bluckei          | CI 22/24                 | <b>II</b> 24 | CI 24/26 | <b>II</b> 26 | Branch       | Stem      | Wodei    |
|   | EVAP-Elektrode mono<br>24–26 Fr 12/30° | Barrel           | -                        | •            | •        | •            | Yellow       | Dark gray | 86782407 |
| • | EVAP-Elektrode mono<br>24–26 Fr 12/30° | Pyramid          | _                        | •            | •        | •            | Yellow       | Dark gray | 86782408 |
|   | Wing electrode mono<br>22 Fr 12/30°    | Wing<br>(bracket | •                        | -            | -        | -            | Green        | Dark gray | 86782206 |
|   | EVAP-Elektrode mono<br>24 Fr 12/30°    | profile, flat)   | -                        | •            | •        | -            | Yellow       | Dark gray | 86782406 |

• Suitable for corresponding sheath size - Not suitable

CI = continuous irrigation

II = intermittent irrigation

| Recommended accessories  |                              | Product no. |
|--|------------------------------|-------------|
| Protective sterilization sleeve Receptacle for max. 5 electrodes, reusable | AUTOGLAVE<br>134° C / 273° F | 33030       |







IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

FOR MULTIPLE USE 0°

# 0°, for multiple use, monopolar

|   | Danis and Adam                      | Dunalist  | for sheath sizes [in Fr] |             |         |              | Color       | coding    | Madal    |
|---|-------------------------------------|-----------|--------------------------|-------------|---------|--------------|-------------|-----------|----------|
|   | Designation                         | Bracket   | CI 22/24                 | <b>1</b> 24 | G 24/26 | <b>II</b> 26 | Branch      | Stem      | Model    |
|   | Cutting electrode<br>mono 24 Fr 0°  | Loop      | _                        | •           | •       | -            | Yellow      | Dark gray | 86792435 |
| 6 | Cutting electrode<br>mono 26 Fr 0°  | Ø 0.35 mm | -                        | _           | _       | •            | Black       | Dark gray | 86792635 |
| 5 | Coag. electrode<br>mono 24 Fr 0°    | Roller    | -                        | •           | •       | -            | Green       | Dark gray | 86792201 |
|   | Coag. electrode<br>mono 24–26 Fr 0° | Ball      | -                        | •           | •       | •            | Transparent | Dark gray | 86792202 |
| 5 | EVAP-Elektrode<br>mono 24–26 Fr 0°  | Barrel    | -                        | •           | •       | •            | Yellow      | Dark gray | 86792407 |
|   | Knife electrode<br>mono 24–26 Fr 0° | Knife     | -                        | •           | •       | •            | Transparent | Dark gray | 86792204 |
|   | Hook electrode<br>mono 24–26 Fr 0°  | Hook      | -                        | •           | •       | •            | Transparent | Dark gray | 86792205 |

Suitable for corresponding sheath size - Not suitable

CI = continuous irrigation

= intermittent irrigation

| Recommended accessories  |                              | Product no. |
|--|------------------------------|-------------|
| Protective sterilization sleeve Receptacle for max. 5 electrodes, reusable | AUT©GLAVE<br>134° C / 273° F | 33030       |



FOR SINGLE USE 12°/30°

# 12°/30°, for single use, sterile\*, monopolar

|                 | Designation                             |                   |          | for sheath   | sizes [in Fr] |              | Color  |             |         |
|-----------------|---|-------------------|----------|--------------|---------------|--------------|--------|-------------|---------|
|                 | (Pack = 5 PCS)                          | Bracket           | CI 22/24 | <b>II</b> 24 | Cl 24/26      | <b>II</b> 26 | Branch | Stem        | Model   |
|                 | Cutting electrode mono<br>22 Fr 12/30°  |                   | •        | -            | _             | -            | Green  | Transparent | 4678223 |
|                 | Cutting electrode mono<br>24 Fr 12/30°  | Loop<br>Ø 0.35 mm | -        | •            | •             | -            | Yellow | Transparent | 4678243 |
|                 | Cutting electrode mono<br>26 Fr 12/30°  |                   | _        | -            | -             | •            | Black  | Transparent | 4678263 |
|                 | Cutting electrode mono<br>22 Fr 12/30°  | Loop              | •        | -            | -             | -            | Green  | Transparent | 4678222 |
| (Pack = 10 PCS) | Cutting electrode mono<br>24 Fr 12/30°  | Ø 0.25 mm         | -        | •            | •             | -            | Yellow | Transparent | 4678242 |
|                 | Cutting electrode mono<br>24 Fr 12/30°  | Loop<br>Ø 0.8 mm  | _        | •            | •             | -            | Yellow | Transparent | 4678248 |
|                 | Hook electrode mono<br>24 Fr 12/30°     |                   | •        | •            | •             | -            | Green  | Transparent | 4678220 |
|                 | Hook electrode mono<br>26 Fr 12/30°     | Hook              | _        | -            | -             | •            | Black  | Transparent | 4678260 |
| <b>E</b>        | Coag. electrode mono<br>22–24 Fr 12/30° | Roller            | •        | •            | •             | -            | Green  | Transparent | 4678220 |
|                 | Coag. electrode mono<br>22–24 Fr 12/30° | Ball              | •        | •            | •             | -            | Green  | Transparent | 4678220 |
|                 | Coag. electrode mono<br>22–24 Fr 12/30° | B. II             | •        | •            | •             | -            | Green  | Transparent | 4678220 |
| \$              | Coag. electrode mono<br>26 Fr 12/30°    | Button            | _        | -            | -             | •            | Black  | Transparent | 4678260 |
|                 | Knife electrode mono<br>22–24 Fr 12/30° | Knife             | •        | •            | •             | -            | Green  | Transparent | 4678220 |
|                 | Knife electrode mono<br>26 Fr 12/30°    | Kille             | _        | _            | -             | •            | Black  | Transparent | 4678260 |

• Suitable for corresponding sheath size - Not suitable

CI = continuous irrigation

= intermittent irrigation

"SHARK" ELECTRODES (MONOPOLAR/BIPOLAR) – "E-LINE" ELECTRODES

<sup>\*</sup> In individual sterile packaging





FOR SINGLE USE 0°

# 0°, for single use, sterile\*, monopolar

|   | Designation                        | Dynakat   | for sheath sizes [in Fr] |              |                | Color        | coding      | Model       |          |
|---|------------------------------------|-----------|--------------------------|--------------|----------------|--------------|-------------|-------------|----------|
|   | (Pack = 5 PCS)                     | Бгаскет   | CI 22/24                 | <b>II</b> 24 | <b>@</b> 24/26 | <b>II</b> 26 | Branch      | Stem        | Model    |
|   | Cutting electrode mono<br>24 Fr 0° | Loop      | -                        | •            | •              | -            | Yellow      | Transparent | 46792435 |
| O | Cutting electrode mono<br>26 Fr 0° | Ø 0.35 mm | -                        | -            | -              | •            | Black       | Transparent | 46792635 |
|   | Hook electrode mono<br>24 Fr 0°    | Hook      | -                        | •            | •              | -            | Transparent | Transparent | 46792205 |
| 5 | Coag. electrode mono<br>24 Fr 0°   | Roller    | -                        | •            | •              | -            | Green       | Transparent | 46792201 |
|   | Knife electrode mono<br>24 Fr 0°   | Knife     | -                        | •            | •              | -            | Transparent | Transparent | 46792204 |

• Suitable for corresponding sheath size

- Not suitable

\* In individual sterile packaging

CI = continuous irrigation

II = intermittent irrigation





FOR MULTIPLE USE 0°/12°/30°

### 12°/30°, for multiple use, bipolar

|  | Decignation                             | Bracket              | for sheath sizes [in Fr] |              |          |       | Color coding |        | Model   |
|--|---|----------------------|--------------------------|--------------|----------|-------|--------------|--------|---------|
|  | Designation                             | brucker              | CI 22/24                 | <b>II</b> 24 | GI 24/26 | II 26 | Branch       | Stem   | Model   |
|  | Cutting electrode bipo<br>22 Fr 12/30°  | Loop                 | •                        | _            | _        | _     | Blue         | Yellow | 8622133 |
|  | Cutting electrode bipo<br>24 Fr 12/30°  | Ø 0.3 mm             | _                        | •            | •        | •     | Blue         | Yellow | 8622131 |
|  | Coag. electrode bipo<br>22–26 Fr 12/30° | Cylinder<br>Ø 1.2 mm | •                        | •            | •        | •     | Blue         | Yellow | 8623022 |
|  | Hook electrode bipo<br>22–26 Fr 12/30°  | Hook                 | •                        | •            | •        | •     | Blue         | Yellow | 862309  |

### 0°, for multiple use, bipolar

| Designation                        | Pracket          | for sheath sizes [in Fr] |             |                 | Color coding |        | Model  |         |
|------------------------------------|------------------|--------------------------|-------------|-----------------|--------------|--------|--------|---------|
| Designation                        | Bracket          | CI 22/24                 | <b>1</b> 24 | <b>CI</b> 24/26 | <b>II</b> 26 | Branch | Stem   | Wodel   |
| Cutting electrode bipo 24 Fr<br>0° | Loop<br>Ø 0.3 mm | _                        | •           | •               | _            | Blue   | Yellow | 8609031 |

• Suitable for corresponding sheath size - Not suitable

CI = continuous irrigation

= intermittent irrigation

| Recommended accessories  |                              | Product no. |
|--|------------------------------|-------------|
| Protective sterilization sleeve Receptacle for max. 5 electrodes, reusable | AUTOGLAVE<br>134° C / 273° F | 33030       |

"SHARK" ELECTRODES (MONOPOLAR/BIPOLAR) – "E-LINE" ELECTRODES





FOR SINGLE USE 12°/30°

# 12°/30°, for single use, sterile\*, bipolar

|  | Designation<br>(Pack = 3 PCS)   | Bracket              | for sheath sizes [in Fr] |             |                 |       | Color coding |      |           |
|--|---|----------------------|--------------------------|-------------|-----------------|-------|--------------|------|-----------|
|  |   |                      | CI 22/24                 | <b>Ⅲ</b> 24 | <b>GI</b> 24/26 | II 26 | Branch       | Stem | Model     |
|  | Cutting electrode bipo<br>22 Fr 12/30°  | Loop<br>Ø 0.3 mm     | •                        | -           | _               | -     | Blue         | Blue | 4622.1333 |
|  | Cutting electrode bipo<br>24 Fr 12/30°  |                      | _                        | •           | •               | -     | Blue         | Blue | 4622.1313 |
|  | Cutting electrode bipo<br>26 Fr 12/30°  |                      | _                        | -           | •               | •     | Green        | Blue | 4624.1313 |
|  | Cutting electrode bipo<br>22 Fr 12/30°  | Loop<br>Ø 0.25 mm    | •                        | -           | -               | -     | Blue         | Blue | 4622.2533 |
|  | Cutting electrode bipo<br>24–26 Fr 12/30°                                       |                      | _                        | •           | •               | •     | Blue         | Blue | 4622.2513 |
|  | Cutting electrode bipo 24–26 Fr 12/30° Oval, specifically for en bloc resection | Loop<br>Ø 0.3 mm     | _                        | •           | •               | •     | Blue         | Blue | 4622.1323 |
|  | Coag. electrode bipo<br>22 Fr 12/30°  | Cylinder<br>Ø 1.2 mm | •                        | -           | -               | -     | Blue         | Blue | 4623.0243 |
|  | Coag. electrode bipo<br>24–26 Fr 12/30°   |                      | _                        | •           | •               | •     | Blue         | Blue | 4623.0223 |
|  | BiVAP-Elektrode bipo<br>22 Fr 12/30°  | Torus                | •                        | -           | -               | -     | Blue         | Blue | 46300223  |
|  | BiVAP-Elektrode bipo<br>24–26 Fr 12/30°   |                      | _                        | •           | •               | •     | Blue         | Blue | 46300243  |
|  | Enucleation electrode bipo<br>22 Fr 12/30°                                      | Torus                | •                        | -           | _               | -     | Blue         | Blue | 46400223  |
|  | Enucleation electrode bipo<br>24 Fr 12/30°                                      |                      | _                        | •           | •               | •     | Blue         | Blue | 46400243  |

• Suitable for corresponding sheath size

- Not suitable

\* In individual sterile packaging

CI = continuous irrigation

= intermittent irrigation



Shark BIPOLAR ELECTRODES

FOR SINGLE USE 0°

# $0^{\circ}$ , for single use, sterile\*, bipolar

|  | Designation<br>(Pack = 3 PCS)         | Bracket              | for sheath sizes [in Fr] |              |                |              | Color coding |      |           |
|--|---------------------------------------|----------------------|--------------------------|--------------|----------------|--------------|--------------|------|-----------|
|  |                                       |                      | CI 22/24                 | <b>II</b> 24 | <b>@</b> 24/26 | <b>II</b> 26 | Branch       | Stem | Model     |
|  | Cutting electrode<br>bipo 24 Fr 0°    | Loop<br>Ø 0.3 mm     | _                        | •            | •              | -            | Blue         | Blue | 4609.0313 |
|  | Cutting electrode<br>bipo 26 Fr 0°    |                      | _                        | -            | _              | •            | Green        | Blue | 4611.0313 |
|  | Cutting electrode<br>bipo 24 Fr 0°    | Loop<br>Ø 0.25 mm    | _                        | •            | •              | -            | Blue         | Blue | 4609.2513 |
|  | Cutting electrode<br>bipo 24–26 Fr 0° | Loop<br>Ø 0.3 mm     | -                        | •            | •              | •            | Blue         | Blue | 4609.0323 |
|  | Coag. electrode<br>bipo 24–26 Fr 0°   | Cylinder<br>Ø 1.2 mm | -                        | •            | •              | •            | Blue         | Blue | 4610.0223 |
|  | BiVAP-Elektrode<br>bipo 24–26 Fr 0°   | Torus                | -                        | •            | •              | •            | Blue         | Blue | 46310243  |

• Suitable for corresponding sheath size

Not suitable

\* In individual sterile packaging

CI = continuous irrigation

= intermittent irrigation

"SHARK" ELECTRODES (MONOPOLAR/BIPOLAR) – "E-LINE" ELECTRODES





# MONOPOLAR ELECTRODES

RICHARD spirit of excellence

FOR RESECTOSCOPES, TELESCOPE 4 MM, 25°, LONG SHEATH

### 25°, for multiple use, monopolar

|   | Designation                      |                  |              | Color  | Model |         |
|---|----------------------------------|------------------|--------------|--------|-------|---------|
|   |                                  |                  | <b>11</b> 24 | Branch | Stem  | Wouei   |
|   | Cutting electrode mono 24 Fr 25° | Loop<br>Ø 0.3 mm | •            | Green  | Red   | 8439.03 |
| è | Coag. electrode mono 24 Fr 25°   | Roller           | •            | Blue   | Red   | 8440.02 |

Recommended accessories Product no. Protective sterilization sleeve 33030 Receptacle for max. 5 electrodes, reusable AUTOGLAVE 134° C / 273° F

IX23 || Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# 

spirit of excellence

### **ACCESSORIES**

### FOR RESECTOSCOPE SHEATHS Shark



| for sheat     | h sizes [in Fr] |                            | Working units of cysto-urethroscope 8650 for use in resectoscope sheaths        |                               | with felescope Ø 4 mm |
|---------------|-----------------|----------------------------|---|-------------------------------|-----------------------|
| 1 24/26<br>Fr | ©l 26 Fr        | Via                        | Version   | Product no.                   |                       |
| •             | •               | Only for diagnostics       | Adapter with instrument port  | 8652.264                      | 0°, 12°, 30°, 70°     |
| •             | •               |                            | Opt. scissors, "Wuppertal" model  | 8650.644                      | 0°                    |
| -             | •               |                            | Opt. biopsy forceps, "Marburg" model  | 8650.614                      | 0°                    |
| -             | •               | Adapter for E-Line sheaths | Opt. grasping forceps, curved downward  | 8650.654                      | 0°                    |
| -             | •               | 8652                       | Opt. biopsy forceps, spoon downward   | 8650.774                      | 0°                    |
| -             | •               | 8652.704                   | Opt. grasping forceps, straight   | 8650.684                      | 0°                    |
| -             | •               |                            | Opt. biopsy forceps, spoon-shaped   | 8650.604                      | 0°                    |
| -             | •               |                            | Opt. coag. biopsy forceps, Tauber   | 8650.624                      | 0°                    |
| -             | •               | without<br>adapter         | Working insert for cystoscope 0/30/70* or working insert for cystoscope 30/70** | 8650.204*<br>or<br>8650.214** | (0°, 12°) 30°, 70°    |

II = intermittent irrigation

"SHARK" ELECTRODES (MONOPOLAR/BIPOLAR) – "E-LINE" ELECTRODES

1.15

CI = continuous irrigation



# ACCESSORIES FOR RESECTOSCOPE SHEATHS Shark WITH 4 MM TELESCOPE

|             |                                      |      | for sheaths                                    |                             |  |
|-------------|--------------------------------------|------|--|-----------------------------|--|
|             |                                      |      | with rotatable and replaceable irrigation ring | with fixed<br>Luer stopcock |  |
| Ţ           |                                      | Ø    | Capacity 4 mm                                  | Capacity 3 mm               |  |
|             | Two-way stopcock, maintenance-free   | 3 mm |  | 88350                       |  |
| A DE PARTIE | with LUER-LOCK connection, reusable  | 4 mm | 88351  |                             |  |
| audi        | Stopcock LUER-LOCK connection Ø 3 mm | 3 mm |  | 884.00                      |  |
|             | Stopcock LUER-LOCK connection Ø 4 mm | 4 mm | 884.01   |                             |  |
| <b>(E)</b>  | Tube with LUER-LOCK connector        | 3 mm |  | 886.00                      |  |

1 16



# ACCESSORIES HF CONNECTION CABLE BIPO FOR RESECTION IN SALINE SOLUTION

| Instrument connector        | Device connector   |   | Product no. |
|-----------------------------|--|---|-------------|
| WOLF S(a)line resectoscopes | Erbe VIO 300D  | Bipolar cable; TUR/TCR;<br>WOLF<br>MF plug; L 4 m | 20196-119   |
| O                           | Erbe VIO 3   | <b>Bipolar cable; MF-U</b><br>MF plug; L 4.5 m    | 21196-119   |
|                             |  | HF connection cable bipo; L 3 m                   | 8108.231    |
|                             | KLS Martin   | HF connection cable bipo; L 5 m                   | 8108.251    |
|                             |  | HF connection cable bipo; L 3 m                   | 8108233     |
|                             | R. Wolf HF surgical generator 400 kHz<br>2260001/2260002 | HF connection cable bipo; L 5 m                   | 8108253     |




X23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with

contact partner or directly with Richard Wolf GmbH

# GREENLIGHT™ CONTINUOUS IRRIGATION LASER CYSTOSCOPE "MoXy™"

PARTICULARLY FOR THE USE OF MOXY™ LASER FIBERS





# GREENLIGHT™ CONTINUOUS IRRIGATION LASER RESECTOSCOPE "MoXy™"


PARTICULARLY FOR THE USE OF MOXY™ LASER FIBERS



| \  |   |                   |  | To a         | 134          | TOGLAVE<br>° C / 273° F |
|--|---|-------------------|--|--------------|--------------|-------------------------|
| C Double sheath s  | Distal end  |                   | Outer shea   | th P         | Inner shed   | uth                     |
| for sheath sizes   |   |                   |  | SL/WL        | Color coding | Product no.             |
| CI   | Outer sheath for resectosc  | ope 24 Fr         |  | SL 189 mm    |              | 8675424                 |
| 24 Fr  | Inner sheath for resectosc  | ope 22 Fr         |  | SL 205 mm    | Green        | 8675322                 |
| Also:  |   |                   |  |              |              |                         |
|  | Obturator for resectoscope  | 22 Fr             |  | WL 232 mm    | Green        | 8673022                 |
| Ð  | Viewing obturator for rese  | ctoscope 22 Fr    |  | WL ZOZ IIIII | Green        | 8673122                 |
| G  | Outer sheath for resectose  | ope 26 Fr         |  | SL 189 mm    | W II         | 8675426                 |
| 26 Fr  | Inner sheath for resectosc  |                   | SL 205 mm  | Yellow       | 8675324      |                         |
| Also:  |   |                   |  |              |              |                         |
|  | Obturator for resectoscope  | 24 Fr             |  | WL 233 mm    |              | 8673024                 |
|  | Viewing obturator for rese  | ctoscope 24 Fr    |  | WL 232 mm    | Yellow       | 8673124                 |
|  | Dilatations obturator f. res                                      | ectoscope 24 Fi   | r  | WL 247 mm    |              | 8673224                 |
|  | eely controlling the laser fiber<br>p incredibly well during Gree |                   |  |              |              | Product no.             |
| aser working insert<br>MoXy™" for flexible au  | <b>12/30</b> uxiliary instruments up to 6.5 F                     | r                 |  |              |              | 8632.284                |
| Rubber cap for hyste   | roscope, extended, red-orange                                     | (1 PC)            |  |              |              | 18.01                   |
| Also:  | -   |                   |  |              |              |                         |
| PANOVIEW   |   | Direction of view | Ø  | WL           | TL           | Product no.             |
| elescope 30° Ø 4 m   | ım WL 300 mm  | 30°               | 4.0 mm   | 300 mm       | 364 mm       | 8654.422                |
| elescope 12° Ø 4 m   | ım WL 297 mm  | 12°               | 4.0 mm   | 297 mm       | 363 mm       | 8654.431                |
| Recommended acces  | ssories   |                   |  |              |              | Product no.             |
| Perforated basket for standard telescope 2   |   |                   | Internal dimensions (W x H x D): 454 x 52 x 40 mm<br>External dimensions (W x H x D): 481 x 54 x 59 mm |              | 38016        |                         |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509)  806625231 |   |                   |  |              |              |                         |

# CONTINUOUS IRRIGATION LASER ENUCLEATION SHEATH 26 Fr "MoXym"

FOR **BLUNT** ENUCLEATION OF THE PROSTATE



| Also:                                      |  |        |        |        |             |  |
|--|--|--------|--------|--------|-------------|--|
| PANOVIEW                                   | Direction of view                        | Ø      | WL     | TL     | Product no. |  |
| Telescope 30° Ø 4 mm WL 300 mm             | 30°                                      | 4.0 mm | 300 mm | 364 mm | 8654.422    |  |
| Telescope 12° Ø 4 mm WL 297 mm             | 12°                                      | 4.0 mm | 297 mm | 363 mm | 8654.431    |  |
| Recommended accessories Product no.        |  |        |        |        |             |  |
| Perforated basket for standard telescope 2 | Internal dimension<br>External dimension |        |        | 38016  |             |  |

Ø 2.5 mm, 2.3 m long

URO78

Fiber light cable bndl consisting of:

and endoscope-side adapter (809509)


Fiber light cable (80662523), projector-side adapter (8095.07),

806625231



### GREENLIGHT™ CONTINUOUS IRRIGATION LASER CYSTOSCOPE "Freestyle"

PARTICULARLY FOR THE USE OF GREENLIGHT™ AND SIMILAR LASER FIBERS



|   |  | ļ           |
|---|--|-------------|
| Recommended accessories   |  | Product no. |
| Perforated basket for standard telescope 2  | Internal dimensions (W x H x D): 454 x 52 x 40 mm<br>External dimensions (W x H x D): 481 x 54 x 59 mm | 38016       |
| Fiber light cable bndl consisting of:<br>Fiber light cable (80662523), projector-side adapter (8095.07),<br>and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long   | 806625231   |






| Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with

contact partner or directly with Richard Wolf GmbH

# GREENLIGHT™ CONTINUOUS IRRIGATION LASER RESECTOSCOPE "Freestyle"


PARTICULARLY FOR THE USE OF GREENLIGHT™ AND SIMILAR LASER FIBERS





# CONTINUOUS IRRIGATION LASER ENUCLEATION SHEATH 26 Fr "Freestyle"

FOR **BLUNT** ENUCLEATION OF THE PROSTATE



| Also:   |                   |  |        |           |             |
|---|-------------------|--|--------|-----------|-------------|
| PANOVIEW  | Direction of view | Ø  | WL     | TL        | Product no. |
| Telescope 30° Ø 4 mm WL 300 mm  | 30°               | 4.0 mm   | 300 mm | 364 mm    | 8654.422    |
| Telescope 12° Ø 4 mm WL 297 mm  | 12°               | 4.0 mm   | 297 mm | 363 mm    | 8654.431    |
| Recommended accessories   |                   |  |        |           | Product no. |
| Perforated basket for standard telescope 2  |                   | Internal dimensions (W x H x D): 454 x 52 x 40 mm<br>External dimensions (W x H x D): 481 x 54 x 59 mm |        |           | 38016       |
| <b>Fiber light cable bndl</b> consisting of:<br>Fiber light cable (80662523), projector-side adapter (and endoscope-side adapter (809509) | Ø 2               | 2.5 mm, 2.3 m long   | )      | 806625231 |             |

X23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with

contact partner or directly with Richard Wolf GmbH

### CONTINUOUS IRRIGATION WORKING INSERT

FOR LASER PROBES UP TO 7.5 Fr






### HOLEP, THULEP

### CONTINUOUS IRRIGATION LASER ENUCLEATION SHEATH 26 Fr

FOR **BLUNT** ENUCLEATION OF THE PROSTATE








| Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with

contact partner or directly with Richard Wolf GmbH

### CONTINUOUS IRRIGATION LASER ENUCLEATION SHEATH, 26 Fr

FOR ENUCLEATION OF THE PROSTATE







### FOR CONTINUOUS IRRIGATION LASER ENUCLEATION SHEATH 26 Fr


| Laser fiber guide tubes for inner shec      | th 24 Fr                                | Fr            | Capacity   | Product no. |
|---|---|---------------|------------|-------------|
|   | Guide tube laser therapy 1,000 µm 22 Fr | 22 Fr         | - 1,000 μm | 8654990     |
| with lateral guide,<br>distal end straight  | Guide tube laser therapy 1,000 µm 24 Fr | 24 Fr         | - 1,000 μπ | 8654991     |
|   | Guide tube laser therapy 600 µm 22 Fr   | 22 Fr         | 400 um     | 8654992     |
| with lateral guide,<br>distal end straight  | Guide tube laser therapy 600 µm 24 Fr   | 24 Fr         | - 600 μm   | 8654993     |
|   | Guide tube laser therapy 600 µm 22 Fr   | 22 Fr         | - 600 µm   | 8654994     |
| with lateral guide,<br>distal end slanted   | Guide tube laser therapy 600 µm 24 Fr   | 24 Fr         | ουσ μπι    | 8654995     |
| ) cc 1880                                   | Guide tube laser therapy 600 µm 22 Fr   | 22 Fr         | - 600 µm   | 8654996     |
| with lateral guide,<br>distal end with ring | Guide tube laser therapy 600 µm 24 Fr   | 24 Fr         | ουυ μπι    | 8654997     |
|   | Curette 22–24 Fr<br>for prostate chips  | From<br>22 Fr | 600 µm     | 8654998     |

Note: Laser fiber guide tubes can only be used in conjunction with the laser working element (8654382) and laser working insert (8654383).



### CONTINUOUS IRRIGATION LASER ENUCLEATION SHEATH, 24/26 Fr

FOR **BIPOLAR** ENUCLEATION OF THE PROSTATE



X23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with

contact partner or directly with Richard Wolf GmbH





# IN COMBINATION WITH **SHARK** OUTER SHEATHS FOR TISSUE MORCELLATION

| _                                    |  | The state of the s | 134                        | TOGLAVE<br>1° C / 273° F  |
|--------------------------------------|--|--|----------------------------|---|
| PANOVIEW                             |  | WL   | TL                         | Product no.   |
|                                      | r WL 224 mm repiece, working channel for instruments up to 4.8 mm, Fr sheath and adapter, suction via morcellator  | 224 mm   | 386 mm                     | 8970405   |
| Autom. sealing elem                  | ent ID 5.7 mm  |  |                            | 8920.311  |
| Pressure ball for blov               | ving air through channels  |  |                            | 103.00  |
| Tube with LUER-LOC                   | K connector  |  |                            | 886.00  |
| Cleaning brush Ø 11                  | 6.01   |  |                            |   |
| for connecting "More                 | escope" to the 24 Fr and 26 Fr continuous irrigation sh  | eaths  |                            | Product no.   |
| Shark adapter for Me                 | orcescope 24/26 Fr   | ŧ  |                            | 8675026   |
| CI Double sheath s                   | system   | å  |                            |   |
| CI Double sheath                     |  | Outer sheath   | Inner sh                   | eath  |
| CI Double sheath s                   |  | Outer sheath SL/WL   | Inner she                  | eath Product no.  |
|                                      |  | <u> </u>   | Color coding               |   |
| for sheath sizes                     | Distal end   | SL/WL  |                            | Product no.   |
| for sheath sizes                     | Distal end  Outer sheath for resectoscope 24 Fr  | SL/WL<br>SL 189 mm   | Color coding               | Product no.<br>8675424  |
| for sheath sizes  CI 22/24 Fr        | Distal end  Outer sheath for resectoscope 24 Fr  | SL/WL SL 189 mm SL 205 mm  | Color coding Green         | Product no.<br>8675424  |
| for sheath sizes  CI 22/24 Fr  Also: | Outer sheath for resectoscope 24 Fr Inner sheath for resectoscope 22 Fr  | SL/WL<br>SL 189 mm   | Color coding               | Product no.<br>8675424<br>8675322                                 |
| for sheath sizes  CI 22/24 Fr  Also: | Outer sheath for resectoscope 24 Fr Inner sheath for resectoscope 22 Fr  Obturator for resectoscope 22 Fr  | SL/WL SL 189 mm SL 205 mm  | Color coding  Green  Green | Product no.  8675424  8675322  8673022                            |
| for sheath sizes  CI 22/24 Fr  Also: | Outer sheath for resectoscope 24 Fr Inner sheath for resectoscope 22 Fr  Obturator for resectoscope 22 Fr  Viewing obturator for resectoscope 22 Fr  | SL/WL SL 189 mm SL 205 mm  WL 232 mm   | Color coding Green         | Product no.  8675424  8675322  8673022  8673122                   |
| for sheath sizes  CI 22/24 Fr  Also: | Outer sheath for resectoscope 24 Fr Inner sheath for resectoscope 22 Fr  Obturator for resectoscope 22 Fr  Viewing obturator for resectoscope 22 Fr  Outer sheath for resectoscope 26 Fr                                     | SL/WL SL 189 mm SL 205 mm  WL 232 mm SL 189 mm   | Color coding  Green  Green | Product no.  8675424  8675322  8673022  8673122  8675426          |
| for sheath sizes  CI 22/24 Fr  Also: | Outer sheath for resectoscope 24 Fr Inner sheath for resectoscope 22 Fr  Obturator for resectoscope 22 Fr  Viewing obturator for resectoscope 22 Fr  Outer sheath for resectoscope 26 Fr                                     | SL/WL SL 189 mm SL 205 mm  WL 232 mm SL 189 mm   | Color coding  Green  Green | Product no.  8675424  8675322  8673022  8673122  8675426          |
| for sheath sizes  CI 22/24 Fr  Also: | Outer sheath for resectoscope 24 Fr Inner sheath for resectoscope 22 Fr  Obturator for resectoscope 22 Fr  Viewing obturator for resectoscope 22 Fr  Outer sheath for resectoscope 26 Fr Inner sheath for resectoscope 24 Fr | SL/WL SL 189 mm SL 205 mm  WL 232 mm SL 189 mm SL 205 mm   | Color coding  Green  Green | Product no.  8675424  8675322  8673022  8673122  8675426  8675324 |
| for sheath sizes  CI 22/24 Fr  Also: | Outer sheath for resectoscope 24 Fr Inner sheath for resectoscope 22 Fr  Obturator for resectoscope 22 Fr  Viewing obturator for resectoscope 22 Fr  Outer sheath for resectoscope 26 Fr Inner sheath for resectoscope 24 Fr | SL/WL  SL 189 mm  SL 205 mm  WL 232 mm  SL 189 mm  SL 205 mm   | Green  Green  Yellow       | 8675424<br>8675322<br>8673022<br>8673122<br>8675426<br>8675324    |





## IN COMBINATION WITH **SHARK** OUTER SHEATHS FOR TISSUE MORCELLATION



| PANOVIEW   | WL                               | TL     | Product no. |  |
|--|----------------------------------|--------|-------------|--|
| Morcescope 0° 24 Fr WL 199 mm Rigid, with parallel eyepiece, working channel for instruments up to 4.8 mm, irrigation via 24.5/26 Fr sheath and adapter, suction via morcellator | 199 mm                           | 393 mm | 8970407     |  |
| Autom. sealing element ID 5.7 mm   | 8920.311                         |        |             |  |
| Pressure ball for blowing air through channels   | 103.00                           |        |             |  |
| Tube with LUER-LOCK connector  |                                  |        | 886.00      |  |
| Cleaning brush Ø 11 mm TL 360 mm   | Cleaning brush Ø 11 mm TL 360 mm |        |             |  |

# Distal end Distal end Outer sheath Inner sheath

SL/WL

Color coding

Product no.


| CI                | Outer sheath for resectoscope 24 Fr         | SL 189 mm     | Oronn    | 8675424   |
|-------------------|---|---------------|----------|-----------|
| 22/24 Fr          | Inner sheath for resectoscope 22 Fr         | SL 205 mm     | Green    | 8675322   |
| Also:             |   |               |          |           |
|                   | Obturator for resectoscope 22 Fr            | WL 232 mm     |          | 8673022   |
|                   | Viewing obturator for resectoscope 22 Fr    | WL 232 IIIIII | Green    | 8673122   |
| GI                | Outer sheath for resectoscope 26 Fr         | SL 189 mm     | Walley . | 8675426   |
| 24/26 Fr          | Inner sheath for resectoscope 24 Fr         | SL 205 mm     | Yellow   | 8675324   |
| Also:             |   |               |          |           |
|                   | Obturator for resectoscope 24 Fr            | WL 233 mm     |          | 8673024   |
| €                 | Viewing obturator for resectoscope 24 Fr    | WL 232 mm     | Yellow   | 8673124   |
|                   | Dilatations obturator f. resectoscope 24 Fr | WL 247 mm     |          | 8673224   |
| Rotary morcellate | ors and accessories                         |               |          | see URO90 |

for sheath sizes





### IN COMBINATION WITH **E-LINE** OUTER SHEATHS FOR TISSUE MORCELLATION





# ROTARY MORCELLATORS/ACCESSORIES FOR THE MORCESCOPE

|           | for single use<br>(Pack = 3 PCS, in individual sterile packaging)                           | WL     | Ø      | Product no. |
|-----------|---|--------|--------|-------------|
| S Piranha | Rotary morcellator Ø 4.8 mm WL 335 mm   | 335 mm | 4.8 mm | 49700113    |
|           | Rotary morcellator Ø 4.8 mm WL 385 mm (for morcellator telescopes from other manufacturers) | 385 mm | 4.8 mm | 49700103    |

|                | for multiple use  | WL     | Ø      | Product no. |
|----------------|---|--------|--------|-------------|
| <i>Piranha</i> | Rotary morcellator Ø 4.8 mm WL 350 mm   | 350 mm | 4.8 mm | 8970.011    |
|                | Rotary morcellator Ø 4.8 mm WL 385 mm (for morcellator telescopes from other manufacturers) | 385 mm | 4.8 mm | 8970010     |

| Recommended accessories  |   | Product no. |
|--|---|-------------|
| Perforated basket for Morcescope with small parts sieve  Holds: standard telescope, for machine reprocessing, sterilization (steam and low-temperature), storage, and transport, | Internal dimensions (W x H x D): 451 x 65 x 164 mm External dimensions (W x H x D): 467 x 75 x 172 mm | 38012       |
| Fiber light cable bndl consisting of: Fiber light cable (80663523), projector-side adapter (8095.07), and endoscope-side adapter (809509)  | Ø 3.5 mm, 2.3 m long  | 806635231   |



### TISSUE MORCELLATOR



spirit of excellence

### FOR MORCELLATION AFTER LASER ENUCLEATION OF THE PROSTATE




|  |  | Artikel-Nr. |
|--|--|-------------|
| Suction pump 2208                              | with LCD display, 100–240 V AC, 50/60 Hz   | 2208001     |
| l-pedal footswitch                             |  | 2030108     |
| Bottle holder                                  |  | 64031.381   |
| Sound absorber                                 | (Pack= 3 PCS)  | 35100.115   |
| RECTO PUMP connection tube                     |  | 8170.6554   |
| Overflow protection/bacteria filter            | (Pack = 10 PCS)  | 2228.901    |
| Secretion container, 2 I                       | 2 liters, without cover  | 8170.6551   |
| Cover  | for secretion trap 8170.6551, reusable   | 8170.6552   |
| optional: 3 L suction jar for RCS              |  | 077.0130    |
| Power cable                                    | Cable length 3 m   | 2440.03     |
| Tube for suction                               | Single use (Pack = 10 PCS)   | 41702208    |
| Collecting container                           | Disposable (Pack = 10 PCS)   | 2208120     |
| Motor Control Unit 2303<br>for motor handpiece | 50/60 Hz, 100-240 V AC   | 2303.001    |
| also: Power cable                              | Cable length 3 m   | 2440.03     |
| Motor handpiece max. 6,000 rpm                 | consisting of:  Motor handpiece max. 6,000 rpm (8564.021), connection cable, WL 3 m (8564.851), sealing insert – open (15178145) | 8564122     |
| Irrigation adapter                             | for motor handpiece 8564.021, reusable   | 163951      |
| Rotary morcellator Ø 4.8 mm WL 335 mm          | (Pack = 3 PCS) in individual sterile packaging   | 49700113    |
| Rotary morcellator Ø 4.8 mm WL 385 mm          | (Pack = 3 PCS) in individual sterile packaging for morcellator telescopes from other manufacturers                               | 49700103    |
| Rotary morcellator Ø 4.8 mm WL 350 mm          |  | 8970.011    |
| Rotary morcellator Ø 4.8 mm WL 385 mm          |  | 8970010     |



IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

### 70 W HOLMIUM: YAG LASER SYSTEM FOR STONE AND BPH THERAPY





|  | Product no. |
|--|-------------|
| MegaPulse 70⁺  |             |
| Laser surgical device tower EU bndl  |             |
| consisting of:   |             |
| MegaPulse 70+ laser surgical device tower 70 W (2286007)                       |             |
| 2x laser protection goggles (OBM003603)  |             |
| 1x key set (2286525)   |             |
| 1x door contact plug (2286520)   |             |
| 2x blast shield with mounting (OAM001523)                                      | 22860070    |
| 1x filling bottle with tube (IAM000088)  |             |
| 1x 2-pedal footswitch (2030232)  |             |
| 1x fiber-stripping forceps for stripping laser fibers, 0.3 to 1.0 mm (2286523) |             |
| 1x fiber-stripping forceps for stripping laser fibers, 0.1 to 0.4 mm (2286527) |             |
| 1x ceramic cutter with silicone pad (AGM000080)                                |             |
| 1x accessories box for MegaPulse (KBM000103)                                   |             |
| 1x power cable TL 3 m (2286230)  |             |
|  |             |





| MEGA Pulse 70⁺             | 22860070  |
|----------------------------|---|
| Device properties          |   |
| Display                    | 12" touchscreen   |
| Power                      | 70 watts  |
| Laser type                 | Holmium:YAG laser (Ho:YAG)                                  |
| Wavelength                 | 2,100 nm (2.1 μm)   |
| Operating principle        | Pulsed  |
| Energy                     | 200-5,000 mJ  |
| Pulse duration             | Adjustable (50–1,100 μs)                                    |
| Pilot beam                 | Green: 532 nm, < 5 mW, can be set to continuous or flashing |
| Max. operating temperature | 10–30 °C  |
| Storage temperature        | Min. +5 °C, max. 40 °C                                      |
| Power supply               |   |
| Voltage                    | 200–230 V, 50/60 Hz, < 32 A                                 |
| Frequency                  | 3–60 Hz   |
| Dimensions and weights     |   |
| Dimensions (W x H x D)     | 595 x 1,200 x 1,074 mm                                      |
| Weight                     | 200 kg  |



| IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.





|              | Sterile (Pack= 1 PC)                   |   | 200 µm | 272 µm | 365 µm | 550 µm | 800 µm | 1,000<br>μm | Product no. |
|--------------|--|---|--------|--------|--------|--------|--------|-------------|-------------|
|              | Power laser fiber Ø 200 μm, disposable | • |        |        |        |        |        |             | 487502200   |
|              | Laser fiber Ø 200 μm, disposable       |   | •      |        |        |        |        |             | 487501200   |
|              | Laser fiber Ø 272 μm, disposable       |   |        | •      |        |        |        |             | 487501272   |
| Single use   | Laser fiber Ø 365 μm, disposable       |   |        |        | •      |        |        |             | 4875013650  |
|              | Laser fiber Ø 550 μm, disposable       |   |        |        |        | •      |        |             | 487501550   |
|              | Laser fiber Ø 800 μm, disposable       |   |        |        |        |        | •      |             | 487501800   |
|              | Laser fiber Ø 1,000 µm, disposable     |   |        |        |        |        |        | •           | 4875011000  |
|              | Power laser fiber Ø 200 μm, reusable   | • |        |        |        |        |        |             | 87502200    |
|              | Laser fiber Ø 200 μm, reusable         |   | •      |        |        |        |        |             | 87501200    |
| e e          | Laser fiber Ø 272 μm, reusable         |   |        | •      |        |        |        |             | 87501272    |
| Multiple use | Laser fiber Ø 365 μm, reusable         |   |        |        | •      |        |        |             | 875013650   |
| 2            | Laser fiber Ø 550 μm, reusable         |   |        |        |        | •      |        |             | 87501550    |
|              | Laser fiber Ø 800 μm, reusable         |   |        |        |        |        | •      |             | 87501800    |
|              | Laser fiber Ø 1,000 µm, reusable       |   |        |        |        |        |        | •           | 875011000   |





| Accessories                      |   |              | Product no.  |
|----------------------------------|---|--------------|--------------|
|                                  |   | Ø 200–272 µm | AGM000053    |
| Fiber-stripping forceps,         | for election in a local fibration   | Ø 365–400 µm | AGM000078    |
| autoclavable                     | for stripping laser fibers  | Ø 550–600 µm | AGM000052    |
|                                  |   | Ø 800 µm     | AGM000064    |
| Film this is a factor            | for this is a love fiber  | Ø 0.1–0.4 mm | 2286527      |
| Fiber-stripping forceps          | for stripping laser fibers  | Ø 0.3–1.0 mm | 2286523      |
| Ceramic cutter with silicone pad |   |              | AGM000080    |
| Filling bottle with tube         |   |              | IAM000088    |
| Laser protection goggles         | (Also suitable for glasses-wearers)   | OBM003603    |              |
| 2-pedal footswitch               |   | 2030232      |              |
| Key set                          |   |              | 2286525      |
| Door contact plug                |   |              | 2286520      |
| Blast shield with mounting       |   |              | OAM001523    |
| Power cable TL 3 m               |   |              | 2286230      |
| Accessories box for MegaPulse    |   |              | KBM000103    |
| Adapter cable                    | CEE coupling, 3-pin 32 A 6 h 230 V AC blu<br>CEE plug, 5-pin 32 A 6 h 400 V AC red (in- | ,            | 100-201-0518 |

| Machine reprocessing              |  | Product no. |
|-----------------------------------|--|-------------|
| Perforated basket for laser fiber | Holds: Laser fiber, for machine reprocessing, sterilization (steam and low-temperature), storage, and transport; internal dimensions (W x H x D): 231 x 52 x 223 mm external dimensions (W x H x D): 248 x 72 x 239 mm | 38001       |
| Also: Fixing ring Ø 34.6 mm       | for holding instruments during machine reprocessing, sterilization (steam and low-temperature), storage, and transport, $\emptyset$ 34.6 x 2.62 mm, Pack = 5 PCS   | 643301262   |



# Pulvis 60<sup>†</sup>

60 W THULIUM FIBER LASER (TFL) FOR STONE THERAPY AND ENDOSCOPIC ENUCLEATION OF THE PROSTATE (EEP)



Pulvis 60+

60 W thulium fiber laser (TFL)

PFMS00006

IX23 | Suject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.



# Pulvis 60<sup>†</sup>

# 60 W THULIUM FIBER LASER (TFL) TECHNICAL DATA

| Pulvis 60⁺  | PFMS00006   |
|---|---|
| Device properties   |   |
| Display   | Fold-out, rotatable touchscreen display (rotates 90° to the right and 180° to the left)                                     |
| Operating temperature   | 15–30 °C (at a room temperature between 25 °C and 30 °C, operation is guaranteed with a maximum output power of up to 40 W) |
| Storage/transport temperature                                       | Min. +5 °C/max. 40 °C   |
| Atmospheric pressure  | 800-1,060 hPa   |
| Operating humidity  | 30–85 %, non-condensing   |
| Max. noise level  | < 70.0 dB   |
| Equipment   |   |
| Cooling method  | Air cooling system  |
| Power supply  |   |
| Mains + frequency   | 100–240 V AC, 50/60 Hz  |
| Power consumption   | 1,000 VA  |
| Regulatory standards  |   |
| Classification according to the Medical Devices Directive 93/42/EEC | Class IIb   |
| Laser classification according to IEC/EN 60825-1:2014               | Class 4   |
| Pilot beam classification according with IEC/EN 60825-1:2014        | Class 3R  |
| Dimensions and weights  |   |
| Weight  | 100 kg  |
| Dimensions (W x H x D)  | 470 x 1,156 x 810 mm<br>470 x 940 x 810 mm – display closed   |



# PUVIS 60\* 60 WTHULIUM FIBER LASER (TFL) TECHNICAL DATA

Pulvis 60+ PFMS00006 Laser source specifications Laser type Thulium fiber-laser Wavelength  $1,940 \text{ nm} \pm 20 \text{ nm}$ 60 W (pulsed/CW) Maximum output power 0.02-6 J Pulse energy Pulsed/CW Operating mode Pulse duration  $50 \ \mu s - CW$ 1-2,500 Hz Frequency of recurrence Large selection of laser fibers (see next page) Delivery system (sterile, disposable, and reusable) Green 532 nm (adjustable) < 5 mW, class 3R Pilot beam Goggles 1940 D LB4



# Pulvis 60°

LASER FIBERS



|              |  | Core diameter |           |           |           |           |           |           |           |             |             |
|--------------|--|---------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-------------|-------------|
|              | Sterile (Pack= 10 PC)                    |               | 200<br>μm | 272<br>μm | 365<br>µm | 500<br>μm | 550<br>µm | 600<br>µm | 800<br>µm | 1,000<br>µm | Product no. |
|              | Single use optical fiber 150 µm          | •             |           |           |           |           |           |           |           |             | OFJ001511   |
|              | Single use optical fiber 200 µm          |               | •         |           |           |           |           |           |           |             | OFJ002011   |
|              | Single use optical fiber 272 µm          |               |           | •         |           |           |           |           |           |             | 0FJ702711   |
|              | Single use optical fiber ball tip 272 µm |               |           | •         |           |           |           |           |           |             | 0FJ302711   |
| Single use   | Single use optical fiber 365 µm          |               |           |           | •         |           |           |           |           |             | 0FJ703611   |
|              | Single use optical fiber 550 µm          |               |           |           |           |           | •         |           |           |             | OFJ005511   |
|              | Single use optical fiber lateral 600 µm  |               |           |           |           |           |           | •         |           |             | OFJ506011   |
|              | Single use optical fiber 800 µm          |               |           |           |           |           |           |           | •         |             | OFJ008011   |
|              | Single use optical fiber 1,000 µm        |               |           |           |           |           |           |           |           | •           | OFJ009911   |
|              | Reusable 10x optical fiber 200 µm        |               | •         |           |           |           |           |           |           |             | 0FJ002013   |
|              | Reusable 10x optical fiber 272 µm        |               |           | •         |           |           |           |           |           |             | 0FJ702713   |
| Multiple use | Reusable 10x optical fiber 365 µm        |               |           |           | •         |           |           |           |           |             | 0FJ703613   |
| Multip       | Reusable 10x optical fiber 500 µm        |               |           |           |           | •         |           |           |           |             | 0FJ005513   |
|              | Reusable 10x optical fiber 800 µm        |               |           |           |           |           |           |           | •         |             | 0FJ008013   |
|              | Reusable 10x optical fiber 1,000 µm      |               |           |           |           |           |           |           |           | •           | 0FJ009913   |

| IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# PUIVIS 60<sup>†</sup> ACCESSORIES

| Accessories                               | Product no.  |
|---|--------------|
| Interlock Conn. Medical Devices Binder    | EAM000045.00 |
| Кеу                                       | MBQ000190.00 |
| Power cord-5m-spina Shuko 16A EUR         | EAM001440.00 |
| Fiberstripper optical fibers Ø300-1000 μm | OBM001079.00 |
| Fiberstripper optical fibers Ø100-400 μm  | OBM001080.00 |
| Case salsa 1650 no brand accessories      | KBM000103.01 |
| Ceramic fiber cutter with slipcase        | AGM000080.00 |
| Goggle protection f18.P1d09.1003          | OBM003778.00 |
| Optical blast shield for tfl ext-access   | OAM002112.00 |

| Machine reprocessing              |  | Product no. |
|-----------------------------------|--|-------------|
| Perforated basket for laser fiber | Holds: Laser fiber, for machine reprocessing, sterilization (steam and low-temperature), storage, and transport; internal dimensions (W x H x D): 231 x 52 x 223 mm external dimensions (W x H x D): 248 x 72 x 239 mm | 38001       |
| Also: Fixing ring Ø 34.6 mm       | for holding instruments during machine reprocessing, sterilization (steam and low-temperature), storage, and transport, $\emptyset$ 34.6 x 2.62 mm, Pack = 5 PCS   | 643301262   |

# | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with



### HF GENERATOR 2260



| Accessories required  | Cable length | Product no. |
|---|--------------|-------------|
| Footswitch, 2 pedals L 5 m with fixed connection cable, reusable  |              | 2260021     |
| Neutral electrode for use with high-frequency surgical device, foil bag with 5 neutral electrodes (Pack = 50 PCS) |              | 1280H       |
| Mono HF neutral electrode cable, L 4.5 m  | 4.5 m        | 2260031     |
| Power cable   | 3.0 m        | 2440.03     |
| Bipo HF connection cable L 3 m  | 3.0 m        | 8108233     |
| Bipo HF connection cable L 5 m  | 5.0 m        | 8108253     |



### HF GENERATOR 2260

### TECHNICAL DATA

| HF surgical generator 40                                   | 00 kHz                      | 2260001/2260002  |  |
|--|-----------------------------|--|--|
| Device properties  |                             |  |  |
| Type of controls on housi                                  | ng front                    | Touch panel  |  |
| 0.1.1  | Max. cutting power          | 400 W  |  |
| Output power   | Max. coagulation power      | 350 W  |  |
| LF and HF leakage currents                                 |                             | Acc. to DIN EN 60601-1 and DIN EN 60601-2-2  |  |
| Signal level   |                             | HF indicator 55 dB(A); adjustable 45–60 dB(A) Alarm 65 dB(A)   |  |
| Operating conditions                                       |                             | $+10~^{\circ}\text{C}$ to $+40~^{\circ}\text{C}$ , 30 % to 75 % rel. humidity, 700 hPa to 1,060 hPa atmospheric pressure |  |
| Storage and transport co                                   | nditions                    | -20 °C to +60 °C, 10 % to 90 % rel humidity, 700 hPa to 1,060 hPa atmospheric pressure                                   |  |
| Power supply   |                             |  |  |
| Mains + frequency  |                             | 100–240 V AC, 50/60 Hz   |  |
|  | without HF output           | 45 VA  |  |
| Power consumption  | at max. output power        | 650 VA   |  |
| Current consumption  |                             | Max. 6.3 A   |  |
| Fuse   |                             | T 6.3 AH 250 V   |  |
| Regulatory standards                                       |                             |  |  |
| Protection class to EN/IEC<br>(UL 2601-1/CSA C22.2 N       |                             | I  |  |
| Electromagnetic compati                                    | ibility (EMC)               | EN/IEC 60601-1-2   |  |
| Medical Devices Directive                                  | e 93/42/EEC                 | Class IIb  |  |
| Degree of protection aga<br>(DIN EN/IEC 60529)             | inst the ingress of liquids | IP XO  |  |
| Degree of protection aga                                   | inst the ingress of solids  | IP 2X  |  |
| Duty factor (duty cycle D                                  | C)                          | Intermittent INT 10 s/30 s corresponding to 25 % DC  |  |
| Protection against electric shock                          |                             | Type CF applied part, defibrillator-proof  |  |
| Degree of protection in the presence of flammable mixtures |                             | Device is not protected against explosions (do not operate this device in explosive atmospheres)                         |  |
| Dimensions and weights                                     | S                           |  |  |
| Weight   |                             | 10.2 kg (22.4 lbs)   |  |
| Dimensions (W x H x D)                                     |                             | 300 x 159 x 419 mm   |  |

# HF CONNECTION CABLE MONO 815XXX

| Instrument connector  | Device connector  |                                | Product no. |
|-----------------------|---|--------------------------------|-------------|
| WOLF<br>Resectoscopes |   | HF connection cable mono L 3 m | 815.032     |
|                       | ERBE (ACC/ICC/VIO)/BOWA (EU) R. Wolf HF surgical generator 400 kHz 2260002                              | HF connection cable mono L 5 m | 815.052     |
| 0                     |   | HF connection cable mono L 3 m | 815.132     |
|                       | ERBE (T series)   | HF connection cable mono L 5 m | 815.152     |
| HF electrodes,        |   | HF connection cable mono L 3 m | 815.031     |
| monopolar             | Martin (M-version)/Berchtold/<br>Aesculap   | HF connection cable mono L 5 m | 815.051     |
|                       |   | HF connection cable mono L 3 m | 815.033     |
|                       | Bovie/Valleylab/Erbe (Int.)/<br>BOWA (Int.)<br>R. Wolf HF surgical generator 400 kHz<br>2260001         | HF connection cable mono L 5 m | 815.053     |
|                       |   | HF connection cable mono L 3 m | 815.034     |
|                       | BOWA (Int./EU) Eschmann and other devices with 4 mm plugs R. Wolf HF surgical generator 400 kHz 2260001 | HF connection cable mono L 5 m | 815.054     |



IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# HF CONNECTION CABLE MONO 8106xxx

| Instrument connector                   | Device connector  |                                | Product no. |
|--|---|--------------------------------|-------------|
| WOLF<br>Instruments/surgical generator |   | HF connection cable mono L 3 m | 8106.032    |
|  | ERBE (ACC/ICC/VIO)/BOWA (EU) R. Wolf HF surgical generator 400 kHz 2260002                                      | HF connection cable mono L 5 m | 8106.052    |
| 67                                     |   | HF connection cable mono L 3 m | 8106.132    |
|  | ERBE (T series)   | HF connection cable mono L 5 m | 8106.152    |
|  |   | HF connection cable mono L 3 m | 8106.031    |
| HF electrodes, monopolar               | Martin (M-version)/Berchtold/<br>Aesculap   | HF connection cable mono L 5 m | 8106.051    |
|  |   | HF connection cable mono L 3 m | 8106.033    |
|  | Bovie/Valleylab/Erbe (Int.)/<br>BOWA (Int.)<br>R. Wolf HF surgical generator 400 kHz<br>2260001                 | HF connection cable mono L 5 m | 8106.053    |
|  |   | HF connection cable mono L 3 m | 8106.034    |
|  | BOWA (Int./EU) Eschmann and other devices with 4 mm plugs R. Wolf HF surgical generator 400 kHz 2260001/2260002 | HF connection cable mono L 5 m | 8106.054    |

# IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.



spirit of excellence

### HF CONNECTION CABLE BIPO 8108XXX

| Instrument connector        | Device connector  |                                 | Product no. |
|-----------------------------|---|---------------------------------|-------------|
| WOLF<br>Bipolar forceps     |   | HF connection cable bipo; L 3 m | 8108.032    |
|                             | ERBE (ACC/ICC/T)/BOWA (EU) R. Wolf HF surgical generator 400 kHz 2260001/2260002            | HF connection cable bipo; L 5 m | 8108.052    |
| ALGOY ALGOY                 |   | HF connection cable bipo; L 3 m | 8108.033    |
|                             | International / 2-pin Valleylab<br>R. Wolf HF surgical generator 400 kHz<br>2260001/2260002 | HF connection cable bipo; L 5 m | 8108.053    |
|                             |   | HF connection cable bipo; L 3 m | 8108.031    |
|                             | WOLF/Martin (M-version)/<br>Berchtold/Aesculap  | HF connection cable bipo; L 5 m | 8108.051    |
|                             | EMC Dolley  | HF connection cable bipo; L 3 m | 8108035     |
| Bipolar tweezers connection |   | HF connection cable bipo; L 3 m | 8108.132    |
|                             | ERBE (ACC/ICC/T)/BOWA (EU) R. Wolf HF surgical generator 400 kHz 2260001/2260002            | HF connection cable bipo; L 5 m | 8108.152    |
|                             |   | HF connection cable bipo; L 3 m | 8108.133    |
| Rugge                       | International / 2-pin Valleylab R. Wolf HF surgical generator 400 kHz 2260001/2260002       | HF connection cable bipo; L 5 m | 8108.153    |
|                             |   | HF connection cable bipo; L 3 m | 8108.131    |
|                             | Martin (M-version)/Berchtold/<br>Aesculap   | HF connection cable bipo; L 5 m | 8108.151    |
|                             | EMC Dolley  | HF connection cable bipo; L 3 m | 8108135     |



# HF CONNECTION CABLE BIPO FOR RESECTION IN SALINE SOLUTION

| Instrument connector        | Device connector   |   | Product no. |
|-----------------------------|--|---|-------------|
| WOLF S(a)line resectoscopes | Erbe VIO 300D  | Bipolar cable; TUR/TCR;<br>WOLF<br>MF plug; L 4 m | 20196-119   |
| O                           | Erbe VIO 3   | <b>Bipolar cable; MF-U</b><br>MF plug; L 4.5 m    | 21196-119   |
|                             |  | HF connection cable bipo; L 3 m                   | 8108.231    |
|                             | KLS Martin   | HF connection cable bipo; L 5 m                   | 8108.251    |
|                             |  | HF connection cable bipo; L 3 m                   | 8108233     |
|                             | R. Wolf HF surgical generator 400 kHz<br>2260001/2260002 | HF connection cable bipo; L 5 m                   | 8108253     |



### FLUID CONTROL 2225

### SUCTION IRRIGATION PUMP



|   | Product no. |
|---|-------------|
| FLUID CONTROL 2225  Irrigation pump for HYS/URO/LAP bndl consisting of: Irrigation pump for HYS/URO/LAP (2225001) and power cable 3 m long (2440.03)  | 22250011    |
| Also:   |             |
| Balancing module for hysteroscopy and endourology, fluid management for fluid balancing in combination with FLUID CONTROL 2225, mobile stand with integrated weighing cells and space for up to 4 irrigation fluid bags | 2225023     |

| Accessories |  | Product no. |
|-------------|--|-------------|
| Footswitch  | Only for use in urology and within the indication TUR/enucleation, possibility of short-term increase in pressure if visibility is poor (Flush function) | 2204901     |

| Cable accessories                  |                    | Product no. |
|------------------------------------|--------------------|-------------|
| Patch cable, RJ45 SFTP, 0.5 m      | Cable length 0.5 m | 72325378    |
| Patch cable, RJ45 HRS TM11, 1.0 m  | Cable length 1.0 m | 72325429    |
| Patch cable, RJ45 S/FTP CAT.6 10 m | Cable length 10 m  | 72325434    |
| Plastic caps for network socket    | (Pack = 8 PCS)     | 5592105     |
| Power cable                        | Cable length 3 m   | 2440.03     |

IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

### FLUID CONTROL 2225

### SUCTION IRRIGATION TUBE SETS

| Irrigation                  |   |  | Product no. |
|-----------------------------|---|--|-------------|
| Accessories<br>– reusable   | Tube set with piercing spike                      | with Luer-Lock connection, autoclavable, incl. 10 spare membranes, reusable for 20 reprocessing cycles | 8171223     |
| Accessories<br>– disposable | Irrigation tube set with piercing spike,<br>L 3 m | (PACK= 10 PCS), with Luer-Lock connection, sterile, disposable product                                 | 4171223     |
|                             | Tube set with CARE-LOCK,<br>L 3 m                 | (PACK= 10 PCS), sterile, disposable product  | 4171224     |
|                             | Suction irrigation tube set                       | (PACK= 10 PCS),<br>with piercing spike, sterile disposable product, PVC                                | 4171225     |

| Suction                   |   |  | Product no. |
|---------------------------|---|--|-------------|
| Accessories<br>– reusable | Tube set for vacuum, incl. filter       | with integrated hygiene filter, PACK= 10 PCS, service life: 30 days (connected to irrigation pump)     | 2206207     |
|                           | Irrigation tube                         | L 1.2 m, with Luer-Lock,<br>for suction irrigation handle 8385.901 and tube set<br>8171223 or 8170.223 | 817123      |
|                           | Suction tube L 3 m                      | for suction irrigation handle 8385.901   | 8171402     |
|                           | Secretion container, 2 I                | 2 liters, without cover  | 8170.6551   |
|                           | Cover                                   | for secretion trap 8170.6551, reusable   | 8170.6552   |
|                           | Secretion container, 2.5 I              | 2.5 liters   | 41706566    |
| Accessories               | Secretion container bndl consisting of: | Secretion container 2.5 I (41706566) and secretion bag (PACK= 90 PCS) (41706564)                       | 4170657     |
| – disposable              | Tube set for suction (2 connections)    | sterile, disposable product, (PACK= 10 PCS) for connecting instruments to collecting container         | T0503-01    |
|                           | Angled 90° plug-in coupling             | (PACK= 10 PCS) For connecting vacuum tube 2206207 to disposable container systems                      | 0771019     |

#### TECHNICAL DATA **FLUID CONTROL 2225**

**FLUID CONTROL 2225** 2225001 **Device properties**  $+10~^{\circ}\text{C}$  to  $+40~^{\circ}\text{C}$ , 30 % to 75 % rel. humidity, 70 to 106 kPa atmospheric pressure Operating conditions 3,000 m max. altitude above sea level Storage and transport conditions -20 °C to +60 °C, 10 % to 90 % rel. humidity, 70 to 106 kPa atmospheric pressure **Power supply** 100-240 V AC, 50/60 Hz Mains + frequency 100 V/60 Hz 110 VA Power consumption 120 VA 240 V/50 Hz 100 V/60 Hz 1.10 A Current consumption 240 V/50 Hz 0.50 A Fuse T 3.15 AH, 250 V Regulatory standards Protection class (I, II) EN 60601-1/IEC 60601-1 Electromagnetic compatibility (EMC) EN 60601-1-2/IEC 60601-1-2 Medical Devices Directive 93/42/EEC Class IIb Housing protection rating (IP code) IP 21 Protection against electric shock Type BF applied part Device is not protected against explosions Degree of protection in the presence of flammable mixtures (do not operate this device in explosive atmospheres) -60 kPa Maximum suction vacuum Dimensions and weights Weight 8.8 kg Dimensions (W x H x D) 300 mm x 157 mm x 436 mm

| Relevant application parameters |  |  |  |  |
|---------------------------------|--|--|--|--|
|                                 | Hysteroscopy: 800 ml/min (max. flow, not adjustable) |  |  |  |
| Nominal flow range              | Endourology: 10-800 ml/min (max. flow)               |  |  |  |
|                                 | Laparoscopy: 0.1–1.8 I/min (max. flow)               |  |  |  |
| Suction power                   | Max. 2 I/min   |  |  |  |
|                                 | Hysteroscopy: 15–200 mmHg                            |  |  |  |
| Starting nominal pressure range | Endourology: 15-90 mmHg/20-120 cmH20                 |  |  |  |
|                                 | Laparoscopy: 300 mmHg (not adjustable)               |  |  |  |
| Pressure                        | 0–300 mmHg   |  |  |  |
| Deficit                         | -9,990 to +9,990 ml/0 to 99.9 l                      |  |  |  |


| IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

## TECHNICAL DATA FLUID CONTROL 2225

| Balancing module                    | 2225023  |
|-------------------------------------|--|
| Device properties                   |  |
| Operating conditions                | +10 °C to +40 °C, 30 % to 75 % rel. humidity, 70 to 106 kPa atmospheric pressure 3,000 m max. altitude above sea level |
| Storage and transport conditions    | -20 °C to +60 °C, 10 % to 90 % rel. humidity, 70 to 106 kPa atmospheric pressure                                       |
| Regulatory standards                |  |
| Electromagnetic compatibility (EMC) | EN 60601-1/IEC 60601-1<br>EN 60601-1-2/IEC 60601-1-2   |
| Housing protection rating (IP code) | IP 21  |
| Maximum load of container scale     | 16 kg/4 containers of 3 I each   |
| Maximum load of bag scale           | 23 kg/4 bags of 5 l each   |
| Dimensions and weights              |  |
| Weight                              | 15.4 kg  |
| Dimensions (W x H x D)              | 618 mm x 1,064 mm x 618 mm   |

| Footswitch                          | 2204901                  |
|-------------------------------------|--------------------------|
| Power supply                        |                          |
| Power supply connection             | Max. 24 V                |
| Power consumption                   | Max. 0.1 A               |
| Regulatory standards                |                          |
| Electromagnetic compatibility (EMC) | EN 60601-1/IEC 60601-1   |
| Housing protection rating (IP code) | IP X8                    |
| Plug                                | 7-pin circular connector |
| Cable length                        | 4.5 m                    |
| Dimensions and weights              |                          |
| Weight                              | 300 g                    |
| Dimensions (W x H x D)              | 66 mm x 27 mm x 91 mm    |





**UPPER URINARY TRACT** 



### **UPPER URINARY TRACT**


| URETE  | RORENOSCOPY   |
|--------|---|
|        | " URETERORENOSCOPE / FIBER URETERORENOSCOPES / CONTINUOUS IRRIGATION RORENOSCOPES |
| FLEXIB | LE FIBER URS 270° – THE VIPER   |
| FLEXIB | LE 2-CHANNEL CONTINUOUS IRRIGATION LASER URS – THE COBRA                          |
| FLEXIB | LE 1-CHANNEL SENSOR URETERORENOSCOPES - BOA vision / BOA vision EF                |
| FLEXIB | LE 2-CHANNEL SENSOR URETERORENOSCOPES – COBRA vision / COBRA vision EF            |
| DISPOS | SABLE SENSOR URETERORENOSCOPE – RIWO D-URS  |
| NEPHR  | OSCOPY  |
| DILATO | RS FOR PERCUTANEOUS UNIVERSAL NEPHROSCOPES  |
| MINI N | EPHROSCOPE BY LAHME   |
| PERCU  | TANEOUS UNIVERSAL NEPHROSCOPE, "DRESDEN MODEL"                                    |
| PERCU  | TANEOUS UNIVERSAL NEPHROSCOPES  |
| FLEXIB | LE FIBER NEPHROSCOPE  |
| LASER  | ENERGY SOURCES  |
| "MEGA  | PULSE 70+" HOLMIUM:YAG LASER (Ho:YAG)   |
| "PULVI | S 60+" THULIUM FIBER LASER (TFL)  |
| SUCTIO | ON IRRIGATION PUMP  |
| ELLIID | CONTROL 2225  |



### **ULTRA-THIN FIBER URETERORENOSCOPE**

WITH LATERAL EYEPIECE





|  | WL     | TL     | Direction of view | Endoscope<br>tip/Sheath tube | Working<br>channel | Product no. |
|--|--------|--------|-------------------|------------------------------|--------------------|-------------|
| Ureterorenoscope 5° 4.5/6.5 Fr WL 430 mm Atraumatically shaped tip | 430 mm | 555 mm | 5°                | 4.5/6.5<br>Fr                | 3 Fr               | 8701.534    |


| Recommended accessories   | Product no. |            |
|---|-------------|------------|
| Flex. grasping forceps 3 Fr WL 530 mm   | 828.605     |            |
| Flex. biopsy forceps 3 Fr WL 530 mm   |             | 829.603    |
| Handle for E-Line ureterorenoscopes   |             | 8702.261   |
| Guide element for ureterorenoscope for LITHOCLAST handpieces  |             | 8702.251   |
| for inserting auxiliary instruments of 1–6 Fr: universal sealing valve  | 4712348     |            |
| Membrane holder standard  | 15256.393   |            |
| Membrane holder with Luer   | 15256.456   |            |
| <b>Seal Ø 7.5 mm</b> (Pack = 10 pcs)  | 89.101      |            |
| Perforated basket, upper urinary tract 1 with small part basket   | 38003       |            |
| Marking pen, black  | 38201.948   |            |
| Fiber light cable bndl consisting of:<br>Fiber light cable (80662523), projector-side adapter (8095.07),<br>and endoscope-side adapter (809509) | 806625231   |            |
| Auxiliary instruments   |             | see URO119 |



### FIBER URETERORENOSCOPE

#### WITH STRAIGHT EYEPIECE






|   | WL     | ΤL     | Direction of view | Endoscope<br>tip/Sheath tube | Working chan-<br>nel         | Product no. |
|---|--------|--------|-------------------|------------------------------|------------------------------|-------------|
| Ureterorenoscope 5° 6/7.5 Fr WL 430 mm Atraumatically shaped tip  | 430 mm | 558 mm | 5°                | 6/7.5<br>Fr                  | 1 x 4 Fr<br>or<br>2 x 2.2 Fr | 8702.514    |
| Ureterorenoscope 12° 8/9.8 Fr WL 430 mm Atraumatically shaped tip | 430 mm | 558 mm | 12°               | 8/9.8<br>Fr                  | 1 x 5 Fr<br>or<br>2 x 3 Fr   | 8703.514    |

| Recommended accessories   | Product no.          |            |
|---|----------------------|------------|
| Handle for E-Line ureterorenoscopes   | 8702.261             |            |
| for inserting auxiliary instruments of 1–6 Fr: universal sealing val  | 4712348              |            |
| Perforated basket, upper urinary tract 1 with small part basket   | 38003                |            |
| Marking pen, black  | 38201.948            |            |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long | 806625231  |
| Auxiliary instruments   |                      | see URO119 |

### FIBER URETERORENOSCOPE

#### WITH LATERALLY OFFSET EYEPIECE





|  | WL     | TL     | Direction of view | Endoscope<br>tip/Sheath tube | Working chan-<br>nel     | Product no. |
|--|--------|--------|-------------------|------------------------------|--------------------------|-------------|
| Ureterorenoscope 5° 6/7.5 Fr WL 430 mm Atraumatically shaped tip     | 430 mm | 599 mm | 5°                | 6/7.5<br>Fr                  | 1 x 4 or<br>(2 x 2.2) Fr | 8702.524    |
| Ureterorenoscope 12° 8/9.8 Fr WL 430 mm Atraumatically shaped tip    | 430 mm | 599 mm | 12°               | 8/9<br>Fr                    | 1 x 5 or<br>(2 x 3) Fr   | 8703.524    |
| Ureterorenoscope 12° 8.5/11.5 Fr WL 430 mm Atraumatically shaped tip | 430 mm | 599 mm | 12°               | 8.5/11.5<br>Fr               | 1 x 6 or<br>(2 x 4) Fr   | 8704.524    |


| Recommended accessories   | Product no.                       |            |
|---|-----------------------------------|------------|
| Handle for E-Line ureterorenoscopes   |                                   | 8702.261   |
| Guide element for ureterorenoscope for LITHOCLAST handpieces  |                                   | 8702.251   |
| for inserting auxiliary instruments of 1–6 Fr: universal sealing valv   | re 1–6 Fr, sterile (Pack = 5 PCS) | 4712348    |
| Membrane holder standard  |                                   | 15256.393  |
| Membrane holder with Luer connection  | 15256.456                         |            |
| <b>Seal Ø 7.5 mm</b> (Pack = 10 pcs)  | 89.101                            |            |
| Perforated basket, upper urinary tract 1 with small part basket   | 38003                             |            |
| Marking pen, black  | 38201.948                         |            |
| Fiber light cable bndl consisting of:<br>Fiber light cable (80662523), projector-side adapter (8095.07),<br>and endoscope-side adapter (809509) | 806625231                         |            |
| Auxiliary instruments   |                                   | see URO119 |



### FIBER URETERORENOSCOPE

#### WITH LATERAL EYEPIECE





|   | WL     | ΤL     | Direction of view | Endoscope tip / Sheath tube | Working<br>channel           | Product no. |
|---|--------|--------|-------------------|-----------------------------|------------------------------|-------------|
| Ureterorenoscope 5° 6/7.5 Fr WL 430 mm Atraumatically shaped tip  | 430 mm | 563 mm | 5°                | 6/7.5<br>Fr                 | 1 x 4 Fr<br>or<br>2 x 2.2 Fr | 8702.534    |
| Ureterorenoscope 12° 8/9.8 Fr WL 430 mm Atraumatically shaped tip | 430 mm | 563 mm | 12°               | 8/9.8<br>Fr                 | 1 x 5 Fr or<br>2 x 3 Fr      | 8703.534    |

| Recommended accessories   | Product no.                       |            |
|---|-----------------------------------|------------|
| Handle for E-Line ureterorenoscopes   |                                   | 8702.261   |
| Guide element for ureterorenoscope for LITHOCLAST handpieces  |                                   | 8702.251   |
| for inserting auxiliary instruments of 1–6 Fr: universal sealing val  | ve 1-6 Fr, sterile (Pack = 5 PCS) | 4712348    |
| Membrane holder standard  |                                   | 15256.393  |
| Membrane holder with Luer   | 15256.456                         |            |
| <b>Seal Ø 7.5 mm</b> (Pack = 10 pcs)  | 89.101                            |            |
| Perforated basket, upper urinary tract 1 with small part basket   | 38003                             |            |
| Marking pen, black  | 38201.948                         |            |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | 806625231                         |            |
| Auxiliary instruments   | ,                                 | see URO119 |





IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

spirit of excellence

### CONTINUOUS IRRIGATION URETERORENOSCOPE

WITH STRAIGHT EYEPIECE





|  | WL     | ΤL     | Direction<br>of view | Endoscope tip / Sheath tube | Working channel  | Product no. |
|--|--------|--------|----------------------|-----------------------------|--|-------------|
| Ureterorenoscope 5° 6.5/8.5 Fr WL 430 mm Atraumatically shaped tip | 430 mm | 572 mm | 5°                   | 6.5 / 8.5<br>Fr             | Working channel 1:<br>1 x 4 (2 x 2.2) Fr<br>Working channel 2:<br>2.4 Fr | 8708.518    |

| Recommended accessories   | Product no.          |            |
|---|----------------------|------------|
| Handle for E-Line ureterorenoscopes   | 8702.261             |            |
| for inserting auxiliary instruments of 1–6 Fr: universal sealing val  | 4712348              |            |
| Perforated basket, upper urinary tract 1 with small part basket   | 38003                |            |
| Marking pen, black  |                      | 38201.948  |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long | 806625231  |
| Auxiliary instruments   |                      | see URO119 |




## WOLF

#### spirit of excellence

### CONTINUOUS IRRIGATION URETERORENOSCOPE

WITH LATERAL EYEPIECE



|  | WL     | ΤL     | Direction of view | Endoscope<br>tip/Sheath tube | Working<br>channel           | Product no. |
|--|--------|--------|-------------------|------------------------------|------------------------------|-------------|
| Ureterorenoscope 5° 6.5/8.5 Fr WL 430 mm Atraumatically shaped tip | 430 mm | 563 mm | 5°                | 6.5/8.5<br>Fr                | 1 x 4.2 Fr and<br>2 x 2.4 Fr | 8708.534    |
| Ureterorenoscope 12° 8/9.8 Fr WL 430 mm Atraumatically shaped tip  | 430 mm | 563 mm | 12°               | 8/9.8<br>Fr                  | 1 x 5 or<br>(2 x 3) Fr       | 8703.534    |

| Recommended accessories   |                                   | Product no. |
|---|-----------------------------------|-------------|
| Handle for E-Line ureterorenoscopes   | 8702.261                          |             |
| Guide element for ureterorenoscope for LITHOCLAST handpieces  |                                   | 8702.251    |
| for inserting auxiliary instruments of 1–6 Fr: universal sealing val  | ve 1-6 Fr, sterile (Pack = 5 PCS) | 4712348     |
| Membrane holder standard  |                                   | 15256.393   |
| Membrane holder with Luer connection  | 15256.456                         |             |
| <b>Seal Ø 7.5 mm</b> (Pack = 10 pcs)  | 89.101                            |             |
| Perforated basket, upper urinary tract 1 with small part basket   | 38003                             |             |
| Marking pen, black  | 38201.948                         |             |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | 806625231                         |             |
| Auxiliary instruments   | ,                                 | see URO119  |

#### FORCEPS AND SCISSORS

## SMALL MODULAR SYSTEM $\ensuremath{\mathsf{H}_{ec{\mathsf{y}}}}$ Scree


 $360^{\circ}$  rotatable, can be flushed through, easy-click

| Grasping forceps jaw insert with                    | ı sheath    |    |          | Handle with overload protection | Complete instrument  • Jaw section |
|---|-------------|----|----------|---------------------------------|------------------------------------|
|   |             |    | • Handle |                                 |                                    |
|   | Product no. | Fr | WL       | 8083.001                        | Product no.                        |
| Biopsy forceps bndl                                 | 8952.6008   | 5  | 550 mm   | •                               | 8952.6002                          |
| Grasping forceps bndl<br>with mouse tooth           | 8952.6118   | 4  | 550 mm   | •                               | 8952.6112                          |
|   | 8959.6218   | 5  | 425 mm   | •                               | 8959.6212                          |
|   | 8952.6218   | 5  | 550 mm   | •                               | 8952.6212                          |
| Grasping forceps bndl<br>with pike-mouth jaws, long | 8959.6808   | 5  | 425 mm   | •                               | 8959.6802                          |
| William .   | 8954.6808   | 5  | 550 mm   | •                               | 8954.6802                          |
| Grasping forceps bndl with pike-mouth jaws, short   | 8952.6508   | 5  | 550 mm   | •                               | 8952.6502                          |



## THEVIPER

## FLEXIBLE FIBER URETERORENOSCOPES $270^{\circ}$



|  | Outer Ø | and laser<br>fiber<br>channel Ø | WL/TL         | Control lever in distal<br>direction –<br>articulation downward | Control lever in distal<br>direction –<br>articulation upward | Product no. |
|--|---------|---------------------------------|---------------|---|---|-------------|
| Fiber ureterorenoscope 9.6 Fr<br>WL 680 mm<br>Slanted distal tip       | 9.6 Fr  | 2x                              | WL<br>680 mm  | •   |   | 7325.071    |
| Articulation +270°/-270°<br>Direction of view 0°, angle of view<br>85° | 7.011   | 3.6 Fr                          | TL<br>1005 mm |   | •   | 7325.076    |
| Also:  |         |                                 |               |   |   |             |
| Pressure equalization valve  |         |                                 |               |   |   |             |
| Leakage tester for flex. endoscopes                                    |         |                                 |               |   |   | 163.903     |
| Adapter  |         |                                 |               |   |   | 163914      |
| Clamping element, orange (20 PCS)                                      |         |                                 |               |   |   | 15394144    |
| Cleaning brush Ø 2 mm, TL 1,200 mm (Pack = 10 PCS)                     |         |                                 |               |   |   |             |

| Recommended accessories  |                                 | Product no. |
|--|---------------------------------|-------------|
| Fiber light cable bndl consisting of: Fiber light cable Ø 2.5 mm, TL 2.3 m (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long            | 806625231   |
| Perforated basket for flexible endoscopes  | (W x H x D): 448 x 106 x 288 mm | 33016       |
| Also: fixing ring Ø 50.39 mm   |                                 | 643301261   |
| Auxiliary instruments  |                                 | see URO121  |





### FLEXIBLE FIBER URETERORENOSCOPES

#### TECHNICAL DATA/ACCESSORIES AND AUXILIARY INSTRUMENTS

| Fiber ureterorenoscope 9.6 Fr WL 680 mm | 7325.071/7325.076   |
|---|---|
| Distal tip                              | Slanted distal tip 6 Fr   |
| Sheath diameter                         | 9.6 Fr  |
| Number of working channels              | 2   |
| Working/irrigation channel diameter     | 3.6 Fr  |
| Articulation                            | 270° upward, 270° downward  |
| Working length                          | 680 mm  |
| Direction of view                       | 0°  |
| Angle of view                           | 85°   |
| Eyepiece                                | Adjustment eyepiece with diopter adjustment   |
| Control lever                           | with position catch at 0° when instrument tip is extended and brake mechanism for locking |

| Accessories and auxiliary instr | Accessories and auxiliary instruments   |          |  |  |  |  |
|---------------------------------|---|----------|--|--|--|--|
|                                 | Adapter with 2 irrigation valves and 1 instrument port, quick-release mechanism | 7305.782 |  |  |  |  |
|                                 | Also: Luer sealing cap  | 15023205 |  |  |  |  |
|                                 | RIWO rubber cap, capacity 0.8 mm  | 88.01    |  |  |  |  |
|                                 | Universal sealing valve 1–6 Fr  for inserting auxiliary instruments of 1–6 Fr   | 4712348  |  |  |  |  |
|                                 | Adapter for machine leakage tests   | 163.905  |  |  |  |  |



### FLEXIBLE FIBER URETERORENOSCOPES

#### ACCESSORIES AND AUXILIARY INSTRUMENTS

|                 |  | Fr  | WL     | TL       | Product no. |
|-----------------|--|-----|--------|----------|-------------|
| \.              | Flex. grasping forceps 3 Fr WL 530 mm                        | 3   | 530 mm | 665 mm   | 828.605     |
|                 | Flex. grasping forceps 5 Fr WL 550 mm                        | 5   | 550 mm | 720 mm   | 828.051     |
| Fine toothing   | Flex. grasping forceps 3 Fr WL 920 mm                        | 3   | 920 mm | 1,050 mm | 828.651     |
|                 | Flex. biopsy forceps 5 Fr WL 550 mm                          | 5   | 550 mm | 720 mm   | 829.051     |
|                 | Flex. biopsy forceps 3 Fr WL 530 mm                          | 3   | 530 mm | 665 mm   | 829.603     |
|                 | Flex. biopsy forceps Ø 3 Fr WL 920 mm                        | 3   | 920 mm | 1,055 mm | 829.601     |
| 3               | Flex. biopsy forceps 4 Fr WL 600 mm                          | 4   | 600 mm | 730 mm   | 8734.606    |
| Pike-mouth jaws | Flex. grasping forceps 4 Fr WL 600 mm                        | 4   | 600 mm | 750 mm   | 8734.656    |
| Mouse tooth     | Flex. grasping forceps 4 Fr WL 600 mm                        | 4   | 600 mm | 750 mm   | 8734.686    |
|                 | Flex. grasping forceps 5 Fr WL 550 mm                        | 5   | 550 mm | 700 mm   | 8735.685    |
|                 | Flex. grasping forceps 3.5 Fr WL<br>550 mm,<br>fine toothing | 3.5 | 550 mm | 700 mm   | 8953.60     |
| 9               | Coag. electrode mono 5 Fr WL 600 mm                          | 5   | 600 mm | -        | 8599.80     |
|                 | Coag. electrode mono 3 Fr WL 580 mm                          | 3   | 580 mm | -        | 823.031     |
|                 | Hook electrode mono 2.4 Fr<br>WL 600 mm                      | 2.4 | 600 mm | -        | 823.221     |



Optional 4712348



## FLEXIBLE FIBER 2-CHANNEL CONTINUOUS IRRIGATION LASER **URETERORENOSCOPES**



|   | Outer Ø | Working<br>and<br>laser fiber<br>channel Ø | WL/TL            | Control lever in distal<br>direction –<br>articulation downward | Control lever in distal<br>direction –<br>articulation upward | Product no. |
|---|---------|--|------------------|---|---|-------------|
| Fiber ureterorenoscope 9.9 Fr<br>WL 680 mm<br>Slanted distal tip  | 9.9 Fr  | 2x   | WL<br>680 mm     | •   |   | 7326071     |
| Articulation +270°/-270°<br>Direction of view 0°, angle of view 85°   |         | 3.3 Fr                                     | 3 Fr TL 1,010 mm |   | •   | 7326076     |
| Fiber ureterorenoscope bndl consisting of: Fiber ureterorenoscope 9.9 Fr WL 680 mm (7326071), pressure equalization valve (163.904), leakage tester for flex. endoscopes (163.903), adapter (163914), clamping element (15394144), and cleaning brush Ø 2 mm, TL 1,200 mm (Pack = 10 PCS) (7990001) |         |  |                  | •   |   | 732607111   |
| Fiber ureterorenoscope bndl consisting of: Fiber ureterorenoscope 9.9 Fr WL 680 mm (7326076), pressure equalization valve (163.904), leakage tester for flex. endoscopes (163.903), adapter (163914), clamping element (15394144), and cleaning brush Ø 2 mm, TL 1,200 mm (Pack = 10 PCS) (7990001) |         |  |                  | •   | 732607611   |             |

| Recommended accessories  |                                 | Product no. |
|--|---------------------------------|-------------|
| Fiber light cable bndl consisting of: Fiber light cable Ø 2.5 mm, TL 2.3 m (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long            | 806625231   |
| Perforated basket for flexible endoscopes  | (W x H x D): 448 x 106 x 288 mm | 33016       |
| Also: fixing ring Ø 50.39 mm   |                                 | 643301261   |
| for auxiliary instruments, see URO125  |                                 |             |



## FLEXIBLE FIBER 2-CHANNEL CONTINUOUS IRRIGATION LASER URETERORENOSCOPES

TECHNICAL DATA

| Fiber ureferorenoscope 9.9 Fr WL 680 mm | 7326071/7326076   |
|---|---|
| Distal tip                              | Slanted distal tip 6 Fr   |
| Sheath diameter                         | 9.9 Fr  |
| Number of working channels              | 2   |
| Working/irrigation channel diameter     | 3.3 Fr  |
| Laser/irrigation channel diameter       | 3.3 Fr  |
| Articulation                            | 270° upward, 270° downward  |
| Working length                          | 680 mm  |
| Direction of view                       | 0°  |
| Angle of view                           | 85°   |
| Eyepiece                                | Adjustment eyepiece with diopter adjustment   |
| Control lever                           | with position catch at 0° when instrument tip is extended and brake mechanism for locking |

| ENDOCAM LOGIC HD equipment |  | Product no. |
|----------------------------|--|-------------|
| COOLIN COOL HOM            | ENDOCAM Logic HD Lite controller bndl  consisting of: ENDOCAM Logic HD Lite camera control unit (5525201) Handheld remote control USB (5525401) USB flash memory 8 GB (56540028) HDMI/DVI-D cable, lockable, 3.0 m (103843) Power cable (2440.03) 5525 DVD license open-source software (64360816) | 55252011    |



## FLEXIBLE FIBER 2-CHANNEL CONTINUOUS IRRIGATION LASER URETERORENOSCOPES

ACCESSORIES AND AUXILIARY INSTRUMENTS

| ACCESSORIES AND AUXI       |  | Outer Ø  | WL     | Product no. |
|----------------------------|--|----------|--------|-------------|
|                            | Flex. biopsy forceps Ø 3 Fr WL 920 mm  | 3 Fr     | 920 mm | 829.601     |
|                            | Flex. grasping forceps 3 Fr WL 920 mm  | 3 Fr     | 920 mm | 828.651     |
|                            | Adapter with 2 irrigation valves and 1 instrument port, quick-               | 7305.782 |        |             |
|                            | Also: Luer sealing cap   | 15023205 |        |             |
|                            | RIWO rubber cap, capacity 0.8 mm   | 88.01    |        |             |
|                            | Universal sealing valve 1–6 Fr for inserting auxiliary instruments of 1–6 Fr | 4712348  |        |             |
|                            | Adapter for machine leakage tests  | 163.905  |        |             |
| Laser adjustment unit bndl |  |          |        | 15369108    |
|                            | Also: clamping element, orange (20 pcs)                                      |          |        | 15394144    |




| IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

## **B**09

#### FLEXIBLE 1-CHANNEL SENSOR URETERORENOSCOPES

#### FOR ENDOCAM Logic 4K CONTROLLER



|  | Outer Ø | Working/<br>irrigation<br>channel | WL         | Control lever in distal<br>direction –<br>articulation downward | Control lever in distal<br>direction –<br>articulation upward | Product no. |
|--|---------|-----------------------------------|------------|---|---|-------------|
| Sensor ureterorenoscope<br>8.7 Fr WL 680 mm<br>Slanted distal tip  | 8.7 Fr  | 3.6 Fr                            | 680 mm     | •   |   | 7355071     |
| Articulation +270°/-270°<br>Direction of view 6.5°,<br>angle of view 90°   | 0.711   | 3.011                             | OOO IIIIII |   | •   | 7355076     |
| Sensor ureterorenoscope bndl consisting of: Sensor ureterorenoscope 8.7 Fr WL 680 mm (7355071), pressure equalization valve (163.904), leakage tester for flex. endoscopes (163.903), and cleaning brush Ø 2 mm, TL 1,200 mm (Pack = 10 PCS) (7990001) |         |                                   | •          |   | 73550712  |             |
| Sensor ureterorenoscope bndl consisting of: Sensor ureterorenoscope 8.7 Fr WL 680 mm (7355076), pressure equalization valve (163.904), leakage tester for flex. endoscopes (163.903), and cleaning brush Ø 2 mm, TL 1,200 mm (Pack = 10 PCS) (7990001) |         |                                   |            | •   | 73550762  |             |

| Recommended accessories  |                                 | Product no. |
|--|---------------------------------|-------------|
| Fiber light cable bndl consisting of: Fiber light cable Ø 2.5 mm, TL 2.3 m (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long            | 806625231   |
| Perforated basket for flexible endoscopes  | (W x H x D): 448 x 106 x 288 mm | 33016       |
| Also: fixing ring Ø 50.39 mm   |                                 | 643301261   |
| for auxiliary instruments, see URO128  |                                 | ,           |





## FLEXIBLE 1-CHANNEL SENSOR URETERORENOSCOPES

#### TECHNICAL DATA

| Sensor ureterorenoscope 8.7 Fr WL 680 mm                                     | 7355071/7355076  |
|--|--|
| Distal tip   | Cylindrical, atraumatic, slanted distal stainless steel tip 6.6 Fr         |
| Sheath diameter  | 8.7 Fr   |
| Number of working channels   | 1  |
| Working/irrigation channel diameter  | 3.6 Fr   |
| Articulation   | 270° upward, 270° downward   |
| Working length   | 680 mm   |
| Angle of view  | 90°  |
| Handle   | Ergonomic handle design with axial cable outlet                            |
| Positioning of the working and irrigation channel in relation to the picture | At 6 o'clock   |
| Endopicture  | Square, 6x digital zoom; automatic white balance, light control, and focus |
| Compatible camera control unit   | ENDOCAM Logic 4K<br>ENDOCAM Logic HD                                       |

| ENDOCAM LOGIC 4K – Video equipment       |  | Product no. |
|--|--|-------------|
| 50 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | ENDOCAM Logic 4K camera control unit bndl consisting of: ENDOCAM Logic 4K camera control unit (5525301) Handheld remote control (5525401) 1x USB flash memory 32 GB (72321829) 1x HDMI/HDMI cable, lockable, 3.0 m (103847) 1x power cable (2440.03) | 55253011    |



## Bog

## FLEXIBLE 1-CHANNEL SENSOR URETERORENOSCOPES

#### ACCESSORIES AND AUXILIARY INSTRUMENTS


|   |  | Outer Ø  | WL     | Product no. |
|---|--|----------|--------|-------------|
|   | Flex. biopsy forceps Ø 3 Fr WL 920 mm  | 3 Fr     | 920 mm | 829.601     |
| A LINE AND | Flex. grasping forceps 3 Fr WL 920 mm  | 3 Fr     | 920 mm | 828.651     |
|   | Laser fiber Ø 365 µm, disposable   | 365 µm   |        | 4875013650  |
|   | Laser fiber Ø 550 μm, disposable   | 550 µm   |        | 487501550   |
|   | Laser fiber Ø 365 μm, reusable   | 365 µm   |        | 875013650   |
| ,   | Laser fiber Ø 550 μm, reusable   | 550 µm   |        | 87501550    |
|   | Adapter with 2 irrigation valves and 1 instrument port, quick-               | 7305.782 |        |             |
|   | Also: Luer sealing cap   | 15023205 |        |             |
|   | RIWO rubber cap, capacity 0.8 mm   | 88.01    |        |             |
|   | Universal sealing valve 1–6 Fr for inserting auxiliary instruments of 1–6 Fr | 4712348  |        |             |
|   | Adapter for machine leakage tests  | 163.905  |        |             |





### FLEXIBLE 1-CHANNEL SENSOR URETERORENOSCOPES

#### FOR ENDOCAM Flex HD CONTROLLER



|   | Outer Ø | working /<br>irrigation<br>channel | WL        | direction – articulation downward | direction – articulation upward | Product no. |
|---|---------|------------------------------------|-----------|-----------------------------------|---------------------------------|-------------|
| Sensor ureterorenoscope<br>8.7 Fr WL 680 mm<br>Slanted distal tip   | 8.7 Fr  | 3.6 Fr                             | 680 mm    | •                                 |                                 | 73551071    |
| Articulation +270°/-270°<br>Direction of view 6.5°,<br>angle of view 90°  | 0.711   | 0.011                              | 300 11111 |                                   | •                               | 73551076    |
| Sensor ureterorenoscope bndl consisting of: Sensor ureterorenoscope 8.7 Fr WL 680 mm (73551071), pressure equalization valve (163.904), leakage tester for flex. endoscopes (163.903), and cleaning brush Ø 2 mm, TL 1,200 mm (Pack = 10 PCS) (7990001) |         |                                    | 1)        | •                                 |                                 | 735510712   |
| Sensor ureterorenoscope bndl consisting of: Sensor ureterorenoscope 8.7 Fr WL 680 mm (73551076), pressure equalization valve (163.904), leakage tester for flex. endoscopes (163.903), and cleaning brush Ø 2 mm, TL 1,200 mm (Pack = 10 PCS) (7990001) |         |                                    |           |                                   | •                               | 735510762   |

| Recommended accessories  |                                 | Product no. |
|--|---------------------------------|-------------|
| Fiber light cable bndl consisting of: Fiber light cable Ø 2.5 mm, TL 2.3 m (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long            | 806625231   |
| Perforated basket for flexible endoscopes  | (W x H x D): 448 x 106 x 288 mm | 33016       |
| Also: fixing ring Ø 50.39 mm   |                                 | 643301261   |
| for auxiliary instruments, see URO131  |                                 | 1           |



## BOS

## FLEXIBLE 1-CHANNEL SENSOR URETERORENOSCOPES

#### TECHNICAL DATA

| Sensor ureterorenoscope 8.7 Fr WL 680 mm                                     | 73551071/73551076  |
|--|--|
| Distal tip   | Cylindrical, atraumatic, slanted distal stainless steel tip 6.6 Fr   |
| Sheath diameter  | 8.7 Fr   |
| Number of working channels   | 1  |
| Working/irrigation channel diameter  | 3.6 Fr   |
| Articulation   | 270° upward, 270° downward   |
| Working length   | 680 mm   |
| Angle of view  | 90°  |
| Handle   | Integrated LED illumination, ergonomic handle design with axial camera cable                                 |
| Positioning of the working and irrigation channel in relation to the picture | At 9 o'clock   |
| Endopicture  | Square, 1.5x zoom, detail enhancement, automatic white balance and brightness control, no focusing necessary |
| Compatible camera control unit   | ENDOCAM Logic 4K<br>ENDOCAM Logic HD   |



| Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with



## FLEXIBLE 1-CHANNEL SENSOR URETERORENOSCOPES

#### ACCESSORIES AND AUXILIARY INSTRUMENTS

|   |  | Outer Ø  | WL       | Product no. |
|---|--|----------|----------|-------------|
|   | Flex. biopsy forceps Ø 3 Fr WL 920 mm  | 3 Fr     | 920 mm   | 829.601     |
|   | Flex. grasping forceps 3 Fr WL 920 mm  | 3 Fr     | 920 mm   | 828.651     |
|   | Laser fiber Ø 365 µm, disposable   | 200 μm   |          | 487501200   |
|   | Laser fiber Ø 550 μm, disposable   | 272 μm   |          | 487501272   |
|   | Laser fiber Ø 365 μm, reusable   | 200 μm   |          | 87501200    |
| , | Laser fiber Ø 550 μm, reusable   | 272 μm   |          | 87501272    |
|   | Adapter with 2 irrigation valves and 1 instrument port, quick-               | 7305.782 |          |             |
|   | Also: Luer sealing cap   |          | 15023205 |             |
|   | RIWO rubber cap, capacity 0.8 mm   |          | 88.01    |             |
|   | Universal sealing valve 1–6 Fr for inserting auxiliary instruments of 1–6 Fr |          |          | 4712348     |
|   | Adapter for machine leakage tests  |          | 163.905  |             |



| IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

## COBRA

#### FLEXIBLE 2-CHANNEL SENSOR URETERORENOSCOPES

### FOR ENDOCAM Logic 4K CONTROLLER



|   | Outer Ø                                     | Working/laser<br>channel     | WL     | direction – articulation downward | direction – articulation upward | Product no. |
|---|---|------------------------------|--------|-----------------------------------|---------------------------------|-------------|
| Sensor ureterorenoscope<br>9.9 Fr WL 680 mm   | 0.0.5**                                     | Working<br>channel<br>3.6 Fr | (00    | •                                 |                                 | 7356071     |
| Slanted distal tip Articulation +270°/-270° Direction of view 0°, angle of view 120°  | 9.9 Fr                                      | laser channel<br>2.4 Fr      | 680 mm |                                   | •                               | 7356076     |
| Sensor ureterorenoscope bndl consisting of: Sensor ureterorenoscope 9.9 Fr WL 680 mm (7356071), pressure equalization valve (163.904), leakage tester for flex. endoscopes (163.903), adapter (163914), cleaning brush Ø 2 mm, TL 1,200 mm (Pack = 10 PCS) (7990001), cleaning brush Ø 0.85 mm, TL 1,200 mm (Pack = 10 PCS) (7990003), and clamping element, orange (20 pcs) (15394144) |   |                              | •      |                                   | 73560712                        |             |
| Sensor ureterorenoscope bndl consisting of: Sensor ureterorenoscope 9.9 Fr WL 680 mm pressure equalization valve (163.904), leakage tester for flex. endoscopes (163.90 cleaning brush Ø 2 mm, TL 1,200 mm (Parcleaning brush Ø 0.85 mm, TL 1,200 mm (clamping element, orange (20 pcs) (1539)  | 03), adapter<br>ck = 10 PCS<br>(Pack = 10 F | (163914),<br>) (7990001),    | and    |                                   | •                               | 73560762    |

| Recommended accessories   |                                 | Product no. |
|---|---------------------------------|-------------|
| Fiber light cable bndl consisting of: Fiber light cable Ø 2.5 mm,TL 2.3 m (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long            | 806625231   |
| Perforated basket for flexible endoscopes   | (W x H x D): 448 x 106 x 288 mm | 33016       |
| Also: fixing ring Ø 50.39 mm  |                                 | 643301261   |
| for auxiliary instruments, see URO134   |                                 |             |





### FLEXIBLE 2-CHANNEL SENSOR URETERORENOSCOPES

#### TECHNICAL DATA

| Sensor ureterorenoscope 9.9 Fr WL 680 mm                                     | 7356071/7356076  |
|--|--|
| Distal tip   | Cylindrical, atraumatic, slanted distal stainless steel tip 5.2 Fr         |
| Sheath diameter  | 9.9 Fr   |
| Number of working channels   | 2  |
| Working/irrigation channel diameter  | 3.6 Fr   |
| Laser/irrigation channel diameter  | 2.4 Fr   |
| Articulation   | 270° upward, 270° downward   |
| Working length   | 680 mm   |
| Angle of view  | 90°  |
| Handle   | Ergonomic handle design with axial cable outlet                            |
| Positioning of the working and irrigation channel in relation to the picture | At 6 o'clock   |
| Positioning of the laser and irrigation channel in relation to the picture   | At 9 o'clock   |
| Endopicture  | Square, 6x digital zoom; automatic white balance, light control, and focus |
| Compatible camera control unit   | ENDOCAM Logic 4K<br>ENDOCAM Logic HD                                       |

| ENDOCAM LOGIC 4K – Video equipment |  | Product no. |
|------------------------------------|--|-------------|
|                                    | ENDOCAM Logic 4K camera control unit bndl consisting of: ENDOCAM Logic 4K camera control unit (5525301) Handheld remote control (5525401) 1x USB flash memory 32 GB (72321829) 1x HDMI/HDMI cable, lockable, 3.0 m (103847) 1x power cable (2440.03) | 55253011    |



| IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

## **COBRA**

#### FLEXIBLE 2-CHANNEL SENSOR URETERORENOSCOPES


#### ACCESSORIES AND AUXILIARY INSTRUMENTS

|   | Outer Ø | WL     | Product no. |
|---|---------|--------|-------------|
| Flex. biopsy forceps Ø 3 Fr WL 920 mm   | 3 Fr    | 920 mm | 829.601     |
| Flex. grasping forceps 3 Fr WL 920 mm 3 Fr 920 mm                               |         |        | 828.651     |
| Adapter with 2 irrigation valves and 1 instrument port, quick-release mechanism |         |        | 7305.782    |
| Also: Luer sealing cap  |         |        | 15023205    |
| RIWO rubber cap, capacity 0.8 mm  |         |        | 88.01       |
| Universal sealing valve 1–6 Fr for inserting auxiliary instruments of 1–6 Fr    |         |        | 4712348     |
| Adapter for machine leakage tests   |         |        | 163.905     |
| Laser adjustment unit bndl  |         |        | 15369108    |
| Also: clamping element, orange (20 pcs)   |         |        | 15394144    |

## COBRA

### FLEXIBLE 2-CHANNEL SENSOR URETERORENOSCOPES

#### FOR ENDOCAM Flex HD CONTROLLER



|  | Ø  | Laser<br>channel                            | WL        | direction – articulation<br>downward | direction – articulation<br>upward | Product no. |
|--|--|---|-----------|--------------------------------------|------------------------------------|-------------|
| Sensor ureterorenoscope 9.9 Fr WL 680 mm Slanted distal tio  | 9.9 Fr                                   | Working<br>channel<br>3.6 Fr                | 680 mm    | •                                    |                                    | 73561071    |
| Articulation +270°/-270°  Direction of view 0°, angle of view 90°  | 7.711                                    | Laser<br>channel<br>2.4 Fr                  | 000 11111 |                                      | •                                  | 73561076    |
| Sensor ureterorenoscope bndl consisting of: Sensor ureterorenoscope 9.9 Fr WL 680 mm (73561071), pressure equalization valve (163.904), leakage tester for flex. endoscopes (163.903), adapter (163914), cleaning brush Ø 2 mm, TL 1,200 mm (Pack = 10 PCS) (7990001), cleaning brush Ø 0.85 mm, TL 1,200 mm (Pack = 10 PCS) (7990003), and clamping element, orange (20 pcs) (15394144) |  |   | 1),       | •                                    |                                    | 735610712   |
| Sensor ureterorenoscope bndl consisting of: Sensor ureterorenoscope 9.9 pressure equalization valve (163.904), leakage tester for flex. endoscopes (163.9 cleaning brush Ø 2 mm, TL 1,200 mm (Pacleaning brush Ø 0.85 mm, TL 1,200 mm and clamping element, orange (20 pcs) (  | 903), adapt<br>ack = 10 PC<br>(Pack = 10 | ter (163914)<br>CS) (799000<br>D PCS) (7990 | ,<br>1),  |                                      | •                                  | 735610762   |

| Recommended accessories  |                                 | Product no. |
|--|---------------------------------|-------------|
| Fiber light cable bndl consisting of: Fiber light cable Ø 2.5 mm, TL 2.3 m (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long            | 806625231   |
| Perforated basket for flexible endoscopes  | (W x H x D): 448 x 106 x 288 mm | 33016       |
| Also: fixing ring Ø 50.39 mm   |                                 | 643301261   |
| for auxiliary instruments, see URO137  |                                 |             |



## COBRA

## FLEXIBLE 2-CHANNEL SENSOR URETERORENOSCOPES

#### TECHNICAL DATA

| Sensor ureterorenoscope 9.9 Fr WL 680 mm                                     | 73561071/73561076  |
|--|--|
| Distal tip   | Cylindrical, atraumatic, slanted distal stainless steel tip 5.2 Fr   |
| Sheath diameter  | 9.9 Fr   |
| Number of working channels   | 2  |
| Working/irrigation channel diameter  | 3.6 Fr   |
| Laser/irrigation channel diameter  | 2.4 Fr   |
| Articulation   | 270° upward, 270° downward   |
| Working length   | 680 mm   |
| Angle of view  | 90°  |
| Handle   | Integrated LED illumination, ergonomic handle design with axial camera cable                                 |
| Positioning of the working and irrigation channel in relation to the picture | At 6 o'clock   |
| Positioning of the laser and irrigation channel in relation to the picture   | At 9 o'clock   |
| Endopicture  | Square, 1.5x zoom, detail enhancement, automatic white balance and brightness control, no focusing necessary |
| Compatible camera control unit   | ENDOCAM Logic 4K<br>ENDOCAM Logic HD   |





## FLEXIBLE 2-CHANNEL SENSOR URETERORENOSCOPES


#### ACCESSORIES AND AUXILIARY INSTRUMENTS

|             |   | Outer Ø | WL     | Product no. |
|-------------|---|---------|--------|-------------|
| <b>&gt;</b> | Flex. biopsy forceps Ø 3 Fr WL 920 mm   | 3 Fr    | 920 mm | 829.601     |
| Auditoria   | Flex. grasping forceps 3 Fr WL 920 mm 3 Fr 920 mm                               |         |        | 828.651     |
| -           | Adapter with 2 irrigation valves and 1 instrument port, quick-release mechanism |         |        | 7305.782    |
|             | Also: Luer sealing cap  |         |        | 15023205    |
|             | RIWO rubber cap, capacity 0.8 mm  |         |        | 88.01       |
|             | Universal sealing valve 1–6 Fr  for inserting auxiliary instruments of 1–6 Fr   |         |        | 4712348     |
|             | Adapter for machine leakage tests   |         |        | 163.905     |
|             | Laser adjustment unit bndl  |         |        | 15369108    |
|             | Also: clamping element, orange (20 pcs)   |         |        | 15394144    |




## D-URS

#### DISPOSABLE SENSOR URETERORENOSCOPE









| Sensor ureterorenoscope 9 Fr WL 600 mm                  | 473572076  |
|---|--|
| Working length (WL)                                     | 600 mm   |
| Cable length (L)  | 2,500 mm   |
| Outer diameter (OD) (flexible area) F                   | 9 Fr   |
| Outer diameter (OD) (semi-rigid area) G                 | 8.1 Fr   |
| Distal instrument tip E                                 | 6 Fr   |
| Working channel <b>(C)</b>                              | 3.6 Fr   |
| Laser fiber channel ( <b>D</b> )                        | 1.65 Fr  |
| Articulation  | +/-300° (up/down)  |
| Direction of view                                       | 0°   |
| Angle of view   | 90°  |
| Luer connection for inlet, color: blue A                | Ø 3.0 mm   |
| Luer connection for outlet, color: gray B               | Ø 3.0 mm   |
| Luer connection for working channel, color: gray C      | Ø 3.0 mm   |
| Luer connection for laser fiber channel, color: green D | Ø 3.0 mm   |
| Operating conditions                                    | Temperature: +10 °C to +40 °C, rel. humidity: 20 % to 75 %, atmospheric pressure: 700 hPa to 1,060 hPa |
| Storage conditions                                      | Temperature: +5 °C to +30 °C, rel. humidity: 10 % to 70 %, atmospheric pressure: 700 hPa to 1,060 hPa  |



#### CAMERA CONTROL UNIT AND ACCESSORIES





#### Adapter for control unit 5525 ...... 5525410

The sensor ureterorenoscope is compatible with the following Richard Wolf camera control units\* using the adapter (5525410) for control unit 5525:

- 5525101 Logic HD camera control unit
- 2525301 Logic 4K camera control unit
- 5525201 Logic HD lite camera control unit
- \* Software version V2.0.9 or higher

| ENDOCAM D camera control unit bndl     | 55221011   |
|--|------------|
| consisting of:                         |            |
| 1x ENDOCAM D camera control unit       | 5522101    |
| 1x Vector Plus coax cable 3.00 m DZGR- | 0300-SW-GN |
| 1x HDMI/DVI-D cable, lockable 3.0 m    | 103843     |
| 1x license for open-source software    | 72321911   |
| 1x power cable 3 m long                | 2440.03    |
| (see rear for technical data)          |            |
| Also:                                  |            |
| Handheld remote control IISB           | 5525401    |

| Handheld remote control USB | 5525401 |
|-----------------------------|---------|
|                             |         |

|  |  | Outer Ø | WL     | Product no. |
|--|--|---------|--------|-------------|
| Flex. biopsy forceps Ø 3 Fr WL 920 mm  |  | 3 Fr    | 920 mm | 829.601     |
| Flex. grasping forceps 3 Fr WL 920 mm  |  | 3 Fr    | 920 mm | 828.651     |
|  |  | Ø       | L      | Product no. |
| Power laser fiber Ø 200 µm, disposable   |  | 200 μm  | 3.0 m  | 487502200   |
| Laser fiber Ø 200 µm, disposable   |  | 200 μm  | 3.0 m  | 487501200   |
| Laser fiber Ø 272 µm, disposable   |  | 272 μm  | 3.0 m  | 487501272   |
| These particular laser fibers are compatible with the Richard Wolf MegaPulse 30+ and MegaPulse 70+ lasers. |  |         |        |             |

|   |  | Product no. |
|---|--|-------------|
| Universal sealing valve 1–6 Fr<br>(Pack = 5 PCS) sterile, for single use<br>for inserting auxiliary instruments<br>1–6 Fr |  | 4712348     |
| Luer sealing cap  |  | 15023205    |
| RIWO rubber cap, capacity 0.8 mm  |  | 88.01       |





#### TECHNICAL DATA OF ENDOCAM D CAMERA CONTROL UNIT

| D camera control unit                                 | 5522101                                       |   |  |
|---|---|---|--|
| Device properties                                     |   |   |  |
| Type of controls                                      | Mechanical buttons                            |   |  |
| Max. video signal resolution                          | 1,920 x 1,080 pixels                          |   |  |
| Brightness control                                    | Automatic shutter control + automatic gain co | ontrol  |  |
| Digital zoom  | 2.5x max.                                     |   |  |
| Operating conditions                                  | +10 °C to +40 °C, 30 % to 75 % rel. humidity  | atmospheric pressure 700 hPa to 1,060 hPa                       |  |
| Storage and transport conditions                      | -20 °C to +60 °C, 10 % to 90 % rel. humidity, | atmospheric pressure 700 hPa to 1,060 hPa                       |  |
| Operating mode  | Continuous operation                          |   |  |
| Equipment   |   |   |  |
| IP rating   | IP 20   |   |  |
| Power supply  |   |   |  |
| Mains + frequency                                     | 100–240 V AC, 50/60 Hz                        |   |  |
| Power consumption                                     | 32 VA   |   |  |
| Current consumption                                   | 0.32-0.13 A                                   |   |  |
| Fuse  | T 1.25 AH 250 V                               |   |  |
| Regulatory standards                                  |   |   |  |
| Safety  | UL 2601-1/CSA C22.2 No.601.1 – for USA        |   |  |
| EMC   | EN/IEC 60601-1-2                              |   |  |
| Medical device class                                  | Class 1                                       |   |  |
| Classification of applied part                        | CF  |   |  |
| Interfaces  |   |   |  |
| Video outputs   | 1x 3G-SDI, 1x HDMI                            |   |  |
| USB port (on front panel, for external storage media) | USB 2.0 (FAT32/NTFS formatting)               |   |  |
|   | Adjustable via DIP switches on housing rear   |   |  |
| Resolution (HDMI output)                              | SXGA<br>Full HD                               | 1,280 x 1,024 p (50 Hz) (5:4)<br>1,920 x 1,080 p (60 Hz) (16:9) |  |
| Resolution (3G-SDI output)                            | 1,920 x 1,080 p (60 Hz)                       |   |  |
| Dimensions and weights                                |   |   |  |
| Weight  | 2.3 kg  |   |  |
| Dimensions (W x H x D)                                | 200 x 60 x 220 mm                             |   |  |



| Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with

our contact partner or directly with Richard Wolf GmbH

#### **DILATORS**


#### FOR PERCUTANEOUS UNIVERSAL NEPHROSCOPES





#### MINI NEPHROSCOPE 15/18 Fr

## BY LAHME





| PANOVIEW  | Direction of view | Ø     | Maximum capacity   | WL/SL        | TL     | Product no. |
|---|-------------------|-------|--------------------|--------------|--------|-------------|
| Nephroscope 12° 12 Fr WL 225 mm<br>with laterally offset eyepiece<br>Working channel for instruments up to 6 Fr | 12°               | 12 Fr | 6 Fr<br>(2 mm)     | WL<br>225 mm | 406 mm | 8968.421    |
| Sheath for nephroscope 15 Fr  | -                 | 15 Fr | 12 Fr<br>(4 mm)    | SL<br>205 mm | -      | 8968.001    |
| Obturator for nephroscope 15 Fr   | -                 | -     | 3.5 Fr<br>(1.2 mm) | 229 mm       | -      | 8968.101    |
| Sheath for nephroscope 18 Fr<br>Round, rotatable irrigation valve   | -                 | 18 Fr | 15 Fr<br>(5 mm)    | SL<br>205 mm | -      | 8968.011    |
| Sheath for nephroscope 18 Fr<br>Round, fixed irrigation valve   | -                 | 18 Fr | 15 Fr<br>(5 mm)    | SL<br>150 mm | -      | 8968.041    |
| Obturator for nephroscope 18 Fr   | -                 | -     | 3.5 Fr<br>(1.2 mm) | WL<br>229 mm | -      | 8968.111    |

| Recommended accessories  |   | Product no. |
|--|---|-------------|
| for inserting auxiliary instruments of 1–6 Fr: <b>universal sealing valve 1–6 Fr</b> , sterile (Pack = 5 PCS)                                |   | 4712348     |
| Fiber light cable bndl consisting of:<br>Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long  | 806625231   |
| Perforated basket,<br>upper urinary tract 1<br>with small part basket  | Internal dimensions (W x H x D): 619 x 65 x 124 mm External dimensions (W x H x D): 635 x 75 x 132 mm | 38003       |
| Marking pen  | Color: black  | 38201.948   |

MINI NEPHROSCOPE BY LAHME



#### **AUXILIARY INSTRUMENTS**

## FOR MINIATURE NEPHROSCOPE 15/18 Fr LAHME



| "One-step" bouginage |                                    | Outer Ø | TL     | Product no. |
|----------------------|------------------------------------|---------|--------|-------------|
| Dilator 12 Fr        | Cannulated, for one-step bouginage | 12 Fr   | 320 mm | 8968.012    |
| Dilator 15 Fr        | Cannulated, for one-step bouginage | 15 Fr   | 320 mm | 8968.015    |

**Note:** Can also be used with telescopic dilators, of course.

| Further accessories                                    | Outer Ø | WL     | Product no. |
|--|---------|--------|-------------|
| Sonotrode Ø 1.9 mm WL 361 mm                           | 1.9 mm  | 361 mm | 8962.519    |
| LithoClast probe Ø 2.0 mm, WL 425 mm                   | 2.0 mm  | 425 mm | 8742.004    |
| Membrane holder  |         |        | 15256.393   |
| Membrane holder  |         |        | 15256.456   |
| Seal Ø 7.5 mm  | 7.5 mm  |        | 89.101      |
| Universal sealing valve 1–6 Fr, sterile (Pack = 5 PCS) |         |        | 4712348     |



# **AUXILIARY INSTRUMENTS**

#### FOR MINIATURE NEPHROSCOPE 15/18 Fr LAHME

| Grasping forceps jaw insert with s    | sheath      | Handle with overload protec-<br>tion | Complete instrument  • Jaw section |          |             |
|---------------------------------------|-------------|--------------------------------------|------------------------------------|----------|-------------|
| H <sub>y</sub> Safe                   | HySafe      |                                      |                                    |          | • Handle    |
|                                       | Product no. | Fr                                   | WL                                 | 8083.001 | Product no. |
| Grasping forceps bndl  Mouse tooth    | 8959.6218   | 5 Fr                                 | 425 mm                             | •        | 8959.6212   |
| Grasping forceps bndl Pike-mouth jaws | 8968.6808   | 6 Fr                                 | 425 mm                             | •        | 8968.6802   |


| Grasping forceps |  | Outer Ø | WL     | ΤL     | Product no. |  |
|------------------|--|---------|--------|--------|-------------|--|
|                  | Rigid grasping forceps 6 Fr WL 365 mm Three arms, detachable | 6 Fr    | 365 mm | 410 mm | 8968.671    |  |
|                  | Grasping forceps jaw insert 6 Fr Three arms, detachable      | 6 Fr    | 365 mm | -      | 8968.675    |  |

MINI NEPHROSCOPE BY LAHME



# PERCUTANEOUS UNIVERSAL NEPHROSCOPE

"DRESDEN" MODEL




| PANOVIEW   | Direction of view | Ø       | Maximum<br>capacity | WL/SL        | TL     | Product no. |
|--|-------------------|---------|---------------------|--------------|--------|-------------|
| Nephroscope 12° 20.8 Fr WL 224 mm<br>with parallel eyepiece<br>working channel for instruments up to 10.5 Fr | 12°               | 20.8 Fr | 3.5 mm              | WL<br>224 mm | 387 mm | 8964.401    |
| Sheath for nephroscope 20.8 Fr   | -                 | 20.8 Fr | -                   | SL<br>204 mm | -      | 8964.021    |
| Obturator for nephroscope 20.8 Fr  | -                 | 20.8 Fr |                     | WL<br>230 mm | -      | 8964.121    |
| Alternative:   |                   |         |                     |              |        |             |
| Sheath for nephroscope 24 Fr   | -                 | 24 Fr   | -                   | SL<br>204 mm | -      | 8965.041    |
| Also: obturator for nephroscope 24 Fr  | -                 | 24 Fr   |                     | WL<br>229 mm | -      | 8965.141    |
| Amplatz sheath for nephroscope 24.3 Fr   |                   | 24.3 Fr | -                   | SL<br>150 mm | -      | 8964.041    |
| Sealing element  |                   |         |                     |              |        | 15176.100   |

| Option of optical percutaneous ureterotomy: |  | Product no. |
|---|--|-------------|
| Working element, urethrotome, passive 0°    | Receptacle for stricture scalpels                | 8670.911    |
| Telescope 0° Ø 3.3 mm WL 297 mm             |  | 8660.424    |
| Scalpel 16.5 Fr ceramic, lancet-shaped      | 12 o'clock cutting position, with ceramic cutter | 8670.981    |



# PERCUTANEOUS UNIVERSAL NEPHROSCOPES

24 Fr



| PANOVIEW   | Direction of view | Ø       | Maximum<br>capacity | WL/SL        | TL     | Product no. |
|--|-------------------|---------|---------------------|--------------|--------|-------------|
| Nephroscope 20° 24 Fr WL 224 mm<br>with parallel eyepiece<br>working channel for instruments up to 10.5 Fr | 20°               | 24 Fr   | 3.5 mm              | WL<br>224 mm | 387 mm | 8965.401    |
| Nephroscope 20° 24 Fr WL 224 mm<br>with lateral eyepiece<br>working channel for instruments up to 10.5 Fr  | 20°               | 24 Fr   | 3.5 mm              | WL<br>224 mm | 387 mm | 8965.411    |
| Sheath for nephroscope 20.8 Fr   | -                 | 20.8 Fr | -                   | SL<br>204 mm | -      | 8964.021    |
| Obturator for nephroscope 20.8 Fr  | -                 | 20.8 Fr |                     | WL<br>230 mm | -      | 8964.121    |
| Alternative:   |                   |         |                     |              |        |             |
| Sheath for nephroscope 24 Fr   | -                 | 24 Fr   | -                   | SL<br>204 mm | -      | 8965.041    |
| Also: obturator for nephroscope 24 Fr  | -                 | 24 Fr   |                     | WL<br>229 mm | -      | 8965.141    |
| Amplatz sheath for nephroscope 24.3 Fr   |                   | 24.3 Fr | -                   | SL<br>150 mm | -      | 8964.041    |
| Sealing element  |                   |         |                     |              |        | 15176.100   |


| Option of optical percutaneous ureterotomy: |  | Product no. |
|---|--|-------------|
| Working element, urethrotome, passive 0°    | Receptacle for stricture scalpels                | 8670.911    |
| Telescope 0° Ø 4 mm WL 298 mm               |  | 8650.414    |
| Scalpel 20.5 Fr ceramic, lancet-shaped      | 12 o'clock cutting position, with ceramic cutter | 8667.981    |

PERCUTANEOUS UNIVERSAL NEPHROSCOPES



#### PERCUTANEOUS UNIVERSAL NEPHROSCOPE

#### LONG VERSION FOR OBESE PATIENTS



10

# **AUXILIARY INSTRUMENTS**

#### FOR PERCUTANEOUS UNIVERSAL NEPHROSCOPES

| Grasping forceps jaw insert with                    | sheath      | Handle with overload protec-<br>tion | Complete instrument • Jaw section |          |             |
|---|-------------|--------------------------------------|-----------------------------------|----------|-------------|
| H <sub>y</sub> Safe                                 |             |                                      |                                   | • Handle |             |
|   | Product no. | Fr                                   | WL                                | 8083.001 | Product no. |
| Grasping forceps bndl Distal angled Pike-mouth jaws | 8962.6028   | 9 Fr                                 | 355 mm                            | •        | 8962.6022   |
| Grasping forceps bndl Pike-mouth jaws               | 8962.6108   | 10.5 Fr                              | 350 mm                            | •        | 8962.6102   |

| Grasping forceps |   | Outer Ø | WL     | TL     | Product no. |
|------------------|---|---------|--------|--------|-------------|
|                  | Rigid grasping forceps 10.5 Fr WL<br>365 mm<br>Three arms, detachable | 10.5 Fr | 365 mm | 410 mm | 8964.671    |

| Further accessories   |       |  | Product no. |
|---|-------|--|-------------|
| Fiber light cable bndl<br>consisting of:<br>Fiber light cable (80663523), projector<br>and endoscope-side adapter (809509 | ' ' ' | Ø 3.5 mm, 2.3 m long   | 806635231   |
| Perforated basket for nephroscope with small part basket  |       | Internal dimensions (W x H x D): 451 x 65 x 164 mm<br>External dimensions (W x H x D): 467 x 75 x 172 mm | 38011       |

PERCUTANEOUS UNIVERSAL NEPHROSCOPES



### RIGID AUXILIARY INSTRUMENTS

FORCEPS AND SCISSORS, SMALL MODULAR SYSTEM **H. Scree** 360° ROTATABLE, CAN BE FLUSHED THROUGH, EASY-CLICK

| Grasping forceps jaw insert with s                  | sheath      |         |          | Handle with overload protec-<br>tion | Complete instrument  • Jaw section |
|---|-------------|---------|----------|--------------------------------------|------------------------------------|
| H <sub>y</sub> Safe                                 |             |         | <b>)</b> |                                      | • Handle                           |
|   | Product no. | Fr      | WL       | 8083.001                             | Product no.                        |
| Grasping forceps bndl Pike-mouth jaws               | 8962.6008   | 10.5 Fr | 350 mm   | •                                    | 8962.6002                          |
| admin   | 8962.6048   | 12 Fr   | 355 mm   | •                                    | 8962.6042                          |
| Grasping forceps bndl Distal angled Pike-mouth jaws | 8962.6028   | 9 Fr    | 355 mm   | •                                    | 8962.6022                          |
| Grasping forceps bndl Pike-mouth jaws               | 8962.6108   | 10.5 Fr | 350 mm   | •                                    | 8962.6102                          |
| Grasping forceps bndl Peanut shape, fine toothing   | 8962.6078   | 12 Fr   | 340 mm   | •                                    | 8962.6072                          |
| Grasping forceps bndl  Mouse tooth                  | 8962.6058   | 12 Fr   | 340 mm   | •                                    | 8962.6052                          |
| Grasping forceps bndl Pike-mouth jaws               | 8962.6808   | 6 Fr    | 425 mm   | •                                    | 8968.6802                          |


FLEXIBLE FIBER NEPHROSCOPE



spirit of excellence

## FLEXIBLE FIBER NEPHROSCOPE 5 MM/15 Fr

CHANNEL 2.5 MM/7.5 Fr



|  | Outer Ø | Working<br>channel | WL              | Control lever in distal<br>direction –<br>articulation downward | Control lever in distal<br>direction –<br>articulation upward | Product no. |
|--|---------|--------------------|-----------------|---|---|-------------|
| Fiber cystoscope 15 Fr WL 400 mm<br>Slanted distal tip   | 16 Cr   | 7 5 Er             | 400 mm          | •   |   | 7305.001    |
| Articulation +210°/-150°<br>Direction of view 0°, angle of view 110°   | 15 FI   | 15 Fr 7.5 Fr       | 7.5 Fr   400 mm |   | •   | 7305.006    |
| Fiber cystoscope bndl  consisting of: Fiber cystoscope 15 Fr WL 400 mm (7305.001)  Adapter with 2 irrigation valves and 1 instrument port (7305.782)Leakage tester for flex. endoscopes (163.903)  Pressure equalization valve (163.904)  Cleaning brush Ø 3 mm, TL 1,200 mm (Pack = 10 PCS) (7990002) |         |                    |                 | •   |   | 730500111   |
| Fiber cystoscope bndl consisting of: Fiber cystoscope 15 Fr WL 400 mm (7305.006) Adapter with 2 irrigation valves and 1 instrument port (7305.782) Leakage tester for flex. endoscopes (163.903) Pressure equalization valve (163.904) Cleaning brush Ø 3 mm, TL 1,200 mm (Pack = 10 PCS) (7990002)    |         |                    |                 |   | •   | 730500611   |

| Recommended accessories  |                                 | Product no.                          |
|--|---------------------------------|--------------------------------------|
| Fiber light cable bndl consisting of: Fiber light cable Ø 2.5 mm, TL 2.3 m (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | 806625231                       |                                      |
| Perforated basket for flexible endoscopes  | (W x H x D): 448 x 106 x 288 mm | 33016                                |
| Also: fixing ring Ø 50.39 mm   |                                 | 643301261                            |
| Flexible auxiliary instruments   |                                 | see section<br>Auxiliary instruments |



# FLEXIBLE FIBER NEPHROSCOPE 5 MM/15 Fr

#### TECHNICAL DATA

| Fiber cystoscope 15 Fr WL 400 mm    | 7305.001/7305.006          |
|-------------------------------------|----------------------------|
| Distal tip                          | Slanted distal tip         |
| Sheath diameter                     | 15 Fr                      |
| Number of working channels          | 1                          |
| Working/irrigation channel diameter | 7.5 Fr                     |
| Articulation                        | 210° upward, 150° downward |
| Working length                      | 400 mm                     |
| Angle of view                       | 110°                       |
| Direction of view                   | 0°                         |

2. I I



2.12



spirit of excellence

# MEGA Pulse 70°

#### 70 W HOLMIUM: YAG LASER SYSTEM FOR STONE AND BPH THERAPY



|  | Product no. |
|--|-------------|
|  |             |
| MegaPulse 70+  |             |
| Laser surgical device tower EU bndl  |             |
| consisting of:   |             |
| MegaPulse 70+ laser surgical device tower 70 W (2286007)                       |             |
| 2x laser protection goggles (OBM003603)  |             |
| 1x key set (2286525)   |             |
| 1x door contact plug (2286520)   |             |
| 2x blast shield with mounting (OAM001523)                                      | 22860070    |
| 1x filling bottle with tube (IAM000088)  |             |
| 1x 2-pedal footswitch (2030232)  |             |
| 1x fiber-stripping forceps for stripping laser fibers, 0.3 to 1.0 mm (2286523) |             |
| 1x fiber-stripping forceps for stripping laser fibers, 0.1 to 0.4 mm (2286527) |             |
| 1x ceramic cutter with silicone pad (AGM000080)                                |             |
| 1x accessories box for MegaPulse (KBM000103)                                   |             |
| 1x power cable TL 3 m (2286230)  |             |
|  |             |

IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.



| MEGA Pulse 70⁺             | 22860070  |
|----------------------------|---|
| Device properties          |   |
| Display                    | 12" touchscreen   |
| Power                      | 70 watts  |
| Laser type                 | Holmium:YAG laser (Ho:YAG)                                  |
| Wavelength                 | 2,100 nm (2.1 μm)   |
| Operating principle        | Pulsed  |
| Energy                     | 200–5,000 mJ  |
| Pulse duration             | Adjustable (50–1,100 μs)                                    |
| Pilot beam                 | Green: 532 nm, < 5 mW, can be set to continuous or flashing |
| Max. operating temperature | 10–30 °C  |
| Storage temperature        | Min. +5 °C, max. 40 °C                                      |
| Power supply               |   |
| Voltage                    | 200–230 V, 50/60 Hz, < 32 A                                 |
| Frequency                  | 3–60 Hz   |
| Dimensions and weights     |   |
| Dimensions (W x H x D)     | 595 x 1,200 x 1,074 mm                                      |
| Weight                     | 200 kg  |

"MEGA PULSE 70+" LASER



spirit of excellence





|              |  | Core diameter |        |        |        |        |        |             | No. 1 of the |
|--------------|--|---------------|--------|--------|--------|--------|--------|-------------|--------------|
|              | Sterile (Pack= 1 PC)                   |               | 200 μm | 272 μm | 365 µm | 550 µm | 800 µm | 1,000<br>μm | Product no.  |
|              | Power laser fiber Ø 200 μm, disposable | •             |        |        |        |        |        |             | 487502200    |
|              | Laser fiber Ø 200 μm, disposable       |               | •      |        |        |        |        |             | 487501200    |
|              | Laser fiber Ø 272 μm, disposable       |               |        | •      |        |        |        |             | 487501272    |
| Single use   | Laser fiber Ø 365 μm, disposable       |               |        |        | •      |        |        |             | 4875013650   |
|              | Laser fiber Ø 550 μm, disposable       |               |        |        |        | •      |        |             | 487501550    |
|              | Laser fiber Ø 800 µm, disposable       |               |        |        |        |        | •      |             | 487501800    |
|              | Laser fiber Ø 1,000 µm, disposable     |               |        |        |        |        |        | •           | 4875011000   |
|              | Power laser fiber Ø 200 μm, reusable   | •             |        |        |        |        |        |             | 87502200     |
|              | Laser fiber Ø 200 µm, reusable         |               | •      |        |        |        |        |             | 87501200     |
| <b>.</b>     | Laser fiber Ø 272 µm, reusable         |               |        | •      |        |        |        |             | 87501272     |
| Multiple use | Laser fiber Ø 365 µm, reusable         |               |        |        | •      |        |        |             | 875013650    |
| 2            | Laser fiber Ø 550 μm, reusable         |               |        |        |        | •      |        |             | 87501550     |
|              | Laser fiber Ø 800 μm, reusable         |               |        |        |        |        | •      |             | 87501800     |
|              | Laser fiber Ø 1,000 µm, reusable       |               |        |        |        |        |        | •           | 875011000    |

IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.




| Accessories                      |   |              | Product no. |
|----------------------------------|---|--------------|-------------|
|                                  |   | Ø 200–272 μm | AGM000053   |
| Fiber-stripping forceps,         |   | Ø 365–400 μm | AGM000078   |
| autoclavable                     | for stripping laser fibers  | Ø 550-600 µm | AGM000052   |
|                                  |   | Ø 800 µm     | AGM000064   |
| Fib. a shine in a face of        | for this is a love floor  | Ø 0.1–0.4 mm | 2286527     |
| Fiber-stripping forceps          | for stripping laser fibers  | Ø 0.3–1.0 mm | 2286523     |
| Ceramic cutter with silicone pad |   |              | AGM000080   |
| Filling bottle with tube         |   | IAM000088    |             |
| Laser protection goggles         | (Also suitable for glasses-wearers)   | OBM003603    |             |
| 2-pedal footswitch               |   | 2030232      |             |
| Key set                          |   |              | 2286525     |
| Door contact plug                |   |              | 2286520     |
| Blast shield with mounting       |   |              | OAM001523   |
| Power cable TL 3 m               |   |              | 2286230     |
| Accessories box for MegaPulse    |   |              | KBM000103   |
| Adapter cable                    | cable  CEE coupling, 3-pin 32 A 6 h 230 V AC blue (on the device side) and CEE plug, 5-pin 32 A 6 h 400 V AC red (in-house) |              |             |

| Machine reprocessing              |  | Product no. |
|-----------------------------------|--|-------------|
| Perforated basket for laser fiber | Holds: Laser fiber, for machine reprocessing, sterilization (steam and low-temperature), storage, and transport; internal dimensions (W x H x D): 231 x 52 x 223 mm external dimensions (W x H x D): 248 x 72 x 239 mm | 38001       |
| Also: Fixing ring Ø 34.6 mm       | for holding instruments during machine reprocessing, sterilization (steam and low-temperature), storage, and transport, $\emptyset$ 34.6 x 2.62 mm, Pack = 5 PCS   | 643301262   |



# Pulvis 60<sup>†</sup>

60 W THULIUM FIBER LASER (TFL) FOR STONE THERAPY AND ENDOSCOPIC ENUCLEATION OF THE PROSTATE (EEP)



# PUVIS 60\* 60 W THULIUM FIBER LASER (TFL) TECHNICAL DATA

| Pulvis 60⁺   | PFMS00006   |
|--|---|
| Device properties  |   |
| Display  | Fold-out, rotatable touchscreen display (rotates 90° to the right and 180° to the left)                                     |
| Operating temperature  | 15–30 °C (at a room temperature between 25 °C and 30 °C, operation is guaranteed with a maximum output power of up to 40 W) |
| Storage/transport temperature  | Min. +5 °C/max. 40 °C   |
| Atmospheric pressure   | 800–1,060 hPa   |
| Operating humidity   | 30–85 %, non-condensing   |
| Max. noise level   | < 70.0 dB   |
| Equipment  |   |
| Cooling method   | Air cooling system  |
| Power supply   |   |
| Mains + frequency  | 100-240 V AC, 50/60 Hz  |
| Power consumption  | 1,000 VA  |
| Regulatory standards   |   |
| Classification according to the<br>Medical Devices Directive 93/42/EEC | Class IIb   |
| Laser classification according to IEC/EN 60825-1:2014                  | Class 4   |
| Pilot beam classification according with IEC/EN 60825-1:2014           | Class 3R  |
| Dimensions and weights   |   |
| Weight   | 100 kg  |
| Dimensions (W x H x D)   | 470 x 1,156 x 810 mm<br>470 x 940 x 810 mm – display closed   |



# PUVIS 60\* 60 W THULIUM FIBER LASER (TFL) TECHNICAL DATA

| Pulvis 60⁺                  | PFMS00006   |
|-----------------------------|---|
| Laser source specifications |   |
| Laser type                  | Thulium fiber-laser   |
| Wavelength                  | 1,940 nm ± 20 nm  |
| Maximum output power        | 60 W (pulsed/CW)  |
| Pulse energy                | 0.02-6 J  |
| Operating mode              | Pulsed/CW   |
| Pulse duration              | 50 μs – CW  |
| Frequency of recurrence     | 1–2,500 Hz  |
| Delivery system             | Large selection of laser fibers (see next page) (sterile, disposable, and reusable) |
| Pilot beam                  | Green 532 nm (adjustable) < 5 mW, class 3R  |
| Goggles                     | 1940 D LB4  |

IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# Pulvis 60<sup>†</sup>

LASER FIBERS



|              |  | Core diameter |           |           |           |           |           |           |           |             |             |  |
|--------------|--|---------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-------------|-------------|--|
|              | Sterile (Pack= 10 PCS)                   | 150<br>μm     | 200<br>μm | 272<br>μm | 365<br>µm | 500<br>µm | 550<br>μm | 600<br>µm | 800<br>µm | 1,000<br>µm | Product no. |  |
|              | Single use optical fiber 150 µm          | •             |           |           |           |           |           |           |           |             | OFJ001511   |  |
|              | Single use optical fiber 200 µm          |               | •         |           |           |           |           |           |           |             | OFJ002011   |  |
|              | Single use optical fiber 272 µm          |               |           | •         |           |           |           |           |           |             | OFJ702711   |  |
|              | Single use optical fiber ball tip 272 µm |               |           | •         |           |           |           |           |           |             | 0FJ302711   |  |
| Single use   | Single use optical fiber 365 µm          |               |           |           | •         |           |           |           |           |             | OFJ703611   |  |
| 0,           | Single use optical fiber 550 µm          |               |           |           |           |           | •         |           |           |             | OFJ005511   |  |
|              | Single use optical fiber lateral 600 µm  |               |           |           |           |           |           | •         |           |             | OFJ506011   |  |
|              | Single use optical fiber 800 µm          |               |           |           |           |           |           |           | •         |             | OFJ008011   |  |
|              | Single use optical fiber 1,000 µm        |               |           |           |           |           |           |           |           | •           | OFJ009911   |  |
|              | Reusable 10x optical fiber 200 µm        |               | •         |           |           |           |           |           |           |             | 0FJ002013   |  |
|              | Reusable 10x optical fiber 272 µm        |               |           | •         |           |           |           |           |           |             | 0FJ702713   |  |
| Multiple use | Reusable 10x optical fiber 365 µm        |               |           |           | •         |           |           |           |           |             | 0FJ703613   |  |
| Mulfip       | Reusable 10x optical fiber 500 µm        |               |           |           |           | •         |           |           |           |             | OFJ005513   |  |
|              | Reusable 10x optical fiber 800 µm        |               |           |           |           |           |           |           | •         |             | OFJ008013   |  |
|              | Reusable 10x optical fiber 1,000 µm      |               |           |           |           |           |           |           |           | •           | OFJ009913   |  |





| Accessories                               | Product no.  |
|---|--------------|
| Interlock Conn. Medical Devices Binder    | EAM000045.00 |
| Кеу                                       | MBQ000190.00 |
| Power cord-5m-spina Shuko 16A EUR         | EAM001440.00 |
| Fiberstripper optical fibers Ø300-1000 μm | OBM001079.00 |
| Fiberstripper optical fibers Ø100-400 µm  | OBM001080.00 |
| Case salsa 1650 no brand accessories      | KBM000103.01 |
| Ceramic fiber cutter with slipcase        | AGM000080.00 |
| Goggle protection f18.P1d09.1003          | OBM003778.00 |
| Optical blast shield for tfl ext-access   | OAM002112.00 |

| Machine reprocessing              |  | Product no. |
|-----------------------------------|--|-------------|
| Perforated basket for laser fiber | Holds: Laser fiber, for machine reprocessing, sterilization (steam and low-temperature), storage, and transport; internal dimensions (W x H x D): 231 x 52 x 223 mm external dimensions (W x H x D): 248 x 72 x 239 mm | 38001       |
| Also: Fixing ring Ø 34.6 mm       | for holding instruments during machine reprocessing, sterilization (steam and low-temperature), storage, and transport, $\emptyset$ 34.6 x 2.62 mm, Pack = 5 PCS   | 643301262   |




| Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with

your contact partner or directly with Richard Wolf GmbH.

### FLUID CONTROL 2225

SUCTION IRRIGATION PUMP



#### Mini PCNL or standard PCNL

Pressure and flow-controlled indication Simultaneous monitoring of nominal pressure and irrigation flow

mobile stand with integrated weighing cells and space for up to 4 irrigation fluid bags

Integrated vacuum function Rapid fluid replacement for optimum viewing conditions

| Accessories |  | Product no. |
|-------------|--|-------------|
| Footswitch  | Only for use in urology and within the indication TUR/enucleation, possibility of short-term increase in pressure if visibility is poor (Flush function) | 2204901     |



# FLUID CONTROL 2225

#### SUCTION IRRIGATION TUBE SETS

| Irrigation                  |   |  | Product no. |
|-----------------------------|---|--|-------------|
| Accessories<br>– reusable   | Tube set with piercing spike                      | with Luer-Lock connection, autoclavable, incl. 10 spare membranes, reusable for 20 reprocessing cycles | 8171223     |
| Accessories<br>– disposαble | Irrigation tube set with piercing spike,<br>L 3 m | (PACK= 10 PCS), with Luer-Lock connection, sterile, disposable product                                 | 4171223     |
|                             | Tube set with CARE-LOCK,<br>L 3 m                 | (PACK= 10 PCS), sterile, disposable product  | 4171224     |
|                             | Suction irrigation tube set                       | (PACK= 10 PCS),<br>with piercing spike, sterile disposable product, PVC                                | 4171225     |

| Suction                |   |  | Product no. |
|------------------------|---|--|-------------|
|                        | Tube set for vacuum, incl. filter       | with integrated hygiene filter, PACK= 10 PCS, service life: 30 days (connected to irrigation pump)     | 2206207     |
|                        | Irrigation tube                         | L 1.2 m, with Luer-Lock,<br>for suction irrigation handle 8385.901 and tube set<br>8171223 or 8170.223 | 817123      |
| Accessories – reusable | Suction tube L 3 m                      | for suction irrigation handle 8385.901   | 8171402     |
|                        | Secretion container, 2 I                | 2 liters, without cover  | 8170.6551   |
|                        | Cover                                   | for secretion trap 8170.6551, reusable   | 8170.6552   |
|                        | Secretion container, 2.5 I              | 2.5 liters   | 41706566    |
| Accessories            | Secretion container bndl consisting of: | Secretion container 2.5 I (41706566) and secretion bag (PACK= 90 PCS) (41706564)                       | 4170657     |
| – disposable           | Tube set for suction (2 connections)    | sterile, disposable product, (PACK= 10 PCS) for connecting instruments to collecting container         | T0503-01    |
|                        | Angled 90° plug-in coupling             | (PACK= 10 PCS) For connecting vacuum tube 2206207 to disposable container systems                      | 0771019     |



# FLUID CONTROL 2225

### CABLE ACCESSORIES

|                                    |                    | Product no. |
|------------------------------------|--------------------|-------------|
| Patch cable, RJ45 SFTP, 0.5 m      | Cable length 0.5 m | 72325378    |
| Patch cable, RJ45 HRS TM11, 1.0 m  | Cable length 1.0 m | 72325429    |
| Patch cable, RJ45 S/FTP CAT.6 10 m | Cable length 10 m  | 72325434    |
| Plastic caps for network socket    | (Pack = 8 PCS)     | 5592105     |
| Power cable                        | Cable length 3 m   | 2440.03     |

# TECHNICAL DATA FLUID CONTROL 2225

| FLUID CONTROL 2225                    |                       | 2225001  |  |  |
|---------------------------------------|-----------------------|--|--|--|
| Device properties                     |                       |  |  |  |
| Operating conditions                  |                       | +10 °C to +40 °C, 30 % to 75 % rel. humidity, 70 to 106 kPa atmospheric pressure 3,000 m max. altitude above sea level |  |  |
| Storage and transport condi           | tions                 | -20 °C to +60 °C, 10 % to 90 % rel. humidity, 70 to 106 kPa atmospheric pressure                                       |  |  |
| Power supply                          |                       |  |  |  |
| Mains + frequency                     |                       | 100–240 V AC, 50/60 Hz   |  |  |
| D !'                                  | 100 V/60 Hz           | 110 VA   |  |  |
| Power consumption                     | 240 V/50 Hz           | 120 VA   |  |  |
| Ourment consumption                   | 100 V/60 Hz           | 1.10 A   |  |  |
| Current consumption                   | 240 V/50 Hz           | 0.50 A   |  |  |
| Fuse                                  |                       | T 3.15 AH, 250 V   |  |  |
| Regulatory standards                  |                       |  |  |  |
| Protection class (I, II)              |                       | ı  |  |  |
| Electromagnetic compatibility (EMC)   |                       | EN 60601-1/IEC 60601-1<br>EN 60601-1-2/IEC 60601-1-2   |  |  |
| Medical Devices Directive 9           | 3/42/EEC              | Class IIb  |  |  |
| Housing protection rating (IF         | code)                 | IP 21  |  |  |
| Protection against electric s         | hock                  | Type BF applied part   |  |  |
| Degree of protection in the pmixtures | oresence of flammable | Device is not protected against explosions (do not operate this device in explosive atmospheres)                       |  |  |
| Maximum suction vacuum                |                       | -60 kPa  |  |  |
| Dimensions and weights                |                       |  |  |  |
| Weight                                |                       | 8.8 kg   |  |  |
| Dimensions (W x H x D)                |                       | 300 mm x 157 mm x 436 mm   |  |  |

| Relevant application parameters |  |  |  |  |  |
|---------------------------------|--|--|--|--|--|
|                                 | Hysteroscopy: 800 ml/min (max. flow, not adjustable) |  |  |  |  |
| Nominal flow range              | Endourology: 10–800 ml/min (max. flow)               |  |  |  |  |
|                                 | Laparoscopy: 0.1–1.8 l/min (max. flow)               |  |  |  |  |
| Suction power                   | Max. 2 I/min   |  |  |  |  |
|                                 | Hysteroscopy: 15–200 mmHg                            |  |  |  |  |
| Starting nominal pressure range | Endourology: 15–90 mmHg/20–120 cmH2O                 |  |  |  |  |
|                                 | Laparoscopy: 300 mmHg (not adjustable)               |  |  |  |  |
| Pressure                        | 0–300 mmHg   |  |  |  |  |
| Deficit                         | -9,990 to +9,990 ml/0 to 99.9 l                      |  |  |  |  |



# TECHNICAL DATA FLUID CONTROL 2225


| Balancing module                    | 2225023   |
|-------------------------------------|---|
| Device properties                   |   |
| Operating conditions                | $+10~^{\circ}\text{C}$ to $+40~^{\circ}\text{C}$ , $30~^{\circ}\text{K}$ to $75~^{\circ}\text{K}$ rel. humidity, $70~\text{to}~106~\text{kPa}$ atmospheric pressure 3,000 m max. altitude above sea level |
| Storage and transport conditions    | -20 °C to +60 °C, 10 % to 90 % rel. humidity, 70 to 106 kPa atmospheric pressure  |
| Regulatory standards                |   |
| Electromagnetic compatibility (EMC) | EN 60601-1/IEC 60601-1<br>EN 60601-1-2/IEC 60601-1-2  |
| Housing protection rating (IP code) | IP 21   |
| Maximum load of container scale     | 16 kg/4 containers of 3 I each  |
| Maximum load of bag scale           | 23 kg/4 bags of 5 I each  |
| Dimensions and weights              |   |
| Weight                              | 15.4 kg   |
| Dimensions (W x H x D)              | 618 mm x 1,064 mm x 618 mm  |

| Footswitch                          | 2204901                  |
|-------------------------------------|--------------------------|
| Power supply                        |                          |
| Power supply connection             | Max. 24 V                |
| Power consumption                   | Max. 0.1 A               |
| Regulatory standards                |                          |
| Electromagnetic compatibility (EMC) | EN 60601-1/IEC 60601-1   |
| Housing protection rating (IP code) | IP X8                    |
| Plug                                | 7-pin circular connector |
| Cable length                        | 4.5 m                    |
| Dimensions and weights              |                          |
| Weight                              | 300 g                    |
| Dimensions (W x H x D)              | 66 mm x 27 mm x 91 mm    |

| IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

**URO166** 





PEDIATRIC UROLOGY



# **PEDIATRIC UROLOGY**

| OPTICAL UI  | RETHROTOME FOR NEWBORNS AND INFANTS       |
|-------------|---|
| CYSTO-URE   | THROSCOPE 8686 FOR NEWBORNS AND INFANTS   |
| CYSTO-URE   | THROSCOPE 8672 FOR INFANTS                |
| MIDI-SIZE   | CYSTO-URETHROSCOPE FOR SMALL ANATOMIES    |
| СҮЅТОЅСО    | PE 4.5/6.5 Fr FOR NEWBORNS AND INFANTS    |
| СҮЅТОЅСО    | PE 8/9.8 Fr FOR REFLUX THERAPY IN INFANTS |
| RESECTOS    | COPES FOR NEWBORNS AND INFANTS            |
| MIDI-SIZE I | RESECTOSCOPE                              |
| ULTRA-THIN  | I FIBER URETERORENOSCOPE                  |



# OPTICAL URETHROTOME

#### FOR TELESCOPE 1.9 MM FOR NEWBORNS AND INFANTS

Fiber light cable (80662523), projector-side adapter (8095.07),

and endoscope-side adapter (809509)



spirit of excellence

|  |  |                |                          | more and a second | 1                              |                    | 12 o'clock cutting position                |
|--|--|----------------|--------------------------|-------------------|--------------------------------|--------------------|--|
|  |  |                | )~(                      |                   |                                | <b>13</b>          | utoglave<br>4° C / 273° F                  |
| Sheath for cystoscope bndl   | consisting of:   |                |                          | Fr                | Capacity<br>in Fr              | Color<br>coding    | Product no.                                |
| Sheath for urethrotome 8.5 Fr with irrigation valve  | Sheath for ureth<br>obturator for ure<br>tube with LUER- | ethrotome 8.5  | Fr (8693.0147),          | 8.5               | 3                              | Red                | 8693.0141                                  |
| Also: individual sheaths and obtu  | rators   |                |                          |                   |                                |                    |  |
|  |  | Å              |                          |                   |                                |                    |  |
| Individual sheath and obturator  | SL/WL  | Color codi     | ing Prod                 | uct no.           |                                | or resecto-<br>ope | Working element for urethrotome passive 0° |
| Sheath for urethrotome 8.5 Fr  | SL 105 mm Red  |                | 8693.0145                |                   | for diagnostics<br>and probing |                    | Receptacle for stricture scalpels          |
| Obturator for urethrotome<br>8.5 Fr  | WL 123 mm  | Red            | 8693.0147                |                   | 8688.264                       |                    | 8693.914                                   |
| Also:  |  |                | ,                        |                   |                                |                    |  |
| PANOVIEW telescope   |  | Directi        | ion of view              | Ø                 | WL                             | TL                 | Product no.                                |
| Telescope 0° Ø 1.9 mm WL 178   | mm   |                | 0°                       | 1.9 mm            | 178 mm                         | 243 mm             | 8686.414 H                                 |
| Stricture scalpels   |  |                |                          |                   | Cuttin                         | g edge             | Product no.                                |
|  | Scalp  | oel 9 Fr ceram | nic, semi-circular       |                   | Semi-                          | circular           | 8693.961                                   |
| Scalpel 8.5 Fr, sich   |  |                | kle-shaped Sickle-shaped |                   | 8693.93                        |                    |  |
|  | ok-shaped  |                | Hook-s                   | shaped            | 8688.94                        |                    |  |
| Recommended accessories  |  |                |                          |                   |                                |                    | Product no.                                |
| Perforated basket for standard telescope 1 Internal dimensions (W x H x D): 270 x 52 x 40 mm External dimensions (W x H x D): 297 x 54 x 59 mm |  |                |                          |                   | 38015                          |                    |  |
| Fiber light cable bndl consisting of   | of:  |                |                          |                   |                                |                    |  |

 $\emptyset$  2.5 mm, 2.3 m long

806625231



# 

spirit of excellence

| IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# CYSTO-URETHROSCOPE 8686

#### FOR TELESCOPE 1.9 MM FOR NEWBORNS AND INFANTS



|   |  |                   |  |                 | <b>AU</b><br>134                     | TOGLAVE<br>°C/273°F |
|---|--|-------------------|--|-----------------|--------------------------------------|---------------------|
| Sheath for cystoscope bndl  | consisting of:                                       | <b>©</b>          | Fr                                     | Color<br>coding | Capacity                             | Product no.         |
| Sheath for cystoscope 7.5 Fr with 2 irrigation valves                             | Sheath for cystoscope 7.5 obturator for cystoscope 7 | 7.5               | Blue                                   | -               | 8686.0141                            |                     |
| Sheath for cystoscope 8.5 Fr<br>with 2 irrigation valves and 1<br>instrument port | Sheath for cystoscope 8.5 obturator for cystoscope 8 |                   | 8.5                                    | Red             | 3 Fr                                 | 8686.0241           |
| Sheath for cystoscope 9.5 Fr<br>with 2 irrigation valves and 1<br>instrument port | Sheath for cystoscope 9.5 obturator for cystoscope 9 |                   | 9.5                                    | Yellow          | 4 Fr                                 | 8686.0341           |
| Also: individual sheaths and obtur  | ators  |                   |  |                 |                                      |                     |
| _   | (  |                   |  | 4               |                                      |                     |
| Individual<br>sheath and obturator  | SL/WL  | Color coding      | Product no.                            | (can only b     | iagnostics<br>e used with<br>ope 0°) | 1 instrument port   |
| Sheath for cystoscope 7.5 Fr  | SL 146 mm  | Blue              | 8686.0145                              | •               | •                                    |                     |
| Obturator for cystoscope 7.5 Fr   | SL 183 mm  | Blue              | 8686.0147                              |                 |                                      |                     |
| Sheath for cystoscope 8.5 Fr  | SL 145 mm  | Red               | 8686.0245                              |                 |                                      | •                   |
| Obturator for cystoscope 8.5 Fr   | WL 180 mm  | Red               | 8686.0247                              |                 |                                      |                     |
| Sheath for cystoscope 9.5 Fr  | SL 145 mm  | Yellow            | 8686.0345                              |                 |                                      | •                   |
| Obturator for cystoscope 9.5 Fr   | WL 180 mm  | Yellow            | 8686.0347                              |                 |                                      |                     |
| Also:   | 1  |                   |  |                 |                                      |                     |
| PANOVIEW telescope  |  | Direction of view | Ø                                      | WL              | TL                                   | Product no.         |
| Telescope 0° Ø 1.9 mm WL 178 r  | 0°   | 1.9 mm            | 178 mm                                 | 243 mm          | 8686.414                             |                     |
| Telescope 30° Ø 1.9 mm WL 179   | 30°  | 1.9 mm            | 179 mm                                 | 241 mm          | 8686.415                             |                     |
| Recommended accessories   |  |                   |  |                 |                                      | Product no.         |
| Perforated basket for standard tel  | escope 2   |                   | nsions (W x H x [<br>nsions (W x H x [ |                 |                                      | 38016               |
| Fiber light cable bndl consisting o   | f:   |                   | · · · · · · · · · · · · · · · · · · ·  | ·               |                                      | 00//05021           |

Ø 2.5 mm, 2.3 m long

806625231

Fiber light cable (80662523), projector-side adapter (8095.07),


and endoscope-side adapter (809509)



#### CYSTO-URETHROSCOPE 8672

FOR TELESCOPE 2.7 MM FOR INFANTS





| Recommended accessories   |  | Product no. |
|---|--|-------------|
| Perforated basket for standard telescope 2  | Internal dimensions (W x H x D): 454 x 52 x 40 mm<br>External dimensions (W x H x D): 481 x 54 x 59 mm | 38016       |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long   | 806625231   |



### CYSTO-URETHROSCOPE 8672

# FOR TELESCOPE 2.7 MM FOR INFANTS



spirit of excellence

| Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with

your contact partner or directly with Richard Wolf GmbH.



| Recommended accessories   |  | Product no. |
|---|--|-------------|
| Perforated basket for standard telescope 2  | Internal dimensions (W x H x D): 454 x 52 x 40 mm<br>External dimensions (W x H x D): 481 x 54 x 59 mm | 38016       |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long   | 806625231   |

2.7 mm

185 mm

247 mm

8672.425

70°

Telescope 70° Ø 2.7 mm WL 185 mm


Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with

your contact partner or directly with Richard Wolf GmbH.

# **OPTICAL FORCEPS**

#### FOR CYSTO-URETHROSCOPE 8672







# FORCEPS AND SCISSORS SMALL MODULAR SYSTEM HySafe FOR CYSTO-URETHROSCOPE 8672

| Grasping forceps jaw insert with                         | ı sheath    |    |        | Handle with overload protection | Complete instrument  • Jaw section  • Handle |
|--|-------------|----|--------|---------------------------------|--|
|  |             |    |        |                                 | • nullule                                    |
|  | Product no. | Fr | WL     | 8083.001                        | Product no.                                  |
| Grasping forceps bndl Distal angled with pike-mouth jaws | 8642.6508   | 5  | 340 mm | •                               | 8642.6502                                    |
|  | 8645.6508   | 7  | 325 mm | •                               | 8645.6502                                    |
| Grasping forceps bndl<br>- Spoon                         | 8642.6008   | 5  | 340 mm | •                               | 8642.6002                                    |
|  | 8645.6008   | 7  | 340 mm | •                               | 8645.6002                                    |
| Biopsy forceps bndl                                      | 8642.6318   | 5  | 340 mm | •                               | 8642.6312                                    |
| Scissors bndl  | 8642.6818   | 5  | 340 mm | •                               | 8642.6812                                    |
| Hook scissors bndl Through-cutting                       | 8992.6408   | 7  | 310 mm | •                               | 8992.6402                                    |


- Can be flushed through optimum internal cleaning
- Easy-Click quick and simple assembly
- Overload protection significantly longer service life

# WOLF

spirit of excellence

# FLEXIBLE GRASPING FORCEPS

#### FOR CYSTO-URETHROSCOPES 8672 AND 8686






| Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with

your contact partner or directly with Richard Wolf GmbH

#### **MIDI-SIZE**

#### CYSTO-URETHROSCOPE



| Recommended accessories   |  | Product no.    |
|---|--|----------------|
| Perforated basket for standard telescope 2  | Internal dimensions (W x H x D): 454 x 52 x 40 mm<br>External dimensions (W x H x D): 481 x 54 x 59 mm | 38016          |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long   | 806625231      |
| HF connection cable   |  | see URO103/104 |



# FLEXIBLE AUXILIARY INSTRUMENTS FOR MIDI-SIZE

|  |                                       | Outer Ø | WL     | TL     | Product no. |
|--|---------------------------------------|---------|--------|--------|-------------|
|  | Flex. biopsy forceps 5 Fr WL 315 mm   | 5 Fr    | 315 mm | 465 mm | 829.05      |
|  | Flex. biopsy forceps 7 Fr WL 375 mm   | 7 Fr    | 375 mm | 490 mm | 829.07      |
|  | Flex. grasping forceps 5 Fr WL 315 mm | 5 Fr    | 315 mm | 465 mm | 828.05      |
|  | Flex. grasping forceps 7 Fr WL 365 mm | 7 Fr    | 365 mm | 515 mm | 828.07      |
|  | Flex. scissors 7 Fr WL 375 mm         | 7 Fr    | 375 mm | 490 mm | 830.07      |

# 

#### spirit of excellence

| IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# CYSTOSCOPE 4.5/6.5 Fr

#### FOR NEWBORNS AND INFANTS




|  |  | Direction of view | Working chan-<br>nel | WL     | Product no. |
|--|--|-------------------|----------------------|--------|-------------|
| Cystoscope bndl consisting of: Cystoscope 5° 4.5/6.5 Fr WL seal Ø 7.5 mm (Pack = 10 P membrane holder (15256.3' "RIWO" rubber cap, red-orang | CS) (89.101),<br>93), and                      | 5°                | 3.3 Fr               | 120 mm | 87154012    |
| Also:  |  |                   |                      |        |             |
| <b>\</b>   | Flex. grasping forceps 3 Fr WL 2 Fine toothing | 230 mm            |                      | 230 mm | 828.03      |
|  | Flex. biopsy forceps 3 Fr WL 230               | 0 mm              |                      | 230 mm | 829.03      |
| for inserting auxiliary instruments of 1–6 Fr:  universal sealing valve 1–6 Fr, sterile (Pack = 5 PCS)                                       |  |                   | 4712348              |        |             |

| Recommended accessories  |                 |   | Product no. |
|--|-----------------|---|-------------|
| Perforated basket for cystoscope/telescope   |                 | Internal dimensions (W x H x D): 451 x 65 x 124 mm External dimensions (W x H x D): 467 x 75 x 132 mm | 38004       |
| Fiber light cable bndl<br>consisting of:<br>Fiber light cable (80662523), projector-side adap<br>and endoscope-side adapter (809509) | oter (8095.07), | Ø 2.5 mm, 2.3 m long  | 806625231   |



## CYSTOSCOPE 8/9.8 Fr

#### FOR REFLUX THERAPY IN INFANTS



| Recommended accessories   |  | Product no. |
|---|--|-------------|
| Perforated basket for cystoscope/telescope  | Internal dimensions (W x H x D):<br>451 x 65 x 124 mm<br>External dimensions (W x H x D):<br>467 x 75 x 132 mm | 38004       |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long   | 806625231   |



# WOLF


#### spirit of excellence

| Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with

your contact partner or directly with Richard Wolf GmbH.

## **RESECTOSCOPE**

#### FOR TELESCOPE 1.9 MM FOR NEWBORNS AND INFANTS



| Recommended accessories   | Product no.  |           |
|---|--|-----------|
| Perforated basket for standard telescope 1  | Internal dimensions (W x H x D): 270 x 52 x 40 mm<br>External dimensions (W x H x D): 297 x 54 x 59 mm | 38015     |
| Fiber light cable bndl consisting of:<br>Fiber light cable (80662523), projector-side adapter (8095.07),<br>and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long   | 806625231 |
| Electrodes and scalpels   | see URO182   |           |
| HF connection cable   | see URO103/104   |           |




## WOLF

#### spirit of excellence

#### **RESECTOSCOPE**

### FOR TELESCOPE 2.7 MM FOR NEWBORNS AND INFANTS



| Recommended accessories   |   | Product no.    |
|---|---|----------------|
| Perforated basket for standard telescope 1  | Internal dimensions (W x H x D): 270 x 52 x 40 mm External dimensions (W x H x D): 297 x 54 x 59 mm | 38015          |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long  | 806625231      |
| Electrodes and scalpels   |   | see URO182     |
| HF connection cable   |   | see URO103/104 |



| IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

### **ELECTRODES AND SCALPELS**

#### FOR RESECTOSCOPE WITH TELESCOPE 1.9 MM AND 2.7 MM

| Electrodes | Electrodes   |         |          |         |
|------------|--|---------|----------|---------|
|            |  | Loop    | 1.9 mm   | 2.7 mm  |
|            | Cutting electrode mono 9 Fr 0°                     | - Round | 8688.93  |         |
| V          | Cutting electrode mono 11.5 Fr 0°                  | Round   |          | 8416.03 |
|            | Coag. electrode mono 9 Fr 0°                       | - Ball  | 8688.91  |         |
|            | Coag. electrode mono 11.5 Fr 0°                    | Bull    |          | 8416.01 |
|            | Hook electrode mono 9 Fr 0°                        | - Hook  | 8688.95  |         |
| Machine S  | Hook electrode mono 11.5 Fr 0°                     |         |          | 8416.09 |
|            | Coag. electrode mono 9 Fr 0° 90° angled retrograde | Ball    | 8688.994 |         |

| Scalpel, for cold cutting of urethral strictures |  |                |          | e with telescope |
|--|--|----------------|----------|------------------|
|  |  | Cutting edge   | 1.9 mm   | 2.7 mm           |
|  | Scalpel 9 Fr ceramic, semi-circular    | Compi piraular | 8693.961 |                  |
|  | Scalpel 11.5 Fr ceramic, semi-circular | Semi-circular  |          | 8677.961         |
|  | Scalpel 8.5 Fr, sickle-shaped          | Cialda abarrad | 8693.93  |                  |
|  | Scalpel 11.5 Fr, sickle-shaped         | Sickle-shaped  |          | 8677.93          |
|  | Scalpel 8.5 Fr, hook-shaped            | Hook-shaped    | 8688.94  |                  |


MIDI-SIZE RESECTOSCOPE

## RICHARD

spirit of excellence

#### **MIDI-SIZE**

#### **RESECTOSCOPE**



| Recommended accessories  |  | Product no.    |
|--|--|----------------|
| Perforated basket for standard telescope 2   | Internal dimensions (W x H x D): 454 x 52 x 40 mm<br>External dimensions (W x H x D): 481 x 54 x 59 mm | 38016          |
| Fiber light cable bndl<br>consisting of:<br>Fiber light cable (80662523), projector-side adapter (8095.07),<br>and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long   | 806625231      |
| Container (W x H x D) 300 x 60 x 200 mm  |  | 33020          |
| Monopolar connection cable   |  | see URO103/104 |

| IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

### **MIDI-SIZE**

#### AUXILIARY INSTRUMENTS FOR THE MIDI-SIZE RESECTOSCOPE

| Stricture scalpels with ceramic cutter |                                | Cutting surface                      | Product no. |
|--|--------------------------------|--------------------------------------|-------------|
|  | Scalpel 14.5 Fr, lancet-shaped | Lancet-shaped,<br>cuts on both sides | 8677981     |
|  | Scalpel 14.5 Fr, sickle-shaped | Sickle-shaped                        | 8677931     |

| Electrodes |   | Electrode shape | Product no. |
|------------|---|-----------------|-------------|
| 8          | Coag. electrode mono 14.5 Fr 0° Stem color yellow   | Button          | 8416011     |
| ()         | Cutting electrode mono 14.5 Fr 0° Stem color yellow | Round loop      | 8416031     |
|            | Hook electrode mono 14.5 Fr 0° Stem color yellow    | Hook            | 8416091     |


FIBER URETERORENOSCOPE



#### **ULTRA-THIN FIBER URETERORENOSCOPE**

#### WITH LATERAL EYEPIECE






| Ureterorenoscope 5° 4.5/6.5 Fr WL 430 mi Atraumatically shaped  |                                | 430 mm                    | 555 mm             | 5°                     | 4.5/6.5<br>Fr | 3 Fr | 8701.534    |
|---|--------------------------------|---------------------------|--------------------|------------------------|---------------|------|-------------|
| Recommended acces   | sories                         |                           |                    |                        |               |      | Product no. |
|   | Flex. gı                       | rasping forceps 3 F       | r WL 530 mm        |                        |               |      | 828.605     |
|   | Flex. bi                       | opsy forceps 3 Fr         | WL 530 mm          |                        |               |      | 829.603     |
|   | Laser f                        | iber Ø 200 μm, di         | sposable           |                        |               |      | 487501200   |
|   | Laser f                        | iber Ø 272 μm, dis        | sposable           |                        |               |      | 487501272   |
|   | Laser f                        | iber Ø 200 µm, reı        | ısable             |                        |               |      | 87501200    |
|   | Laser fiber Ø 272 μm, reusable |                           |                    |                        |               |      | 87501272    |
| Handle for E-Line ureterorenoscopes   |                                |                           |                    |                        | 8702.261      |      |             |
| Guide element for ure   | eterorenos                     | scope for LITHOCLA        | ST handpieces      |                        |               |      | 8702.251    |
| for inserting auxiliary i   | nstrument                      | s of 1–6 Fr: <b>unive</b> | rsal sealing valve | e 1–6 Fr, sterile (Pac | k = 5 PCS)    |      | 4712348     |
| Membrane holder sta   | ındard                         |                           |                    |                        |               |      | 15256.393   |
| Membrane holder wit   | h Luer                         |                           |                    |                        |               |      | 15256.456   |
| Seal Ø 7.5 mm (Pack   | = 10 pcs                       | )                         |                    |                        |               |      | 89.101      |
| LithoClast probe Ø 0.8 mm WL 605 mm   |                                |                           |                    |                        | 8742.001      |      |             |
| Perforated basket, upper urinary tract 1 with small part basket  Internal dimensions (W x H x D): 619 x 65 x 124 mm  External dimensions (W x H x D): 635 x 75 x 132 mm |                                |                           |                    |                        | 38003         |      |             |
| Marking pen, black  |                                |                           |                    |                        | 38201.948     |      |             |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509)  Ø 2.5 mm, 2.3 m long         |                                |                           |                    |                        | 806625231     |      |             |
| Auxiliary instruments   | Auxiliary instruments          |                           |                    |                        |               |      | see URO197  |







**AUXILIARY INSTRUMENTS** 




### **AUXILIARY INSTRUMENTS**

| BLADDER SYRINGES       |                                  |
|------------------------|----------------------------------|
| SEALING CAPS           |                                  |
| LUER-LOCK PARTS / STO  | PCOCKS AND IRRIGATION ADAPTERS / |
| SEALING VALVE / ADAPTI | ER / LASER ADJUSTMENT UNIT       |
| FORCEPS AND SCISSOR    | S, RIGID                         |
| FORCEPS AND SCISSOR    | S, FLEXIBLE                      |
| ELECTRODES             |                                  |



#### **BLADDER SYRINGES**



|  |  | Ø     | ml     | L/TL         | Product no. |
|--|--|-------|--------|--------------|-------------|
| Bladder syringe 150 ml Ø 54 mm                 | for flexible and rigid adapters                                    | 54 mm | 150 ml | L<br>248 mm  | 822.31      |
| Flexible adapter for bladder syringe           | Compatible with bladder syringe<br>822.31                          |       |        | TL<br>106 mm | 822.13      |
| Rigid adapter for bladder syringe              | Compatible with instruments with cone B and bladder syringe 822.31 |       |        | TL<br>37 mm  | 822.14      |
| Bladder syringe 150 ml Ø 54 mm                 |  | 54 mm | 150 ml | L<br>248 mm  | 822.40      |
| Rigid adapter for bladder syringe              | Compatible with bladder syringe 822.40                             |       |        | TL<br>50 mm  | 822.60      |
| for bladder syringe 150 ml (822.31 and 822.40) |  |       |        |              |             |
| Spare cylinder 150 ml                          |  |       | 150 ml |              | 82295       |

| IX23 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product, for more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

### **SEALING CAPS**

| Figure                             |   | Capacity Ø | Color      | Product no. |
|------------------------------------|---|------------|------------|-------------|
| Sealing cap                        | Sealing cap without hole                              | -          | Red-orange | 89.20       |
| Small, Pack = 10 PCS               | Sealing cap capacity < 2.4 mm                         | < 2.4      | Black      | 89.00       |
| 15 mm                              | Sealing cap capacity 2.4–3.4 mm                       | 2.4–3.4    | Red        | 89.01       |
|                                    | Sealing cap capacity 3.4–5.1 mm                       | 3.4–5.1    | Blue       | 89.02       |
| 0 /                                | Sealing cap capacity 5.1–6.0 mm                       | 5.1–6.0    | Gray       | 89.03       |
|                                    | Sealing cap capacity 6.0–7.0 mm                       | 6.0-7.0    | Brown      | 89.04       |
|                                    | Sealing cap capacity 6.0–7.0 mm                       | 7.0–8.0    | Yellow     | 89.05       |
|                                    | Sealing cap capacity 9.5–10.1 mm                      | 9.5–10.1   | Red        | 89.08       |
| 17                                 | Sealing cap capacity > 10.1 mm                        | > 10.1     | Blue       | 89.09       |
| 17 mm                              | Sealing cap capacity 13.0–13.8 mm                     | 13.0–13.8  | Red        | 89.10       |
|                                    | Sealing cap capacity 4–6 mm                           | 4.0-6.0    | Red        | 89.141      |
|                                    | Sealing cap capacity 7.5–8.5 mm                       | 7.5–8.5    | Blue       | 89.161      |
|                                    | Sealing cap capacity 7.0 mm                           | 7.0        | Brown      | 89.171      |
| Sealing cap with cross-shaped slot | for trocar sleeve with threaded sheath, Pack = 10 PCS | -          | Red-orange | 89.90       |
| RIWO rubber cap Pack = 10 PCS      | RIWO rubber cap without hole                          | -          | Red-orange | 88.00       |
| PUCK = TU PCS                      | RIWO rubber cap capacity 0.5 mm                       | 0.5        | Red        | 88.005      |
|                                    | RIWO rubber cap capacity 0.8 mm                       | 0.8        | Red-orange | 88.01       |
| ø                                  | RIWO rubber cap capacity 1.4 mm                       | 1.4        | Blue       | 88.02       |
|                                    | RIWO rubber cap capacity 2.4 mm                       | 2.4        | Black      | 88.03       |
|                                    | RIWO rubber cap capacity 4.0 mm                       | 4.0        | Green      | 88.04       |
|                                    | Rubber cap for hysteroscope Extended, Pack = 1 PC     | -          | Red-orange | 18.01       |



## LUER-LOCK PARTS / STOPCOCKS AND IRRIGATION ADAPTERS / SEALING VALVE / ADAPTER/LASER ADJUSTMENT UNIT

spirit of excellence

|        |   | Hole   |        | Product no. |  |  |  |
|--------|---|--|--------|-------------|--|--|--|
| A-1    | Tube with LUER-LOCK connector   | Ø3 mm  | Male   | 886.00      |  |  |  |
|        | Tube with LUER-LOCK connector Ø 4 mm<br>Length 29.5 mm                          | Ø 4 mm   | Male   | 886.01      |  |  |  |
|        | Tube with LUER-LOCK connector Ø 3 mm<br>Length 28 mm                            | Ø 3 mm   | Female | 891.00      |  |  |  |
|        | Tube with LUER-LOCK connector, 891.011  | Ø 4 mm   | Female | 15023.041   |  |  |  |
| Raco   | Stopcock LUER-LOCK connection Ø 3 mm  | Ø3 mm  | Male   | 884.00      |  |  |  |
|        | Stopcock LUER-LOCK connection Ø 4 mm  | Ø 4 mm   | Male   | 884.01      |  |  |  |
|        | Two-way stopcock, maintenance-free with LUER-LOCK connection                    | Ø 3 mm   | Male   | 88350       |  |  |  |
| 4 Topa | Two-way stopcock, maintenance-free with LUER-LOCK connection                    | Ø 4 mm   | Female | 88351       |  |  |  |
|        | Adapter with 2 Luer connections, male, quick-releas                             | Adapter with 2 Luer connections, male, quick-release mechanism, TL 36 mm |        |             |  |  |  |
| -      | Adapter with 2 irrigation valves and 1 instrument po                            | ort, quick-release mecl  | nanism | 7305.782    |  |  |  |
|        | Also:<br>Luer sealing cap   |  |        | 15023205    |  |  |  |
|        | Universal sealing valve 1–6 Fr<br>for inserting auxiliary instruments of 1–6 Fr |  |        | 4712348     |  |  |  |
|        | Adapter for machine leakage tests   | 163.905  |        |             |  |  |  |
|        | Laser adjustment unit bndl  | 15369108   |        |             |  |  |  |
|        | Also: clamping element, orange (20 pcs)   | 15394144   |        |             |  |  |  |



#### RIGID FORCEPS AND SCISSORS

### SMALL MODULAR SYSTEM **HySafe**

RECOMMENDED FOR CYSTOSCOPY

| Grasping forceps jaw insert with                         | Grasping forceps jaw insert with sheath |    |        |          | Complete instrument  • Jaw section  • Handle |
|--|---|----|--------|----------|--|
|  | (1000 ) ·                               |    |        |          | • Hanale                                     |
|  | Product no.                             | Fr | WL     | 8083.001 | Product no.                                  |
| Grasping forceps bndl Distal angled with pike-mouth jaws | 8642.6508                               | 5  | 340 mm | •        | 8642.6502                                    |
|  | 8645.6508                               | 7  | 325 mm | •        | 8645.6502                                    |
| Grasping forceps bndl - Spoon                            | 8642.6008                               | 5  | 340 mm | •        | 8642.6002                                    |
|  | 8645.6008                               | 7  | 340 mm | •        | 8645.6002                                    |
| Biopsy forceps bndl                                      | 8642.6318                               | 5  | 340 mm | •        | 8642.6312                                    |
| Scissors bndl  | 8642.6818                               | 5  | 340 mm | •        | 8642.6812                                    |
| Hook scissors bndl Through-cutting                       | 8992.6408                               | 7  | 310 mm | •        | 8992.6402                                    |



#### RIGID FORCEPS AND SCISSORS

### SMALL MODULAR SYSTEM **HySafe**RECOMMENDED FOR URETERORENOSCOPY

| Grasping forceps jaw insert with                  | sheath      |    |        | Handle with overload protection | Complete instrument • Jaw section • Handle |
|---|-------------|----|--------|---------------------------------|--|
|   | Product no. | Fr | WL     | 8083.001                        | Product no.                                |
| Biopsy forceps bndl                               | 8952.6008   | 5  | 550 mm | •                               | 8952.6002                                  |
| <b>Grasping forceps bndl</b> with mouse tooth     | 8952.6118   | 4  | 550 mm | •                               | 8952.6112                                  |
|   | 8959.6218   | 5  | 425 mm | •                               | 8959.6212                                  |
|   | 8952.6218   | 5  | 550 mm | •                               | 8952.6212                                  |
| Grasping forceps bndl                             | 8959.6808   | 5  | 425 mm | •                               | 8959.6802                                  |
| distribute.                                       | 8954.6808   | 5  | 550 mm | •                               | 8954.6802                                  |
| Grasping forceps bndl with pike-mouth jaws, short | 8952.6508   | 5  | 550 mm | •                               | 8952.6502                                  |



#### RIGID FORCEPS AND SCISSORS

### SMALL MODULAR SYSTEM HySafe

RECOMMENDED FOR NEPHROSCOPY

| Grasping forceps jaw insert with s                  | sheath      |         |          | Handle with overload protec-<br>tion | Complete instrument  • Jaw section |
|---|-------------|---------|----------|--------------------------------------|------------------------------------|
| H <sub>y</sub> Safe                                 |             |         | <b>)</b> |                                      | • Handle                           |
|   | Product no. | Fr      | WL       | 8083.001                             | Product no.                        |
| Grasping forceps bndl Pike-mouth jaws               | 8962.6008   | 10.5 Fr | 350 mm   | •                                    | 8962.6002                          |
|   | 8962.6048   | 12 Fr   | 355 mm   | •                                    | 8962.6042                          |
| Grasping forceps bndl Distal angled Pike-mouth jaws | 8962.6028   | 9 Fr    | 355 mm   | •                                    | 8962.6022                          |
| Grasping forceps bndl Pike-mouth jaws               | 8962.6108   | 10.5 Fr | 350 mm   | •                                    | 8962.6102                          |
| Grasping forceps bndl Peanut shape, fine toothing   | 8962.6078   | 12 Fr   | 340 mm   | •                                    | 8962.6072                          |
| Grasping forceps bndl  Mouse tooth                  | 8962.6058   | 12 Fr   | 340 mm   | •                                    | 8962.6052                          |
| Grasping forceps bndl Pike-mouth jaws               | 8962.6808   | 6 Fr    | 425 mm   | •                                    | 8968.6802                          |

### WOLF

spirit of excellence

### RIGID FORCEPS AND SCISSORS

#### RECOMMENDED FOR NEPHROSCOPY

|               |  | Area of application                               | Fr | WL     | Product no. |
|---------------|--|---|----|--------|-------------|
| Fine toothing | Rigid grasping forceps 5 Fr<br>WL 340 mm | Surgical<br>urethro-<br>cystoscopy<br>for infants | 5  | 340 mm | 8626.65     |
| Serrated      | Biopsy forceps WL 270 mm                 | Intrarenal stone surgery                          | 8  | 270 mm | 8280.22     |
|               | Biopsy forceps WL 270 mm                 | Intrarenal stone surgery                          | 6  | 270 mm | 8280.23     |
|               | Scissors WL 230 mm                       | Intrarenal<br>stone surgery                       | 8  | 230 mm | 8283.21     |

### FLEXIBLE FORCEPS AND SCISSORS

#### RECOMMENDED FOR CYSTOSCOPY

|             |  | Fr  | WL     | TL     | Product no. |
|-------------|--|-----|--------|--------|-------------|
|             | Flex. grasping forceps 3 Fr WL 230 mm      | 3   | 230 mm | 380 mm | 828.03      |
| <b></b>     | Flex. grasping forceps 5 Fr WL 315 mm      | 5   | 315 mm | 465 mm | 828.05      |
| 100         | Flex. grasping forceps 7 Fr WL 365 mm      | 7   | 365 mm | 515 mm | 828.07      |
|             | Flex. grasping forceps 10 Fr WL<br>325 mm  | 10  | 325 mm | 475 mm | 828.10      |
|             | Flex. grasping forceps 5 Fr WL 550 mm      | 5   | 550 mm | 720 mm | 828.051     |
|             | Flex. biopsy forceps 3 Fr WL 230 mm        | 3   | 230 mm | 380 mm | 829.03      |
|             | Flex. biopsy forceps 5 Fr WL 315 mm        | 5   | 315 mm | 465 mm | 829.05      |
|             | Flex. biopsy forceps 7 Fr WL 375 mm        | 7   | 375 mm | 490 mm | 829.07      |
|             | Flex. biopsy forceps 10 Fr WL 325 mm       | 10  | 325 mm | 475 mm | 829.10      |
| Marco IIII  | Flex. biopsy forceps 5 Fr WL 550 mm        | 5   | 550 mm | 720 mm | 829.051     |
|             | Flex. scissors 7 Fr WL 375 mm              | 7   | 375 mm | 490 mm | 830.07      |
|             | Flex. grasping forceps 5 Fr WL 550 mm      | 5   | 550 mm | 680 mm | 8735.685    |
| Mouse tooth | Flex. grasping forceps 6.6 Fr WL<br>550 mm | 6.6 | 550 mm | 690 mm | 8736.685    |

15

## WOLF

spirit of excellence

### FLEXIBLE FORCEPS AND SCISSORS

#### RECOMMENDED FOR URETERORENOSCOPY

|                 |  | Fr  | WL     | TL       | Product no. |
|-----------------|--|-----|--------|----------|-------------|
| 3               | Flex. grasping forceps 3 Fr WL 530 mm                        | 3   | 530 mm | 665 mm   | 828.605     |
| cirities .      | Flex. grasping forceps 5 Fr WL 550 mm                        | 5   | 550 mm | 720 mm   | 828.051     |
| Fine toothing   | Flex. grasping forceps 3 Fr WL 920 mm                        | 3   | 920 mm | 1,050 mm | 828.651     |
|                 | Flex. biopsy forceps 5 Fr WL 550 mm                          | 5   | 550 mm | 720 mm   | 829.051     |
|                 | Flex. biopsy forceps 3 Fr WL 530 mm                          | 3   | 530 mm | 665 mm   | 829.603     |
|                 | Flex. biopsy forceps Ø 3 Fr WL 920 mm                        | 3   | 920 mm | 1,055 mm | 829.601     |
|                 | Flex. biopsy forceps 4 Fr WL 600 mm                          | 4   | 600 mm | 730 mm   | 8734.606    |
| Pike-mouth jaws | Flex. grasping forceps 4 Fr WL 600 mm                        | 4   | 600 mm | 750 mm   | 8734.656    |
| Mouse tooth     | Flex. grasping forceps 4 Fr WL 600 mm                        | 4   | 600 mm | 750 mm   | 8734.686    |
|                 | Flex. grasping forceps 5 Fr WL 550 mm                        | 5   | 550 mm | 700 mm   | 8735.685    |
| 3               | Flex. grasping forceps 3.5 Fr WL<br>550 mm,<br>Fine toothing | 3.5 | 550 mm | 700 mm   | 8953.60     |



#### FLEXIBLE FORCEPS AND SCISSORS

#### RECOMMENDED FOR NEPHROSCOPY

WL TL Fr Product no. Flex. grasping forceps 3 Fr WL 530 mm 828.605 3 530 mm 665 mm 5 550 mm 720 mm 828.051 Flex. grasping forceps 5 Fr WL 550 mm Flex. biopsy forceps 5 Fr WL 550 mm 5 550 mm 720 mm 829.051 Flex. grasping forceps 5 Fr WL 550 mm 550 mm 680 mm 8735.685 8736.685 Flex. grasping forceps 6.6 Fr WL 550 mm 6.6 550 mm 690 mm Mouse tooth


4.5

### **ELECTRODES**

|   | Area of applica-<br>tion | Electrode<br>shape | WL     | Fr  | Product no. |
|---|--------------------------|--------------------|--------|-----|-------------|
| Coag. electrode mono<br>5 Fr WL 600 mm  | Ureterorenoscopy         | Button             | 600 mm | 5   | 8599.80     |
| Coag. electrode mono<br>4 Fr WL 400 mm  |                          |                    |        | 4   | 823.04      |
| Coag. electrode mono<br>5 Fr WL 400 mm  | Cyatagony                | Button 400         | 400 mm | 5   | 823.05      |
| Coag. electrode mono<br>6 Fr WL 400 mm  | Cystoscopy               |                    |        | 6   | 823.06      |
| Coag. electrode mono<br>10 Fr WL 400 mm |                          |                    |        | 10  | 823.10      |
| Coag. electrode mono<br>3 Fr WL 580 mm  | Ureterorenoscopy         | Button             | 580 mm | 3   | 823.031     |
| Hook electrode mono<br>2.4 Fr WL 600 mm | Ureterorenoscopy         | Hook               | 600 mm | 2.4 | 823.221     |









### **UROLOGICAL LAPAROSCOPY**

| BASIC SE  | rs  |
|-----------|---|
| TELESCOF  | PES   |
| TROCAR S  | SLEEVES/DILATION/EXTRACTION/REDUCING SLEEVES                |
| ERAGONN   | IODULAR GRASPING FORCEPS/DISSECTORS/BIOPSY FORCEPS/SCISSORS |
| GRASPING  | FORCEPS   |
| BIPOLAR I | FORCEPS AND SCISSORS  |
| HF ELECTI | RODES (MONOPOLAR/BIPOLAR)                                   |
| MULTIFUN  | ICTIONAL SUCTION IRRIGATION SYSTEM                          |
| TISSUE RE | ETRACTOR  |
| CLIP APPL | ICATOR  |
| NEEDLE H  | OLDER/KNOT PUSHER/FASCIA CLOSURE                            |
| CANNULA   | S/SURGICAL PROBES/MYOMA DRILLS                              |
| DEVICES/  | ACCESSORIES   |
| CHOLEDO   | CHOSCOPY  |
| TRAINING  | MODELS  |



### **BASIC SET**

#### FOR ALL LAPAROSCOPIC PROCEDURES

| Product                                 | Product no. | Quantity | Catalog / Section       |
|---|-------------|----------|-------------------------|
| Insufflator 45 EVAC + HEAT bndl         | 22350312    | 1        | Laparoscopy / 13        |
| VERES cannula Ø 2.1 mm WL 120 mm        | 8302.12     | 1        | Laparoscopy / 3         |
| LAP suction irrigation pump bndl        | 22160011    | 1        | Laparoscopy / 13        |
| LED light source ENDOLIGHT LED 2.1 bndl | 51630011    | 1        | Imaging / Light sources |
| Fiber light cable                       |             | 1        | Imaging / Light cables  |
| ENDOCAM Logic HD                        | 5525        | 1        | Imaging / ENDOCAM       |
| Monitors                                |             | 1        | Imaging / Monitors      |
| Device cart                             |             | 1        | Imaging / Device cart   |

### BASIC SET

#### FOR LAPAROSCOPIC CHOLECYSTECTOMY

| Product  | Product no. | Quantity | Catalog / Section |
|--|-------------|----------|-------------------|
| Telescope 30° Ø 10 mm WL 307 mm                    | 8934.432    | 1        | Laparoscopy / 2   |
| and/or   |             |          |                   |
| Telescope 0° Ø 10 mm WL 307 mm                     | 8934.431    | 1        | Laparoscopy / 2   |
| Fiber light cable bndl                             | 806650231   | 1        | Laparoscopy / 2   |
| Trocar sleeve, slanted, capacity 5.5 mm WL 100 mm  | 8921.013    | 2–3      | Laparoscopy / 3   |
| and/or   |             |          |                   |
| Trocar sleeve, straight, capacity 5.5 mm WL 102 mm | 8919.351    | 2–3      | Laparoscopy / 3   |
| Trocar sleeve, slanted, capacity 10 mm WL 100 mm   | 8923.013    | 2        | Laparoscopy / 3   |
| Guide rod 5.5 mm TL 500 mm                         | 8923.921    | 1        | Laparoscopy / 3   |
| Instrument sleeve 10 mm WL 170 mm                  | 8385.50     | 1        | Laparoscopy / 3   |
| VERES cannula Ø 2.1 mm WL 120 mm                   | 8302.12     | 1        | Laparoscopy / 3   |
| Multifunctional suction irrigation system          |             | I.       | 1                 |
| Suction irrigation tube Ø 5 mm WL 310 mm           | 8383.911    | 1        | Laparoscopy / 8   |
| Suction irrigation handle                          | 8385.901    | 1        | Laparoscopy / 8   |
| Sealing cap  | 8385.902    | 1        | Laparoscopy / 8   |
| ERAGONmodular                                      |             | _        |                   |
| Atraumatic grasping forceps Ø 5 mm bndl            | 83932925    | 1        | Laparoscopy / 4   |
| Atraumatic grasping forceps mono Ø 5 mm bndl       | 83931817    | 2        | Laparoscopy / 4   |
| Maryland dissector forceps mono Ø 5 mm bndl        | 83932817    | 1        | Laparoscopy / 4   |
| Metzenbaum scissors Ø 5 mm bndl                    | 83930417    | 1        | Laparoscopy / 4   |
| Grasping forceps Ø 10 mm bndl                      | 83952048    | 1        | Laparoscopy / 4   |
| Plate-shaped grasping forceps Ø 10 mm bndl         | 83952347    | 1        | Laparoscopy / 4   |
|  |             | _        |                   |
| Hook electrode mono Ø 5 mm WL 340 mm               | 8383.423    | 1        | Laparoscopy / 7   |
| Clip applicator Ø 10 mm WL 340 mm                  | 8389.911    | 1        | Laparoscopy / 10  |
| Ethicon® Ligaclips® (PACK= 108 PCS)                | 8389.915    | 1        | Laparoscopy / 10  |
| Needle forceps Ø 2.45 mm WL 160 mm                 | 8756.201    | 1        | Laparoscopy / 11  |
| Sealing cone Ø 12–15 mm                            | 8943.915    | 1        | Laparoscopy / 11  |
| Monopolar HF cable                                 | 8106        | 2        | Laparoscopy / 13  |

### **BASIC SET**

#### FOR LAPAROSCOPIC CHOLECYSTECTOMY

| Product   | Product no. | Quantity | Catalog / Section |
|---|-------------|----------|-------------------|
| Also on request:                                  | '           |          |                   |
| Telescope 30° Ø 5.3 mm WL 303 mm                  | 8935442     | 1        | Laparoscopy / 2   |
| Trocar sleeve, slanted, capacity 5.5 mm WL 100 mm | 8921.013    | 1        | Laparoscopy / 3   |
| Trocar tip sharp size 5.5 mm WL 169 mm            | 8921.113    | 1        | Laparoscopy / 3   |
| ERAGONmodular                                     |             |          |                   |
| Atraumatic grasping forceps mono Ø 5 mm bndl      | 83931957    | 1        | Laparoscopy / 4   |
| Biopsy forceps mono Ø 5 mm bndl                   | 83930937    | 1        | Laparoscopy / 4   |
| Dissector forceps Ø 10 mm bndl                    | 83952268    | 1        | Laparoscopy / 4   |
| ERAGONbipolar                                     |             |          |                   |
| Grasping forceps bipo Ø 5.5 mm bndl               | 839300312   | 1        | Laparoscopy / 6   |

| In addition to laparoscopic choledochus revision |         |   |                 |
|--|---------|---|-----------------|
| Grasping forceps Ø 5 mm WL 295 mm                | 8383311 | 1 | Laparoscopy / 5 |

## BASIC SET FOR LAPAROSCOPIC APPENDECTOMY

| Product  | Product no. | Quantity | Catalog / Section |
|--|-------------|----------|-------------------|
| Telescope 30° Ø 10 mm WL 307 mm                    | 8934.432    | 1        | Laparoscopy / 2   |
| and/or   |             |          |                   |
| Telescope 0° Ø 10 mm WL 307 mm                     | 8934.431    | 1        | Laparoscopy / 2   |
| Fiber light cable bndl                             | 806650231   | 1        | Laparoscopy / 2   |
| Trocar sleeve, slanted, capacity 10 mm WL 100 mm   | 8923.013    | 2        | Laparoscopy / 3   |
| Trocar tip sharp size 10 mm                        | 8923.113    | 2        | Laparoscopy / 3   |
| and/or   |             |          |                   |
| Trocar sleeve, straight, capacity 5.5 mm WL 102 mm | 8919.351    | 2–3      | Laparoscopy / 3   |
| Trocar tip sharp size 5.5 mm WL 144 mm             | 8919.3512   | 2–3      | Laparoscopy / 3   |
| Trocar sleeve, slanted, capacity 5.5 mm WL 100 mm  | 8921.013    | 2–3      | Laparoscopy / 3   |
| Trocar tip sharp size 5.5 mm WL 169 mm             | 8921.113    | 2–3      | Laparoscopy / 3   |
| Guide rod 5.5 mm TL 500 mm                         | 8923.921    | 1        | Laparoscopy / 3   |
| Instrument sleeve 10 mm WL 170 mm                  | 8385.50     | 1        | Laparoscopy / 3   |
| ERAGONmodular                                      | '           |          |                   |
| Grasping forceps mono Ø 5 mm bndl                  | 83932877    | 1        | Laparoscopy / 4   |
| Atraumatic grasping forceps mono Ø 5 mm bndl       | 83931817    | 2        | Laparoscopy / 4   |
| Maryland dissector forceps mono Ø 5 mm bndl        | 83932817    | 1        | Laparoscopy / 4   |
| Metzenbaum scissors Ø 5 mm bndl                    | 83930417    | 1        | Laparoscopy / 4   |
| Grasping and dissector forceps 5 mm                | 83932827    | 1        | Laparoscopy / 4   |
| ERAGONbipolar                                      |             |          |                   |
| Grasping forceps bipo Ø 5.5 mm bndl                | 839300312   | 1        | Laparoscopy / 6   |
| Multifunctional suction irrigation system          | ·           |          |                   |
| Suction irrigation tube Ø 5 mm WL 310 mm           | 83839.11    | 1        | Laparoscopy / 8   |
| Suction irrigation handle                          | 8385.901    | 1        | Laparoscopy / 8   |
| Sealing cap  | 8385.902    | 1        | Laparoscopy / 8   |
|  |             | · ·      |                   |
| Surgical probe Ø 5 mm WL 328 mm                    | 8383.66     | 1        | Laparoscopy / 12  |
| VERES cannula Ø 2.1 mm WL 120 mm                   | 8302.12     | 1        | Laparoscopy / 3   |
| Bipolar HF cable                                   | 8108        | 1        | Laparoscopy / 13  |
| Monopolar HF cable                                 | 8106        | 1        | Laparoscopy / 13  |

### BASIC SET

#### FOR LAPAROSCOPIC APPENDECTOMY

| Product                                 | Product no. | Quantity | Catalog / Section |
|---|-------------|----------|-------------------|
| Also on request:                        |             | ,        |                   |
| ERAGONmodular                           |             |          |                   |
| Dissector forceps mono Ø 5 mm bndl      | 83932897    | 1        | Laparoscopy / 4   |
| Grasping forceps mono Ø 5 mm bndl       | 83931837    | 2        | Laparoscopy / 4   |
| Biopsy forceps mono Ø 5 mm bndl         | 83930917    | 1        | Laparoscopy / 4   |
| Maryland dissector forceps Ø 10 mm bndl | 83952257    | 1        | Laparoscopy / 4   |
|   |             |          |                   |
| Clip applicator Ø 10 mm WL 340 mm       | 8389.911    | 1        | Laparoscopy / 10  |
| Ethicon® Ligaclips® (PACK= 108 PCS)     | 8389.915    | 1        | Laparoscopy / 10  |
| Introduction sleeve 10 mm WL 80 mm      | 8389.991    | 1        | Laparoscopy / 10  |
| Needle holder Ø 5 mm bndl               | 8393.502    | 1        | Laparoscopy / 11  |



### **BASIC SET LEVD**

#### LAPAROSCOPIC SINGLE-CHANNEL VARICOCELE DISSECTION

| Product  | Product no. | Quantity | Catalog / Section |
|--|-------------|----------|-------------------|
| OR endoscope bndl                                  | 8920.4011   | 1        | Laparoscopy / 2   |
| Perforated basket for telescope                    | 38008       |          | Laparoscopy / 2   |
| Fiber light cable bndl                             | 806625231   | 1        | Laparoscopy / 2   |
| Trocar sleeve, straight, capacity 5.5 mm WL 102 mm | 8919.353    | 1        | Laparoscopy / 3   |
| Optional:  |             |          |                   |
| Trocar tip blunt size 5.5 mm WL 144 mm             | 8919.3511   | 1        | Laparoscopy / 3   |
| Trocar tip sharp size 5.5 mm WL 144 mm             | 8919.3512   | 1        | Laparoscopy / 3   |
| Trocar tip triangular size 5.5 mm WL 144 mm        | 8919.3513   | 1        | Laparoscopy / 3   |
| ERAGONmodular mini                                 | '           |          |                   |
| Universal grasping forceps Ø 3.5 mm bndl           | 83912097    | 1        | Laparoscopy / 4   |
| Atraumatic grasping forceps Ø 3.5 mm bndl          | 83912087    | 1        | Laparoscopy / 4   |
| Babcock forceps Ø 3.5 mm bndl                      | 83912107    | 1        | Laparoscopy / 4   |
| Dissector forceps mono Ø 3.5 mm bndl               | 83912077    | 1        | Laparoscopy / 4   |
| Hook scissors mono Ø 3.5 mm bndl                   | 83912277    | 1        | Laparoscopy / 4   |
| Metzenbaum scissors mono Ø 3.5 mm bndl             | 83912247    | 1        | Laparoscopy / 4   |
| Connection cable                                   | ·           |          |                   |
| Bipolar HF cable                                   | 8108        | 1        | Laparoscopy / 13  |
| Monopolar HF cable                                 | 8106        | 1        | Laparoscopy / 13  |



### BASIC SET MINI E-MILOS

| Product  | Product no. | Quantity | Catalog / Section |  |  |
|--|-------------|----------|-------------------|--|--|
| Telescope 30° Ø 10 mm WL 307 mm                    | 8934.432    | 1        | Laparoscopy / 2   |  |  |
| Light tube for MILOS method Ø 10 mm                | 893420      | 1        | Laparoscopy / 2   |  |  |
| Trocar sleeve, straight, capacity 3.5 mm WL 100 mm | 8903.014    | 2        | Laparoscopy / 3   |  |  |
| Trocar tip blunt size 3.5 mm WL 169 mm             | 8903.103    | 2        | Laparoscopy / 3   |  |  |
| ERAGONmodular mini                                 |             |          |                   |  |  |
| Handle, pistol-shaped, mono                        | 83930073    | 4        | Laparoscopy / 4   |  |  |
| Sheath tube insulated Ø 3.5 mm SL 330 mm           | 8391933     | 4        | Laparoscopy / 4   |  |  |
| Dissector forceps insert Ø 3.5 mm                  | 8391222     | 1        | Laparoscopy / 4   |  |  |
| Metzenbaum scissors insert Ø 3.5 mm                | 8391215     | 1        | Laparoscopy / 4   |  |  |
| Grasping forceps insert Ø 3.5 mm                   | 8391208     | 2        | Laparoscopy / 4   |  |  |
| Electrode  | '           |          |                   |  |  |
| Hook electrode mono Ø 3.5 mm WL 310 mm             | 8379.452    | 1        | Laparoscopy / 7   |  |  |
| ERAGONstitch                                       |             |          |                   |  |  |
| Needle holder insert Ø 3.5 mm                      | 8391506     | 1        | Laparoscopy / 11  |  |  |
| Sheath tube Ø 3.5 mm SL 330 mm                     | 8391533     | 1        | Laparoscopy / 11  |  |  |
| Needle holder handle, axial                        | 8393943     | 1        | Laparoscopy / 11  |  |  |



## BASIC SET E-MILOS

| Product  | Product no. | Quantity | Catalog / Section |
|--|-------------|----------|-------------------|
| Telescope 30° Ø 10 mm WL 307 mm                    | 8934.432    | 1        | Laparoscopy / 2   |
| Light tube for MILOS method Ø 10 mm                | 893420      | 1        | Laparoscopy / 2   |
| Trocar sleeve, straight, capacity 5.5 mm WL 100 mm | 8921.014    | 2        | Laparoscopy / 3   |
| Trocar tip blunt size 5.5 mm WL 169 mm             | 8921.103    | 2        | Laparoscopy / 3   |
| ERAGONmodular                                      |             |          |                   |
| Handle, pistol-shaped, mono                        | 83930073    | 4        | Laparoscopy / 4   |
| Sheath tube insulated Ø 5 mm SL 330 mm             | 8391933     | 4        | Laparoscopy / 4   |
| Dissector forceps insert Ø 5 mm                    | 8393240     | 1        | Laparoscopy / 4   |
| Metzenbaum scissors insert Ø 5 mm                  | 8393.041    | 1        | Laparoscopy / 4   |
| Grasping forceps insert Ø 5 mm                     | 8393.181    | 2        | Laparoscopy / 4   |
| Electrode  |             |          |                   |
| Hook electrode mono Ø 5 mm WL 340 mm               | 8383.423    | 1        | Laparoscopy / 7   |
| ERAGONstitch                                       |             |          |                   |
| Needle holder insert Ø 5 mm                        | 8393508     | 1        | Laparoscopy /11   |
| Sheath tube Ø 5 mm SL 330 mm                       | 8393533     | 1        | Laparoscopy / 11  |
| Needle holder handle, axial                        | 8393943     | 1        | Laparoscopy / 11  |

### **BASIC SET**

#### LAPAROSCOPIC BARIATRIC SURGERY

| Product   | Product no. | Quantity | Catalog / Section |
|---|-------------|----------|-------------------|
| Telescope 0° Ø 10 mm WL 305 mm                        | 8934461     | 1        | Laparoscopy / 2   |
| Telescope 30° Ø 10 mm WL 305 mm                       | 8934462     | 1        | Laparoscopy / 2   |
| Fiber light cable bndl                                | 806550231   | 1        | Laparoscopy / 2   |
| Trocar sleeve, straight, capacity 5.5 mm WL 150 mm    | 8921.016    | 3        | Laparoscopy / 3   |
| Trocar sleeve, straight, capacity 10 mm WL 150 mm     | 8923.016    | 1        | Laparoscopy / 3   |
| Trocar sleeve, straight, capacity 12.5 mm WL 150 mm   | 8924.016    | 1        | Laparoscopy / 3   |
| Optional:   |             |          |                   |
| Trocar tip sharp size 5.5 mm                          | 8921.115    | 3        | Laparoscopy / 3   |
| Trocar tip sharp size 10 mm                           | 8923.115    | 1        | Laparoscopy / 3   |
| Trocar tip sharp size 12.7 mm                         | 8924.115    | 1        | Laparoscopy / 3   |
| Reducing adapter                                      | 8923.802    | 1        | Laparoscopy / 3   |
| Multifunctional suction irrigation system             |             |          |                   |
| Suction irrigation tube Ø 5 mm WL 450 mm              | 8384.911    | 1        | Laparoscopy / 8   |
| Suction irrigation handle                             | 8385.901    | 1        | Laparoscopy / 8   |
| Sealing cap   | 8385.902    | 1        | Laparoscopy / 8   |
| Suction irrigation tube set with piercing spike L 3 m | 4170.956    | 1        | Laparoscopy / 8   |
| ERAGONmodular   |             |          |                   |
| Atraumatic grasping forceps mono Ø 5 mm bndl          | 83941817    | 1        | Laparoscopy / 4   |
| Dissector forceps mono Ø 5 mm bndl                    | 83942407    | 1        | Laparoscopy / 4   |
| Metzenbaum scissors mono Ø 5 mm bndl                  | 83940417    | 1        | Laparoscopy / 4   |
| Atraumatic Grasping forceps Ø 5 mm bndl               | 83942297    | 1        | Laparoscopy / 4   |
| Biopsy forceps mono Ø 5 mm bndl                       | 83940917    | 1        | Laparoscopy / 4   |
| Atraumatic Grasping forceps Ø 5 mm bndl               | 83942507    | 1        | Laparoscopy / 4   |
| Stapler head grasping forceps Ø 10 mm bndl            | 83976558    | 1        | Laparoscopy / 4   |
| Plate-shaped grasping forceps Ø 10 mm bndl            | 83962347    | 1        | Laparoscopy / 4   |
| Babcock forceps Ø 10 mm bndl                          | 83961877    | 1        | Laparoscopy / 4   |
| ERAGONbipolar   |             |          |                   |
| Maryland dissector bipo Ø 5.5 mm bndl                 | 839400322   | 1        | Laparoscopy / 6   |
| Metzenbaum scissors bipo Ø 5.5 mm bndl                | 839400412   | 1        | Laparoscopy / 6   |
| Electrode   |             |          |                   |
| Hook electrode mono Ø 5 mm WL 420 mm                  | 8384.423    | 1        | Laparoscopy / 7   |




### **BASIC SET**

#### LAPAROSCOPIC BARIATRIC SURGERY

| Product   | Product no. | Quantity | Catalog / Section |  |  |
|---|-------------|----------|-------------------|--|--|
| Clip applicator Ø 10 mm WL 340 mm                                 | 8389.911    | 1        | Laparoscopy / 10  |  |  |
| Ethicon® Ligaclips® (PACK= 108 PCS)                               | 8389.915    | 1        | Laparoscopy / 10  |  |  |
| Needle holder Ø 5 mm bndl with carbide insert                     | 8394.502    | 1        | Laparoscopy / 11  |  |  |
| Needle holder Ø 5 mm bndl curved to the right with carbide insert | 8394.511    | 1        | Laparoscopy / 11  |  |  |
| Needle forceps Ø 2.45 mm WL 160 mm                                | 8756.201    | 1        | Laparoscopy / 11  |  |  |
| Sealing cone Ø 12–15 mm   | 8943.915    | 1        | Laparoscopy / 11  |  |  |
| Sealing cone Ø 10–12 mm   | 8934.915    | 1        | Laparoscopy / 11  |  |  |
| VERES cannula Ø 2.1 mm WL 120 mm                                  | 8302.12     | 1        | Laparoscopy / 3   |  |  |
| Handle, axial, mono   | 83930084    | 1        | Laparoscopy / 4   |  |  |
| Rotatable knob  | 8988        | 1        | Laparoscopy / 4   |  |  |
| Connection cable  |             |          |                   |  |  |
| Mono HF connection cable L 3 m                                    | 8106.033    | 1        | Laparoscopy / 13  |  |  |
| Bipo HF connection cable L 3 m                                    | 8108.132    | 1        | Laparoscopy / 13  |  |  |

### MINI FIBER TELESCOPES 2.0 MM

spirit of excellence




| Long version   | Direction of view    | WL                  | TL                  | Ø           | Product no.             |
|--|----------------------|---------------------|---------------------|-------------|-------------------------|
| Telescope 0° Ø 2 mm NL 268 mm  | 0°                   | 268 mm              | 365 mm              | 2.0 mm      | 8754.401                |
| for this:  |                      |                     |                     |             |                         |
| VERES cannula Ø 2.3 mm WL 250 mm consisting of:  1x VERES cannula Ø 2.3 mm WL 274 mm (8754.21)  1x outer sheath Ø 2.8 mm, WL 250 mm (8754.221) | ,                    | 250 mm              |                     | 2.3 mm      | 8754.201                |
|  |                      |                     |                     |             |                         |
| Short version  | Direction of<br>view | WL                  | TL                  | Ø           | Product no.             |
| Short version  Telescope 0° Ø 2 mm NL 158 mm   |                      | <b>WL</b><br>158 mm | <b>TL</b><br>255 mm | Ø<br>2.0 mm | Product no.<br>8754.451 |
|  | view                 |                     | · ·                 |             |                         |

| Recommended accessories   |                              | Product no. |
|---|------------------------------|-------------|
| Perforated basket for standard telescope 1 (for telescope 8754.451)   | (W x H x D) 297 x 54 x 59 mm | 38015       |
| Perforated basket for standard telescope 2 (for telescope 8754.401)   | (W x H x D) 481 x 54 x 59 mm | 38016       |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long         | 806625231   |


V124 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

#### LAPAROSCOPES 3.5 MM



| Recommended accessories   |                              | Product no. |
|---|------------------------------|-------------|
| Perforated basket for standard telescope 1 (for telescope 8930.461/.462)  | (W x H x D) 297 x 54 x 59 mm | 38015       |
| Perforated basket for standard telescope 2 (for telescope 8930.421/.422)  | (W x H x D) 481 x 54 x 59 mm | 38016       |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long         | 806625231   |

#### LAPAROSCOPES 5.3 MM



| Recommended accessories   |                              | Product no. |
|---|------------------------------|-------------|
| Perforated basket for standard telescope 2  | (W x H x D) 481 x 54 x 59 mm | 38016       |
| Fiber light cable bndl consisting of: Fiber light cable (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long         | 806625231   |



VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

### MINI OR LAPAROSCOPE 5.5 MM WITH 3.5 MM WORKING CHANNEL



| OR endoscope bndl consisting of: OR endoscope 0° Ø 5.5 mm SL 215 mm (8920.401) Autom. sealing element ID 5.7 mm (8920.311) Sealing cap, red-orange (15176.020) Sealing membrane Ø 17 mm (PACK= 10 PCS) (89.103) |  | of view | SL     | TL     | Ø      | channel Ø | Product no. |
|---|--|---------|--------|--------|--------|-----------|-------------|
|   | consisting of:  OR endoscope 0° Ø 5.5 mm SL 215 mm (8920.401)  Autom. sealing element ID 5.7 mm (8920.311)  Sealing cap, red-orange (15176.020)  Sealing membrane Ø 17 mm (PACK= 10 PCS) | 0°      | 215 mm | 370 mm | 5.5 mm | 3.5 mm    | 8920.4011   |

| Recommended accessories   |                      | Product no. |
|---|----------------------|-------------|
| Trocar sleeve, straight, capacity 5.5 mm WL 62 mm   | -                    | 8919.333    |
| Trocar sleeve, straight, capacity 5.5 mm WL 102 mm  |                      | 8919.353    |
| Perforated basket for telescope Dimensions (W x L x H): 132 x 467 x 75 mm   |                      | 38008       |
| Fiber light cable bndl consisting of: Fiber light cable (80663523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 3.5 mm, 2.3 m long | 806635231   |

PANOVIEW ULTRA

PANOVIEW ULTRA


Telescope Ø 5.5 mm WL 430 mm

Telescope Ø 5.5 mm WL 430 mm





spirit of excellence



| Recommended accessories   |                              | Product no. |
|---|------------------------------|-------------|
| Perforated basket for standard telescope 2 (for telescope 8935416/8935426)  | (W x H x D) 481 x 54 x 59 mm | 38016       |
| Perforated basket for standard telescope 3<br>(for telescope 89354416/89354426)   | (W x H x D) 619 x 54 x 59 mm | 38017       |
| Fiber light cable bndl consisting of: Fiber light cable (80663523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 3.5 mm, 2.3 m long         | 806635231   |

0°

30°


430 mm

89354416

89354426

VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

#### LAPAROSCOPES 10 MM




| PANOVIEW Telescope 0° Ø 10 mm WL 307 mm          | 0°  | 307 mm | 375 mm |       | 8934.431  |
|--|-----|--------|--------|-------|-----------|
| PANOVIEW Telescope 30° Ø 10 mm WL 307 mm         | 30° | 307 mm | 375 mm |       | 8934.432  |
| PANOVIEW Telescope 50° Ø 10 mm WL 310 mm         | 50° | 310 mm | 378 mm | 10 mm | 8934.433  |
| PANOVIEW PLUS<br>Telescope 25° Ø 10 mm WL 438 mm | 25° | 438 mm | 507 mm |       | 8934.4424 |
| PANOVIEW PLUS<br>Telescope 50° Ø 10 mm WL 447 mm | 50° | 447 mm | 516 mm |       | 8934.4434 |

| Recommended accessories   |                              | Product no. |
|---|------------------------------|-------------|
| Perforated basket for standard telescope 2 (for telescope 8934.431/.432/.433)   | (W x H x D) 481 x 54 x 59 mm | 38016       |
| Perforated basket for standard telescope 3 (for telescope 8934.4424/.4434)  | (W x H x D) 619 x 54 x 59 mm | 38017       |
| Fiber lightcable bndl consisting of: Fiber light cable Ø 5 mm TL 2.3 m (80665023), projector-side adapter (8095.07), and endoscope-side adapter (809509)          | Ø 5.0 mm, 2.3 m long         | 806650231   |
| Fusion  Fiber light cable bndl consisting of: Fiber light cable Ø 5 mm TL 2.3 m (80655023), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 5.0 mm, 2.3 m long         | 806550231   |

#### 3D ENDOSCOPE 10 MM

3D endoscope 30° Ø 10 mm WL 435 mm



| Recommended accessories  |                                | Product no. |
|--|--------------------------------|-------------|
| Perforated basket for 3D telescope   | (W x H x D): 583 x 200 x 80 mm | 38014       |
| Fusion  Fiber light cable bndl consisting of:  Fiber light cable Ø 5 mm TL 2.3 m (80d adapter (8095.07), and endoscope-sid | <br>Ø 5.0 mm, 2.3 m long       | 806550231   |

435 mm

501 mm

30°


89344632



VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

#### SURGICAL LAPAROSCOPE 10 MM

#### FOR ONE HOLE APPENDECTOMY



| Recommended accessories   |                      | Product no. |
|---|----------------------|-------------|
| Universal perforated basket 4 (W x H x D): 538 x 117 x 250 mm   | - CE                 | 33004       |
| for this: Instrument mat for perforated basket  |                      | 33001       |
| Fiber light cable bndl consisting of: Fiber light cable Ø 5 mm TL 2.3 m (80655023), projector-side adapter (8095.07), and endoscope-side adapter (809509)           | Ø 5.0 mm, 2.3 m long | 806650231   |
| Fusion  Fiber light cable bndl consisting of:  Fiber light cable Ø 5 mm TL 2.3 m (80655023),  projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 5.0 mm, 2.3 m long | 806550231   |

PANDVIEW
TELESCOPES 10 MM



## OPTIMIZED FOR 4K UHD AND ICG/NIR APPLICATION SHORT VERSION




Note: Compatible with System green (see Imaging Catalog) (ICG/NIR-capable) and its recommended Fusion fiber light cable

| Recommended accessories  |                              | Product no. |
|--|------------------------------|-------------|
| Perforated basket for standard telescope 2   | (W x H x D) 481 x 54 x 59 mm | 38016       |
| Fiber lightcable bndl consisting of: Fiber light cable $\varnothing$ 5 mm TL 2.3 m (80665023), projector-side adapter (8095.07), and endoscope-side adapter (809509)         | Ø 5.0 mm, 2.3 m long         | 806650231   |
| Fusion fiber light cable bndI consisting of: Fiber light cable $\varnothing$ 5 mm TL 2.3 m (80655023), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 5.0 mm, 2.3 m long         | 806550231   |



## OPTIMIZED FOR 4K UHD AND ICG/NIR APPLICATION LONG VERSION



Note: Compatible with System green (see Imaging Catalog) (ICG/NIR-capable) and its recommended Fusion fiber light cable

| Recommended accessories  |                              | Product no. |
|--|------------------------------|-------------|
| Perforated basket for standard telescope 3   | (W x H x D) 619 x 54 x 59 mm | 38017       |
| Fiber lightcable bndl consisting of: Fiber light cable Ø 5 mm TL 2.3 m (80665023), projector-side adapter (8095.07), and endoscope-side adapter (809509)           | Ø 5.0 mm, 2.3 m long         | 806650231   |
| Fusion  Fiber light cable bndl consisting of: Fiber light cable Ø 5 mm TL 2.3 m (80655023), projector-side adapter (8095.07), and endoscope-side adapter (8095.09) | Ø 5.0 mm, 2.3 m long         | 806550231   |




## WOLF

spirit of excellence

#### LIGHT TUBE FOR MILOS METHOD

(MINI LESS OPEN SUBLAY METHOD)




| Recommended accessories  |                      | Product no. |
|--|----------------------|-------------|
| Fiber light cable bndl consisting of: Fiber light cable $\emptyset$ 5 mm, TL 2.3 m (80665023), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 5.0 mm, 2.3 m long | 806650231   |
| Fusion  Fiber light cable bndl consisting of:  Fiber light cable Ø 5 mm, TL 2.3 m (80655023),  projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 5.0 mm, 2.3 m long | 806550231   |
| Sealing cap, sulfur yellow, cap. 1.3 mm  |                      | 8934201     |



### LAPAROSCOPES

#### **ACCESSORIES**

|                 |   | Product no. |
|-----------------|---|-------------|
| Sterile adapter | immersible and autoclavable for changing telescopes | 8580.91     |





#### TROCAR SLEEVES 2.2 / 2.5 MM

spirit of excellence

|   | Tip triangular  Trocar tip triangular Size 2.2 mm |          |             |          |
|---|---|----------|-------------|----------|
| Plastic sheath tube with thread                                     | WL  | Capacity | Product no. | WL 82 mm |
| Trocar sleeve capacity 2.2 mm WL 60 mm with universal sealing valve | 60 mm   | 2.2 mm   | 8309.072    | 8309.121 |

| Trocar sleeve with insufflation connector | 8     |          |             | Tip triangular  Trocar tip triangular Size 2.2 mm |
|---|-------|----------|-------------|---|
| Stainless steel sheath tube, smooth       | WL    | Capacity | Product no. | WL 82 mm  |
| Trocar sleeve capacity 2.5 mm WL 55 mm    | 55 mm | 2.5 mm   | 8309.012    | 8309.121  |
|   |       |          |             | WL 119 mm   |
| Trocar sleeve capacity 2.5 mm WL 95 mm    | 95 mm | 2.5 mm   | 8309.014    | 8309.123  |

| Accessories                                   | Product no. |
|---|-------------|
| Rubber cap capacity 0.8 mm (PACK= 10 PCS) red | 88.01       |



#### TROCAR SLEEVES 3.5 MM

#### WITH INSUFFLATION STOPCOCK

| RIWO-ART trocar sleeves with magnetic ball valve with insufflation stopcock |        |          | Tip<br>tapered/blunt | Tip<br>triangular                  |   |
|---|--------|----------|----------------------|------------------------------------|---|
|   |        |          |                      | Trocar tip<br>blunt<br>Size 3.5 mm | Trocar tip<br>triangular<br>Size 3.5 mm |
| Stainless steel sheath tube, smooth   | WL     | Capacity | Product no.          | WL 169 mm                          | WL 169 mm                               |
| Trocar sleeve straight capacity 3.5 mm WL 100 mm                            | 100 mm | 3.5 mm   | 8903.014             | 8903.103                           | 8903.123                                |
| Plastic sheath tube with thread   |        |          |                      |                                    |   |
| Trocar sleeve straight capacity 3.5 mm WL 100 mm                            | 100 mm | 3.5 mm   | 8903.034             | 8903.103                           | 8903.123                                |
|   |        |          |                      | WL 129 mm                          | WL 129 mm                               |
| Trocar sleeve slanted capacity 3.5 mm WL 60 mm                              | 60 mm  | 3.5 mm   | 8903.072             | 8903.101                           | 8903.121                                |

| Accessories   | Product no. |
|---|-------------|
| Spare ball capacity 5.5 mm  | 8921.901    |
| Spare O rings capacity 3.5 mm (PACK= 10 PCS), capacity Ø 3.5–5.5 mm | 8921.951    |
| Sealing cap capacity 2.4–3.4 mm (PACK= 10 PCS) red                  | 89.01       |
| Stopcock insert bndl cap. 3.0 mm (PACK= 5 PCS)                      | 896.0002    |

| Trocar sleeve with membrane valve               | Tip<br>tapered/blunt               |          |             |           |
|---|------------------------------------|----------|-------------|-----------|
|   | Trocar tip<br>blunt<br>Size 3.5 mm |          |             |           |
| Plastic sheath tube with distal screw anchor    | WL                                 | Capacity | Product no. | WL 169 mm |
| Trocar sleeve straight capacity 3.5 mm WL 40 mm | 40 mm                              | 3.5 mm   | 8929.223    | 8903.103  |



#### TROCAR SLEEVES 5.5 MM

| RIWO-ART trocar sleeves with magnetic ball valve with insufflation stopcock |        | To the second se |             | Tip tapered/blunt  Trocar tip blunt Size 5.5 mm | Tip tapered/pointed  Trocar tip pointed Size 5.5 mm | Tip triangular  Trocar tip triangular Size 5.5 mm |
|---|--------|--|-------------|---|---|---|
| Stainless steel sheath tube   | WL     | Capacity   | Product no. | WL 169 mm                                       | WL 169 mm   | WL 169 mm   |
| Trocar sleeve straight capacity 5.5 mm WL 100 mm smooth                     | 100 mm | 5.5 mm   | 8921.014    | 8921.103  | 8921.113  | 8921.123  |
| Trocar sleeve slanted capacity 5.5 mm WL 100 mm smooth                      | 100 mm | 5.5 mm   | 8921.013    | 8921.103  | 8921.113  | 8921.123  |
| Trocar sleeve straight capacity 5.5 mm WL 100 mm with thread                | 100 mm | 5.5 mm   | 8921.024    | 8921.103  | 8921.113  | 8921.123  |
| Trocar sleeve slanted capacity 5.5 mm WL 100 mm with thread                 | 100 mm | 5.5 mm   | 8921.023    | 8921.103  | 8921.113  | 8921.123  |
| Plastic tube Trocar sleeve straight capacity 5.5 mm WL 100 mm with thread   | 100 mm | 5.5 mm   | 8921.034    | 8921.103  | 8921.113  | 8921.123  |
|   |        |  |             | WL 219 mm                                       | WL 219 mm   | WL 219 mm   |
| Trocar sleeve straight capacity 5.5 mm WL 150 mm smooth                     | 150 mm | 5.5 mm   | 8921.016    | 8921.105  | 8921.115  | 8921.125  |
| Trocar sleeve straight capacity 5.5 mm WL 150 mm with thread                | 150 mm | 5.5 mm   | 8921.026    | 8921.105  | 8921.115  | 8921.125  |

| Accessories   | Product no. |
|---|-------------|
| Spare ball capacity 5.5 mm  | 8921.901    |
| Spare O rings capacity 3.5 mm (PACK= 10 PCS), capacity Ø 3.5–5.5 mm | 8921.951    |
| Sealing cap capacity 3.4-5.1 mm (PACK= 10 PCS) blue                 | 89.02       |
| Stopcock insert bndl cap. 3.0 mm (PACK= 5 PCS)                      | 896.0002    |

#### TROCAR SLEEVES 5.5 MM

spirit of excellence

VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.


| RIWO-ART trocar sleeves<br>with magnetic ball valve                      |                  |          |             | Tip<br>tapered/blunt               | Tip<br>tapered/<br>pointed           | Tip<br>triangular                       |
|--|------------------|----------|-------------|------------------------------------|--------------------------------------|---|
|  | US 5 5<br>971.44 |          |             | Trocar tip<br>blunt<br>Size 5.5 mm | Trocar tip<br>pointed<br>Size 5.5 mm | Trocar tip<br>triangular<br>Size 5.5 mm |
| Stainless steel sheath tube  | WL               | Capacity | Product no. | WL 129 mm                          | WL 129 mm                            | WL 129 mm                               |
| Trocar sleeve straight capacity 5.5 mm WL 60 mm smooth                   | 60 mm            | 5.5 mm   | 8921.052    | 8921.101                           | 8921.111                             | 8921.121                                |
| Trocar sleeve slanted capacity 5.5 mm WL 60 mm smooth                    | 60 mm            | 5.5 mm   | 8921.051    | 8921.101                           | 8921.111                             | 8921.121                                |
| Trocar sleeve straight capacity 5.5 mm WL 60 mm with thread              | 60 mm            | 5.5 mm   | 8921.062    | 8921.101                           | 8921.111                             | 8921.121                                |
| Trocar sleeve slanted capacity 5.5 mm WL 60 mm with thread               | 60 mm            | 5.5 mm   | 8921.061    | 8921.101                           | 8921.111                             | 8921.121                                |
| Plastic tube Trocar sleeve straight capacity 5.5 mm WL 60 mm with thread | 60 mm            | 5.5 mm   | 8921.072    | 8921.101                           | 8921.111                             | 8921.121                                |
|  |                  |          |             | WL 169 mm                          | WL 169 mm                            | WL 169 mm                               |
| Trocar sleeve straight capacity 5.5 mm WL 100 mm smooth                  | 100 mm           | 5.5 mm   | 8921.054    | 8921.103                           | 8921.113                             | 8921.123                                |
| Trocar sleeve straight capacity 5.5 mm WL 100 mm with thread             | 100 mm           | 5.5 mm   | 8921.053    | 8921.103                           | 8921.113                             | 8921.123                                |

| Accessories   | Product no. |
|---|-------------|
| Spare ball capacity 5.5 mm  | 8921.901    |
| Spare O rings capacity 3.5 mm (PACK= 10 PCS), capacity Ø 3.5–5.5 mm | 8921.951    |
| Sealing cap capacity 3.4–5.1 mm (PACK= 10 PCS) blue                 | 89.02       |




#### **TROTEC** TROCAR WITH AUTOMATIC PROTECTIVE FUNCTION


FOR TROCAR SLEEVES 5.5 MM




| Accessories    | Product no. |
|----------------|-------------|
| Protective cap | 8923.991    |



Protective tip automatically pushes back into the cannula through contact with the abdominal wall



The protective tip advances into the free abdomen immediately after penetration of the peritoneum



The atraumatic protective tip in a far distal position prevents perforation of organs and vessels

## 

#### spirit of excellence

#### TROCAR SLEEVE 5.5 MM/5.8 MM

PLASTIC WITH SEALING MEMBRANE

Tip Tip Tip tapered/blunt tapered/pointed triangular AUTOGLAVE 134° C / 273° F Trocar tip Trocar tip Trocar tip blunt pointed triangular Size 5.5 mm Size 5.5 mm Size 5.5 mm Flexible plastic with WL Capacity Product no. WL 104 mm WL 104 mm WL 104 mm sheath tube with thread stopcock 8919.333 Trocar sleeve straight 62 mm 5.5 mm 8919.3311 8919.3312 8919.3313 capacity 5.5 mm WL 62 mm with membrane valve 8919.331 WL 144 mm WL 144 mm WL 144 mm 8919.353 Trocar sleeve straight 102 mm 8919.3512 capacity 5.5 mm WL 102 mm 5.5 mm 8919.3511 8919.3513 with membrane valve 8919.351 Tip for curved instruments Tip tapered/blunt tapered/pointed triangular tapered/blunt Trocar tip Trocar tip Trocar tip Trocar tip AUTOGLAVE blunt pointed triangular blunt 134° C / 273° F Size 5.5 mm Size 5.5 mm Size 5.5 mm Size 5.5 mm Flexible plastic Capacity Product no. WL 80 mm WL WL 80 mm WL 80 mm WL 80 mm sheath tube with thread Trocar sleeve straight capacity 5.8 mm WL 5.8 mm 8905.331 8905.3311 8905.3312 8905.3313 8905.3315 62 mm 62 mm with membrane valve WL 120 mm WL 120 mm WL 120 mm WL 120 mm Trocar sleeve straight capacity 5.8 mm WL 102 mm 5.8 mm 8905.3515 8905.3511 8905.3512 8905.3513 8905.3515 102 mm

| Accessories                                     | Product no. |
|---|-------------|
| Sealing membrane Ø 17 mm, yellow (PACK= 10 PCS) | 89.103      |
| Stopcock insert bndl cap 3.0 mm (PACK= 5 PCS)   | 896.0002    |

with membrane valve



#### TROCAR SLEEVE 5.7 MM/7 MM/10 MM/12.5 MM

## FLEXIBLE PLASTIC SHEATH TUBE



|  | Tip tapered/blunt  Trocar tip blunt |          |             |                       |
|--|-------------------------------------|----------|-------------|-----------------------|
| Ribbed flexible plastic sheath tube                                  | WL                                  | Capacity | Product no. | Size 7.3 mm/TL 108 mm |
| Trocar sleeve flexible capacity 7 mm WL 74 mm with universal seal    | 74 mm                               | 7 mm     | 8906.001    | 8913.11               |
|  |                                     |          |             | Size 10 mm/TL 85 mm   |
| Trocar sleeve flexible capacity 10 mm WL 56 mm with universal seal   | 56 mm                               | 10 mm    | 8906.011    | 8906.111              |
|  | Size 12.5 mm/TL 86 mm               |          |             |                       |
| Trocar sleeve flexible capacity 12.5 mm WL 57 mm with universal seal | 57 mm                               | 12.5 mm  | 8906.031    | 8906.131              |

### TROCAR SLEEVE 10 MM

#### WITH INSUFFLATION STOPCOCK


| RIWO-ART trocar sleeves<br>with magnetic ball valve         |        | R. GIOLF<br>6723.014 |             | Tip<br>tapered/blunt              | Tip tapered/pointed                 | Tip<br>triangular                      |
|---|--------|----------------------|-------------|-----------------------------------|-------------------------------------|--|
|   |        |                      |             | Trocar tip<br>blunt<br>Size 10 mm | Trocar tip<br>pointed<br>Size 10 mm | Trocar tip<br>triangular<br>Size 10 mm |
| Stainless steel sheath tube                                 | WL     | Capacity             | Product no. | WL 164 mm                         | WL 164 mm                           | WL 164 mm                              |
| Trocar sleeve straight capacity 10 mm WL 100 mm             | 100 mm | 10 mm                | 8923.014    | 8923.103                          | 8923.113                            | 8923.123                               |
| Trocar sleeve slanted capacity 10 mm WL 100 mm              | 100 mm | 10 mm                | 8923.013    | 8923.103                          | 8923.113                            | 8923.123                               |
| Trocar sleeve straight capacity 10 mm WL 100 mm with thread | 100 mm | 10 mm                | 8923.024    | 8923.103                          | 8923.113                            | 8923.123                               |
| Trocar sleeve slanted capacity 10 mm WL 100 mm with thread  | 100 mm | 10 mm                | 8923.023    | 8923.103                          | 8923.113                            | 8923.123                               |
|   | ·      |                      |             | WL 214 mm                         | WL 214 mm                           | WL 214 mm                              |
| Trocar sleeve straight capacity 10 mm WL 150 mm             | 150 mm | 10 mm                | 8923.016    | -                                 | 8923.115                            | 8923.125                               |
| Trocar sleeve straight capacity 10 mm WL 150 mm with thread | 150 mm | 10 mm                | 8923.026    | -                                 | 8923.115                            | 8923.125                               |

| Accessories  | Product no. |
|--|-------------|
| Spare ball capacity 7 mm   | 8923901     |
| Spare O rings capacity 7 mm (PACK= 10 PCS), capacity Ø 7–12.5 mm | 8923951     |
| Sealing cap capacity 9.5–10.1 mm (PACK= 10 PCS) red              | 8908        |
| Stopcock insert bndl cap. 3.0 mm (PACK= 5 PCS)                   | 896.0002    |




## TROTEC TROCAR WITH AUTOMATIC PROTECTIVE FUNCTION


FOR TROCAR SLEEVES 10 MM




| Accessories    | Product no. |
|----------------|-------------|
| Protective cap | 8923.991    |



Protective tip automatically pushes back into the cannula through contact with the abdominal wall



The protective tip advances into the free abdomen immediately after penetration of the peritoneum



The atraumatic protective tip in a far distal position prevents perforation of organs and vessels

VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

#### HIGH FLOW TROCAR SLEEVE 10 MM

#### WITH CONNECTOR FOR HIGH FLOW INSUFFLATION TUBE

| RIWO-ART trocar sleeves with magnetic ball valve |        | 0        | 3042  | Tip<br>tapered/blunt              | Tip<br>tapered/pointed              | Tip<br>triangular                      |
|--|--------|----------|---|-----------------------------------|-------------------------------------|--|
|  |        |          |   | Trocar tip<br>blunt<br>Size 10 mm | Trocar tip<br>pointed<br>Size 10 mm | Trocar tip<br>triangular<br>Size 10 mm |
| Stainless steel sheath tube                      | WL     | Capacity | Product no.                                   | WL 164 mm                         | WL 164 mm                           | WL 164 mm                              |
| Trocar sleeve straight capacity 10 mm WL 100 mm  | 100 mm | 10 mm    | 8923.042                                      | 8923.103                          | 8923.113                            | 8923.123                               |
| for this:  |        |          |   |                                   |                                     | Product no.                            |
| Reducing adapter<br>(PACK= 5 PCS)                | 810    |          | for reduction f<br>Ø 7 mm,Ø 10<br>to Ø 5.5 mm | from<br>) mm, and Ø 12.5 mm       | ı                                   | 8923802                                |

| Accessories  | Product no. |
|--|-------------|
| Spare ball capacity 7 mm   | 8923901     |
| Spare O rings capacity 7 mm (PACK= 10 PCS), capacity Ø 7–12.5 mm | 8923951     |
| Sealing cap capacity 9.5–10.1 mm (PACK= 10 PCS) red              | 8908        |



#### TROCAR SLEEVE 12.5 MM

#### WITH INSUFFLATION STOPCOCK


| RIWO-ART trocar sleeves<br>with magnetic ball valve           |   |        | R.WOLF<br>6723.014 |   | Tip<br>tapered/blunt   | Tip<br>tapered/pointed                | Tip<br>triangular                        |
|---|---|--------|--------------------|---|--|---------------------------------------|--|
|   |   |        |                    |   | Trocar tip<br>blunt<br>Size 12.7 mm                              | Trocar tip<br>pointed<br>Size 12.7 mm | Trocar tip<br>triangular<br>Size 12.7 mm |
| Stainless steel sheath tube                                   |   | WL     | Capacity           | Product no.                             | WL 164 mm  | WL 164 mm                             | WL 164 mm                                |
| Trocar sleeve straight capacity 12.5 mm<br>WL 100 mm          | c | 100 mm | 12.5 mm            | 8924.014                                | 8924.103   | 8924.113                              | 8924.123                                 |
| Trocar sleeve slanted capacity 12.5 mm WL 100 mm              | c | 100 mm | 12.5 mm            | 8924.013                                | 8924.103   | 8924.113                              | 8924.123                                 |
|   |   |        |                    |   | WL 214 mm  | WL 214 mm                             | WL 214 mm                                |
| Trocar sleeve straight capacity 12.5 mm WL 150 mm with thread |   | 150 mm | 12.5 mm            | 8924.026                                | -  | 8924.115                              | 8924.125                                 |
| Trocar sleeve straight<br>capacity 12.5 mm<br>WL 150 mm       | c | 150 mm | 12.5 mm            | 8924.016                                | -  | 8924.115                              | 8924.125                                 |
| for this:   |   |        |                    |   |  |                                       |  |
| Reducing adapter  |   |        |                    |   | for reduction from Ø 10 mm to Ø 5.5 mm and Ø 12.5 mm to Ø 5.5 mm |                                       | 8923.802                                 |
| (PACK= 5 PCS)   |   |        |                    | for reduction from Ø 12.5 mm to Ø 10 mm |  |                                       | 8924.802                                 |

| Accessories  | Product no. |
|--|-------------|
| Spare ball capacity 7 mm   | 8923.901    |
| Spare O rings capacity 7 mm (PACK= 10 PCS), capacity Ø 7–12.5 mm | 8923.951    |
| Sealing cap capacity 9.5–10.1 mm (PACK= 10 PCS) red              | 89.08       |
| Stopcock insert bndl cap. 3.0 mm (PACK= 5 PCS)                   | 896.0002    |


V124 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

## TROTEC TROCAR WITH AUTOMATIC PROTECTIVE FUNCTION


FOR TROCAR SLEEVES 12.5 MM




| Accessories    | Product no. |
|----------------|-------------|
| Protective cap | 8923.991    |



Protective tip automatically pushes back into the cannula through contact with the abdominal wall



The protective tip advances into the free abdomen immediately after penetration of the peritoneum




The atraumatic protective tip in a far distal position prevents perforation of organs and vessels



### **DILATATION AND EXTRACTION INSTRUMENTS**


5.5 TO 10/10 TO 12.5 MM




| Incision<br>widening | Guide rod                           | Trocar sleeve<br>slanted                        | Dilatation<br>sleeve                       | Instrument<br>sleeve | Reducing<br>sleeve                 |
|----------------------|-------------------------------------|---|--|----------------------|------------------------------------|
| 3.5 mm < 5.5 mm      | -                                   | <b>8921.013</b><br>capacity 5.5 mm WL<br>100 mm |  |                      | <b>8383.78</b> Size 5 mm L 155 mm  |
| 5.5 mm < 10 mm       | <b>8923.921</b><br>5.5 mm TL 500 mm | <b>8923.013</b> capacity 10 mm WL 100 mm        | <b>8923.931</b><br>Size 10 mm WL<br>170 mm | 8385.50              |                                    |
| 5.0 mm < 10 mm       | <b>8934.951</b><br>5 mm TL 500 mm   |   | <b>8934.95</b><br>Size 10 mm WL<br>172 mm  | 10 mm WL 170 mm      |                                    |
| 10 mm < 12.5 mm      |                                     | 8924.013  |  |                      | <b>8941.901</b><br>12 mm WL 180 mm |
| 5.5 mm < 12.5 mm     |                                     | capacity 12.5 mm WL<br>100 mm                   |  |                      | <b>8941.951</b><br>12 mm WL 180 mm |
| 10 mm < 15 mm        | <b>8943.901</b><br>10 mm TL 500 mm  |   |  |                      |                                    |



## REDUCING SLEEVES FOR RIWO-ART TROCAR SLEEVES





V124 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.



| Accessories   | Product no. |
|---|-------------|
| Sealing cap capacity 3.4–5.1 mm (PACK= 10 PCS) blue | 89.02       |
| Sealing cap capacity 9.5–10.1 mm (PACK= 10 PCS) red | 8908        |







| Accessories                                    | Product no. |
|--|-------------|
| Stopcock insert bndl cap. 3.0 mm (PACK= 5 PCS) | 896.0002    |






#### THE LAPAROSCOPIC TOOLBOX


#### The toolbox principle

**ERAGON modular** allows the surgeon to create their ideal laparoscopic set. Ergonomic handles, diameters relevant to all medical practice, useful working lengths, and a range of jaw sections can be combined as necessary. This universal compatibility also ensures that individual trays can comprise fewer instruments – for more efficiency and one way of cutting costs









VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# **ERAGON** micro Ø 2 MM, INSULATED

|   |             | Handle                             | e, axial                           |
|---|-------------|------------------------------------|------------------------------------|
| ERAGON axial  |             |                                    |                                    |
| All jaw inserts and sheath tubes can also bined with <b>ERAGONaxial</b> | be com-     | without lock,<br>with HF connector | without lock,<br>with HF connector |
| Rotatable knob  | Product no. | 83930083                           | 83930084                           |
| 2 Fritting  | 8988        | •                                  | •                                  |

| Jaw insert                                   |      |             | Sheath tube, Ø 2.0 mm, insulated | Handle, pistol-shaped          | Complete instrument                    |
|--|------|-------------|----------------------------------|--------------------------------|--|
| JL JL  |      |             |                                  | 65                             | Jaw insert with sheath tube     Handle |
|  |      |             | WL<br>240 mm                     | without lock,<br>with HF, mono | -                                      |
|  | JL*  | Product no. |                                  | 83930073                       | Product no.                            |
| Scissors<br>mono Ø 2 mm bndl                 | 7 mm | 8388200     | •                                | •                              | 83882007                               |
| Dissector forceps<br>mono Ø 2 mm bndl        | 7 mm | 8388201     | •                                | •                              | 83882017                               |
| Atraumatic grasping forceps mono Ø 2 mm bndl | 7 mm | 8388202     | •                                | •                              | 83882027                               |

 $<sup>^{*}</sup>$  JL = jaw length when jaw section closed (approximate measurements) HF connection cable: see sheet BDE116/117



### ERAGON micro Ø 2 MM, INSULATED

| Jaw insert                           |      |             | Sheath tube, Ø 2.0 mm,<br>insulated | Handle, pistol-shaped       | Complete instrument                |
|--------------------------------------|------|-------------|-------------------------------------|-----------------------------|------------------------------------|
| JL ,                                 |      |             |                                     | 3                           | Jaw insert with sheath tube Handle |
|                                      |      |             | WL<br>240 mm                        | with lock,<br>with HF, mono |                                    |
|                                      | JL*  | Product no. |                                     | 83930074                    | Product no.                        |
| Grasping forceps<br>mono Ø 2 mm bndl | 7 mm | 8388203     | •                                   | •                           | 83882037                           |

 $<sup>^{\</sup>ast}$  JL = jaw length when jaw section closed (approximate measurements) HF connection cable: see sheet BDE116/117

| Accessories for manual and machine reprocess | Accessories for manual and machine reprocessing |        |  |  |  |
|--|---|--------|--|--|--|
|  | Irrigation adapter<br>Ø 9 mm, length 64 mm      | 163502 |  |  |  |

# **ERAGON** mini Ø 3.5 MM, INSULATED

|   |             | Handle                             | e, axial                           |  |
|---|-------------|------------------------------------|------------------------------------|--|
| ERAGON axial  |             |                                    |                                    |  |
| All jaw inserts and sheath tubes can also bined with <b>ERAGONaxial</b> | be com-     | without lock,<br>with HF connector | without lock,<br>with HF connector |  |
| Rotatable knob  | Product no. | 83930083                           | 83930084                           |  |
| 2 PHOLE   | 8988        | •                                  | •                                  |  |

| Jaw insert                              |          | Sheath tube<br>insu | e, Ø 3.5 mm,<br>lated | Handle, pistol-shaped | Complete instrument         |  |
|---|----------|---------------------|-----------------------|-----------------------|-----------------------------|--|
| R.WOLF                                  |          |                     |                       |                       | <b>3</b>                    | Jaw insert with sheath tube     Handle |
|   | '        |                     | WL<br>240 mm          | WL<br>330 mm          | with lock,<br>with HF, mono |  |
|   | JL*      | Product no.         | 8390933               | 8391933               | 83930074                    | Product no.                            |
| Dissector forceps<br>mono Ø 3.5 mm bndl | 15 mm    | 8390207             | •                     |                       | •                           | 83902077                               |
| curved to the left, double-action       | 1311111  | 8391207             |                       | •                     | •                           | 83912077                               |
| Dissector forceps<br>mono Ø 3.5 mm bndl | l 18 mm  | 8390221             | •                     |                       | •                           | 83902217                               |
| long, fine tip,<br>double-action        | 1011111  | 8391221             |                       | •                     | •                           | 83912217                               |
| Dissector forceps<br>mono Ø 3.5 mm bndl | 14 mm    | 8390222             | •                     |                       | •                           | 83902227                               |
| short, fine tip, double-action          | (4111111 | 8391222             |                       | •                     | •                           | 83912227                               |
| Dissector forceps mono Ø 3.5 mm bndl    | 14 mm    | 8390223             | •                     |                       | •                           | 83902237                               |
| angled, double-action                   | 14111111 | 8391223             |                       | •                     | •                           | 83912237                               |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)

HF connection cable: see sheet BDE116/117



# **ERAGON** mini Ø 3.5 MM, INSULATED

| Jaw insert                                 |          |             |              | Sheath tube, Ø 3.5 mm, insulated |                                | stol-shaped                 | Complete instrument                             |  |
|--|----------|-------------|--------------|----------------------------------|--------------------------------|-----------------------------|---|--|
| JL   | R.WOLF   |             |              | -                                | 3                              | Ó                           | • Jaw insert<br>with sheath<br>tube<br>• Handle |  |
|  | <b>—</b> |             | WL<br>240 mm | WL<br>330 mm                     | without lock,<br>with HF, mono | with lock,<br>with HF, mono |   |  |
|  | JL*      | Product no. | 8390933      | 8391933                          | 83930073                       | 83930074                    | Product no.                                     |  |
| Metzenbaum scissors<br>mono Ø 3.5 mm bndl  |          | 8390215     | •            |                                  | •                              |                             | 83902157  |  |
| R.WOLF double-action                       | 16 mm    | 8391215     |              | •                                | •                              |                             | 83912157  |  |
| Metzenbaum scissors<br>mono Ø 3.5 mm bndl  |          | 8390224     | •            |                                  | ٠                              |                             | 83902247  |  |
| fine-toothed, curved, double-action        | 14 mm    | 8391224     |              | •                                | •                              |                             | 83912247  |  |
| Hook scissors<br>mono Ø 3.5 mm bndl        | 0        | 8390227     | •            |                                  | •                              |                             | 83902277  |  |
| R.WOLF single-action                       | 8 mm     | 8391227     |              | •                                | •                              |                             | 83912277  |  |
| Double spoon forceps<br>mono Ø 3.5 mm bndl | 10       | 8390216     | •            |                                  |                                | •                           | 83902167  |  |
| R.Walf                                     | 12 mm    | 8391216     |              | •                                |                                | •                           | 83912167  |  |
| Friedel punch<br>mono Ø 3.5 mm bndl        | 10       | 8390217     | •            |                                  |                                | •                           | 83902177  |  |
| R.WOLF                                     | 10 mm    | 8391217     |              | •                                |                                | •                           | 83912177  |  |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)

HF connection cable: see sheet BDE116/117

| Accessories for manual and machine reprocess | Product no.                                |        |
|--|--|--------|
|  | Irrigation adapter<br>Ø 9 mm, length 64 mm | 163502 |

### **ERAGON** minir Ø 3.5 MM, UNINSULATED

|  |             | Handle                          | e, axial                                       |  |
|--|-------------|---------------------------------|--|--|
| ERAGON axial   |             |                                 |  |  |
| All jaw inserts and sheath tubes can also<br>bined with <b>ERAGONaxial</b> | be com-     | with lock, without HF connector | with lock, without HF connector, not rotatable |  |
| Rotatable knob   | Product no. | 83930082                        | not rotatable                                  |  |
| P. Wate  | 8988        | •                               |  |  |

| Jaw insert                                   |           |             | Sheath tube, Ø 3.5 mm, uninsulated |              | Handle, pistol-shaped    | Complete instrument                            |  |
|--|-----------|-------------|------------------------------------|--------------|--------------------------|--|--|
|  |           |             | -                                  | -            | 3                        | Jaw insert     with sheath     tube     Handle |  |
|  |           |             | WL<br>240 mm                       | WL<br>330 mm | with lock,<br>without HF |  |  |
|  | JL*       | Product no. | 8390934                            | 8391934      | 83930072                 | Product no.                                    |  |
| Atraumatic grasping forceps<br>Ø 3.5 mm bndl | 14 mm     | 8390208     | •                                  |              | •                        | 83902087                                       |  |
| fenestrated, double-action                   | 14111111  | 8391208     |                                    | •            | •                        | 83912087                                       |  |
| Atraumatic grasping forceps<br>Ø 3.5 mm bndl | 17 mm     | 8390218     | •                                  |              | •                        | 83902187                                       |  |
| fenestrated, single-action                   | 17 111111 | 8391218     |                                    | •            | •                        | 83912187                                       |  |
| Atraumatic grasping forceps<br>Ø 3.5 mm bndl | 17 mm     | 8390225     | •                                  |              | •                        | 83902257                                       |  |
| double fenestrated, curved, single-action    | 17 111111 | 8391225     |                                    | •            | •                        | 83912257                                       |  |
| Atraumatic grasping forceps<br>Ø 3.5 mm bndl | 19 mm     | 8390226     | •                                  |              | •                        | 83902267                                       |  |
| fenestrated, double-action                   | 17        | 8391226     |                                    | •            | •                        | 83912267                                       |  |

 $<sup>^{*}</sup>$  JL = jaw length when jaw section closed (approximate measurements) HF connection cable: see sheet BDE116/117

BDE46



### ERAGON modular $\emptyset$ 3.5 MM, UNINSULATED

spirit of excellence

| Jaw insert                                  |           |             | Sheath tube, Ø 3.5 mm, uninsulated |              | Handle, pistol-shaped                          | Complete instrument |
|---|-----------|-------------|------------------------------------|--------------|--|---------------------|
| JL  | OLF       | -           | -                                  | 3            | Jaw insert     with sheath     tube     Handle |                     |
|   |           |             | WL<br>240 mm                       | WL<br>330 mm | with lock,<br>without HF                       |                     |
|   | JL*       | Product no. | 8390934                            | 8391934      | 83930072                                       | Product no.         |
| Grasping forceps<br>Ø 3.5 mm bndl           | 12 mm     | 8390219     | •                                  |              | •  | 83902197            |
| fenestrated, double-action                  | 13 mm     | 8391219     |                                    | •            | •  | 83912197            |
| Grasping forceps<br>Ø 3.5 mm bndl           | 17 mm     | 8390220     | •                                  |              | •  | 83902207            |
| fenestrated, single-action                  | 17 111111 | 8391220     |                                    | •            | •  | 83912207            |
| Universal grasping forceps<br>Ø 3.5 mm bndl | 14 mm     | 8390209     | •                                  |              | •  | 83902097            |
| double-action                               | 14 111111 | 8391209     |                                    | •            | •  | 83912097            |
| Babcock forceps<br>Ø 3.5 mm bndl            | 19 mm     | 8390210     | •                                  |              | •  | 83902107            |
| double-action                               | 17111111  | 8391210     |                                    | •            | •  | 83912107            |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements) HF connection cable: see sheet BDE116/117

| Accessories for manual and machine reprocess | ing  | Product no. |
|--|--|-------------|
|  | Irrigation adapter<br>Ø 9 mm, length 64 mm | 163503      |



### **ERAGON** modular

### Ø 5.0 MM, INSULATED

|                   |             | Handle, axial |                                    |                                    |                             |  |  |  |
|-------------------|-------------|---------------|------------------------------------|------------------------------------|-----------------------------|--|--|--|
| ERAGON axial      |             | -             |                                    |                                    |                             |  |  |  |
| with  ERAGONaxial |             |               | without lock,<br>with HF connector | without lock,<br>with HF connector | with lock,<br>not rotatable |  |  |  |
| Rotatable knob    | Product no. | 83930082      | 83930083                           | 83930084                           | 83930085                    |  |  |  |
| 2 IF WOLF         | 8988        | •             | •                                  | •                                  |                             |  |  |  |

| Jaw insert   |       |             | Sheath tube, Ø 5 | .0 mm, insulated | Handle, pistol-shaped       | Complete instrument                                |  |
|--|-------|-------------|------------------|------------------|-----------------------------|--|--|
| JL   |       |             | -                |                  | 33                          | • Jaw insert<br>with<br>sheath<br>tube<br>• Handle |  |
|  | '     |             | SL<br>330 mm     | SL<br>450 mm     | with lock,<br>with HF, mono |  |  |
|  | JL*   | Product no. | 8393933          | 8394933          | 83930074                    | Product no.  |  |
| Maryland dissector forceps<br>mono Ø 5 mm bndl   |       | 8393.281    | •                |                  | •                           | 83932817   |  |
| curved,<br>with fine cross toothing,<br>double-action  | 21 mm | 8394.281    |                  | •                | •                           | 83942817   |  |
| Mixter dissector forceps mono Ø 5 mm bndl  R.WOLF  angled, fine, pyramid-shaped toothing, double-action        | 22 mm | 8393.283    | •                |                  | •                           | 83932837   |  |
| Grasping forceps, mono Ø 5 mm bndl  R.WOLF  fenestrated, with fine cross toothing, 15 mm long, sin- gle-action | 21 mm | 8393.185    | •                |                  | •                           | 83931857   |  |
| Grasping forceps, mono<br>Ø 5 mm bndl  |       | 8393.184    | •                |                  | •                           | 83931847   |  |
| fenestrated, with fine cross<br>toothing, 20 mm long, sin-<br>gle-action                                       | 26 mm | 8394.184    |                  | •                | •                           | 83941847   |  |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)

HF connection cable: see sheet BDE116/117

# **ER GON** modular Ø 5.0 MM, INSULATED

| Jaw insert  |           | Sheath tube, Ø 5.0 mm, insulated |              | Handle, pistol-shaped |              |                          | Complete instrument            |   |             |
|---|-----------|----------------------------------|--------------|-----------------------|--------------|--------------------------|--------------------------------|---|-------------|
| JL  |           |                                  |              |                       | ठि           | 8                        | Ø5                             | Jaw insert<br>with<br>sheath<br>tube     Handle |             |
|   |           |                                  | SL<br>260 mm | SL<br>330 mm          | SL<br>450 mm | with lock,<br>without HF | without lock,<br>with HF, mono | with lock,<br>with HF, mono                     |             |
|   | JL*       | Product no.                      | 8392933      | 8393933               | 8394933      | 83930072                 | 83930073                       | 83930074  | Product no. |
| Dolphin dissector forceps mono Ø 5 mm bndl  angled, with fine cross-toothing, with channel, narrow, 15 mm long, double-action | 17 mm     | 8393.285                         |              | •                     |              |                          | •                              |   | 83932857    |
| Dissector forceps mono Ø 5 mm bndl R.WDLF  fine pyramid-shaped toothing, narrow, 18 mm, double-action                         | 23 mm     | 8393.289                         |              | •                     |              |                          |                                | •   | 83932897    |
| Atraumatic grasping forceps Ø 5 mm bndl  Channel with wavy tooth edge, 20 mm, single-action                                   | 26 mm     | 8393.292                         |              | •                     |              | •                        |                                |   | 83932925    |
| Atraumatic grasping forceps Ø 5 mm bndl   | 26 mm     | 8393.293                         |              | •                     |              | •                        |                                |   | 83932935    |
| Channel<br>with wavy tooth edge,<br>20 mm, double-action  | 20 111111 | 8394.293                         |              |                       | •            | •                        |                                |   | 83942935    |
| Grasping forceps, mono Ø 5 mm bndl  R.WOLF  fine, pyramid-shaped toothing, narrow double-action                               | 19 mm     | 8393.288                         |              | •                     |              |                          |                                | •   | 83932887    |
| Atraumatic grasping forceps<br>mono Ø 5 mm bndl   |           | 8392.181                         | •            |                       |              |                          |                                | •   | 83921817    |
| R.WOLF fenestrated,   | 19 mm     | 8393.181                         |              | •                     |              |                          |                                | •   | 83931817    |
| with cross toothing,<br>double-action   |           | 8394.181                         |              |                       | •            |                          |                                | •   | 83941817    |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)

HF connection cable: see sheet BDE116/117

## **ERAGON** modular

### Ø 5.0 MM, INSULATED

|   |             | Handle, axial |                                    |  |                           |  |
|---|-------------|---------------|------------------------------------|--|---------------------------|--|
| ERAGON <sub>axial</sub>   |             | -             |                                    |  |                           |  |
| All jaw inserts and sheath tubes can also be combined with<br>ERAGONaxial |             | with lock     | without lock,<br>with HF connector | without lock,<br>with HF connector with lock,<br>not rotatab |                           |  |
| Rotatable knob  | Product no. | 83930082      | 83930083                           | 83930084   | not rotatable<br>83930085 |  |
| 2 IF WOLF   | 8988        | •             | •                                  | •  |                           |  |

| Jaw insert  |          |              | Sheath tube, Ø 5.0 mm, insulated |                          | Handle, pis                    | Complete instrument Jaw insert with sheath tube Handle |             |
|---|----------|--------------|----------------------------------|--------------------------|--------------------------------|--|-------------|
| R.WOLF  |          |              |                                  |                          | क क                            |  |             |
|   |          | SL<br>330 mm | SL<br>450 mm                     | with lock,<br>without HF | without lock,<br>with HF, mono |  |             |
|   | JL*      | Product no.  | 8393933                          | 8394933                  | 83930072                       | 83930073   | Product no. |
| Atraumatic grasping forceps<br>mono Ø 5 mm bndl   | 18 mm    | 8393.195     | •                                |                          |                                | •  | 83931957    |
| smooth, double-action   |          | 8394.195     |                                  | •                        |                                | •  | 83941957    |
| Babcock forceps Ø 5 mm bndl  R:WOLF  Gripping surface with fine cross toothing, double-action | 24<br>mm | 8393.186     | •                                |                          | •                              |  | 83931867    |
| Babcock forceps<br>Ø 5 mm bndl  | 26 mm    | 8393.187     | •                                |                          | •                              |  | 83931877    |
| large distal gripping surface<br>with fine cross toothing,<br>double-action                   |          | 8394.187     |                                  | •                        | •                              |  | 83941877    |
| Debakey forceps Ø 5 mm bndl  atraumatic clamp, double-action                                  | 39<br>mm | 8393190      | •                                |                          | •                              |  | 83931907    |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)

HF connection cable: see sheet BDFdxX6071710

# Ø 5.0 MM, INSULATED

#### Complete Jaw insert Sheath tube, Ø 5.0 mm, insulated Handle, pistol-shaped instrument Jaw insert with sheath tube • Handle SL SL with lock. with lock. 330 mm 450 mm without HF with HF, mono **Product** JL\* 8393933 8394933 83930072 83930074 Product no. no. Debakey forceps Ø 5 mm bndl R.WOLF 48 mm 8393191 83931917 atraumatic clamp, double-action Grasping forceps, mono Ø 5 mm bndl R.WOLF 17 mm 8393.485 83934857 with a row of teeth, double-action Grasping forceps, mono Ø 5 mm bndl R.WOLF 19 mm 8393.486 83934867 with one tooth, fine cross toothing, narrow, double-action Grasping forceps, mono Ø 5 mm bndl R.WOLF 17 mm 8393.487 83934877 with two teeth, fine cross toothing, single-action **Grasping forceps** Ø 5 mm bndl 8393.490 83934907 R.WOLF 26 mm with two teeth 83944907 8394.490 wavy gripping surface, double-action Petelin dissector forceps mono Ø 5 mm bndl R.WOLF ■ 17 mm 8393.282 83932827 angled $30^{\circ}$ to the left, with cross toothing, single-action

HF connection cable: see sheet BDE116/117

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)

## **ERAGON** modular

### $\emptyset$ 5.0 MM, INSULATED

|   |             | Handle, axial |                                    |  |                           |  |
|---|-------------|---------------|------------------------------------|--|---------------------------|--|
| ERAGON <sub>axial</sub>   |             | -             |                                    |  |                           |  |
| All jaw inserts and sheath tubes can also be combined with<br>ERAGONaxial |             | with lock     | without lock,<br>with HF connector | without lock,<br>with HF connector with lock,<br>not rotatab |                           |  |
| Rotatable knob  | Product no. | 83930082      | 83930083                           | 83930084   | not rotatable<br>83930085 |  |
| 2 IF WOLF   | 8988        | •             | •                                  | •  |                           |  |

| Jaw insert  |          |             | Sheath tube, Ø 5.0 mm, insulated | Handle, pistol-shaped    |                                | Complete instrument         |   |  |
|---|----------|-------------|----------------------------------|--------------------------|--------------------------------|-----------------------------|---|--|
| R.WOLF  |          |             |                                  | Ø,                       | 65                             | Ø,                          | Jaw insert<br>with<br>sheath<br>tube     Handle |  |
|   |          |             | SL<br>330 mm                     | with lock,<br>without HF | without lock,<br>with HF, mono | with lock,<br>with HF, mono |   |  |
|   | JL*      | Product no. | 8393933                          | 83930072                 | 83930073                       | 83930074                    | Product no.                                     |  |
| Plate-shaped grasping forceps mono Ø 5 mm bndl  RWOLF fenestrated with fine cross toothing, double-action | 18 mm    | 8393.182    | •                                |                          |                                |                             | 83931827  |  |
| Grasping forceps mono Ø 5 mm bndl  R.WOLF  with cross toothing, double-action                             | 21<br>mm | 8393.183    | •                                |                          | •                              |                             | 83931837  |  |
| Grasping forceps mono Ø 5 mm bndl R.WOLF  distal cross toothing with channel, double-action               | 15 mm    | 8393.287    | •                                |                          | •                              |                             | 83932877  |  |
| Claw grasping forceps Ø 5 mm bndl R.WOLF  double-action   | 27<br>mm | 8393.494    | •                                | •                        |                                |                             | 83934945  |  |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)

HF connection cable: see sheet BDE116/117



## **ERAGON** modular

### Ø 5.0 MM, INSULATED

| Jaw insert  | Jaw insert |             | Sheath tube, Ø 5    | .0 mm, insulated | Har                      | ndle, pistol-sha               | ped                         | Complete instrument                    |
|---|------------|-------------|---------------------|------------------|--------------------------|--------------------------------|-----------------------------|--|
| JL  | R.WOLF     |             | -(                  |                  | 05                       | 65                             | Ø5                          | Jaw insert with sheath tube     Handle |
|   |            |             | SL SL 330 mm 450 mm |                  | with lock,<br>without HF | without lock,<br>with HF, mono | with lock,<br>with HF, mono | 0                                      |
|   | JL*        | Product no. | 8393933             | 8394933          | 83930072                 | 83930073                       | 83930074                    | Product no.                            |
| Myoma grasping forceps<br>Ø 5 mm bndl  R.WOLF  2x3-claw, single-action                                      | 29 mm      | 8393.488    | •                   |                  | •                        |                                |                             | 83934887                               |
| Universal grasping forceps mono Ø 5 mm bndl  with pyramid-shaped toothing and cross toothing, double-action | 18 mm      | 8393.481    |                     |                  |                          |                                | •                           | 83934817                               |
| Universal grasping forceps Ø 5 mm bndl  RUDLF  pyramid-shaped toothing and cross toothing, double-action    | 26 mm      | 8393.482    | •                   |                  | •                        |                                |                             | 83934827                               |
| Grasping forceps mono Ø 5 mm bndl  Pike-mouth, double-action  | 20 mm      | 8393.483    | •                   |                  |                          |                                | •                           | 83934837                               |
| Biopsy forceps<br>mono Ø 5 mm bndl  | 10         | 8393.091    | •                   |                  |                          | •                              |                             | 83930917                               |
| with spikes,<br>double-action   | 13 mm      | 8394.091    |                     | •                |                          | •                              |                             | 83940917                               |
| Biopsy forceps<br>mono Ø 5 mm bndl  | 14 -       | 8393.092    | •                   |                  |                          | •                              |                             | 83930927                               |
| severing, single-action   | 14 mm      | 8394.092    |                     | •                |                          | •                              |                             | 83940927                               |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)

# ER/GON modular

### Ø 5.0 MM, INSULATED

|   |             |           | Handle                             | e, axial                           |                             |
|---|-------------|-----------|------------------------------------|------------------------------------|-----------------------------|
| ERAGON axial  | aambinad    |           | -                                  |                                    |                             |
| All jaw inserts and sheath tubes can also be with ERAGONaxial | combined    | with lock | without lock,<br>with HF connector | without lock,<br>with HF connector | with lock,<br>not rotatable |
| Rotatable knob  | Product no. | 83930082  | 83930083                           | 83930084                           | 83930085                    |
| 2 PAUDIE  | 8988        | •         | •                                  | •                                  |                             |

| Jaw insert   |       |             | Sheath tube, Ø 5 | .0 mm, insulated | Handle, pis              | stol-shaped  | Complete instrument |
|--|-------|-------------|------------------|------------------|--------------------------|--|---------------------|
| JL   |       | -(          |                  | \$30             | 80                       | • Jaw insert<br>with<br>sheath<br>tube<br>• Handle |                     |
|  |       |             | SL<br>330 mm     | SL<br>450 mm     | with lock,<br>without HF | without lock,<br>with HF, mono                     |                     |
|  | JL*   | Product no. | 8393933          | 8394933          | 83930072                 | 83930073   | Product no.         |
| Biopsy forceps mono Ø 5 mm bndl  R.WOLF  pointed spoon forceps, single-action                    | 20 mm | 8393.093    | •                |                  |                          | •  | 83930937            |
| Knot pusher<br>Ø 5 mm bndl<br>R.WOLF   |       | 8393.345    | •                |                  | •                        |  | 83933457            |
| with distal recess,<br>double-action   | 17 mm | 8394.345    |                  | •                | •                        |  | 83943457            |
| Grasping forceps Ø 5 mm bndl  spring jaw sections fenestrated with cross toothing, double-action | 37 mm | 8393.188    | •                |                  | •                        |  | 83931887            |
| Grasping forceps Ø 5 mm bndl   | 47 mm | 8393.189    | •                |                  | •                        |  | 83931897            |
| spring jaw sections fenestrated with cross toothing, double-action                               | 4/ mm | 8394.189    |                  | •                | •                        |  | 83941897            |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)



# **ERAGON** modular Ø 5.0 MM, INSULATED

#### Complete Jaw insert Sheath tube, $\emptyset$ 5.0 mm, insulated Handle, pistol-shaped instrument Jaw insert with sheath tube • Handle SL with lock. with lock. SL450 mm 330 mm without HF with HF, mono **Product** JL\* 8393933 8394933 83930072 83930074 Product no. no. Debakey forceps Ø 5 mm bndl R.WOLF 8393.291 83932917 atraumatic, spring jaw sections with cross toothing, double-action **Dissector forceps** mono Ø 5 mm bndl 8393192 83931927 **R.WOLF** 18 mm angled, 8394192 83941927 double-action Grasping forceps, mono Ø 5 mm bndl 8393193 83931937 16 mm 8394193 83941937 double-action Dissector forceps mono Ø 5 mm bndl 83931947 8393194 R.WOLF 8394194 83941947 double-action Dissector forceps mono Ø 5 mm bndl 8393197 83931977 R.WOLF 30 mm 83941977 8394197 double-action Dissector forceps mono Ø 5 mm bndl 8393198 83931987 **₹.WOLF** 33 mm 8394198 83941987 double-action

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)

# ERAGON modular

### $\emptyset$ 5.0 MM, INSULATED

|  |             | Handle, axial |                                    |                                    |                             |  |
|--|-------------|---------------|------------------------------------|------------------------------------|-----------------------------|--|
| ERAGON <sub>axial</sub>  |             |               | -                                  |                                    |                             |  |
| All jaw inserts and sheath tubes can also be with <b>ERAGONaxial</b> | e combined  | with lock     | without lock,<br>with HF connector | without lock,<br>with HF connector | with lock,<br>not rotatable |  |
| Rotatable knob   | Product no. | 83930082      | 83930083                           | 83930084                           | 83930085                    |  |
| 2 IF WOLF  | 8988        | •             | •                                  | •                                  |                             |  |

| Jaw insert  |          |             | Sheath tube, Ø 5 | .0 mm, insulated | Handle, pistol-shaped       | Complete instrument                                |
|---|----------|-------------|------------------|------------------|-----------------------------|--|
|   | JL JL    |             |                  |                  | E Company                   | • Jaw insert<br>with<br>sheath<br>tube<br>• Handle |
|   | <u> </u> |             | SL<br>330 mm     | SL<br>450 mm     | with lock,<br>with HF, mono |  |
|   | JL*      | Product no. | 8393933          | 8394933          | 83930074                    | Product no.  |
| Dissector forceps<br>mono Ø 5 mm bndl   | 20       | 8393199     | •                |                  | •                           | 83931997   |
| double-action   | 32 mm    | 8394199     |                  | •                | •                           | 83941997   |
| Dissector forceps<br>mono Ø 5 mm bndl   | 19 mm    | 8393200     | •                |                  | •                           | 83932007   |
| fine tip,<br>double-action  | 19       | 8394200     |                  | •                | •                           | 83942007   |
| Atraumatic grasping forceps mono Ø 5 mm bndl  R.WOLF atraumatic, with cross toothing, double-action | 16 mm    | 8393210     | •                |                  | •                           | 83932107   |
| Atraumatic grasping forceps<br>mono Ø 5 mm bndl   | 10       | 8393220     | •                |                  | •                           | 83932207   |
| atraumatic,<br>with cross toothing,<br>double-action  | 19mm     | 8394220     |                  | •                | •                           | 83942207   |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)



# **ERAGON** modular Ø 5.0 MM, INSULATED

#### spirit of excellence

| Jaw insert  |           |              | Sheath tube, Ø 5 | .0 mm, insulated | Handle, pis              | Handle, pistol-shaped       |                               |
|---|-----------|--------------|------------------|------------------|--------------------------|-----------------------------|-------------------------------|
|   | R.WOLF    |              | -(               |                  | <b>E</b>                 | <b>E</b>                    | • Jaw insert with sheath tube |
|   |           |              | SL<br>330 mm     | SL<br>450 mm     | with lock,<br>without HF | with lock,<br>with HF, mono |                               |
|   | JL*       | Product no.: | 8393933          | 8394933          | 83930072                 | 83930074                    | Product no.:                  |
| Atraumatic grasping forceps Ø 5 mm bndl   | 29 mm     | 8393223      | •                |                  | •                        |                             | 83932237                      |
| atraumatic, with pyramid-<br>shaped toothing and cross<br>toothing, double-action |           | 8394223      |                  | •                | •                        |                             | 83942237                      |
| Atraumatic grasping forceps<br>Ø 5 mm bndl  | 25 mm     | 8393250      | •                |                  | •                        |                             | 83932507                      |
| atraumatic,<br>single fenestrated with cross<br>toothing, double-action           | 25 mm     | 8394250      |                  | •                | •                        |                             | 83942507                      |
| Atraumatic grasping forceps<br>Ø 5 mm bndl  |           | 8393229      | •                |                  | •                        |                             | 83932297                      |
| atraumatic,<br>double fenestrated and curved<br>single-action                     | 02 111111 | 8394229      |                  | •                | •                        |                             | 83942297                      |
| Grasping forceps<br>Ø 5 mm bndl   | 15 mm     | 8393230      | •                |                  | •                        |                             | 83932307                      |
| atraumatic, narrow and rounded, double-action                                     | 13 111111 | 8394230      |                  | •                | •                        |                             | 83942307                      |
| Dissector forceps<br>mono Ø 5 mm bndl   | 19 mm     | 8393240      | •                |                  |                          | •                           | 83932407                      |
| curved,<br>double-action  | 17        | 8394240      |                  | •                |                          | •                           | 83942407                      |
| Dissector forceps<br>mono Ø 5 mm bndl   | 17 mm     | 8393242      | •                |                  | •                        |                             | 83932427                      |
| single fenestrated double-action  | 17 111111 | 8394242      |                  | •                | •                        |                             | 83942427                      |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)

VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# ERAGON modular

### Ø 5.0 MM, INSULATED

|  |             |           | Handle                             | e, axial                           |                             |
|--|-------------|-----------|------------------------------------|------------------------------------|-----------------------------|
| ERAGON axial   |             |           | -                                  |                                    |                             |
| All jaw inserts and sheath tubes can also be with<br>ERAGONaxial | e combined  | with lock | without lock,<br>with HF connector | without lock,<br>with HF connector | with lock,<br>not rotatable |
| Rotatable knob   | Product no. | 83930082  | 83930083                           | 83930084                           | 83930085                    |
| Z PUDIF  | 8988        | •         | •                                  | •                                  |                             |

| Jaw insert  | Jaw insert |             |              | .0 mm, insulated | Handle, pistol-shaped    |  | Complete instrument |
|---|------------|-------------|--------------|------------------|--------------------------|--|---------------------|
| R.WOLF  |            |             |              | क क              |                          | • Jaw insert<br>with<br>sheath<br>tube<br>• Handle |                     |
|   |            | Н           | SL<br>330 mm | SL<br>450 mm     | with lock,<br>without HF | with lock,<br>with HF, mono                        |                     |
|   | JL*        | Product no. | 8393933      | 8394933          | 83930072                 | 83930074   | Product no.         |
| Intestine grasping forceps Ø 5 mm bndl                                  | 20         | 8393249     | •            |                  | •                        |  | 83932497            |
| atraumatic,<br>single fenestrated with cross<br>toothing, double-action | 38 mm      | 8394249     |              | •                | •                        |  | 83942497            |
| Debakey forceps<br>mono Ø 5 mm bndl<br>curved,<br>double-action         | 35 mm      | 8393256     | •            |                  |                          | •  | 83932567            |
| Debakey forceps<br>mono Ø 5 mm bndl                                     | 47 mrs     | 8393258     | •            |                  |                          | •  | 83932587            |
| double-action   | 47 MM      | 8394258     |              | •                |                          | •  | 83942587            |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements) HF connection cable: see sheet BDE116/117



# **ERAGON** modular Ø 5.0 MM, INSULATED

| Jaw insert  | Jaw insert |             |                     | i.0 mm, insulated | Handle, pistol-shaped          | Complete instrument                                |
|---|------------|-------------|---------------------|-------------------|--------------------------------|--|
| Ju  | JL         |             | -                   |                   | 65                             | • Jaw insert<br>with<br>sheath<br>tube<br>• Handle |
|   |            |             | SL SL 330 mm 450 mm |                   | without lock,<br>with HF, mono |  |
|   | JL*        | Product no. | 8393933             | 8394933           | 83930073                       | Product no.  |
| Metzenbaum scissors<br>mono Ø 5 mm bndl                                   |            | 8393.041    | •                   |                   | •                              | 83930417   |
| R.WOLF  curved, double-action   | 23 mm      | 8394.041    |                     | •                 | •                              | 83940417   |
| Metzenbaum micro scissors mono Ø 5 mm bndl  R.WOLF  curved, double-action | 18 mm      | 8393.044    | •                   |                   | •                              | 83930447   |
| Scissors mono Ø 5 mm bndl  narrow, straight, double-action                | 20 mm      | 8393.045    |                     |                   | •                              | 83930457   |
| Hook scissors<br>mono Ø 5 mm bndl   | 14 mm      | 8393.081    | •                   |                   | •                              | 83930817   |
| serrated, single-action   | 14111111   | 8394.081    |                     | •                 | •                              | 83940817   |
| Metzenbaum micro scissors<br>mono Ø 5 mm bndl                             | 0.1        | 8393243     | •                   |                   | •                              | 83932437   |
| double-action   | 21 mm      | 8394243     |                     | •                 | •                              | 83942437   |
| Scissors<br>mono Ø 5 mm bndl  |            | 8393246     | •                   |                   | •                              | 83932467   |
| curved and toothed double-action  | 26 mm      | 8394246     |                     | •                 | •                              | 83942467   |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)

# **ERAGON** modular

### Ø 5.0 MM, INSULATED

|  | Handle, axial     |           |                                    |                                    |                             |
|--|-------------------|-----------|------------------------------------|------------------------------------|-----------------------------|
| ERAGON axial   | . a a malhi m a d |           | -                                  |                                    |                             |
| All jaw inserts and sheath tubes can also be with<br>ERAGONaxial | combined          | with lock | without lock,<br>with HF connector | without lock,<br>with HF connector | with lock,<br>not rotatable |
| Rotatable knob   | Product no.       | 83930082  | 83930083                           | 83930084                           | 83930085                    |
| 2 Princip  | 8988              | •         | •                                  | •                                  |                             |

| Jaw insert                           | Jaw insert |             |              | .0 mm, insulated | Handle, pis              | stol-shaped                    | Complete instrument                |
|--------------------------------------|------------|-------------|--------------|------------------|--------------------------|--------------------------------|------------------------------------|
| JL                                   |            |             | -            |                  | E S                      | 65                             | Jaw insert with sheath tube Handle |
|                                      | <u> </u>   |             | SL<br>330 mm | SL<br>450 mm     | with lock,<br>without HF | without lock,<br>with HF, mono |                                    |
|                                      | JL*        | Product no. | 8393933      | 8394933          | 83930072                 | 83930073                       | Product no.                        |
| Scissors<br>mono Ø 5 mm bndl         | 22 mm      | 8393248     | •            |                  |                          | •                              | 83932487                           |
| fine-toothed, fine tip double-action |            | 8394248     |              | •                |                          | •                              | 83942487                           |
| Knot pusher<br>Ø 5 mm bndl           | 1.7        | 8393.345    | •            |                  | •                        |                                | 83933457                           |
| with distal recess,<br>double-action | 17 mm      | 8394345     |              | •                | •                        |                                | 83943457                           |
| Gastric band manipulator Ø 5 mm bndl | 47         | 8393253     | •            |                  | •                        |                                | 83932537                           |
| 90° articulating with distal slot    | 47 mm      | 8394253     |              | •                | •                        |                                | 83942537                           |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)

| Accessories for manual and machine reprocess | Product no.                                |        |
|--|--|--------|
|  | Irrigation adapter<br>Ø 9 mm, length 64 mm | 163502 |



# **ERAGON** modu blades Ø 5.0 MM, INSULATED

|  |             | Handle, axial                      |
|--|-------------|------------------------------------|
| All jaw inserts and sheath tubes can also be combined with ERAGONaxial |             |                                    |
|  |             | without lock,<br>with HF connector |
| Rotatable knob   | Product no. | 83930083                           |
| 2 P. WOLZ  | 8988        | •                                  |

| Scissors attachme                         | Tension rod Ø 5.0 mm |         | Sheath tul       | oe insulated     | Ø 5.0 mm     | Handle<br>pistol-shaped | Complete instrument |   |  |
|---|----------------------|---------|------------------|------------------|--------------|-------------------------|---------------------|---|--|
|   |                      |         |                  |                  |              |                         |                     | 8   | Jaw insert with sheath tube     Handle |
|   |                      |         | for SL<br>330 mm | for SL<br>450 mm | SL<br>240 mm | SL<br>310 mm            | SL<br>430 mm        | without lock,<br>rotatable<br>with HF connector |  |
|   | Product no.          | 8392934 | 8393934          | 8394934          | 8392935      | 8393935                 | 8394935             | 83930073  | Product no.                            |
| Metzenbaum scissors<br>attachment<br>mono |                      | •       |                  |                  | •            |                         |                     | •   | 83920407                               |
|   | 4393040              |         | •                |                  |              | •                       |                     | •   | 83930407                               |
| (PACK= 10 PCS), sterile,<br>disposable    |                      |         |                  | •                |              |                         | •                   | •   | 83940407                               |



# **ER** GON modular

### Ø 10 MM, UNINSULATED

|   |   | Handle, axial |  |  |  |  |  |
|---|---|---------------|--|--|--|--|--|
| ER GONaxial   |   |               |  |  |  |  |  |
| All jaw inserts and sheath tubes can also bined with <b>ERAGONaxial</b> | inserts and sheath tubes can also be com-<br>vith <b>ERAGONaxia</b> l |               | with lock, without HF connector, not rotatable |  |  |  |  |
| Rotatable knob  | Product no.   | 83930082      | 83930085                                       |  |  |  |  |
| 2 Pillots   | 8988  | •             |  |  |  |  |  |

| Jaw insert                                 |           |             | Sheath tube<br>unins | , Ø 10.0 mm,<br>ulated | Handle, pistol-shaped    | Complete instrument                             |
|--|-----------|-------------|----------------------|------------------------|--------------------------|---|
| Tr wote                                    |           |             | 02                   | <b>5</b> -             | 76                       | • Jaw insert<br>with sheath<br>tube<br>• Handle |
| , JL                                       |           |             | SL<br>327 mm         | SL<br>447 mm           | with lock,<br>without HF |   |
|  | JL*       | Product no. | 8395902              | 8396902                | 83930072                 | Product no.                                     |
| Maryland dissector forceps<br>Ø 10 mm bndl | 2/ 22     | 8395.225    | •                    |                        | •                        | 83952257  |
| double-action                              | 36 mm     | 8396225     |                      | •                      | •                        | 83962257  |
| Dissector forceps<br>Ø 10 mm bndl          | 35 mm     | 8395.226    | •                    |                        | •                        | 83952268  |
| angled,<br>double-action                   | 33 111111 | 8396226     |                      | •                      | •                        | 83962267  |
| Grasping forceps<br>Ø 10 mm bndl           | 20 mm     | 8395.236    | •                    |                        | •                        | 83952368  |
| Pike-mouth double-action                   | 20 111111 | 8396236     |                      | •                      | •                        | 83962367  |
| Grasping forceps<br>Ø 10 mm bndl           | 49 mm     | 8395.204    | •                    |                        | •                        | 83952048  |
| 2/3 jaws<br>single-action                  | 47 111111 | 8396204     |                      | •                      | •                        | 83962047  |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)


# **ERAGON** modular


### Ø 10 MM, UNINSULATED


| Jaw insert   |           |             |              | tube, Ø 10<br>uninsulated |              | Handle, pis  | stol-shaped     | Complete instrument   |
|--|-----------|-------------|--------------|---------------------------|--------------|--------------|-----------------|---|
| JL.  |           |             | -            |                           |              | 3            |                 | <ul> <li>Jaw insert         with sheath         tube</li> <li>Handle</li> </ul> |
| - JL   |           |             | SL<br>327 mm | SL<br>447 mm              | SL<br>387 mm | with<br>with | lock,<br>out HF |   |
|  | JL*       | Product no. | 8395902      | 8396902                   | 8397902      | 83930072     | 83930082        | Product no.   |
| Claw grasping forceps Ø 10 mm bndl  double-action                              | 38 mm     | 8395.489    | •            |                           |              | •            |                 | 83954897  |
| Claw grasping forceps Ø 10 mm bndl with additional row of teeth, double-action | 38 mm     | 8395490     | •            |                           |              | •            |                 | 83954907  |
| Babcock forceps<br>Ø 10 mm bndl  | 42 mm     | 8395.187    | •            |                           |              | •            |                 | 83951877  |
| large distal gripping surface with fine cross toothing, double-action          | 42 111111 | 8396187     |              | •                         |              | •            |                 | 83961877  |
| Babcock forceps Ø 10 mm bndl  double-action                                    | 38<br>mm  | 8395.214    | •            |                           |              | •            |                 | 83952148  |
| Plate-shaped grasping forceps<br>Ø 10 mm bndl                                  | 50        | 8395.234    | •            |                           |              | •            |                 | 83952347  |
| double-action  | mm        | 8396234     |              | •                         |              | •            |                 | 83962347  |
| Spoon forceps<br>Ø 10 mm bndl<br>single-action                                 | 31<br>mm  | 8395.244    | •            |                           |              | •            |                 | 83952448  |
| Stapler head grasping forceps Ø 10 mm bndl  angled 30°, double-action          |           | 8397.655    |              |                           | •            |              | •               | 83976558  |

<sup>\*</sup>JL = jaw length when jaw section closed (approximate measurements)/HF connection cable: see sheet BDE116/117

# **ERAGON** modular ACCESSORIES







|               |   | Ø    | SL     | Product no. |
|---------------|---|------|--------|-------------|
| ERAGONmodular | Sheath tube insulated Ø 5 mm SL 330 mm with distal cm scale | 5 mm | 330 mm | 8393932     |
| R.WOLF        | Sheath tube insulated Ø 5 mm SL 450 mm with distal cm scale | 5 mm | 450 mm | 8394932     |



### HANDLE VARIANTS FOR MODULAR SYSTEMS

spirit of excellence

| Handle, pistol-shaped                                | rotatable | with lock | without lock | with HF | without HF | Product no. |
|--|-----------|-----------|--------------|---------|------------|-------------|
| E S  | •         | •         |              |         | •          | 83930072    |
| 36   | •         |           | •            | •       |            | 83930073    |
| 3  | •         | •         |              | •       |            | 83930074    |
| Handle, axial ERAGON axial                           | rotatable | with lock | without lock | with HF | without HF | Product no. |
|  | •         | •         |              |         | •          | 83930082    |
|  | •         |           | •            | •       |            | 83930083    |
|  | •         | •         |              | •       |            | 83930084    |
|  |           | •         |              |         | •          | 83930085    |
| Optional for 83930082/83930083/83930084: Product no. |           |           |              |         |            |             |


 Optional for 83930082/83930083/83930084:
 Product no.

 Rotatable knob autoclavable
 8988

All ERAGON modular components are compatible with ERAGON axial




# CHOLANGIOGRAPHY CATHETERGRASPING FORCEPS 5 MM



For inserting a cholangiography catheter up to 7 Fr into the cystic duct

# BIPOLAR FORCEPS 3.5 MM/5.0 MM WITH SPRING HANDLE MODULAR SYSTEM





| Accessories                | Product no. |
|----------------------------|-------------|
| RIWO rubber cap, jet black | 15220.019   |
| Luer sealing cap           | 15023.153   |

 $<sup>^{*}</sup>$  JL = jaw length when jaw section closed (approximate measurements) Bipolar connection cable: see sheet BDE118/119




V124 || Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with

your contact partner or directly with Richard Wolf GmbH.

### ERAGON bipolar

# MODULAR BIPOLAR INSTRUMENTS, 5.5 MM ROTATABLE




 $<sup>^{*}</sup>$  JL = jaw length when jaw section closed (approximate measurements) Bipolar connection cable: see sheet BDE118/119



### **ERAGON** bipolar

# MODULAR BIPOLAR INSTRUMENTS, 5.5 MM, ROTATABLE




 $<sup>^{*}</sup>$  JL = jaw length when jaw section closed (approximate measurements) Bipolar connection cable: see sheet BDE118/119



VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# ELECTRODES 2.0 MM/3.5 MM

MONOPOLAR




|  |         |        | 3379.452    |
|--|---------|--------|-------------|
|  | Outer Ø | WL     | Product no. |
| Hook electrode mono Ø 3.5 mm<br>WL 310 mm                                  | 3.5 mm  | 310 mm | 8379.452    |
| Hook electrode mono Ø 3.5 mm  WL 240 mm  with distally extended insulation | 3.5 mm  | 240 mm | 8785.642    |
| Needle electrode mono Ø 3.5 mm<br>WL 310 mm                                | 3.5 mm  | 310 mm | 8379.482    |
| Coagulation electrode mono Ø 3.5 mm<br>WL 310 mm                           | 3.5 mm  | 310 mm | 8379.462    |

# 

spirit of excellence

# ELECTRODES 5.0 MM

## MONOPOLAR




|  | (333,423) |        |             |  |
|--|-----------|--------|-------------|--|
|  | Outer Ø   | WL     | Product no. |  |
| Hook electrode mono Ø 5 mm<br>WL 340 mm    | F 0       | 340 mm | 8383.423    |  |
| Hook electrode mono Ø 5 mm<br>WL 420 mm    | 5.0 mm    | 420 mm | 8384.423    |  |
| Needle electrode mono Ø 5 mm WL 340 mm     | 5.0 mm    | 340 mm | 8383.426    |  |
| Spatula electrode mono Ø 5 mm<br>WL 340 mm | 5.0 mm    | 340 mm | 8383.428    |  |
| Myoma dissector mono Ø 5 mm<br>WL 340 mm   | 5.0 mm    | 340 mm | 8383429     |  |



#### MULTIFUNCTIONAL SUCTION IRRIGATION SYSTEM

#### **COMBINATION OPTIONS**



#### Suction or irrigation:

| Suction irrigation tube Ø 5 mm WL 310 mm        | 8383.911 |
|---|----------|
| Suction irrigation tube Ø 5 mm WL 450 mm        | 8384.911 |
| Suction irrigation tube Ø 3.5 mm WL 300 mm      | 8391.911 |
| Suction irrigation tube curved Ø 5 mm WL 310 mm | 8383.912 |
| for this: Sealing cap                           | 8385.902 |

#### 2 Blunt aquadissection:

Pressure irrigation tube Ø 5 mm WL 310 mm8383.913for this: Sealing cap8385.902

#### 3 Suction, irrigation, and use

#### of auxiliary instruments Ø 5 mm


| 8385.942  |
|-----------|
| . 8385951 |
|           |
| 8385.944  |
| 8385.903  |
|           |

#### Preparation of tissue with HF:

| HF suction irrigation tube Ø 5.2 mm WL 317 mm    |          |
|--|----------|
| insulated with integrated HF spatula probe       | 8383.811 |
| HF suction irrigation tube Ø 5.2 mm WL 317 mm    |          |
| insulated with integrated HF hook electrode      | 8383.812 |
| HF suction irrigation tube Ø 5.2 mm WL 317 mm    |          |
| insulated with integrated HF button electrode $$ | 8383.813 |
| HF suction irrigation tube Ø 5.4 mm WL 380 mm    |          |
| curved with distal openings,                     |          |
| insulated with integrated HF button electrode    | 8383.814 |
| for this: Sealing cap                            | 8385.902 |

#### MULTIFUNCTIONAL SUCTION IRRIGATION SYSTEM


#### SUCTION IRRIGATION HANDLE





#### MULTIFUNCTIONAL SUCTION IRRIGATION SYSTEM

#### SUCTION IRRIGATION TUBE SETS - ILLUSTRATION



**Suction irrigation tube sets** are used in conjunction with the suction irrigation handle 8385.901 and pump-side tube systems as well as corresponding collection and secretion containers and/or vacuum pumps.



### MULTIFUNCTIONAL SUCTION IRRIGATION SYSTEM

#### SUCTION IRRIGATION TUBE SETS FOR SUCTION IRRIGATION HANDLE 8385.901


| Disposable  |  | Product no. |
|---|--|-------------|
| Suction irrigation tube set, L 3 m  (PACK= 10 PCS), sterile                     | Irrigation tube: With Luer-Lock, for connection to the irrigation tube of a suction irrigation tube set, e.g., irrigation tube of the Endo-Irrigator 2211 Suction tube: For connection to a collection or secretion container and/or vacuum pump | 4170.954    |
| Suction irrigation tube set<br>with care-lock, L 3 m<br>(PACK= 10 PCS), sterile | Irrigation tube: With CARE-LOCK, for connection to an irrigation container Suction tube: For connection to a collection or secretion container and/or vacuum pump  | 4170.955    |
| Suction irrigation tube set with piercing spike, L 3 m  (PACK= 10 PCS), sterile | Irrigation tube: With 2 piercing spikes, for connection to an irrigation container Suction tube: For connection to a collection or secretion container and/or vacuum pump  | 4170.956    |
| Suction irrigation tube set, L 3 m  (PACK= 10 PCS), sterile                     | Irrigation tube: With 2 piercing spikes, for connection to an irrigation container, and Fluid Control Lap 2216 Suction tube: For connection to a collection or secretion container and/or vacuum pump Also observe instruction manual GA-A 276   | 4171.225    |
| Secretion container, 2.5 I  | 2.5 liters   | 41706566    |
| Tube set for suction (2 connections)  | sterile disposable product (PACK= 10 PCS), for connecting instruments to collecting container  | T0503-01    |

| Reusable                 |   | Product no. |
|--------------------------|---|-------------|
| Irrigation tube L 1.2 m  | Irrigation tube: With Luer-Lockconnection for connection to the irrigation tube of a suction irrigation tube set, e.g., 8171223 or 8170.223 | 817123      |
| Suction tube L 3 m       | 8171402   |             |
| Secretion container, 2 I | 2 liters, without cover   | 8170.6551   |
| Cover                    | for secretion trap 8170.6551, reusable  | 8170.6552   |




#### MULTIFUNCTIONAL SUCTION IRRIGATION SYSTEM

#### SUCTION IRRIGATION TUBES



#### Zur Anwendung von 5 mm Hilfsinstrumenten




|   |                                       |         | <del></del> | TO THE PARTY OF TH |
|---|---------------------------------------|---------|-------------|--|
|   |                                       | Outer Ø | WL          | Product no.  |
| isoliert, mit atraumatischer<br>Präparierspitze | Saug-Spül-Rohr mono Ø 10 mm NL 330 mm | 10,0 mm | 330 mm      | 8385.944   |

| for use of 5 mm auxiliary instru | nents   | Product no. |  |  |
|----------------------------------|---|-------------|--|--|
|                                  | <b>Dichtaufsatz</b> mit Durchgang und Membranventil Dichtmembrane Ø 17 mm | 8385.903    |  |  |



#### MULTIFUNCTIONAL SUCTION IRRIGATION SYSTEM

#### **SUCTION IRRIGATION TUBES**





| Accessories         | Product no.         |
|---------------------|---------------------|
| HF connection cable | See page BDE116/117 |




#### MULTIFUNCTIONAL SUCTION IRRIGATION SYSTEM

**SUCTION IRRIGATION TUBES** 












#### **ACCESSORIES**

#### FOR SUCTION AND IRRIGATION








| Accessories         | Product no.         |
|---------------------|---------------------|
| HF connection cable | See page BDE116/117 |

# WOLF

spirit of excellence

#### **ACCESSORIES**

#### FOR SUCTION AND IRRIGATION






### DISPOSABLE HAND BLOWER


#### FOR SUCTION AND IRRIGATION

VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.



VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

### TISSUE RETRACTOR 5 MM




| Accessories      | Product no. |
|------------------|-------------|
| Luer sealing cap | 887.00      |



#### CLIP APPLICATOR 10 MM

#### FOR SUCTION AND IRRIGATION




| Accessories                      | Product no. |
|----------------------------------|-------------|
| Sealing cap capacity 9.5–10.1 mm | 89.08       |





#### THE ERGONOMIC GENERATION OF NEEDLE HOLDERS


Thanks to the custom combination options it offers, **ERAGONstitch** can accommodate any user requirement. The way in which it brings together ergonomics, versatility, modularity, and precision sets new standards in comfort







# ERAGON stitch NEEDLE HOLDER Ø 3.5 MM



<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)

| Accessories for manual and machine reprocessing |   | Product no. |
|---|---|-------------|
|   | Irrigation adapter cleaning<br>Ø 9 mm, length 64 mm<br>for uninsulated sheath tubes | 163503      |



# ERAGON stitch NEEDLE HOLDER Ø 5.0 MM

| Needle holder jaw insert                     |                             |             | Sheath tube, Ø 5.0 mm |              | Needle holder handle |   | Complete instrument |  |
|--|-----------------------------|-------------|-----------------------|--------------|----------------------|---|---------------------|--|
| E WOLF                                       |                             | -           | ) <u> </u>            |              |                      | <ul><li>Jaw insert</li><li>Sheath<br/>tube</li><li>Handle</li></ul> |                     |  |
|  |                             |             | SL<br>330 mm          | SL<br>450 mm | with on-off det      | ent mechanism,<br>-action   |                     |  |
|  |                             |             | 330 111111            | 430 11111    | axial                | angled  |                     |  |
|  | JL*                         | Product no. | 8393533               | 8394533      | 8393943              | 8393944   | Product no.         |  |
| Needle holder<br>Ø 5 mm bndl                 |                             | 8393507     | •                     |              | •                    |   | 83935073            |  |
| RINDLE                                       | 19 mm                       | 0393307     | •                     |              |                      | •   | 83935074            |  |
|  | 19 mm -                     | 8394507     |                       | •            | •                    |   | 83945073            |  |
| straight with carbide insert single-action   |                             | 0394307     |                       | •            |                      | •   | 83945074            |  |
| Needle holder<br>Ø 5 mm bndl                 | Ø 5 mm bndl                 | 0202500     | •                     |              | •                    |   | 83935083            |  |
| D minis                                      |                             | 8393508     | •                     |              |                      | •   | 83935084            |  |
| straight and narrow with carbide             |                             | 8394508     |                       | •            | •                    |   | 83945083            |  |
| insert<br>single-action                      |                             | 0074000     |                       | •            |                      | •   | 83945084            |  |
| Needle holder jaw insert<br>Ø 5 mm bndl      |                             | 8393509     | •                     |              | •                    |   | 83935093            |  |
|  |                             | 8393509     | •                     |              |                      | •   | 83935094            |  |
| straight,                                    | 19 mm                       | 8394509     |                       | •            | •                    |   | 83945093            |  |
| with self-righting function<br>single-action | with self-righting function | 0074009     |                       | •            |                      | •   | 83945094            |  |

<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)

| Accessories for manual and machine reprocessing |   | Product no. |
|---|---|-------------|
|   | Irrigation adapter cleaning<br>Ø 9 mm, length 64 mm<br>for uninsulated sheath tubes | 163503      |



VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# ERAGON stitch NEEDLE HOLDER Ø 5.0 MM


| Needle holder jaw insert   |       |             | Sheath tube, Ø 5.0 mm |              | Needle holder handle                        |         | Complete instrument   |
|--|-------|-------------|-----------------------|--------------|---|---------|---|
| arum sa (  |       |             |                       |              |   |         | <ul><li>Jaw insert</li><li>Sheath tube</li><li>Handle</li></ul> |
|  |       |             | SL<br>330 mm          | SL<br>450 mm | with on-off detent mechanism, single-action |         |   |
|  |       | Axial       |                       |              | Angled                                      |         |   |
|  | JL*   | Product no. | 8393533               | 8394533      | 8393943                                     | 8393944 | Product no.   |
| Needle holder Ø 5 mm bndl  R WILLE  curved right with carbide insert single-action | 19 mm | 8393518     | •                     |              | •   |         | 83935183  |
|  |       |             | •                     |              |   | •       | 83935184  |
|  |       | 8394518     |                       | •            | •   |         | 83945183  |
|  |       |             |                       | •            |   | •       | 83945184  |
| Needle holder<br>Ø 5 mm bndl   | 19 mm | 8393519     | •                     |              | •   |         | 83935193  |
| RWDLE  |       |             | •                     |              |   | •       | 83935194  |
|  |       | 8394519     |                       | •            | •   |         | 83945193  |
| Curved left with carbide insert single-action                                      |       |             |                       | •            |   | •       | 83945194  |

| Accessories for manual and machine reprocessing | Product no.   |        |  |
|---|---|--------|--|
|   | Irrigation adapter cleaning<br>Ø 9 mm, length 64 mm<br>for uninsulated sheath tubes | 163503 |  |



### NEEDLE HOLDER Ø 3.5 MM/5 MM

#### **MODULAR SYSTEM**



<sup>\*</sup> with automatic needle placement apparatus and cutting edge

VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# NEEDLE HOLDER HANDLE

| Needle holder handle, axial | not rotatable | with lock | without HF | Product no. |
|-----------------------------|---------------|-----------|------------|-------------|
|                             | •             | •         | •          | 8393.941    |

| Needle holder handle<br>ERAGON statch | axial | angled | with on-off<br>detent<br>mechanism | single-action | Not<br>rotatable | Product no. |
|---------------------------------------|-------|--------|------------------------------------|---------------|------------------|-------------|
|                                       | •     |        | •                                  | •             | •                | 8393943     |
|                                       |       | •      | •                                  | •             | •                | 8393944     |





# MODULAR KNOT PUSHER Ø 5.0 MM, INSULATED

|  |             | Handle, axial |                                    |                                    |                             |  |
|--|-------------|---------------|------------------------------------|------------------------------------|-----------------------------|--|
| ERAGON axial   |             | S.            | -                                  | 1                                  | S.                          |  |
| All jaw inserts and sheath tubes can also be with <b>ERAGONaxial</b> | combined    | with lock     | without lock,<br>with HF connector | without lock,<br>with HF connector | with lock,<br>not rotatable |  |
| Rotatable knob   | Product no. | 83930082      | 83930083                           | 83930084                           | 83930085                    |  |
| 2 PRODE  | 8988        | •             | •                                  | •                                  | •                           |  |

| Jaw insert                        |       | Sheath tube, Ø 5 | .0 mm, insulated | Handle       | Complete instrument                    |             |
|-----------------------------------|-------|------------------|------------------|--------------|--|-------------|
| ERAGON modular  R.WOLF            |       |                  |                  | <b>B</b>     | Jaw insert with sheath tube     Handle |             |
|                                   | ,     |                  | SL<br>330 mm     | SL<br>450 mm | with lock,<br>without HF               |             |
|                                   | JL*   | Product no.      | 8393933          | 8394933      | 83930072                               | Product no. |
| Knot pusher<br>Ø 5 mm bndl        | 17 mm | 8393.345         | •                |              | •                                      | 83933457    |
| with distal recess, double-action | 17 mm | 8394345          |                  | •            | •                                      | 83943457    |


<sup>\*</sup> JL = jaw length when jaw section closed (approximate measurements)
HF connection cable: see sheet BDE116/117

# 

spirit of excellence

VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# KNOT PUSHER 5 MM FOR ENDOSCOPIC SUTURING



|  |   |         |        | -      |             |
|--|---|---------|--------|--------|-------------|
|  |   | Outer Ø | WL     | TL     | Product no. |
| with distal notch and lateral opening<br>for optimum knotting, extremely atrau-<br>matic tip for use as a surgical probe | Knot pusher Ø 5 mm WL 330 mm<br>as per Bueß | 5.0 mm  | 330 mm | 380 mm | 8383.552    |



# Endoscopically controlled fascia closure system AS PER BUSCHE





# 

spirit of excellence

VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

### CANNULAS 3.0 MM/4.7 MM






| for this: |   | WL    | Product no. |
|-----------|---|-------|-------------|
| E E       | Introduction sleeve size 5.5 mm WL 45 mm  This sleeve prevents damage to the cannula tip when the trocar sleeve valve is opened | 45 mm | 8383.00     |




### **SURGICAL PROBES**

|  | Ø      | WL     | Product no. |
|--|--------|--------|-------------|
| Surgical probe 3.5 mm WL 350 mm<br>graduated | 3.5 mm | 350 mm | 8379.672    |



# MYOMA DRILL 5 MM/10 MM



# **INSUFFLATOR HIGHFLOW 45 BASIC**



|  |                             | Product no.        |
|--|-----------------------------|--------------------|
| Insufflator 45 BASIC bndl consisting of: Insufflator 45 BASIC FR 45 I/min (2235001) and power cable 3 m long (2440.03)   |                             | 22350012           |
| Accessories: Tube sets for insufflation  |                             |                    |
| Insufflation set, insufflation tube with integrated hygiene filter, disposable, (PACK= 10 PCS) in indicates the control of the | vidual sterile packaging    | 2200/48BIKBTUA123  |
| <b>Insufflation tube set L 2.5 m</b> , High Flow, D = 8 mm, autoclavable   |                             | 8170.232           |
| Insufflation tube set L 2.5 m, autoclavable  |                             | 8170.101           |
| Hygiene filter, sterile, disposable (PACK= 10 PCS) in individual sterile packaging   |                             | 4171.111           |
| Accessories for gas supply CO <sub>2</sub> bottle  |                             |                    |
| <b>Qualityreg CO</b> <sub>2</sub> , Inlet pressure connection DIN ISO 477-6 outlet connection NIST, pressure gauge Flow meter  | DIN ISO 477-6               | DM-DIN6-MS-NISTCO2 |
| <b>Qualityreg CO</b> <sub>2</sub> , Inlet connection DIN EN ISO 407 PIN INDEX, outlet connection NIST ,pressure gauge Flow meter   | DIN EN ISO 407<br>PIN INDEX | DM-PIN-MS-NIST-CO2 |
| <b>Qualityreg CO<sub>2</sub></b> , Inlet connection ISO 5145 outlet connection NIST, pressure gauge Flow meter   | ISO 5145                    | DM-ISO-MS-NIST-CO2 |
| with   |                             |                    |
| Connection hose, quality CONNECT, $\mathrm{CO_2}\ 1.5\ \mathrm{m}\ \mathrm{long}$  |                             | DINCO2NIST-NIST1.5 |
| Optional for faster CO <sub>2</sub> bottle changes   |                             |                    |
| Quick plug adapter NIST, (2 pieces recommended) DIN with safety chain, adapter NIST / coupling   | g with chain and ring       | DM-AD-CO2NISTDINKU |
| Connection hose DIN, CO <sub>2</sub> , ZGV plug to NIST fitting, ISO-colored, 1.5 m long (Ceiling light)   |                             | DIN-CO2-ZGVNIST1.5 |
| ZGV connection   |                             |                    |
| $\textbf{Connection hose, quality CONNECT, } \text{CO}_2 \text{ 5 m long, DIN for centralized } \text{CO}_2 \text{ gas supply (Dräger)}$   |                             | RW-CO2-ZGV-NIST5.0 |
| $\textbf{Connection hose, quality CONNECT, } \text{CO}_2 \text{ 5 m long, NF for centralized CO}_2 \text{ gas supply (Liquid Air)}$  | NF-CO2-ZGV-NIST5.0          |                    |
| Connection hose DIN, CO <sub>2</sub> , ZGV plug to NIST fitting, ISO-colored, 1.5 m long (Ceiling light)   | DIN-CO2-ZGVNIST1.5          |                    |
| Software modules (optional)  |                             |                    |
| Software module CAN bus CAN bus interface for integration in CORE  | 2235101                     |                    |
| Software module BABY MODE BABY MODE for special use in pediatrics  |                             | 2235102            |
| Software module VIDEO DISPLAY: video display using DIALOG via CAN bus  |                             | 2235103            |



VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# TECHNICAL DATA

#### INSUFFLATOR HIGHFLOW 45 BASIC

| Insufflator 45 BASIC   | 2235001  |
|--|--|
| Device properties  |  |
| Operating mode   | Continuous operation   |
| Operating conditions   | $+10^{\circ}\text{C}$ to $+40^{\circ}\text{C}$ , 30% to 75% rel. humidity, atmospheric pressure 700 hPa to 1,060 hPa |
| Storage and transport conditions   | -20°C to +60°C, 10% to 90% rel. humidity, atmospheric pressure 700 hPa to 1,060 hPa                                  |
| Power supply   |  |
| Mains + frequency  | 100-240 V~, 50/60 Hz   |
| Power consumption  | 60 VA  |
| Current rating   | 0.6-0.2 A  |
| Fuse   | T 3.15 AH 250 V  |
| Regulatory standards   |  |
| Protection class to IEC/EN 60601-1<br>(UL 60601-1/CSA C222 No6011 – for USA) | I  |
| Electromagnetic compatibility (EMC)  | IEC/EN 60601-1-2   |
| Medical Devices Directive 93/42/EEC  | Class IIb  |
| Protection against electric shock  | Type CF applied part   |
| Degree of protection against the ingress of liquids                          | IP 20 (not protected)  |
| Degree of protection in the presence of flammable mixtures                   | Device is not protected against explosions (do not operate this device in explosive atmospheres)                     |
| Dimensions and weights   |  |
| Weight   | 8.9 kg (19.5 lbs)  |
| Dimensions (W x H x D)   | 300 mm x 160 mm x 455 mm   |

| Relevant application parameters |   |  |  |  |
|---------------------------------|---|--|--|--|
| Insufflation medium             | Medical-grade CO <sub>2</sub> (degree of purity > 99.5%)        |  |  |  |
| Intraabdominal pressure         | 3 mmHg to 25 mmHg (± 2 mmHg) selectable in increments of 1 mmHg |  |  |  |
| Gas flow rate primary filling   | 1 I/min (± 50%)   |  |  |  |
| Gas flow rate, High Flow        | 2 I/min to 45 I/min (± 20%) selectable in increments of 1 I/min |  |  |  |
| Consumption indicator           | 0   to 9,999   (± 20%)  |  |  |  |



# INSUFFLATOR HIGHFLOW 45 EVAC + HEAT

#### WITH SMOKE GAS EVACUATION AND GAS HEATING



| cord  |                             |                    |
|---|-----------------------------|--------------------|
|   |                             | Artikel-Nr.        |
| Insufflator 45 EVAC + HEAT bndI consisting of: Insufflator 45 EVAC + HEAT FR 45 I/min(2235031), power cable, 3 m long (2440.03 and footswitch with 1 pedal (20301031) | 3)                          | 22350312           |
| Accessories: Tube sets for insufflation with heating and smoke gas evacuation   |                             |                    |
| <b>Insufflation tube set L 3m</b> high-flow with heating coil and integrated hygiene filter, (PACK=10 PCS sterile, for single use                                     | ),                          | 4170502            |
| <b>Insufflation tube for 2235021/031 L 3m</b> , high-flow with heating coil, autoclavable Up to 100 uses are possible with the reusable hose.                         |                             | 8170202            |
| Hygiene filter, sterile, disposable (PACK= 10 PCS) in individual sterile packaging  |                             | 4171.111           |
| Smoke gas evacuation tube set, steril, sterile, for single use (PACK= 10 PCS)   |                             | 2200/72BTUA123000  |
| Accessories for gas supply CO <sub>2</sub> bottle   |                             |                    |
| <b>Qualityreg CO</b> <sub>2</sub> , Inlet pressure connection DIN ISO 477-6 outlet connection NIST, pressure gauge Flow meter   | DIN ISO 477-6               | DM-DIN6-MS-NISTCO2 |
| Qualityreg CO <sub>2</sub> , Inlet connection DIN EN ISO 407 PIN INDEX, outlet connection NIST ,pressure gauge Flow meter   | DIN EN ISO 407<br>PIN INDEX | DM-PIN-MS-NIST-CO2 |
| <b>Qualityreg CO</b> <sub>2</sub> , Inlet connection ISO 5145<br>outlet connection NIST, pressure gauge Flow meter  | - 150 3143                  |                    |
| with  |                             |                    |
| Connection hose, quality CONNECT, CO <sub>2</sub> 1.5 m long  | DINCO2NIST-NIST1.5          |                    |
| Optional for faster CO <sub>2</sub> bottle changes  |                             |                    |
| Quick plug adapter NIST, (2 pieces recommended) DIN with safety chain, adapter NIST / coupling  | with chain and ring         | DM-AD-CO2NISTDINK  |
| Connection hose DIN, CO <sub>2</sub> , ZGV plug to NIST fitting, ISO-colored, 1.5 m long (Ceiling light)  |                             | DIN-CO2-ZGVNIST1.5 |
| ZGV connection  |                             |                    |
| $\textbf{Connection hose, quality CONNECT, } \text{CO}_2 \text{ 5 m long, DIN for centralized } \text{CO}_2 \text{ gas supply (Dräger)}$                              |                             | RW-CO2-ZGV-NIST5.0 |
| $\textbf{Connection hose, quality CONNECT, } \text{CO}_2 \text{5 m long, NF for centralized CO}_2 \text{ gas supply (Liquid Air)}$                                    | NF-CO2-ZGV-NIST5.0          |                    |
| Connection hose DIN, CO <sub>2</sub> , ZGV plug to NIST fitting, ISO-colored, 1.5 m long (Ceiling light)  | DIN-CO2-ZGVNIST1.5          |                    |
| Software modules (optional)   |                             |                    |
| Software module CAN bus CAN bus interface for integration in CORE   |                             | 2235101            |
| Software module BABY MODE BABY MODE for special use in pediatrics   |                             | 2235102            |
| Software module VIDEO DISPLAY: video display using DIALOG via CAN bus   |                             | 2235103            |

VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# TECHNICAL DATA

#### INSUFFLATOR HIGHFLOW 45 EVAC

| Insufflator 45 EVAC  | 2235011  |
|--|--|
| Device properties  |  |
| Operating mode   | Continuous operation   |
| Operating conditions   | $+10^{\circ}\text{C}$ to $+40^{\circ}\text{C}$ , 30% to 75% rel. humidity, atmospheric pressure 700 hPa to 1,060 hPa |
| Storage and transport conditions   | -20°C to +60°C, 10% to 90% rel. humidity, atmospheric pressure 700 hPa to 1,060 hPa                                  |
| Power supply   |  |
| Mains + frequency  | 100–240 V~, 50/60 Hz   |
| Power consumption  | 60 VA  |
| Current rating   | 0.6-0.2 A  |
| Fuse   | T 3.15 AH 250 V  |
| Regulatory standards   |  |
| Protection class to IEC/EN 60601-1<br>(UL 60601-1/CSA C222 No6011 – for USA) | I  |
| Electromagnetic compatibility (EMC)  | IEC/EN 60601-1-2   |
| Medical Devices Directive 93/42/EEC  | Class IIb  |
| Protection against electric shock  | Type CF applied part   |
| Degree of protection against the ingress of liquids                          | IP 20 (not protected)  |
| Degree of protection in the presence of flammable mixtures                   | Device is not protected against explosions (do not operate this device in explosive atmospheres)                     |
| Dimensions and weights   |  |
| Weight   | 8.9 kg (19.5 lbs)  |
| Dimensions (W x H x D)   | 300 mm x 160 mm x 455 mm   |

| Relevant application parameters |   |
|---------------------------------|---|
| Insufflation medium             | Medical-grade CO <sub>2</sub> (degree of purity > 99.5%)        |
| Intraabdominal pressure         | 3 mmHg to 25 mmHg (± 2 mmHg) selectable in increments of 1 mmHg |
| Gas flow rate primary filling   | 1 I/min (± 50%)   |
| Gas flow rate, High Flow        | 2 I/min to 45 I/min (± 20%) selectable in increments of 1 I/min |
| Consumption indicator           | 0   to 9,999   (± 20%)  |



# INSUFFLATOR HIGHFLOW 45 HEAT

#### WITH GAS HEATING



|   |                             | Product no.        |
|---|-----------------------------|--------------------|
| Insufflator 45 HEAT bndI consisting of: Insufflator 45 HEAT FR 45 L/min(2235021) and power cable, 3 m long (2440.03)                          |                             | 22350212           |
| Accessories: Tube sets for insufflation with heating  |                             |                    |
| <b>Insufflation tube set L 3m</b> high-flow with heating coil and integrated hygiene filter, (PACK=10 PCS) sterile, for single use            | ),                          | 4170502            |
| <b>Insufflation tube for 2235021/031 L 3m</b> , high-flow with heating coil, autoclavable Up to 100 uses are possible with the reusable hose. |                             | 8170202            |
| Hygiene filter, sterile, disposable (PACK= 10 PCS) in individual sterile packaging  |                             | 4171.111           |
| Accessories for gas supply CO <sub>2</sub> bottle   |                             |                    |
| <b>Qualityreg CO<sub>2</sub></b> , Inlet pressure connection DIN ISO 477-6 outlet connection NIST, pressure gauge Flow meter                  | DIN ISO 477-6               | DM-DIN6-MS-NISTCO2 |
| Qualityreg CO <sub>2</sub> , Inlet connection DIN EN ISO 407 PIN INDEX, outlet connection NIST ,pressure gauge Flow meter                     | DIN EN ISO 407<br>PIN INDEX | DM-PIN-MS-NIST-CO2 |
| Qualityreg CO <sub>2</sub> , Inlet connection ISO 5145 outlet connection NIST, pressure gauge Flow meter                                      |                             | DM-ISO-MS-NIST-CO2 |
| with  |                             |                    |
| Connection hose, quality CONNECT, CO <sub>2</sub> 1.5 m long  |                             | DINCO2NIST-NIST1.5 |
| Optional for faster CO <sub>2</sub> bottle changes  |                             |                    |
| Quick plug adapter NIST, (2 pieces recommended) DIN with safety chain, adapter NIST / coupling  | with chain and ring         | DM-AD-CO2NISTDINK  |
| Connection hose DIN, CO <sub>2</sub> , ZGV plug to NIST fitting, ISO-colored, 1.5 m long (Ceiling light)                                      |                             | DIN-CO2-ZGVNIST1.5 |
| ZGV connection  |                             |                    |
| $\textbf{Connection hose, quality CONNECT, } \text{CO}_2 \text{ 5 m long, DIN for centralized } \text{CO}_2 \text{ gas supply (Dräger)}$      |                             | RW-CO2-ZGV-NIST5.0 |
| Connection hose, quality CONNECT, CO <sub>2</sub> 5 m long, NF for centralized CO <sub>2</sub> gas supply (Liquid Air)                        |                             | NF-CO2-ZGV-NIST5.0 |
| Connection hose DIN, CO <sub>2</sub> , ZGV plug to NIST fitting, ISO-colored, 1.5 m long (Ceiling light)                                      |                             | DIN-CO2-ZGVNIST1.5 |
| Software modules (optional)   |                             |                    |
| Software module CAN bus CAN bus interface for integration in CORE   |                             | 2235101            |
| Software module BABY MODE BABY MODE for special use in pediatrics   |                             | 2235102            |
| Software module VIDEO DISPLAY: video display using DIALOG via CAN bus   |                             | 2235103            |



VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# TECHNICAL DATA

#### **INSUFFLATOR HIGHFLOW 45 HEAT**

| Insufflator 45 HEAT  | 2235021  |
|--|--|
| Device properties  |  |
| Operating mode   | Continuous operation   |
| Operating conditions   | +10°C to +40°C, 30% to 75% rel. humidity, atmospheric pressure 700 hPa to 1,060 hPa              |
| Storage and transport conditions   | -20°C to +60°C, 10% to 90% rel. humidity, atmospheric pressure 700 hPa to 1,060 hPa              |
| Power supply   |  |
| Mains + frequency  | 100–127/220–240 V~, 50/60 Hz   |
| Power consumption  | 80 VA  |
| Current rating   | 0.8-0.3 A  |
| Fuse   | T 3.15 AH 250 V  |
| Regulatory standards   |  |
| Protection class to IEC/EN 60601-1<br>(UL 60601-1/CSA C222 No6011 – for USA) | I  |
| Electromagnetic compatibility (EMC)  | IEC/EN 60601-1-2   |
| Medical Devices Directive 93/42/EEC  | Class IIb  |
| Protection against electric shock  | Type CF applied part   |
| Degree of protection against the ingress of liquids                          | IP 20 (not protected)  |
| Degree of protection in the presence of flammable mixtures                   | Device is not protected against explosions (do not operate this device in explosive atmospheres) |
| Dimensions and weights   |  |
| Weight   | 11.0 kg (23.3 lbs)   |
| Dimensions (W x H x D)   | 300 mm x 160 mm x 455 mm   |

| Relevant application parameters |   |
|---------------------------------|---|
| Insufflation medium             | Medical-grade CO <sub>2</sub> (degree of purity > 99.5%)        |
| Intraabdominal pressure         | 3 mmHg to 25 mmHg (± 2 mmHg) selectable in increments of 1 mmHg |
| Gas flow rate primary filling   | 1 I/min (± 50%)   |
| Gas flow rate, High Flow        | 2 I/min to 45 I/min (± 20%) selectable in increments of 1 I/min |
| Consumption indicator           | 0   to 9,999   (± 20%)  |



# INSUFFLATOR HIGHFLOW 45 EVAC + HEAT

#### WITH SMOKE GAS EVACUATION AND GAS HEATING



| cord   |                     |                    |
|--|---------------------|--------------------|
|  |                     | Artikel-Nr.        |
| Insufflator 45 EVAC + HEAT bndI consisting of: Insufflator 45 EVAC + HEAT FR 45 I/min(2235031), power cable, 3 m long (2440.03 and footswitch with 1 pedal (20301031)  | 3)                  | 22350312           |
| Accessories: Tube sets for insufflation with heating and smoke gas evacuation  |                     |                    |
| <b>Insufflation tube set L 3m</b> high-flow with heating coil and integrated hygiene filter, (PACK=10 PCS sterile, for single use                                      | ),                  | 4170502            |
| <b>Insufflation tube for 2235021/031 L 3m</b> , high-flow with heating coil, autoclavable Up to 100 uses are possible with the reusable hose.                          |                     | 8170202            |
| Hygiene filter, sterile, disposable (PACK= 10 PCS) in individual sterile packaging   |                     | 4171.111           |
| Smoke gas evacuation tube set, steril, sterile, for single use (PACK= 10 PCS)  |                     | 2200/72BTUA123000  |
| Accessories for gas supply CO <sub>2</sub> bottle  |                     |                    |
| <b>Qualityreg CO</b> <sub>2</sub> , Inlet pressure connection DIN ISO 477-6 outlet connection NIST, pressure gauge Flow meter  | DIN ISO 477-6       | DM-DIN6-MS-NISTCO2 |
| Qualityreg CO <sub>2</sub> , Inlet connection DIN EN ISO 407 PIN INDEX,       DIN EN ISO 407         outlet connection NIST ,pressure gauge Flow meter       PIN INDEX |                     | DM-PIN-MS-NIST-CO2 |
| Qualityreg CO <sub>2</sub> , Inlet connection ISO 5145 outlet connection NIST, pressure gauge Flow meter   |                     | DM-ISO-MS-NIST-CO2 |
| with   |                     |                    |
| Connection hose, quality CONNECT, CO <sub>2</sub> 1.5 m long   |                     | DINCO2NIST-NIST1.5 |
| Optional for faster CO <sub>2</sub> bottle changes   |                     |                    |
| Quick plug adapter NIST, (2 pieces recommended) DIN with safety chain, adapter NIST / coupling   | with chain and ring | DM-AD-CO2NISTDINK  |
| Connection hose DIN, CO <sub>2</sub> , ZGV plug to NIST fitting, ISO-colored, 1.5 m long (Ceiling light)   |                     | DIN-CO2-ZGVNIST1.5 |
| ZGV connection   |                     |                    |
| Connection hose, quality CONNECT, CO <sub>2</sub> 5 m long, DIN for centralized CO <sub>2</sub> gas supply (Dräger)  |                     | RW-CO2-ZGV-NIST5.0 |
| Connection hose, quality CONNECT, CO <sub>2</sub> 5 m long, NF for centralized CO <sub>2</sub> gas supply (Liquid Air)   |                     | NF-CO2-ZGV-NIST5.0 |
| Connection hose DIN, CO <sub>2</sub> , ZGV plug to NIST fitting, ISO-colored, 1.5 m long (Ceiling light)   |                     | DIN-CO2-ZGVNIST1.5 |
| Software modules (optional)  |                     |                    |
| Software module CAN bus CAN bus interface for integration in CORE  |                     | 2235101            |
| Software module BABY MODE BABY MODE for special use in pediatrics  |                     | 2235102            |
| Software module VIDEO DISPLAY: video display using DIALOG via CAN bus  |                     | 2235103            |



VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# TECHNICAL DATA

#### INSUFFLATOR HIGHFLOW 45 EVAC + HEAT

| Insufflator 45 EVAC + HEAT   | 2235031  |  |  |
|--|--|--|--|
| Device properties  |  |  |  |
| Operating mode   | Continuous operation   |  |  |
| Operating conditions   | +10°C to +40°C, 30% to 75% rel. humidity, atmospheric pressure 700 hPa to 1,060 hPa              |  |  |
| Storage and transport conditions   | -20°C to +60°C, 10% to 90% rel. humidity, atmospheric pressure 700 hPa to 1,060 hPa              |  |  |
| Power supply   |  |  |  |
| Mains + frequency  | 100–127/220–240 V~, 50/60 Hz   |  |  |
| Power consumption  | 80 VA  |  |  |
| Current rating   | 0.8-0.3 A  |  |  |
| Fuse   | T 3.15 AH 250 V  |  |  |
| Regulatory standards   | Regulatory standards   |  |  |
| Protection class to IEC/EN 60601-1<br>(UL 60601-1/CSA C222 No6011 – for USA) |  |  |  |
| Electromagnetic compatibility (EMC)  | IEC/EN 60601-1-2   |  |  |
| Medical Devices Directive 93/42/EEC  | Class IIb  |  |  |
| Protection against electric shock  | Type CF applied part   |  |  |
| Degree of protection against the ingress of liquids                          | IP 20 (not protected)  |  |  |
| Degree of protection in the presence of flammable mixtures                   | Device is not protected against explosions (do not operate this device in explosive atmospheres) |  |  |
| Dimensions and weights   |  |  |  |
| Weight   | 11.0 kg (23.3 lbs)   |  |  |
| Dimensions (W x H x D)   | 300 x 160 x 455 mm   |  |  |

| Relevant application parameters |   |
|---------------------------------|---|
| Insufflation medium             | Medical-grade CO <sub>2</sub> (degree of purity > 99.5%)        |
| Intraabdominal pressure         | 3 mmHg to 25 mmHg (± 2 mmHg) selectable in increments of 1 mmHg |
| Gas flow rate primary filling   | 1 I/min (± 50%)   |
| Gas flow rate, High Flow        | 2 I/min to 45 I/min (± 20%) selectable in increments of 1 I/min |
| Consumption indicator           | 0   to 9,999   (± 20%)  |




### STERILE SMOKE

#### FOR SMOKE GAS DISCHARGE



#### FLUID CONTROL 2225

#### SUCTION IRRIGATION PUMP



| Accessories |  | Product no. |
|-------------|--|-------------|
| Footswitch  | only for use in urology and within the indication TUR/enucleation, possibility of short-term increase in pressure if visibility is poor (Flush function) | 2204901     |



# FLUID CONTROL 2225

#### SUCTION IRRIGATION TUBE SETS

| Irrigation                  |   |  | Product no. |
|-----------------------------|---|--|-------------|
| Accessories<br>– reusable   | Tube set with piercing spike                      | with Luer-Lock connection, autoclavable, incl. 10 spare membranes, reusable for 20 reprocessing cycles | 8171223     |
| Accessories<br>– disposable | Irrigation tube set with piercing spike,<br>L 3 m | (PACK= 10 PCS), with Luer-Lock connection, sterile, disposable product                                 | 4171223     |
|                             | Tube set with CARE-LOCK,<br>L 3 m                 | (PACK= 10 PCS), sterile, disposable product  | 4171224     |
|                             | Suction irrigation tube set                       | (PACK= 10 PCS),<br>with piercing spike, sterile disposable product, PVC                                | 4171225     |

| Suction                     |   |  | Product no. |
|-----------------------------|---|--|-------------|
|                             | Tube set for vacuum, incl. filter       | with integrated hygiene filter, PACK= 10 PCS, service life: 30 days (connected to irrigation pump)     | 2206207     |
|                             | Irrigation tube                         | L 1.2 m, with Luer-Lock,<br>for suction irrigation handle 8385.901 and tube set<br>8171223 or 8170.223 | 817123      |
| Accessories – reusable      | Suction tube L 3 m                      | for suction irrigation handle 8385.901   | 8171402     |
|                             | Secretion container, 2 I                | 2 liters, without cover  | 8170.6551   |
|                             | Cover                                   | for secretion trap 8170.6551, reusable   | 8170.6552   |
| Accessories<br>– disposable | Secretion container, 2.5 I              | 2.5 liters   | 41706566    |
|                             | Secretion container bndl consisting of: | Secretion container 2.5 I (41706566) and secretion bag (PACK= 90 PCS) (41706564)                       | 4170657     |
|                             | Tube set for suction (2 connections)    | sterile, disposable product, (PACK= 10 PCS) for connecting instruments to collecting container         | T0503-01    |
|                             | Angled 90° plug-in coupling             | (PACK= 10 PCS) For connecting vacuum tube 2206207 to disposable container systems                      | 0771019     |



# FLUID CONTROL 2225

#### CABLE ACCESSORIES

|                                   |                    | Product no. |
|-----------------------------------|--------------------|-------------|
| Patch cable, RJ45 SFTP, 0.5 m     | Cable length 0.5 m | 72325378    |
| Patch cable, RJ45 HRS TM11, 1.0 m | Cable length 1.0 m | 72325429    |
| Patch cable, RJ45 S/FTP CAT6 10 m | Cable length 10 m  | 72325434    |
| Plastic caps for network socket   | (PACK= 8 PCS)      | 5592105     |
| Power cable                       | Cable length 3 m   | 2440.03     |



# TECHNICAL DATA

#### FLUID CONTROL 2225

| FLUID CONTROL 2225   |             | 2225001  |
|--|-------------|--|
| Device properties  |             |  |
| Operating conditions                                       |             | +10°C to +40°C, 30% to 75% rel. humidity, 70 to 106 kPa atmospheric pressure 3,000 m max. altitude above sea level |
| Storage and transport con                                  | ditions     | -20°C to +60°C , 10% to 90% rel. humidity 70 to 106 kPa atmospheric pressure                                       |
| Power supply   |             |  |
| Mains + frequency  |             | 100–240 V~, 50/60 Hz   |
| Day or acres mention                                       | 100 V/60 Hz | 110 VA   |
| Power consumption  | 240 V/50 Hz | 120 VA   |
| Current rating   | 100 V/60 Hz | 1.10 A   |
| Current rating   | 240 V/50 Hz | 0.50 A   |
| Fuse   |             | T 3.15 AH, 250 V   |
| Regulatory standards                                       |             |  |
| Protection class (I, II)                                   |             | T. C.  |
| Electromagnetic compatibility (EMC)                        |             | EN 60601-1/IEC 60601-1<br>EN 60601-1-2/IEC 60601-1-2   |
| Medical Devices Directive                                  | 93/42/EEC   | Class IIb  |
| Housing protection rating                                  | (IP code)   | IP21   |
| Protection against electric                                | shock       | Type BF applied part   |
| Degree of protection in the presence of flammable mixtures |             | Device is not protected against explosions (do not operate this device in explosive atmospheres)                   |
| Maximum suction vacuum                                     |             | -60 kPa  |
| Dimensions and weights                                     |             |  |
| Weight   |             | 8.8 kg   |
| Dimensions (W x H x D)                                     |             | 300 mm x 157 mm x 436 mm   |

| Relevant application parameters |  |  |
|---------------------------------|--|--|
|                                 | Hysteroscopy: 800 ml/min (max. flow, not adjustable) |  |
| Nominal flow range              | Endourology: 10–800 ml/min (max. flow)               |  |
|                                 | Laparoscopy: 0.1–1.8 l/min (max. flow)               |  |
| Suction power                   | max. 2 I/min   |  |
|                                 | Hysteroscopy: 15–200 mmHg                            |  |
| Starting nominal pressure range | Endourology: 15–90 mmHg/20–120 cmH20                 |  |
|                                 | Laparoscopy: 300 mmHg (not adjustable)               |  |
| Pressure                        | 0–300 mmHg   |  |
| Deficit                         | -9,990 to +9,990 ml/0 to 99.9 l                      |  |

VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# TECHNICAL DATA FLUID CONTROL 2225

| Balancing module                    | 2225023  |  |
|-------------------------------------|--|--|
| Device properties                   |  |  |
| Operating conditions                | $+10^{\circ}$ C to $+40^{\circ}$ C, 30% to 75% rel. humidity, 70 to 106 kPa atmospheric pressure 3,000 m max. altitude above sea level |  |
| Storage and transport conditions    | -20°C to +60°C , 10% to 90% rel. humidity 70 to 106 kPa atmospheric pressure   |  |
| Regulatory standards                |  |  |
| Electromagnetic compatibility (EMC) | EN 60601-1/IEC 60601-1<br>EN 60601-1-2/IEC 60601-1-2   |  |
| Housing protection rating (IP code) | IP21   |  |
| Maximum load of container scale     | 16 kg/4 containers of 3 I each   |  |
| Maximum load of bag scale           | 23 kg/4 bags of 5 I each   |  |
| Dimensions and weights              |  |  |
| Weight                              | 15.4 kg  |  |
| Dimensions (W x H x D)              | 618 mm x 1,064 mm x 618 mm   |  |

| Footswitch                          | 2204901                  |  |
|-------------------------------------|--------------------------|--|
| Power supply                        |                          |  |
| Power supply connection             | max. 24 V                |  |
| Power consumption                   | max. 0.1 A               |  |
| Regulatory standards                |                          |  |
| Electromagnetic compatibility (EMC) | EN 60601-1/IEC 60601-1   |  |
| Housing protection rating (IP code) | IPX8                     |  |
| Plug                                | 7-pin circular connector |  |
| Cable length                        | 4.5 m                    |  |
| Dimensions and weights              |                          |  |
| Weight                              | 300 g                    |  |
| Dimensions (W x H x D)              | 66 mm x 27 mm x 91 mm    |  |

# FLUID CONTROL LAP 2216



| Accessories      |   | Product no. |
|------------------|---|-------------|
| Bracket          | for fixing the suction container on the irrigator stand or MUT cart | 2215.992    |
| Universal holder | for FLUID CONTROL LAP on RIWOmobil                                  | 32114605    |



VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# LAP SUCTION IRRIGATION PUMP 2216

#### SUCTION IRRIGATION TUBE SETS

| Irrigation                |   |  | Product no. |
|---------------------------|---|--|-------------|
| Accessories<br>– reusable | Tube set with piercing spike                      | with Luer-Lock connection, autoclavable, incl. 10 spare membranes, reusable for 20 reprocessing cycles | 8171223     |
|                           | Irrigation tube set with piercing spike,<br>L 3 m | (PACK= 10 PCS), with Luer-Lock connection, sterile, disposable product                                 | 4171223     |
| Accessories  – disposable | Tube set with CARE-LOCK,<br>L 3 m                 | (PACK= 10 PCS), sterile, disposable product  | 4171224     |
|                           | Suction irrigation tube set                       | (PACK= 10 PCS), with piercing spike, sterile disposable product, PVC                                   | 4171225     |

| Suction                     |   |  | Product no. |
|-----------------------------|---|--|-------------|
|                             | Tube set for vacuum, incl. filter       | with integrated hygiene filter, PACK= 10 PCS, service life: 30 days (connected to irrigation pump)     | 2206207     |
|                             | Irrigation tube                         | L 1.2 m, with Luer-Lock,<br>for suction irrigation handle 8385.901 and tube set<br>8171223 or 8170.223 | 817123      |
| Accessories<br>– reusable   | Suction tube L 3 m                      | for suction irrigation handle 8385.901   | 8171402     |
|                             | Secretion container, 2 I                | 2 liters, without cover  | 8170.6551   |
|                             | Cover                                   | for secretion trap 8170.6551, reusable   | 8170.6552   |
| Accessories<br>– disposable | Secretion container, 2.5 I              | 2.5 liters   | 41706566    |
|                             | Secretion container bndl consisting of: | Secretion container 2.5 I (41706566) and secretion bag (PACK= 90 PCS) (41706564)                       | 4170657     |
|                             | Tube set for suction (2 connections)    | sterile, disposable product, (PACK= 10 PCS) for connecting instruments to collecting container         | T0503-01    |
|                             | Angled 90° plug-in coupling             | (PACK= 10 PCS) For connecting vacuum tube 2206207 to disposable container systems                      | 0771019     |




# TECHNICAL DATA FLUID CONTROL LAP 2216

| LAP suction irrigation pump                                |                            | 2216001   |  |
|--|----------------------------|---|--|
| Device properties  |                            |   |  |
| Operating conditions                                       |                            | +10°C to +40°C, 30% to 75% rel. humidity, atmospheric pressure 700 hPa to 1,060 hPa 3,000 m max. altitude above sea level |  |
| Storage conditions   |                            | +5°C to +40°C, 5% to 90% rel. humidity, atmospheric pressure 700 hPa to 1,060 hPa   |  |
| Transport and shipping co                                  | onditions                  | -20°C to +60°C, 5% to 90% rel. humidity, atmospheric pressure 700 hPa to 1,060 hPa  |  |
| Power supply   |                            |   |  |
| Mains + frequency  |                            | 100–240 V~, 50/60 Hz  |  |
| Davier consumption   | 100 V/60 Hz                | 65 VA   |  |
| Power consumption  | 240 V/50 Hz                | 96 VA   |  |
| 0 1 1  | 100 V/60 Hz                | 0.65 A  |  |
| Current rating   | 240 V/50 Hz                | 0.42 A  |  |
| Protection class   |                            | 1   |  |
| Electromagnetic compatibility (EMC)                        |                            | IEC 60601-1/EN 60601-1<br>IEC 60601-1-2/EN 60601-1-2  |  |
| Medical Devices Directive                                  | 93/42/EEC                  | Class IIa   |  |
| Protection against electric                                | c shock                    | Type BF applied part  |  |
| Degree of protection agai                                  | nst the ingress of liquids | IP 41   |  |
| Degree of protection in the presence of flammable mixtures |                            | Device is not protected against explosions (do not operate this device in explosive atmospheres)                          |  |
| Dimensions and weights                                     |                            |   |  |
| Weight   |                            | 4 kg  |  |
| Dimensions (W x H x D) with toggle screw                   |                            | 140 mm x 210 mm x 295 mm  |  |

| Relevant application parameters |  |  |
|---------------------------------|--|--|
| Maximum delivery rate           | Rinsing: 2.0 I/min (± 10%), suction: 2.0 I/min (+0.4/-0.1 I/min) |  |
| Maximum pump pressure           | 400 mmHg (± 50 mmHg)   |  |
| Motor cut-out                   | 500 mmHg after 5 s (± 25 mmHg)                                   |  |
| Suction pressure                | between -50 kPa and -60 kPa                                      |  |
| Connections                     | Equipotential bonding, vacuum connection                         |  |



#### HF GENERATOR 2260



| Accessories required  | Cable length | Product no. |
|---|--------------|-------------|
| Footswitch, 2 pedals L 5 m with fixed connection cable, reusable  |              | 2260021     |
| Neutral electrode for use with high-frequency surgical device, Foil bag with 5 neutral electrodes, (PACK= 50 PCS) |              | 1280H       |
| Mono HF neutral electrode cable, L 4.5 m  | 4.5 m        | 2260031     |
| Power cable   | 3.0 m        | 2440.03     |
| Bipo HF connection cable L 3 m  | 3.0 m        | 8108233     |
| Bipo HF connection cable L 5 m  | 5.0 m        | 8108253     |



# HF GENERATOR 2260

#### TECHNICAL DATA

| HF surgical generator 40                                   | OOkHz                       | 2260001/2260002  |  |
|--|-----------------------------|--|--|
| Device properties  |                             |  |  |
| Type of controls on housi                                  | ng front                    | Touch panel  |  |
| Outrot and an  | max.cutting power           | 400 W  |  |
| Output power   | max.coagulation power       | 350 W  |  |
| LF and HF leakage currents                                 |                             | acc. to DIN EN 60601-1 and DIN EN 60601-2-2  |  |
| Signal level   |                             | HF indicator 55 dB(A); adjustable 45–60 dB(A) Alarm 65 dB(A)                                     |  |
| Operating conditions                                       |                             | +10°C to +40°C, 30% to 75% rel humidity, 700 hPa to 1,060 hPa atmospheric pressure               |  |
| Storage and transport co                                   | nditions                    | - 20°C to + 60°C, 10% to 90% rel humidity, 700 hPa to 1,060 hPa atmospheric pressure             |  |
| Power supply   |                             |  |  |
| Mains + frequency  |                             | 100–240 V~, 50/60 Hz   |  |
| Power consumption  | without HF output           | 45 VA  |  |
| rower consumption  | at max. output power        | 650 VA   |  |
| Current rating   |                             | max. 6.3 A   |  |
| Fuse   |                             | T 6.3 AH 250 V   |  |
| Regulatory standards                                       |                             |  |  |
| Protection class to EN/IEC<br>(UL 2601-1/CSA C222 No       |                             | I  |  |
| Electromagnetic compati                                    | bility (EMC)                | EN/IEC 60601-1-2   |  |
| Medical Devices Directive                                  | 93/42/EEC                   | Class IIb  |  |
| Degree of protection aga<br>(DIN EN/IEC 60529)             | inst the ingress of liquids | IPXO   |  |
| Degree of protection aga                                   | inst the ingress of solids  | IP2X   |  |
| Duty factor (duty cycle DO                                 | C)                          | Intermittent INT 10 s/30 s corresponding to 25% DC   |  |
| Protection against electric shock                          |                             | Model CF applied part, defibrillator-proof   |  |
| Degree of protection in the presence of flammable mixtures |                             | Device is not protected against explosions (do not operate this device in explosive atmospheres) |  |
| Dimensions and weights                                     | S                           |  |  |
| Weight   |                             | 10.2 kg (22.4 lbs)   |  |
| Dimensions (W x H x D)                                     |                             | 300 x 159 x 419 mm   |  |



# HF CONNECTION CABLE MONO 815xxx

| Instrument connector   | Device connector  |                                | Product no. |
|------------------------|---|--------------------------------|-------------|
| WOLF<br>Resectoscopes  |   | HF connection cable mono L 3 m | 815.032     |
|                        | ERBE (ACC/ICC/VIO)/BOWA (EU) R. Wolf HF surgical generator 400 kHz 2260002                              | HF connection cable mono L 5 m | 815.052     |
| 0                      |   | HF connection cable mono L 3 m | 815.132     |
|                        | ERBE (T series)   | HF connection cable mono L 5 m | 815.152     |
| HF electrodes,         |   | HF connection cable mono L 3 m | 815.031     |
| monopolar Radar 122.34 | Martin (M-version)/Berchtold/<br>Aesculap   | HF connection cable mono L 5 m | 815.051     |
|                        |   | HF connection cable mono L 3 m | 815.033     |
|                        | Bovie/Valleylab/Erbe (Int.)/<br>BOWA (Int.)<br>R. Wolf HF surgical generator 400 kHz<br>2260001         | HF connection cable mono L 5 m | 815.053     |
|                        |   | HF connection cable mono L 3 m | 815.034     |
|                        | BOWA (Int./EU) Eschmann and other devices with 4 mm plugs R. Wolf HF surgical generator 400 kHz 2260001 | HF connection cable mono L 5 m | 815.054     |

VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.



# HF CONNECTION CABLE MONO 8106xxx

| Instrument connector                   | Device connector  |                                | Product no. |
|--|---|--------------------------------|-------------|
| WOLF<br>Instruments/surgical generator |   | HF connection cable mono L 3 m | 8106.032    |
|  | Erbe (ACC/ICC/VIO)/BOWA (EU) R. Wolf HF surgical generator 400 kHz 2260002                                      | HF connection cable mono L 5 m | 8106.052    |
| 67                                     |   | HF connection cable mono L 3 m | 8106.132    |
|  | Erbe (T series)   | HF connection cable            | 8106.152    |
|  |   | HF connection cable mono L 3 m | 8106.031    |
| HF electrodes, monopolar               | Martin (M-version)/Berchtold/<br>Aesculap   | HF connection cable mono L 5 m | 8106.051    |
|  |   | HF connection cable mono L 3 m | 8106.033    |
|  | Bovie/Valleylab/Erbe (Int.)/<br>BOWA (Int.)<br>R. Wolf HF surgical generator 400 kHz<br>2260001                 | HF connection cable mono L 5 m | 8106.053    |
|  |   | HF connection cable mono L 3 m | 8106.034    |
|  | BOWA (Int./EU) Eschmann and other devices with 4 mm plugs R. Wolf HF surgical generator 400 kHz 2260001/2260002 | HF connection cable mono L 5 m | 8106.054    |



VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# BIPO HF CONNECTION CABLE 8108xxx

| Instrument connector        | Device connector  |                                 | Product no. |
|-----------------------------|---|---------------------------------|-------------|
| WOLF<br>Bipolar forceps     |   | HF connection cable bipo; L 3 m | 8108.032    |
|                             | ERBE (ACC/ICC/T)/BOWA (EU) R. Wolf HF surgical generator 400 kHz 2260001/2260002            | HF connection cable bipo; L 5 m | 8108.052    |
| near near                   |   | HF connection cable bipo; L 3 m | 8108.033    |
|                             | International / 2-pin Valleylab<br>R. Wolf HF surgical generator 400 kHz<br>2260001/2260002 | HF connection cable bipo; L 5 m | 8108.053    |
|                             |   | HF connection cable bipo; L 3 m | 8108.031    |
|                             | WOLF/Martin (M-version)/<br>Berchtold/Aesculap  | HF connection cable bipo; L 5 m | 8108.051    |
|                             | EMC Dolley  | HF connection cable bipo; L 3 m | 8108035     |
| Bipolar tweezers connection |   | HF connection cable bipo; L 3 m | 8108.132    |
|                             | ERBE (ACC/ICC/T)/BOWA (EU) R. Wolf HF surgical generator 400 kHz 2260001/2260002            | HF connection cable bipo; L 5 m | 8108.152    |
| F.COLF                      |   | HF connection cable bipo; L 3 m | 8108.133    |
|                             | International / 2-pin Valleylab R. Wolf HF surgical generator 400 kHz 2260001/2260002       | HF connection cable bipo; L 5 m | 8108.153    |
|                             |   | HF connection cable bipo; L 3 m | 8108.131    |
|                             | Martin (M-version)/Berchtold/<br>Aesculap   | HF connection cable bipo; L 5 m | 8108.151    |
|                             | EMC Dolley  | HF connection cable bipo; L 3 m | 8108135     |



# HF CONNECTION CABLE BIPO FOR RESECTION IN SALINE SOLUTION

| Instrument connector        | Device connector                                      |   | Product no. |
|-----------------------------|---|---|-------------|
| WOLF S(a)line resectoscopes | Erbe VIO 300D   | Bipolar cable; TUR/TCR;<br>WOLF<br>MF plug; L 4 m | 20196-119   |
| O                           | Erbe VIO 3  | <b>Bipolar cable; MF-U</b><br>MF plug; L 4.5 m    | 21196-119   |
|                             |   | HF connection cable bipo; L 3 m                   | 8108.231    |
|                             | KLS Martin  | HF connection cable bipo; L 5 m                   | 8108.251    |
|                             |   | HF connection cable bipo; L 3 m                   | 8108233     |
|                             | R. Wolf HF surgical generator 400 kHz 2260001/2260002 | HF connection cable bipo; L 5 m                   | 8108253     |



# MONO HF NEUTRAL ELECTRODE CABLE

| Instrument connector  | Device connector   |   | Product no. |
|---|--|---|-------------|
| 2-pole neutral electrode  |  |   |             |
| COUNTY OF THE PROPERTY OF THE |  | Mono HF neutral electrode<br>cable, L 4.5 m | 2260031     |
|   | R. Wolf HF surgical generator 400 kHz<br>2260001/2260002 |   |             |



# FLEXIBLE FIBER CHOLEDOCHOSCOPE 5 MM **CHANNEL 2.5 MM**



|  | Outer Ø       | Working<br>channel | WL     | Control lever in distal<br>direction – articulation<br>downward | Control lever in distal<br>direction – articulation<br>upward | Product no. |
|--|---------------|--------------------|--------|---|---|-------------|
| Fiber cystoscope 15 Fr WL<br>400 mm  |               |                    |        | •   |   | 7305.001    |
| Slanted distal tip Articulation +210°/-150° Direction of view 0°, viewing angle 110°   | 5 mm<br>15 Fr | 25 mm<br>75 Fr     | 400 mm |   | •   | 7305.006    |
| Fiber cystoscope bndl consisting of: Fiber cystoscope 15 Fr WL 400 mm (7305.001) Adapter with 2 irrigation valves and 1 instrument port (7305.782) Leakage tester for flex. endoscopes (163.903) Pressure equalization valve (163.904) Cleaning brush Ø 3 mm, TL 1,200 mm (PACK= 10 PCS) (7990002) |               |                    | •      |   | 730500111   |             |
| Fiber cystoscope bndl consisting of: Fiber cystoscope 15 Fr WL 400 mm (7305.006) Adapter with 2 irrigation valves and 1 instrument port (7305.782) Leakage tester for flex. endoscopes (163.903) Pressure equalization valve (163.904) Cleaning brush Ø 3 mm, TL 1,200 mm (PACK= 10 PCS) (7990002) |               |                    |        | •   | 730500611   |             |

| Recommended accessories   |                         | Product no. |
|---|-------------------------|-------------|
| Fiber light cable bndl consisting of: Fiber light cable Ø 2.5 mm TL 2.3 m (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm,<br>2.3 m long | 806625231   |



VI24 | Subject to modifications. Please note that some products may not be available in all countries. Please always take note of the information that is provided with the product. For more detailed information, please consult with your contact partner or directly with Richard Wolf GmbH.

# Mamaa

# FLEXIBLE SENSOR ENDOSCOPE FOR USE IN CHOLEDOCHOSCOPY


# FOR ENDOCAM Logic 4K CONTROLLER



|   | Outer Ø  | Working<br>channel | WL         | Control lever in distal<br>direction — articulation<br>downward | Control lever in distal<br>direction — articulation<br>upward | Product no. |
|---|----------|--------------------|------------|---|---|-------------|
| Sensor cystoscope<br>16.2 Fr WL 400 mm<br>Slanted distal tip  | 16.2 Fr  | 2.5 mm             | 400 mm     | •   |   | 7315001     |
| Articulation +210°/-210°<br>Direction of view 0°,<br>viewing angle 120°   | 10.2 FI  | 7.5 Fr             | 400 111111 |   | •   | 7315006     |
| Sensor cystoscope bndl consisting of: Sensor cystoscope 16.2 Fr, WL 400 mm (7315001) Leakage tester for flex. endoscopes (163.903), pressure equalization valve (163.904), Luer sealing cap (15023205), and cleaning brush Ø 5 mm, TL 1,200 mm (PACK= 10 PCS) (7990005) |          |                    | •          |   | 73150012  |             |
| Sensor cystoscope bndl consisting of: Sensor cystoscope 16.2 Fr, WL 400 m Leakage tester for flex. endoscopes (1 pressure equalization valve (163.904) Luer sealing cap (15023205), and cleaning brush Ø 5 mm, TL 1200 mm   | 63.903), |                    | ))         |   | •   | 73150062    |

| Recommended accessories   |                      | Product no. |
|---|----------------------|-------------|
| Fiber light cable bndl consisting of: Fiber light cable $\emptyset$ 2.5 mm TL 2.3 m (80662523), projector-side adapter (8095.07), and endoscope-side adapter (809509) | Ø 2.5 mm, 2.3 m long | 806625231   |

# TÜBINGER MIC TRAINING DEVICE



| Recommended accessories                       | Product no. |
|---|-------------|
| Abdominal wall, foam rubber, PACK= 5 PCS      | 9500.0561   |
| Available on request with transportation case |             |



Managing Directors: Jürgen Pfab VAT ID no.: DE144521586
Jürgen Steinbeck Tax no.: 48020/00171

